



December 2020

Preliminary Engineering Report

SR 826/Palmetto Expressway
From South of NW 36th Street (MP 8.355) to North of NW 154th Street (MP 17.950)
Project Development & Environment Study
Miami-Dade County, Florida

Financial Management Numbers: 447165-1-22-01, 441830-1-22-01, 441831-1-22-01
Federal Aid Project Number: N/A
ETDM Number: 14455

[page blank for two-sided printing]

PRELIMINARY ENGINEERING REPORT

Florida Department of Transportation

District VI

SR 826 / Palmetto Expressway


Project Development & Environment (PD&E) Study from South of NW 36th
Street to North of NW 154th Street

Miami-Dade County, Florida

Financial Project ID Number: N/A

ETDM Number: 14455

The environmental review, consultation, and other actions required by applicable federal environmental laws for this project are being, or have been, carried out by FDOT pursuant to 23 U.S.C. § 327 and a Memorandum of Understanding dated December 14, 2016, and executed by FHWA and FDOT.



William Leidy, P.E.
P.E. License Number 83790
Project Manager

[page blank for two-sided printing]

Contents

| | |
|--|----------|
| Contents | ii |
| List of Tables | v |
| List of Figures | vii |
| List of Appendices | viii |
| Abbreviations | x |
| 1.0 Project Summary | 1 |
| 1.1 Project Description | 1 |
| 1.2 Purpose and Need | 3 |
| 1.2.1 Roadway Deficiencies: Address Congestion and Speed Differentials | 3 |
| 1.2.2 System Linkage: Provide Better Access to the EL System | 3 |
| 1.3 Commitments | 4 |
| 1.4 Preferred Alternative | 5 |
| 2.0 Existing Conditions | 6 |
| 2.1 Existing Roadway Conditions | 6 |
| 2.1.1 Typical Section | 6 |
| 2.1.2 Roadway Classification | 21 |
| 2.1.3 Vertical Alignment | 21 |
| 2.1.4 Horizontal Alignment | 22 |
| 2.1.4.1 SR 826 | 22 |
| 2.1.4.2 SR 826 Ramps | 22 |
| 2.1.4.3 SR 826 Frontage Roads | 23 |
| 2.1.5 Frontage Roads Existing Deficiencies | 26 |
| 2.1.5.1 Lane Widths | 26 |
| 2.1.5.2 Shoulder Widths | 26 |
| 2.1.5.3 Pedestrian and bicyclists | 28 |
| 2.1.5.4 Sidewalks | 29 |
| 2.2 Existing ITS Conditions | 30 |
| 2.2.1 ITS Devices | 30 |
| 2.3 Existing Structures | 34 |
| 2.3.1 Historical Significance | 36 |

| | | |
|---------|---|----|
| 2.4 | Existing Lighting Conditions | 36 |
| 2.5 | Pedestrian and Bicycle Facilities | 36 |
| 2.6 | Transit Facilities..... | 37 |
| 2.6.1 | Miami Dade Transit..... | 37 |
| 2.6.1.1 | Transit Ridership..... | 37 |
| 2.6.1.2 | SMART Plan | 42 |
| 2.6.2 | Frontage Roads | 46 |
| 2.6.3 | Metrorail | 46 |
| 2.7 | Existing Drainage Systems..... | 46 |
| 2.7.1 | Existing Drainage System SR 826 | 46 |
| 2.7.2 | Existing Drainage System Frontage Road East | 47 |
| 2.7.3 | Existing Drainage System Frontage Road West | 47 |
| 2.8 | Geotechnical Characteristics..... | 47 |
| 2.9 | Utilities | 47 |
| 2.10 | Design and Posted Speeds | 49 |
| 2.11 | Traffic Characteristics | 49 |
| 2.11.1 | Existing Conditions | 49 |
| 2.12 | Existing Traffic Volumes | 50 |
| 2.12.1 | Data Collection | 50 |
| 2.13 | Modeling and Travel Demand | 51 |
| 2.13.1 | VISSIM Model Development and Calibration | 51 |
| 2.13.2 | Selection of Measures of Effectiveness (MOE) | 52 |
| 3.0 | Design Controls and Criteria..... | 53 |
| 3.1 | Design Controls | 53 |
| 3.2 | Design Criteria | 54 |
| 4.0 | Alternatives Analysis | 59 |
| 4.1 | No-Build Alternative | 59 |
| 4.2 | Build Alternative..... | 59 |
| 4.2.2 | Mainline SR 826 Build Alternative | 60 |
| 4.2.3 | Frontage Road Build Alternative..... | 61 |
| 4.3 | Future Conditions Analysis..... | 63 |
| 4.3.1 | Build 2023(2040) Peak Hour Traffic Development..... | 63 |

| | | |
|------------|---|-----------|
| 4.4 | Evaluation and Elimination of Alternatives | 65 |
| 5.0 | Public Involvement/Project Coordination | 67 |
| 5.1 | MPO Coordination | 67 |
| 5.2 | Coordination with Elected/Appointed Officials..... | 67 |
| 5.3 | Public Hearing | 67 |
| 6.0 | Preferred Alternative | 67 |
| 6.1 | Right-of-Way Needs and Relocation | 68 |
| 6.2 | Typical Sections..... | 68 |
| 6.3 | Horizontal and Vertical Geometry..... | 70 |
| 6.3.1 | SR 826 | 70 |
| 6.3.2 | Ramps..... | 71 |
| 6.3.2.1 | Ramp A – SR 826 SB Off-Ramp at NW 74 th Street..... | 72 |
| 6.3.2.2 | Ramp B – SR 826 SB Off-Ramp at NW 103 rd Street | 73 |
| 6.3.2.3 | Ramp C – NW 77 th Avenue On-Ramp..... | 74 |
| 6.3.2.4 | Ramp D – NW 103 rd SB Flyover On-Ramp | 75 |
| 6.3.2.5 | Ramp E – NW 103 rd Street NB Off-Ramp | 76 |
| 6.3.3 | Frontage Roads | 76 |
| 6.4 | Access Management | 78 |
| 6.5 | Design Variations and Exceptions..... | 78 |
| 6.5.1 | Design Variations..... | 78 |
| 6.5.2 | Design Exceptions | 80 |
| 6.6 | Lighting | 80 |
| 6.7 | Utilities | 81 |
| 6.8 | Preliminary Drainage Analysis..... | 82 |
| 6.8.1 | Proposed Drainage Systems | 82 |
| 6.9 | Structures | 82 |
| 6.9.1 | Horizontal and Vertical Clearance | 82 |
| 6.9.2 | Flyover Bridge from SR 932/NW 103 rd westbound to SR 826 southbound..... | 83 |
| 6.9.2.1 | Bridge Analysis | 83 |
| 6.9.2.2 | Construction Sequence | 84 |
| 6.9.3 | Southbound 826 over Metrorail | 86 |
| 6.9.4 | West Frontage Road over Little River Canal | 87 |

| | | |
|---------|---|-----|
| 6.9.5 | East Frontage Road over Little River Canal | 88 |
| 6.9.6 | Southbound SR 826 over FEC Railroad..... | 88 |
| 6.9.7 | Southbound SR 826 at SR934/NW 74 th Street..... | 89 |
| 6.9.8 | Southbound SR 826 at SR 932/NW 103 rd Street | 90 |
| 6.9.9 | Northbound SR 826 at SR 932/NW 103 rd Street..... | 90 |
| 6.9.10 | Retaining Wall Modifications..... | 91 |
| 6.9.11 | Aesthetics | 91 |
| 6.9.12 | ITS Features | 91 |
| 6.10 | Maintenance of Traffic | 92 |
| 6.10.1 | Southbound SR 826 | 92 |
| 6.10.2 | Northbound SR 826 | 92 |
| 6.10.3 | Frontage Roads | 92 |
| 6.10.4 | Miscellaneous Overhead Structures..... | 92 |
| 6.11 | Cost Estimates..... | 92 |
| 6.12 | Environmental Analysis | 92 |
| 6.12.1 | Existing and Future Land Use | 93 |
| 6.12.2 | Cultural Resource Assessment Survey | 94 |
| 6.12.3 | Community Facilities..... | 97 |
| 6.12.4 | Parks and Recreational Facilities | 114 |
| 6.12.5 | Wetlands | 114 |
| 6.12.6 | Essential Fish Habitat | 119 |
| 6.12.7 | Wildlife and Habitat Survey..... | 119 |
| 6.12.8 | Floodplains/Floodways | 121 |
| 6.12.9 | Noise..... | 122 |
| 6.12.10 | Contamination..... | 122 |
| 6.12.11 | Right-of-Way | 123 |
| 6.12.12 | Value Engineering Review..... | 123 |
| 7.0 | List of Technical Reports Completed for the Project | 124 |

List of Tables

| | |
|---|----|
| Table 2-1 Horizontal Alignment: SR 826 | 22 |
| Table 2-2 Horizontal Alignment: Ramp A – SR 826 SB Off-Ramp at NW 74 th Street..... | 22 |
| Table 2-3 Horizontal Alignment: Ramp B – SR 826 SB Off-Ramp at NW 103 rd Street..... | 23 |
| Table 2-4 Horizontal Alignment: Ramp C – SR 826 SB On-Ramp at NW 77 th Avenue | 23 |

| | |
|--|-----|
| Table 2-5 Horizontal Alignment: Ramp E – SR 826 NB Off-Ramp at NW 103 rd Street | 23 |
| Table 2-6 Horizontal Alignment: SR 826 Frontage Roads 441830-1-52-01 project limits | 24 |
| Table 2-7 Horizontal Alignment: SR 826 Frontage Roads 441831-1-52-01 project limits | 25 |
| Table 2-8 Existing ITS Devices | 31 |
| Table 2-9 Existing Structures | 34 |
| Table 2-10 Existing Utility Owners | 48 |
| Table 2-11 Vissim Calibration Targets ¹ | 51 |
| Table 3-1 Project Design Controls: SR 826 | 53 |
| Table 3-2 Project Design Controls: SR 826 Ramps | 53 |
| Table 3-3 Project Design Controls: SR 826 Frontage Roads | 53 |
| Table 3-4 Design Criteria: SR 826 | 55 |
| Table 3-5 Design Criteria: Ramps (30 mph) | 56 |
| Table 3-6 Design Criteria: Ramps (40 mph) | 57 |
| Table 3-7 Design Criteria: Frontage Roads | 58 |
| Table 4-1 Alternative Comparison Matrix | 65 |
| Table 6-1 Geometry: SR 826 | 71 |
| Table 6-2 Geometry: Ramp A | 72 |
| Table 6-3 Geometry: Ramp B | 73 |
| Table 6-4 Geometry: Ramp C | 74 |
| Table 6-5 Geometry: Ramp D | 75 |
| Table 6-6 Geometry: Ramp E | 76 |
| Table 6-7 Geometry: Frontage Roads | 77 |
| Table 6-8 SCE Study Area Existing Land Use | 93 |
| Table 6-9 SCE Study Area Future Land Use | 94 |
| Table 6-10 Group Care Facilities in SCE Study Area | 106 |
| Table 6-11 Park and Recreational Facilities in SCE Study Area | 106 |
| Table 6-12 Law Enforcement Facilities in SCE Study Area | 106 |
| Table 6-13 Hospitals in SCE Study Area | 106 |
| Table 6-14 Healthcare Facilities in SCE Study Area | 107 |
| Table 6-15 Government Buildings in SCE Study Area | 111 |
| Table 6-16 Fire Stations in SCE Study Area | 111 |
| Table 6-17 Cultural Centers in SCE Study Area | 112 |
| Table 6-18 Schools in SCE Study Area | 112 |
| Table 6-19 Religious Centers in SCE Study Area | 113 |
| Table 6-20 Park and Recreational Facilities in SCE Study Area | 114 |
| Table 6-21 Summary of Individual Water Features | 116 |

Table 6-22 | Summary of Listed Species and Effect Determinations 120

List of Figures

| | |
|--|----|
| Figure 1-1 Project Location Map | 2 |
| Figure 2-1 Typical Section – SR 826 | 10 |
| Figure 2-2 Ramp A- SB off-ramp at NW 74 th Street | 11 |
| Figure 2-3 Ramp B - SB off-ramp at NW 103 rd Street | 11 |
| Figure 2-4 Ramp C - SB on-ramp at NW 77 th Avenue | 12 |
| Figure 2-5 Ramp E - NB off-ramp at NW 103 rd Street | 12 |
| Figure 2-6 441830-1-52-01 SR 826 East Frontage Roads Typical Section – W 20 th Avenue from Okeechobee Road to south of W 39 th Street | 13 |
| Figure 2-7 441830-1-52-01 SR 826 East Frontage Roads Typical Section – W 20 th Avenue from W 39 th Street to W 41 st Street | 13 |
| Figure 2-8 441830-1-52-01 SR 826 East Frontage Roads Typical Section – W 20 th Avenue from W 41 st Street to W 44 th Place | 14 |
| Figure 2-9 441830-1-52-01 SR 826 West Frontage Roads Typical Section – NW 77 th Avenue from the begin project to south of the Walmart Driveway, and from north of NW 95 th Street to NW 98 th Street | 14 |
| Figure 2-11 441830-1-52-01 SR 826 West Frontage Roads Typical Section – NW 77 th Avenue from NW 98 th Street to NW 103 rd Street | 15 |
| Figure 2-12 441831-1-52-01 SR 826 East Frontage Roads Typical Section – W 20 th Avenue East from NW 103 rd Street to south of the Little River Canal | 16 |
| Figure 2-13 441831-1-52-01 SR 826 East Frontage Roads Typical Section – W 20 th Avenue East from south of the Little River Canal to south of W 60 th Street and from north of W 60 th Street to north of W 64 th Street | 16 |
| Figure 2-14 441831-1-52-01 SR 826 East Frontage Roads Typical Section – W 20 th Avenue East from south of W 60 th Street to north of W 60 th Street | 17 |
| Figure 2-15 441831-1-52-01 SR 826 East Frontage Roads Typical Section – W 67 th Place from north of W 64 th Street to NW 122 nd Street/W 68 th Street | 17 |
| Figure 2-16 441831-1-52-01 SR 826 West Frontage Roads Typical Section – NW 77 th Court from north of NW 103 rd Street to south of the Little River Canal | 18 |
| Figure 2-17 441831-1-52-01 SR 826 West Frontage Roads Typical Section – 20 th Avenue West from south of the Little River Canal to south of W 60 th Street and from north of W 60 th Street to NW 122 nd Street/W 68 th Street | 18 |
| Figure 2-18 441831-1-52-01 SR 826 West Frontage Roads Typical Section – W 20 th Avenue West from south of W 60 th Street to north of W 60 th Street | 19 |
| Figure 2-19 441831-1-52-01 SR 826 East Frontage Road Bridge Typical Section – Bridge 870570, W 20 th Avenue East over the Little River Canal | 19 |

| | |
|---|-----|
| Figure 2-20 441831-1-52-01 SR 826 West Frontage Road Bridge Typical Section – Bridge 870569, W 20 th Avenue East over the Little River Canal | 20 |
| Figure 2-21 Route 29..... | 38 |
| Figure 2-22 Route 33..... | 39 |
| Figure 2-23 Route 36..... | 40 |
| Figure 2-24 Route 95..... | 41 |
| Figure 2-25 Route 132..... | 42 |
| Figure 2-26 Express Bus System Vision | 44 |
| Figure 2-27 SMART Plan Map | 45 |
| Figure 4-1 Build Alternative: SR 826 Southbound..... | 62 |
| Figure 6-1 Typical Section: SR 826 Southbound One Express Lane | 68 |
| Figure 6-2 Typical Section: SR 826 Southbound Two Express Lanes | 69 |
| Figure 6-3 Typical Section: SR 826 Northbound | 69 |
| Figure 6-4 Typical Section: Frontage Roads | 70 |
| Figure 6-5 Typical Section: Flyover Bridge from SR 932/NW 103rd WB to SR 826 SB, Bridge No. 870856..... | 84 |
| Figure 6-6 Construction Sequence | 85 |
| Figure 6-7 Typical Section: SB 826 over Metrorail, Bridge No. 870257..... | 86 |
| Figure 6-8 Typical Section: West Frontage Road over Little River Canal, Bridge No. 870569..... | 87 |
| Figure 6-9 Typical Section: East Frontage Road over Little River Canal, Bridge No. 870570..... | 88 |
| Figure 6-10 Typical Section: SB SR 826 over FEC Railroad, Bridge No. 870258 | 89 |
| Figure 6-11 Typical Section: SB SR 826 over NW 74 th Street, Bridge No. 870964 | 89 |
| Figure 6-12 Typical Section: SB SR 826 over NW 103 rd Street, Bridge No. 870757 | 90 |
| Figure 6-13 Typical Section: NB SR 826 over NW 103 rd Street, Bridge No. 870995..... | 91 |
| Figure 6-14 Community Features Key Sheet | 99 |
| Figure 6-15 Community Features (1 of 6) | 100 |
| Figure 6-16 Community Features (2 of 6) | 101 |
| Figure 6-17 Community Features (3 of 6) | 102 |
| Figure 6-18 Community Features (4 of 6) | 103 |
| Figure 6-19 Community Features (5 of 6) | 104 |
| Figure 6-20 Community Features (6 of 6) | 105 |

List of Appendices

- Appendix A – Concept Plans
- Appendix B – Typical Section Package
- Appendix C – Cost Estimates
- Appendix D – Utility Design Ticket

Abbreviations

| | |
|---------------|--|
| AADT | Average Annual Daily Traffic |
| AASHTO | American Association of State Highway and Transportation Officials |
| ADA | American with Disabilities Act |
| AMS | Arterial Management Services |
| APE | Area of Potential Effect |
| ATMS | Advanced Transportation Management Systems |
| ATS | Automatic Transfer Switches |
| ATSC | Adaptive Traffic Signal Control |
| BDR | Bridge Development Report |
| BHP | Borehole Permeability Tests |
| BMAP | Basin Management Action Plan |
| BTTS | Bluetooth Travel Time System |
| CARS | Crash Analysis Reporting System |
| CCTV | Closed Circuit Television |
| CD | Collector-Distributor |
| CDR | Concept Development Report |
| CFR | Code of Federal Regulation |
| CNEs | Common Noise Environments |
| CRA | Community Redevelopment Agency |
| DMS | Dynamic Messaging Signs |
| DOA | Determination of Applicability |
| EB | Eastbound |

| | |
|-------------|--|
| EFH | Essential Fish Habitat |
| EL | Express Lanes |
| EPA | United States Environmental Protection Agency |
| ESA | Endangered Species Act |
| ETDM | Efficient Transportation Decision Making |
| FDEP | Florida Department of Environmental Protection |
| FDM | FDOT Florida Design Manual (2020) |
| FDOT | Florida Department of Transportation |
| FEMA | Federal Emergency Management Agency |
| FHWA | Federal Highway Administration |
| FO | Fiber Optic |
| FOC | Fiber Optic Cable |
| FPID | Financial Project Identification Number |
| FWC | Florida Fish and Wildlife Commission |
| FWRA | Food Waste Reduction Alliance |
| GP | General Purpose |
| HD | High Definition |
| HOA | Homeowner's Association |
| HOV | High Occupancy Vehicles |
| ID | Identification |
| IOAR | Interchange Operational Analysis Report |
| ITS | Intelligent Transportation System |
| LDCA | Location and Design Concept Acceptance |

| | |
|-------------|---|
| LHR | Location Hydraulic Report |
| LOS | Level of Service |
| LFR | Load Factor and Resistance |
| LRE | Long Range Estimate |
| MDT | Miami-Dade Transit |
| MLOU | Methodology Letter of Understanding |
| MOEs | Measures of Effectiveness |
| MP | Milepost |
| mph | miles per hour |
| MPO | Metropolitan Planning Organization |
| MSE | Mechanically Stabilized Earth |
| MVDS | Microwave Vehicle Detection System |
| NAC | Noise Abatement Criteria |
| NAVD | North American Vertical Datum |
| NB | Northbound |
| NBI | National Bridge Inventory |
| NE | Northeast |
| NEPA | National Environmental Policy Act |
| NFHL | National Flood Hazard Layer |
| NGVD | National Geodetic Vertical Datum |
| NHS | National Highways System |
| NMFS | National Marine Fisheries Service |
| NOAA | National Oceanic and Atmospheric Administration |

| | |
|-----------------|--|
| NRCS | Natural Resources Conservation Service |
| NRE | Natural Resources Evaluation |
| NSR | Noise Study Report |
| NW | Northwest |
| O-D | Origin - Destination |
| OEM | Office of Environmental Management |
| OWJ | Official with Jurisdiction |
| PD&E | Project Development and Environment Study |
| PPM | Plans Preparation Manual |
| PSC | Prestressed Concrete |
| PTZ | Pan-Tilt-Zoom |
| RSS | Ramp Signaling System |
| RSC | Ramp Signal Cabinets |
| RTMC | Regional Transportation Management Centers |
| SB | Southbound |
| S-DMS | Lane Status Dynamic Messaging Sign |
| SE | Southeast |
| SERPM | Southeast Florida Regional Planning Model |
| SFWMD | South Florida Water Management District |
| SHGWT | Seasonal High Groundwater Table |
| SHPO | State Historic Preservation Office |
| SIMR | Systems Interchange Modification Report |
| SIS | Strategic Intermodal System |

| | |
|------------------|--|
| SR | State Road |
| SW | Southwest |
| SWEPT | Statewide Environmental Project Tracker |
| T-DMS | Toll Amount Dynamic Messaging Sign |
| TMDL | Total Maximum Daily Load |
| TSM&O | Transportation Systems Management and Operations |
| US- | U.S. Route or U.S. Highway |
| USACE | United States Army Corps of Engineers |
| USCG | United States Coast Guard |
| USDA | United States Department of Agriculture |
| USFWS | United States Fish and Wildlife Service |
| vpd | vehicles per day |
| VoIP | Voice over Internet Protocol |
| WAP | Wireless Access Points |
| WB | Westbound |
| WBID | Water body Identification |

1.0 Project Summary


1.1 Project Description

This roadway project involves the addition of general use lanes, conversion of express (managed) lanes to general use lanes, as well as traffic operational and geometrical design improvements on SR 826/Palmetto Expressway from South of NW 36th Street (Milepost (MP) 8.355) to North of NW 154th Street (MP 17.950) within Miami-Dade County. The improvements are proposed to address existing congestion and higher than expected speed differentials between the general purpose (GP) lanes and the express lanes (EL) along the project corridor, as well as provide additional access to the EL system. Connecting population and commercial centers in north-central Miami-Dade County, the project traverses the cities of Doral, Medley, Hialeah Gardens, Hialeah, and Miami Lakes, as well as unincorporated portions of the county. SR 826/Palmetto Expressway connects to essential east-west facilities within north-central Miami-Dade County, including SR 836/Dolphin Expressway, SR 948/NW 36th Street, SR 934/NW 74th Street, US 27/Okeechobee Road, SR 932/NW 103rd Street, and I-75/SR 93 and SR 924/Gratigny Parkway.

The proposed southbound (SB) improvements include modification to the NW 103rd Street westbound (WB) to SB Flyover ramp piers, thereby widening the SR 826 mainline bridge and mechanically stabilized earth (MSE) walls, which will allow for an additional GP lane through the interchange and extension of the auxiliary lane between NW 74th Street and Okeechobee Road interchanges. In an effort to improve the existing weaving condition, three SB bridges (over NW 74th Street, Metrorail, and FEC Rail) are expected to be widened. One SB EL will be converted to provide an additional GP lane, between NW 103rd Street and NW 154th Street by milling and resurfacing, restriping and moving the delineators. In addition, the existing SB EL ingress currently located at north of NW 154th Street is expected to be relocated to NW 103rd Street in order to provide better access to residents in northern Miami-Dade County. Proposed northbound (NB) improvements include widening the mainline within the NW 103rd Street interchange to provide the minimum 10-foot recommended shoulder width for both inside and outside shoulders. In addition, the project includes improvements to the frontage road system on both sides of SR 826/Palmetto Expressway including milling, resurfacing, and construction between Okeechobee Road and NW 122nd Street.

Within the project limits, SR 826/Palmetto Expressway is classified as 'Principal Arterial-Other Freeways and Expressways' and consists of six to eight general use lanes and zero to four express (managed) lanes; the typical section varies throughout the project segment. In addition, SR 826/Palmetto Expressway is part of the state's emergency evacuation network and is a designated Strategic Intermodal System (SIS) highway corridor, providing access via SR 934/NW 74th Street (also known as Hialeah Expressway) and surface streets to the Miami Hialeah FEC Intermodal Terminal, an SIS Freight Rail Terminal. Existing right-of-way along the corridor ranges from approximately 200 feet to 455 feet or more in width near the existing interchanges. Right-of-way is not expected to be required to accommodate the proposed improvements.

Figure 1-1 | Project Location Map



1.2 Purpose and Need

The purpose of this project is to address various roadway deficiencies causing congestion and large speed differentials between GP lanes and EL along the SR 826 corridor. Proposed improvements are anticipated to increase roadway safety, facilitate the movement of people and goods, and increase the capacity in the GP lanes. Another goal of the project is to improve access to the EL system by relocating an ingress point in northern Miami-Dade County. Additionally, the purpose of the project is to improve the geometry of the expressway frontage road system. The need for the project is based on the following criteria:

1.2.1 Roadway Deficiencies: Address Congestion and Speed Differentials

Following the opening of the SR 826 ELs to traffic in September 2019, additional congestion and higher than expected speed differentials between EL (higher speeds) and GP lanes (lower speeds) were observed in both the northbound and southbound directions during peak travel times. Areas identified for improvement include the NW 103rd Street interchange and from NW 74th Street to US 27 in the southbound direction. The issues identified in these areas are caused by geometric and operational deficiencies such as the lack of auxiliary lanes, insufficient ramp lengths, and substandard shoulders.

The implementation of operational improvements to correct the identified roadway deficiencies on SR 826 would improve congestion and better align speeds between the EL and GP lanes. According to the Palmetto Express Lanes Modification Summary Report, an earlier planning study, the proposed improvements would result in a 56% and 42% reduction in travel times for the southbound and northbound GP lanes, respectively. In addition, throughput would increase a combined 58% and 11% in the southbound and northbound directions, respectively. While speed in the EL is not projected to increase, speeds in the GP lanes are forecasted to rise by 26 miles per hour in the southbound direction and 19 miles per hour in the northbound direction. These metrics illustrate how implementation of the potential improvements would address congestion and speed differentials currently caused by roadway deficiencies.

1.2.2 System Linkage: Provide Better Access to the EL System

Currently the southbound EL lanes begin north of NW 154th Street and do not provide southbound ingress for motorists in this area of north-central Miami-Dade County (after NW 67th Avenue). To better facilitate the movement of traffic from this area of increased demand into the EL system, the potential project improvements include relocating the existing EL ingress point from north of NW 154th Street to south of NW 103rd Street. This will create access to the EL system for residents in this portion of Miami-Dade County and create an important linkage to the EL system.

1.3 Commitments

Natural Resources Implementation Measures

Based on the field and literature reviews outlined in the NRE, federally listed or state-listed protected species have the potential to occur within the project study area. In order to ensure that the proposed project will not adversely impact these species, the FDOT will adhere to the following measures:

- The contractor will be advised of state and local law regarding the harassment of crocodiles prior to the commencement of and during construction activities.
- While mitigation is not anticipated, any adverse impacts to suitable foraging habitat for the federally listed wood stork for which mitigation is deemed necessary will be mitigated through the purchase of credits from a FWS-approved mitigation bank pursuant to Section 373.4137, FS or as otherwise agreed to by the FDOT and the FWS.
- Should protected plant species be identified within the project impact area during the design and permitting phase, coordination will be initiated with the FDACS or other appropriate agencies to allow for relocation to adjacent habitat or other suitable protected lands prior to construction.
- During the construction phase of this project, the FDOT will implement the Standard Specifications for Road and Bridge Construction and other BMPs to avoid, where possible, and otherwise minimize adverse impacts to wetlands/surface waters and water quality within the project limits to the maximum extent practicable.
- Manatee exclusion grating will be added for the following existing outfalls which are part of the proposed stormwater management system:
 - Miami Canal (C-6): Station 482+52.12 - 60" pipe
 - Miami Canal (C-6): Station 483+53.87 - 60" pipe
 - Miami Canal (C-6): Station 486+24.20 - two (2) 36" pipes
 - Little River Canal (C-7): Station 540+84.00 - 72" pipe

Natural Resources Commitments

Based on the field and literature reviews outlined in the NRE, federally listed or state listed protected species have the potential to occur within the project study area. In order to assure that the proposed project will not adversely impact these species, the FDOT will adhere to the following commitments:

- Prior to commencing construction activities, the FDOT is committed to re-surveying the project corridor for features that could serve as potential roosting habitat and signs of the Florida bonneted bat. If any signs of the Florida bonneted bat are observed, the FDOT is committed to reinitiating consultation with the FWS to determine the appropriate course of action.
- During the construction phase of this project, the FDOT will adhere to the most recent version of the FWS' Standard Manatee Conditions for In-Water Work to minimize the potential for adverse effects.

- During the construction phase of this project, the FDOT will adhere to the most recent version of the FWS' Standard Protection Measures for the Eastern Indigo Snake to minimize the potential for adverse effects.

Noise Commitments

- Construction noise and vibration impacts to the project corridor will be minimized by adherence to the controls listed in the latest edition of the FDOT's Standard Specifications for Road and Bridge Construction.

Cultural Resources Commitments

- The monitoring of subsurface impacts will be conducted by a professional archaeologist at the location of site 8DA40.

Contamination Commitments

- There are currently no commitments related to contamination issues.

Air Quality Commitments

- There are currently no commitments related to air quality issues.

Sociocultural Commitments

- There are currently no commitments related to sociocultural issues.

Public Involvement Commitments

- There are currently no commitments related to public involvement issues.

1.4 Preferred Alternative

The study's Preferred Alternative includes:

Project improvements in the SR 826 southbound direction include:

- Add a GP lane from the exit to NW 103rd Street to the exit to Okeechobee Road, to provide additional capacity via roadway widening, bridge widening and shoulder width reductions.
- Modify NW 103rd Street WB to SB flyover ramp pier along the outside GP lane and widen the SR 826 mainline bridge and walls to create an additional GP lane through the NW 103rd Street interchange.
- Extend auxiliary lane between NW 74th Street and Okeechobee Road interchanges to better facilitate weaving.

- Widen bridge over NW 74th Street, Metrorail and FEC railroad to accommodate additional lane up to NW 74th Street on-ramp.
- Relocate existing ingress from North of NW 154th Street to South of NW 103rd Street to provide access from NW 154th Street and NW 122nd Street to the EL.

Project improvements in the SR 826 northbound direction include:

- Widen mainline over NW 103rd Street interchange to provide full width inside and outside shoulders.

Project improvements for the SR 826 frontage road include:

- Mill and resurface the existing pavement.
- Construct paved shoulders (5 feet wide) in segments without existing roadside landscaping or utility impacts.
- Upgrade guardrail, guardrail terminals, and guardrail-to-rigid barrier transition connections.
- Upgrade/replace sidewalk and substandard curb cut ramps
- Update all sub-standard ground-mounted signs
- Upgrade signalization including pedestrian features
- Bridge 870570 – East Frontage Road over Little River Canal/C-7 modifications including replacing bridge railings, constructing sidewalk, and replacing existing expansion joints and joint headers
- Bridge 870569 – West Frontage Road over Little River Canal/C-7 modifications including replacing bridge railings and constructing sidewalks

2.0 Existing Conditions

2.1 Existing Roadway Conditions

2.1.1 Typical Section

The current typical along the SR 826/Palmetto Expressway northbound consists of one express lane throughout the entire study limits with five general purpose lanes from NW 36th Street to Okeechobee Road and four general purpose lanes from Okeechobee Road to I-75 interchange.

The current typical along the SR 826/Palmetto Expressway southbound consists of a single express lane and three general purpose lanes from south of NW 54th Street to south of I-75 interchange; two express lanes and four general purpose lanes from south of I-75 Interchange to north of NW 103rd Street interchange; two express lanes and three general purpose lanes carried through the NW 103rd Street interchange; and, two express lanes and four general purpose lanes from south of NW 103rd Street interchange to north of NW 36th Street interchange.

The existing SR 826/Palmetto Expressway limited access right of way varies within the study limits. The right of way is generally consistent throughout the corridor ranging from 200' to 270' except at the interchanges, where it varies to accommodate entrance and exit ramps.

The typical section for SR 826 is depicted in **Figure 2-1**.

There are four existing on/off SR 826 ramps within the project limits that will be modified under this project.

Existing Ramp A, SB off-ramp at NW 74th Street, consist of a two to four-lane ramp with fully paved 10' outside shoulders and fully paved 6' inside shoulders.

Existing Ramp B, SB off-ramp at NW 103rd Street, consists of a two to four-lane ramp with fully paved 10' outside shoulders and 8' (4' paved) inside shoulders.

Existing Ramp C, SB on-ramp at NW 77th Avenue, consists of a one-lane ramp with 6' fully paved shoulders on both sides.

Existing Ramp E, NB off-ramp at NW 103rd Street, consists of a two to four-lane ramp with 8' fully paved inside shoulders and 10' fully paved outside shoulders.

The typical sections for SR 826 Ramps are depicted in **Figure 2-2** through **Figure 2-5**

Six existing frontage road typical sections are identified within the **441830-1-52-01** project limits.

Existing Roadway Typical Section 1 (Section 87260151), SR 826 East Frontage Road, W 20th Avenue from Okeechobee Road to south of W 39th Street, consists of a two-lane undivided section, with flush unpaved shoulders, and sidewalk along the right side of the roadway for most of the limits.

Existing Roadway Typical Section 2 (Section 87260151), SR 826 East Frontage Road, W 20th Avenue from south of W 39th Street to W 41st Street, consists of a two-lane undivided section, with flush paved shoulders and concrete barrier wall on the left side of the roadway adjacent to SR 826 Northbound, flush unpaved shoulder and sidewalk along the right side of the roadway.

Existing Roadway Typical Section 3 (Section 87260151), SR 826 East Frontage Road, W 20th Avenue from W 41st Street to W 44th Place, consists of a two-lane undivided section, with flush unpaved shoulders and landscaping on both sides, and sidewalk along the right side of the roadway.

Existing Roadway Typical Section 4 (Section 87260152), SR 826 West Frontage Road, NW 77th Avenue from the south project limit to south of Walmart Driveway, and from north of NW 95th Street to NW 98th Street, consists of a two-lane undivided section, with flush unpaved shoulders along both sides of the roadway and concrete barrier wall on the right side of the roadway adjacent to SR 826 Southbound.

Existing Roadway Typical Section 5 (Section 87260152), SR 826 West Frontage Road, NW 77th Avenue from south of Walmart Driveway to north of NW 95th Street, consists of a two-lane undivided section, with flush paved shoulder and concrete barrier wall on the right side of the roadway adjacent to SR 826 Southbound, and flush unpaved shoulder along the left side of the roadway.

Existing Roadway Typical Section 6 (Section 87260152), SR 826 West Frontage Road, NW 77th Avenue from NW 98th Street to NW 103rd Street, consists of a two-lane undivided one-way section with traffic in the southbound direction, with an existing drop curb and trench drain on the left side of the roadway, and a flush paved shoulder along the right side of the roadway.

Seven existing roadway typical sections and two existing bridge typical sections are identified within the **441831-1-52-01** project limits.

Existing Roadway Typical Section 1 (Section 87260298), SR 826 East Frontage Road, W 20th Avenue East from NW 103rd Street to south of Little River Canal, consists of a two-lane undivided one-way section with traffic in the northbound direction; with a flush shoulder on the left side; and curb & gutter, grass strip, and sidewalk along the right side.

Existing Roadway Typical Section 2 (Section 87260298), SR 826 East Frontage Road, W 20th Avenue East from south of Little River Canal to north of W 64th Street, consists of a two-lane undivided section, with flush unpaved shoulders on both sides, and sidewalk along the right side for most of the limits.

Existing Roadway Typical Section 3 (Section 87260298), SR 826 East Frontage Road, W 20th Avenue East from south of W 60th Street to north of W 60th Street, consists of a two-lane undivided section with a left-turn lane, with curb & gutter on both sides, and sidewalk along the right side.

Existing Roadway Typical Section 4 (Section 87260298), SR 826 East Frontage Road, W 67th Place from north of W 64th Street to NW 122nd Street/W 68th Street, consists of a two-lane divided section with auxiliary lanes in both directions, a raised median, curb & gutter along both sides, and sidewalk along the right side.

Existing Roadway Typical Section 5 (Section 87260506), SR 826 West Frontage Road, NW 77th Court from north of NW 103rd Street to south of Little River Canal, consists of a two-lane undivided section, curb & gutter along both sides, and sidewalk along the left side.

Existing Roadway Typical Section 6 (Section 87260521), SR 826 West Frontage Road, W 20th Avenue West from south of Little River Canal to NW 122nd Street/W 68th Street, consists of a two-lane undivided section, with flush unpaved shoulders along both sides, guardrail along the right side at the Peter's Pike Canal, and sidewalk along the left side for most of the limits.

Existing Roadway Typical Section 7 (Section 87260152), SR 826 West Frontage Road, W 20th Avenue West from south of W 60th Street to north of W 60th Street, consists of a two-lane undivided section with a left-turn lane, with curb & gutter and sidewalk along the left side, and paved shoulder and shoulder barrier along the right side at the Peter's Pike Canal.

Existing Bridge Typical Section 1 (Bridge 870570), SR 826 East Frontage Road, W 20th Avenue East over Little River Canal, consists of a two-lane undivided section with flush shoulders and post and beam railings on both sides; the right shoulder connects to sidewalks on the bridge approaches.


Existing Bridge Typical Section 2 (Bridge 870569), SR 826 West Frontage Road, W 20th Avenue West over Little River Canal, consists of a two-lane undivided section with wide curb and post and beam railings on both sides.

The existing right of way along the five frontage road sections is typically 50' and varies at a few locations as follows:

- W 20 Avenue (Section 87260151) – 50' typical
- NW 77 Avenue (Section 87260152) – 50' typical
- W 20 Avenue East (Section 87260298) – 50' typical, varies 46.4'-108.9'
- NW 77 Court (Section 87260506) – 50' typical
- W 20 Avenue West (Section 87260521) – 50' typical, maximum 100'

The typical sections for the frontage roads are depicted in **Figure 2-6** through **Figure 2-20**.

Figure 2-1 | Typical Section – SR 826



EXISTING TYPICAL SECTION
SR 826
STA. 278+24.88 TO STA. 784+63.90 ℓ SR 826

Figure 2-2 | Ramp A- SB off-ramp at NW 74th Street




Figure 2-3 | Ramp B - SB off-ramp at NW 103rd Street




Figure 2-4 | Ramp C - SB on-ramp at NW 77th Avenue




Figure 2-5 | Ramp E - NB off-ramp at NW 103rd Street




Figure 2-6 | 441830-1-52-01 SR 826 East Frontage Roads Typical Section – W 20th Avenue from Okeechobee Road to south of W 39th Street




Figure 2-7 | 441830-1-52-01 SR 826 East Frontage Roads Typical Section – W 20th Avenue from W 39th Street to W 41st Street




Figure 2-8 | 441830-1-52-01 SR 826 East Frontage Roads Typical Section – W 20th Avenue from W 41st Street to W 44th Place




Figure 2-9 | 441830-1-52-01 SR 826 West Frontage Roads Typical Section – NW 77th Avenue from the begin project to south of the Walmart Driveway, and from north of NW 95th Street to NW 98th Street




Figure 2-10 | 441830-1-52-01 SR 826 West Frontage Roads Typical Section – NW 77th Avenue from south of the Walmart Driveway to north of NW 95th Street




Figure 2-11 | 441830-1-52-01 SR 826 West Frontage Roads Typical Section – NW 77th Avenue from NW 98th Street to NW 103rd Street




Figure 2-12 | 441831-1-52-01 SR 826 East Frontage Roads Typical Section – W 20th Avenue East from NW 103rd Street to south of the Little River Canal




Figure 2-13 | 441831-1-52-01 SR 826 East Frontage Roads Typical Section – W 20th Avenue East from south of the Little River Canal to south of W 60th Street and from north of W 60th Street to north of W 64th Street




Figure 2-14 | 441831-1-52-01 SR 826 East Frontage Roads Typical Section – W 20th Avenue East from south of W 60th Street to north of W 60th Street




Figure 2-15 | 441831-1-52-01 SR 826 East Frontage Roads Typical Section – W 67th Place from north of W 64th Street to NW 122nd Street/W 68th Street




Figure 2-16| 441831-1-52-01 SR 826 West Frontage Roads Typical Section – NW 77th Court from north of NW 103rd Street to south of the Little River Canal




Figure 2-17| 441831-1-52-01 SR 826 West Frontage Roads Typical Section – 20th Avenue West from south of the Little River Canal to south of W 60th Street and from north of W 60th Street to NW 122nd Street/W 68th Street




Figure 2-18 | 441831-1-52-01 SR 826 West Frontage Roads Typical Section – W 20th Avenue West from south of W 60th Street to north of W 60th Street




Figure 2-19 | 441831-1-52-01 SR 826 East Frontage Road Bridge Typical Section – Bridge 870570, W 20th Avenue East over the Little River Canal





Figure 2-20 | 441831-1-52-01 SR 826 West Frontage Road Bridge Typical Section – Bridge 870569, W 20th Avenue East over the Little River Canal



2.1.2 Roadway Classification

The FDOT classifies roadways according to the nature and character of their uses. Functional Classification defines the role that a particular roadway plays in serving the flow of vehicular traffic through the network. The functional classification of SR 826 (86070000) is that of a Freeway/Expressway that serves as a major north/south mode of transportation for Miami Dade County. SR 826 is also designated as an SIS corridor, which is part of a statewide network of high priority transportation facilities that are critical to Florida's economic competitiveness.

The Access Management classification of SR 826 is Access Class 1 (Limited Access).

The functional classification of the Frontage Roads (86006000) is that of a local road that serves the commercial businesses adjacent to SR 826.

The FDOT Context Classification in combination with Transportation Characteristics of a roadway will determine key design criteria for all non-limited-access state roadways. The Context Classification system describes the general characteristics of the land use, development patterns, and roadway connectivity, providing cues as to the types of uses and user groups that will likely utilize the roadway. The Transportation Characteristics define the type of access the roadway provides, the types of trips served, and the users served. The Context Classification designation for the Frontage Roads is C3-Suburban Commercial.

2.1.3 Vertical Alignment

The vertical profile of SR 826 was obtained from the Financial Project Identification Number (FPID) 430795-1-52-0 plans. Within the limits of the study, the SR 826 profile slopes upward to a high point with an elevation of approximately 40' as it passes over NW 36th Street, and slopes downward and continues with minimal elevation changes between approximate elevations of 12' and 14', passing under NW 58th Street, north of NW 58th Street the profile slopes upward passing over NW 74th Street at an approximate elevation of 39.5'. North of 74th Street the profile continues elevated with a low point of approximately 27', and passes over NW South River Drive and Okeechobee Road with an elevation of approximately 38', the profile then slopes downward to an elevation of approximately 13' before rising again to an approximate elevation of 38 'and passing over NW 103rd Street, north of NW 103rd Street the profile slopes downward to a low point of approximately 14' in elevation, and sloping upward once more to an approximate elevation of 33.5' as it passes over NW 54th Street.

The partial vertical profiles of the west and east frontage roads were obtained from as-built plans. Within the limits of the study, the existing grades of the frontage roads vary from 0.0% minimum to approximately 2.5% maximum.

2.1.4 Horizontal Alignment

2.1.4.1 SR 826

The existing geometry of SR 826 is mostly linear between NW 36th Street and NW 154th Street. **Table 2-1** provides a summary of the existing horizontal alignment data.

Table 2-1 | Horizontal Alignment: SR 826

| Curve Ref. # | Reference Station Limits | Design Speed (mph) | Curve Length (feet) | Radius | Degree |
|--------------|--|--------------------|---------------------|-----------|----------|
| C3 | PC Sta. 537+55.08 to PT Sta. 546+56.46 | 60 | 901.38 | 61,756.14 | 0°05'34" |
| C4 | PC Sta. 608+10.72 to PT Sta. 612+21.47 | 60 | 410.76 | 18,000 | 0°19'06" |

2.1.4.2 SR 826 Ramps

Summary of the existing horizontal alignment data for the SR 826 Ramps is provided in **Table 2-2** to **Table 2-5**.

Table 2-2 | Horizontal Alignment: Ramp A – SR 826 SB Off-Ramp at NW 74th Street

| Curve Ref. # | Design Speed (mph) | Curve Length (feet) | Radius |
|--------------|--------------------|---------------------|--------|
| C1 | 40 | 53.95 | 50 |
| C2 | 55 | 87.92 | 220 |

Table 2-3 | Horizontal Alignment: Ramp B – SR 826 SB Off-Ramp at NW 103rd Street

| Curve Ref. # | Design Speed (mph) | Curve Length (feet) | Radius | Degree |
|--------------|--------------------|---------------------|---------|-----------|
| C1 | 40 | 484.45 | 5754 | 00°59'45" |
| C2 | 40 | 518.26 | 5642.57 | 01°00'56" |

Table 2-4 | Horizontal Alignment: Ramp C – SR 826 SB On-Ramp at NW 77th Avenue

| Curve Ref. # | Design Speed (mph) | Curve Length (feet) | Radius | Degree |
|--------------|--------------------|---------------------|--------|-----------|
| C1 | 60 | 400.05 | 5834 | 00°58'56" |
| C2 | 40 | 379.41 | 5730 | 01°00'00" |

Table 2-5 | Horizontal Alignment: Ramp E – SR 826 NB Off-Ramp at NW 103rd Street

| Curve Ref. # | Design Speed (mph) | Curve Length (feet) | Radius | Degree |
|--------------|--------------------|---------------------|----------|-----------|
| C1 | 55 | 400.05 | 9,822.14 | 00°35'00" |

2.1.4.3 SR 826 Frontage Roads

2.1.4.3.1 441830-1-52-01 project limits

Seven horizontal curves are located within the project limits. The curve data is summarized in Table 2-6, based on the plans from the previous projects and the design survey. The existing horizontal curves C1, C2, C4 and C6 are sub-standard with criteria for minimum radius. All existing horizontal curves are sub-standard with criteria for minimum curve length.

Table 2-6 | Horizontal Alignment: SR 826 Frontage Roads 441830-1-52-01 project limits

| Curve Ref. # | Original Construction Project | Reference Station Limits | Design Speed (mph) | Curve Length (feet) | Radius | Degree | Super Elevation Rate | |
|--|-------------------------------|---|--------------------|---------------------|----------|-----------|----------------------|-----------------------------|
| | | | | | | | Existing | Required ($e_{max}=0.05$) |
| East Frontage Road/W 20th Avenue (section 87260151) | | | | | | | | |
| C1 | State Project 87260-3501 | PC Sta. 200+26.67 to PT Sta. 201+39.17 | 15 | 112.50 | 72.00 | 79°34'39" | NC | 0.044 |
| C2 | State Project 87260-3501 | PC Sta. 202+88.51 to PT Sta. 203+56.51 | 15 | 68.00 | 80.00 | 71°37'11" | RC | 0.042 |
| C3 | State Project 87260-3529 | PC Sta. 208+57.66 to PT Sta. 210+84.92 | 30 | 227.26 | 290.00 | 19°45'26" | 0.087 | 0.050 |
| C4 | State Project 87260-3529 | PC Sta. 213+62.45 to PCC Sta. 215+43.84 | 30 | 181.39 | 250.00 | 22°55'06" | 0.089 | 0.050 |
| C5 | FPID 432687-1-52-01 | PCC Sta. 215+43.84 to PT Sta. 216+00.00 | 30 | 56.16 | 974.95 | 5°52'36" | 0.064 | NC |
| West Frontage Road/NW 77th Avenue (section 87260152) | | | | | | | | |
| C6 | FPID 249653-1-52-01 | PC Sta. 700+30.87 to PT Sta. 701+43.48 | 20 | 112.60 | 175.00 | 32°44'26" | 0.082 | 0.042 |
| C7 | FPID 432687-1-52-01 | PC Sta. 706+52.17 to PT Sta. 707+58.81 | 30 | 106.64 | 1,528.36 | 03°44'56" | NC | NC |

2.1.4.3.2 441831-1-52-01 project limits

Twelve existing horizontal curves are located within the project limits. The curve data is summarized in Error! Reference source not found. 2-7, based on the plans from the previous projects and the design survey. The existing horizontal curves C6, C7, C8, and C12 are sub-standard with criteria for minimum radius. All existing horizontal curves, except C3, are sub-standard with criteria for minimum curve length.

Table 2-7 | Horizontal Alignment: SR 826 Frontage Roads 441831-1-52-01 project limits

| Curve Ref. # | Original Construction Project | Reference Station Limits | Design Speed (mph) | Curve Length (feet) | Radius | Degree | Super Elevation Rate | |
|--|-------------------------------|---|--------------------|---------------------|----------|-------------|----------------------|-----------------------------|
| | | | | | | | Existing | Required ($e_{max}=0.05$) |
| East Frontage Road/W 20th Avenue East (section 87260298) | | | | | | | | |
| C1 | FPID 249113-1-52-01 | PC Sta. 301+34.70 to PT Sta. 303+24.65 | 30 | 189.95 | 3,340.00 | 1°42'56" | NC | NC |
| C2 | FPID 249113-1-52-01 | PC Sta. 307+34.73 to PT Sta. 308+46.31 | 30 | 111.59 | 2,520.00 | 2°16'25" | NC | NC |
| C3 | State Project 87260-3573 | PC Sta. 353+00.58 to PT Sta. 357+39.20 | 30 | 438.62 | 430.00 | 13°19'29" | 0.070 | RC |
| C4 | State Project 87260-3536 | PC Sta. 360+14.80 to PT Sta. 362+29.30 | 20 | 214.50 | 275.00 | 20°50'05" | 0.050 | 0.036 |
| C5 | State Project 87260-3536 | PC Sta. 363+39+62 to PT Sta. 365+45.07 | 20 | 205.45 | 150.00 | 38°11'50" | 0.070 | 0.044 |
| C6 | N/A | PC Sta. 372+09.16 to PT Sta. 373+28.45.00 | 15 | 119.29 | 76.00 | 75°23'21" | NC | N/A |
| West Frontage Road/NW 77th Avenue (section 87260152) | | | | | | | | |
| C7 | FPID 249113-1-52-01 | PC Sta. 406+17+76 to PT Sta. 407+42.31 | 20 | 124.55 | 100.00 | 57°17'45" | NC | 0.049 |
| C8 | FPID 249113-1-52-01 | PC Sta. 408+93.36 to PT Sta. 409+68.42 | 15 | 75.06 | 47.00 | 121°54'2 1" | NC | N/A |
| West Frontage Road/W 20th Avenue West (section 87260521) | | | | | | | | |
| C9 | State Project 87260-3534 | PC Sta. 450+69.64 to PT Sta. 453+54.36 | 35 | 284.73 | 1,885.00 | 3°02'22" | NC | NC |
| C10 | State Project 87260-3534 | PC Sta. 455+68.30 to PT Sta. 458+78.52 | 35 | 310.23 | 2,115.00 | 2°42'32" | NC | NC |
| C11 | State Project 87260-3534 | PC Sta. 462+12.54 to PT Sta. 464+41.60 | 20 | 229.06 | 150.00 | 38°11'50" | 0.100 | 0.044 |
| C12 | State Project 87260-3534 | PC Sta. 469+85.61 to PT Sta. 471+00.48 | 15 | 114.87 | 75.00 | 76°23'40" | NC | N/A |

2.1.5 Frontage Roads Existing Deficiencies

2.1.5.1 Lane Widths

2.1.5.1.1 441830-1-52-01 project limits

The existing lane widths were reviewed based on the plans of the previous projects and the design survey. The existing travel lane widths are typically 12 feet, except in the following segments.

- W 20th Avenue, 11 feet wide lanes in the two-way segment from south of W 39th Street to W 41st Street
- NW 77th Avenue, 11 feet wide through lane and 15 feet wide on-ramp lane in the one-way segment from NW 99th Street to NW 103rd Street

2.1.5.1.2 441831-1-52-01 project limits

The existing lane widths were reviewed from the plans of the previous projects and the design survey. The existing travel lane widths are typically 11-12 feet. The existing turn lane widths are typically 10-11 feet.

2.1.5.2 Shoulder Widths

2.1.5.2.1 441830-1-52-01 project limits

Flush shoulders are located throughout the project limits. A review of the plans from the previous resurfacing projects indicates the existing shoulder width vary as follows:

- East Frontage Road/W 20th Avenue (Section 87260151)
 - Typical Section 1 – From Okeechobee Road to south of W 39th Street
 - Full-width shoulder = 8 feet typical (LT and RT)
 - No paved shoulders
 - Typical Section 2 – From south of W 39th Street to W 41st Street
 - Full-width shoulder = minimum 2.5 feet LT at the SR 826 barrier wall and varies 6-8 feet RT
 - Paved shoulder width = minimum 2.5 feet LT and no paved shoulder RT
 - Typical Section 3 – From W 41st Street to W 44th Place
 - Full-width shoulder = ± 2 feet typical (LT and RT) at landscaping areas
 - No paved shoulders
- West Frontage Road/NW 77th Avenue (Section 87260152)
 - Typical Section 4 – From south project limit to south of Walmart Driveway and from north of NW 95th Street to NW 98th Street
 - Full-width shoulder = 8 feet typical (LT and RT)
 - No paved shoulders

- Typical Section 5 – From south of Walmart Driveway to north of NW 95th Street
 - Full-width shoulder = minimum 2.5 feet RT at the SR 826 barrier wall and 6 feet typical LT
 - Paved shoulder width = minimum 2.5 feet RT and no paved shoulder LT
- Typical Section 6 – From NW 98th Street to NW 103rd Street
 - Full-width shoulder = 2-6 feet RT
 - Paved shoulder width = 1-2 feet RT
 - No LT shoulder at existing drop curb and trench drain

2.1.5.2.2 441831-1-52-01 project limits

Flush shoulders are located throughout most of the project limits. A review of the plans from the previous resurfacing projects indicates the existing shoulder width vary as follows:

- East Frontage Road/W 20th Avenue East (section 87260298)
 - Roadway Typical Section 1 – From NW 103rd Street to south of Little River Canal
 - Full-width shoulder = 6 feet LT
 - Paved shoulder width = 2 feet LT
 - Roadway Typical Section 2 – From south of Little River Canal to north of W 64th Street, Exceptions are Little River Canal Bridge and from south of W 60th Street to north of W 60th Street
 - Full-width shoulder = 8 feet LT and 6 feet RT
 - No paved shoulders
 - Roadway Typical Section 3 – From south of W 60th Street to north of W 60th Street
 - No shoulders at curb & gutter segment
 - Roadway Typical Section 4 – W 67th Place, from north of W 64th Street to NW 122nd Street/W 68th Street
 - No shoulders at curb & gutter segment
 - Bridge Typical Section 1 – W 20th Avenue East over Little River Canal
 - 5 feet shoulders (LT & RT)
- West Frontage Road/NW 77th Court (section 87260506), Roadway Typical Section 5, From north of NW 103rd Street to south of Little River Canal
 - No shoulders at curb & gutter segment
- West Frontage Road/W 20th Avenue West (section 87260521)
 - Roadway Typical Section 6, From south of Little River Canal to NW 122nd Street/ W 68th Street, Exceptions are Little River Canal Bridge and from south of W 60th Street to north of W 60th Street

- Full-width shoulder = 6 feet LT and 8 feet RT
- No paved shoulders
- Roadway Typical Section 7, From south of W 60th Street to north of W 60th Street
 - Paved shoulder width = 2 feet RT at barrier wall
 - No LT shoulder at curb & gutter segment
- Bridge Typical Section 2 – W 20th Avenue West over Little River Canal
 - 2 feet shoulders (LT & RT)

2.1.5.3 Pedestrian and bicyclists

2.1.5.3.1 441830-1-52-01 project limits

The existing sidewalk widths (5 feet typical) meet RRR criteria per FDM Table 222.1.1. The following sub-standard conditions were identified:

- Damaged and Uneven Sidewalk at multiple segments
- Unobstructed Sidewalk Width – The existing unobstructed sidewalk width at several utility poles is sub-standard (less than 32 inches) along the East Frontage Road/W 20th Avenue
 - Two utility poles north of W 35th Street
 - One utility pole north of the Best Buy driveway
 - One utility pole north of Southern Winds Hospital (First Driveway)
 - One utility pole north of Florida National College (Second Driveway)

The existing pedestrian ramps were evaluated for compliance with the FDOT Standard Plans for Road Construction and ADA Standards.

- Pedestrian ramps are not provided at several locations.
- The existing ramp slopes were field verified with a smart level and some existing pedestrian ramps do not meet current FDOT requirements for ramp slope, landing width or cross slope, or transition slope.
- Most existing pedestrian ramps within the project limits have no detectable warning surface or have a sub-standard concrete tactile surface.

No existing designated bicycle facilities are present within the project limits. The existing shoulders are unpaved throughout most of the project limits.

2.1.5.3.2 441831-1-52-01 project limits

The existing sidewalk widths (5-6 feet) meet RRR criteria per FDM Table 222.1.1. The following sub-standard conditions were identified:

- Damaged and Uneven Sidewalk at multiple segments

- Unobstructed Sidewalk Width – The existing unobstructed sidewalk width at one existing utility pole is sub-standard (less than 32 inches) along the West Frontage Road/W 20th Avenue south of W 64th Street
- Unobstructed Sidewalk Width – The existing unobstructed sidewalk width is sub-standard (less than 48 inches) at the following locations:
 - Two mast arm signal poles at W 20th Ave. East and W 60th St. (SE and NE corners)
 - One mast arm signal pole at W 20th Ave. West and W 60th St. (SW corner)
 - One light pole along W 20th Ave. East north of NW 103rd St.
 - Two light poles along NW 77th Ct. north of NW 103rd St.
 - One newspaper bin (El Clarin) at W 20th Ave. West, north of W 52nd St.

The existing pedestrian ramps were evaluated for compliance with the FDOT Standard Plans for Road Construction and ADA Standards.

- Pedestrian ramps are not provided at several locations.
- The existing ramp slopes were field verified with a smart level and some existing pedestrian ramps do not meet current FDOT requirements for ramp slope, landing width, cross slope, or transition slope.
- Most existing pedestrian ramps within the project limits have no detectable warning surface or have a sub-standard concrete tactile surface.

Two signalized intersections are located within the project limits:

- East Frontage Road/W 20th Avenue East at W 60th Street (Asset 5914)
- West Frontage Road/W 20th Avenue West at W 60th Street (Asset 5913)

No existing designated bicycle facilities are present within the project limits. The existing shoulders are unpaved throughout most of the project limits.

2.1.5.4 Sidewalks

2.1.5.4.1 441830-1-52-01 project limits

No existing sidewalks are present along the West Frontage Road/NW 77th Avenue (section 87260152). Existing sidewalk is located along the East Frontage Road/W 20th Avenue (section 87260151) along the right side of the roadway in three discontinuous segments covering most of the limits:

- From W 35th Street (sta. 202+01) to the second driveway at Westland Promenade (sta. 209+89)
- From W 39th Street (sta. 217+03) to the driveway at Citrus Health Center (sta. 226+06)
- From the driveway at Southern Winds Hospital (sta. 228+15) to W 44th Place (sta. 236+82)

2.1.5.4.2 441831-1-52-01 project limits

Existing sidewalk is located along the Frontage Roads throughout most of the project limits in the following discontinuous segments:

- East Frontage Road/W 20th Avenue East (section 87260298)
 - Existing sidewalk along the RT side from NW 103rd Street (sta. 300+63) to W 64th Street (sta. 354+36)
 - Existing sidewalk along the RT side from a point north of W 64th Street (sta. 357+42) to the end of the segment at NW 122nd Street/W 68th Street (sta. 373+34).
- West Frontage Road/NW 77th Court (section 87260506)
 - Existing sidewalk along the LT side from NW 103rd Street (sta. 400+91) to the end of the segment south of the Little River Canal (sta. 409+23).
- West Frontage Road/W 20th Avenue West (section 87260521)
 - Existing sidewalk along the LT side from W 52nd Street (sta. 413+19) to W 62nd Street (sta. 445+98).
 - Existing sidewalk along the LT side from a point south of W 64th Street (sta. 450+26) to a point north of W 64th Street (sta. 455+22).
 - Existing sidewalk along the LT side of W 67th Place, from a point east of W 21st Avenue (sta. 466+98) to the end of the segment at NW 122nd Street/W 68th Street (sta. 471+35).

2.2 Existing ITS Conditions

The existing ITS devices within the study limits on SR 826 are currently operated, monitored, and managed from the FDOT District Six SunGuide Transportation Management Center (TMC) using the SunGuide software to control and monitor the existing ITS devices. The following is a description of all the existing ITS devices within the study area and the potential impacts on them for the proposed improvements as part of the Preferred Alternative.

2.2.1 ITS Devices

Pan-Tilt-Zoom (PTZ) CCTV cameras: Within the study limits, the District Six TMC operates six (6) CCTV cameras along SR 826. It is anticipated that each of these camera locations would be affected by the Preferred Alternative and will require relocation or replacement.

Microwave Vehicle Detection System (MVDS): Within the study limits, the District Six TMC operates forty-seven (47) MVDS along SR 826. Most of these devices will remain and be calibrated, however twelve (12) will require replacement.

Dynamic Messaging Signs (DMS): Within the study limits, the District Six TMC operates fifteen (15) DMS used for the freeway operations, seven (7) lane status DMS and eight (8) toll amount DMS. All of these devices will be removed and replaced.

Wireless Access Points (WAP): Within the study limits, the District Six TMC operates two (2) WAPs along SR 826. Both of these WAP locations would be affected by the Preferred Alternative and most likely require relocation.

Ramp Signaling System (RSS): Within the study limits, the District Six TMC operates two (2) RSS sites along SR 826, both at the interchange with 103rd St. The RSS consists of several components which include loop detectors, (ramp queue loop, demand loop, and passage loop), flashing beacons, ramp signal heads, and ramp signal cabinets (RSC). The RSS will be impacted by the Preferred Alternative and require replacement.

Table 2-8 | Existing ITS Devices

| DEVICE TYPE | PLAN ID | SUNGUIDE ID | STATION | NOTES |
|-------------|-------------------|----------------------------|---------|------------------|
| CCTV | CCTV 826-21-TADMS | 1624-826EL008.84-VCCTV | 302+24 | TO BE REMOVED |
| CCTV | CCTV 826-55-RSS | 1663-826RS013.18-VCCTV2 | 529+97 | TO BE REMOVED |
| CCTV | CCTV 826-53-EX | 1661-826EL013.2-CCTV | 531+27 | TO BE REMOVED |
| CCTV | CCTV 826-56-RSS | 1664-826RS013.2-VCCTV | 531+27 | TO BE REMOVED |
| CCTV | CCTV 826-57-EX | 1665-826EL013.33-CCTV-CCTV | 535+01 | TO BE REMOVED |
| CCTV | CCTV 826-58-RSS | 1666-826RS013.33-VCCTV | 535+01 | TO BE REMOVED |
| DMS | LSDMS 826-07-EX | DMS-826ELNB011.68-LS | 451+00 | TO BE REMOVED |
| DMS | TADMS 826-13-EX | DMS-826ELNB011.92-TA1 | 467+59 | TO BE REMOVED |
| DMS | TADMS 826-14-EX | DMS-826ELNB011.92-TA2 | 467+59 | TO BE REMOVED |
| DMS | LSDMS 826-08-EX | DMS-826ELNB012.14-LS | 478+00 | TO BE REMOVED |
| DMS | LSDMS 826-06-EX | DMS-826ELNB009.61-LS | 488+85 | TO BE REMOVED |
| DMS | DMS 826-06-SB | DMS-826SB013.74 | 563+76 | TO BE REMOVED |
| DMS | LSDMS 826-11-EX | DMS-826ELSB016.27-LS | 693+61 | TO BE REMOVED |
| DMS | TADMS 826-19-EX | DMS-826ELSB016.41-TA1 | 701+61 | TO BE REMOVED |
| DMS | TADMS 826-20-EX | DMS-826ELSB016.41-TA2 | 701+61 | TO BE REMOVED |
| DMS | TADMS 826-21-EX | DMS-826ELSB016.41-TA3 | 701+61 | TO BE REMOVED |
| DMS | LSDMS 826-11A-EX | DMS-826ELSB016.76-LS | 717+98 | TO BE REMOVED |
| DMS | TADMS 826-22-EX | DMS-826ELSB016.96-TA1 | 728+34 | TO BE REMOVED |
| DMS | TADMS 826-23-EX | DMS-826ELSB016.96-TA2 | 728+34 | TO BE REMOVED |
| DMS | TADMS 826-24-EX | DMS-826ELSB016.96-TA3 | 728+34 | TO BE REMOVED |
| DMS | LSDMS 826-12-EX | DMS-826ELSB017.20-LS | 742+51 | TO BE REMOVED |
| MVDS | MVDS 826-56-SB | DS-826SB011.41 | 437+66 | TO BE CALIBRATED |
| MVDS | MVDS 826-57-EX | DS-826ELNS011.41 | 437+66 | TO BE CALIBRATED |
| MVDS | MVDS 826-58-NB | DS-826NB011.68 | 451+00 | TO BE REMOVED |

| | | | | |
|------|-----------------|------------------|--------|------------------|
| MVDS | MVDS 826-60-EX | DS-826ELNB011.68 | 451+00 | TO BE REMOVED |
| MVDS | MVDS 826-59-SB | DS-826SB011.68 | 451+00 | TO BE REMOVED |
| MVDS | MVDS 826-61-EX | DS-826ELSB011.68 | 451+00 | TO BE REMOVED |
| MVDS | MVDS 826-65-EX | DS-826ELSB011.92 | 467+59 | TO BE CALIBRATED |
| MVDS | MVDS 826-63-SB | DS-826SB011.92 | 467+59 | TO BE CALIBRATED |
| MVDS | MVDS 826-65B-SB | DS-826SB012.04 | 473+95 | TO BE CALIBRATED |
| MVDS | MVDS 826-63A-SB | DS-826SB012.23 | 485+44 | TO BE CALIBRATED |
| MVDS | MVDS 826-64A-EX | DS-826ELNS012.23 | 485+44 | TO BE CALIBRATED |
| MVDS | MVDS 826-63B-SB | DS-826SB012.45 | 497+19 | TO BE CALIBRATED |
| MVDS | MVDS 826-66-SB | DS-826SB012.67 | 505+49 | TO BE CALIBRATED |
| MVDS | MVDS 826-67-EX | DS-826ELNS012.67 | 505+49 | TO BE CALIBRATED |
| MVDS | MVDS 826-67A-SB | DS-826SB012.72 | 508+50 | TO BE CALIBRATED |
| MVDS | MVDS 826-68-NB | DS-826NB013.00 | 522+00 | TO BE REMOVED |
| MVDS | MVDS 826-69-SB | DS-826SB013.00 | 522+00 | TO BE REMOVED |
| MVDS | MVDS 826-70-EX | DS-826ELNS013.00 | 522+00 | TO BE REMOVED |
| MVDS | MVDS 826-71A-SB | DS-826SB013.20 | 531+27 | TO BE REMOVED |
| MVDS | MVDS 826-71B-NB | DS-826NB013.33 | 535+01 | TO BE REMOVED |
| MVDS | MVDS 826-71-SB | DS-826SB013.34-A | 539+08 | TO BE CALIBRATED |
| MVDS | MVDS 826-72-SB | DS-826SB013.34-B | 539+08 | TO BE CALIBRATED |
| MVDS | MVDS 826-73-EX | DS-826ELSB013.34 | 539+08 | TO BE CALIBRATED |
| MVDS | MVDS 826-75-SB | DS-826SB013.70 | 558+06 | TO BE CALIBRATED |
| MVDS | MVDS 826-76-EX | DS-826ELNS013.70 | 558+06 | TO BE CALIBRATED |
| MVDS | MVDS 826-78-SB | DS-826SB014.00 | 574+85 | TO BE CALIBRATED |
| MVDS | MVDS 826-79-EX | DS-826ELNS014.00 | 574+85 | TO BE CALIBRATED |
| MVDS | MVDS 826-79B-SB | DS-826SB014.12 | 582+38 | TO BE CALIBRATED |
| MVDS | MVDS 826-81-SB | DS-826SB014.38 | 591+00 | TO BE CALIBRATED |

| | | | | |
|------|------------------|---------------------|--------|------------------|
| MVDS | MVDS 826-83-EX | DS-826ELSB014.38 | 591+00 | TO BE CALIBRATED |
| MVDS | MVDS 826-83A-SB | DS-826SB014.51 | 601+00 | TO BE CALIBRATED |
| MVDS | MVDS 826-85-SB | DS-826SB014.68 | 610+16 | TO BE CALIBRATED |
| MVDS | MVDS 826-86-EX | DS-826ELNS014.68 | 610+16 | TO BE CALIBRATED |
| MVDS | MVDS 826-87-NB | DS-826NB014.96-A | 624+06 | TO BE REMOVED |
| MVDS | MVDS 826-88-EX | DS-826ELNB014.96 | 624+06 | TO BE REMOVED |
| MVDS | MVDS 826-88A-NB | DS-826NB014.96-B | 624+06 | TO BE REMOVED |
| MVDS | MVDS 826-89-SB | DS-826SB014.99 | 626+53 | TO BE CALIBRATED |
| MVDS | MVDS 826-90-EX | DS-826ELSB014.99 | 626+53 | TO BE CALIBRATED |
| MVDS | MVDS 826-92-SB | DS-826SB015.35-A | 645+65 | TO BE CALIBRATED |
| MVDS | MVDS 826-93-SB | DS-826SB015.35-B | 645+65 | TO BE CALIBRATED |
| MVDS | MVDS 826-94-EX | DS-826ELNS015.35-A | 645+65 | TO BE CALIBRATED |
| MVDS | MVDS 826-95-EX | DS-826ELNS015.35-B | 645+65 | TO BE CALIBRATED |
| MVDS | MVDS 826-97-EX | DS-826ELNS015.70 | 663+43 | TO BE CALIBRATED |
| MVDS | MVDS 826-98-SB | DS-826SB015.70 | 663+63 | TO BE CALIBRATED |
| MVDS | MVDS 826-100-SB | DS-826SB016.08 | 681+50 | TO BE CALIBRATED |
| MVDS | MVDS 826-100A-EX | DS-826ELSB016.08 | 681+50 | TO BE CALIBRATED |
| MVDS | MVDS 826-81A-SB | DS-826SB016.21 | 690+42 | TO BE CALIBRATED |
| RSS | RSS 826-13-SB | RSS-826SBNW103ST-WB | 517+43 | TO BE REMOVED |
| RSS | RSS 826-14-SB | RSS-826SBNW103ST-EB | 525+92 | TO BE REMOVED |
| WAP | WAP 826-07-WB | - | 531+27 | TO BE REMOVED |
| WAP | WAP 826-08-EB | - | 531+27 | TO BE REMOVED |

2.3 Existing Structures

There are thirteen existing bridges within the study limits:

Table 2-9 | Existing Structures

| Bridge ID | Bridge No. | Bridge Description | Existing Superstructure Type |
|-----------|------------|---|------------------------------|
| B1 | 870856 | Flyover bridge from SR 932 westbound to SR 826 Southbound | Steel Plate Girders |
| B2 | 870257 | Southbound SR 826 over Metrorail | Concrete Beams |
| B3 | 870569 | SR 826 west Frontage Road over Little River Canal | Concrete Slabs |
| B4 | 870570 | SR 826 east Frontage Road over Little River Canal | Concrete Slabs |
| B5 | 870258 | Southbound SR 826 over FEC Railroad | Concrete Beams |
| B6 | 870964 | Southbound SR 826 at SR 934/NW 74 th Street | Steel Plate Girders |
| B7A | 870757 | Southbound SR 826 at SR 932/NW 103 rd Street | Concrete Beams |
| B7B | 870995 | Northbound SR 826 at SR 932/NW 103 rd Street | Concrete Beams |
| B8 | 870975 | SR 826 over S. River Dr. / Miami Canal / Okeechobee Road | Steel Plate Girders |
| B9 | 870758 | SR 826 over Little River Canal | Concrete Beams |
| B10 | 870957 | SR 826 over W 60 th Street | Concrete Beams |
| B11 | 870766 | SR 826 over NW 122th Street | Steel Plate Girders |
| B12 | 870467 | SR 826 over NW 138 th Street | Concrete Beams |

| | | | |
|--|--------|---|---------------------|
| | 870977 | US 27 NB to SR 826 SB flyover | Steel Plate Girders |
| | 870755 | SR 826 SB off ramp to NW 103 rd St. | Concrete Beams |
| | 870756 | SR 826 NB on ramp from NW 103 rd St. | Concrete Beams |
| | 870643 | SR 826 NB to I-75 NB flyover | Concrete Box |
| | 871096 | SR 826 Express Lanes to/from I-75 Express Lanes | Concrete Box |

2.3.1 Historical Significance

The historical significance of the existing bridges within the project study area along SR 826 were reviewed to determine if any are considered historic or possess any substantial community value. All the bridges in the study area are not eligible for the National register of Historic Places as they are not more than 50 years old and have mostly been widened. As such, these bridges are either non-historic or have non-historic reconstruction dates.

2.4 Existing Lighting Conditions

The existing roadway lighting along SR 826 southbound and northbound mainline and ramps within the project limits consists of a combination of median barrier wall mounted light poles with 400 watt High Pressure Sodium (HPS) luminaires at 45 feet mounting height attached on two 15 feet bracket arms opposite to each other , bridge mounted light poles with 400 watt HPS luminaires at 45 feet mounting height attached one 15' bracket arm, and on the outside shoulders, barrier wall mounted light poles with 250 watt HPS luminaires at 35 feet mounting height attached on 8 feet bracket arm . Also, there are light poles mounted on the west outside barrier walls of SR 826 with a 35 feet mounting height measured from SR 826 roadway surface and one 15 feet bracket arm with a 400 watt HPS luminaire facing west side to illuminate NW 77th Avenue from Okeechobee Road to NW 103rd Street. The existing conventional lighting system appears to be in good physical condition.

SR 826 frontage road/W 20th Avenue East and West intersections with NW 103rd Street roadway lighting assemblies consists of 250 watt and 400 watt HPS luminaires at 35 feet and 45 feet mounting heights respectively attached on single bracket arms. The intersections of SR 826 frontage roads at W 60th Avenue East and West does not have existing FDOT lighting and there are few power poles with 250 watt HPS luminaires.

Existing conventional lighting assemblies at NW 77th Court (West Frontage Road), W 20th Avenue West (West Frontage Road), W 20th Avenue East (East Frontage Road) roadway segments excluding the intersections at NW 103rd Street and W 60th Street lighting consist of 250 watt HPS luminaires attached on aluminum, concrete and power company wooden poles with an approximate mounting height between 30 to 40 feet and one 8 feet bracket arm.

2.5 Pedestrian and Bicycle Facilities

SR 826/Palmetto Expressway is a limited access facility and does not have pedestrian and bicycle facilities.

No existing sidewalks are present along the West Frontage Road/NW 77th Avenue (section 87260152).

Existing sidewalk is located along the East Frontage Road/W 20th Avenue (section 87260151) along the right side of the roadway in three discontinuous segments covering most of the limits:

- From W 35th Street (sta. 202+01) to the second driveway at Westland Promenade (sta.

209+89)

- From W 39th Street (sta. 217+03) to the driveway at Citrus Health Center (sta. 226+06)
- From the driveway at Southern Winds Hospital (sta. 228+15) to W 44th Place (sta. 236+82)

East Frontage Road/W 20th Avenue East (section 87260298)

- Existing sidewalk along the RT side from NW 103rd Street (sta. 300+63) to W 64th Street (sta. 354+36)
- Existing sidewalk along the RT side from a point north of W 64th Street (sta. 357+42) to the end of the segment at NW 122nd Street/W 68th Street (sta. 373+34).

West Frontage Road/NW 77th Court (section 87260506)

- Existing sidewalk along the LT side from NW 103rd Street (sta. 400+91) to the end of the segment south of the Little River Canal (sta. 409+23).

West Frontage Road/W 20th Avenue West (section 87260521)

- Existing sidewalk along the LT side from W 52nd Street (sta. 413+19) to W 62nd Street (sta. 445+98).
- Existing sidewalk along the LT side from a point south of W 64th Street (sta. 450+26) to a point north of W 64th Street (sta. 455+22).
- Existing sidewalk along the LT side of W 67th Place, from a point east of W 21st Avenue (sta. 466+98) to the end of the segment at NW 122nd Street/W 68th Street (sta. 471+35).

On the frontage road, no existing designated bicycle facilities are present within the project limits.

2.6 Transit Facilities

2.6.1 Miami Dade Transit


2.6.1.1 Transit Ridership

MDT, the public transit authority in Miami-Dade County, has the following routes that service the arterials that cross SR 826: Routes 29, 33, 36, 95 and 132. There are currently no MDT stops within the study area. The Miami-Dade Transit Technical Report dated September of 2020, outlines the following average monthly boardings for the routes within the project limits to be as follows:

- Route 29: 13,388 monthly boardings
- Route 33: 40,412 monthly boardings
- Route 36: 58,566 monthly boardings
- Route 95 Express Golden Glades: 36,052 monthly boardings
- Route 132 Tri-Rail Doral Shuttle: 289 monthly boardings

Figure 2-21 to Figure 2-25 show the detailed map of the transit routes within the project limits.

Figure 2-21 | Route 29

**29**NORTH
MAP NOT TO SCALE
09/2019

@GoMiamiDade



GO Miami-Dade Transit

06.2020

miamidade.gov/transit 311 or 305.468.5900 TTY/Fla Relay: 711



Figure 2-22 | Route 33




Figure 2-23 | Route 36

Route 36




Figure 2-24 | Route 95





Figure 2-25 | Route 132

Route 132 Tri-Rail Doral Shuttle



2.6.1.2 SMART Plan

As part of the Department of Transportation and Public Works (DPTW) ten-year program of projects, in an effort to implement mass transit projects in Miami-Dade County, the Strategic Miami Area Rapid Transit (SMART) Plan is the principal initiative. The SMART Plan intends to advance six of the People's Transportation Plan's (PTP) rapid transit corridors, along with a network system of nine Bus Express Rapid Transit (BERT) routes.

DTWP's ten-year implementation plan also includes operational, capital, and state of good repair projects.

2.6.1.2.1 Palmetto Metrorail Station

The existing Palmetto Metrorail Station at SR 826 at NW 74th will undergo improvements as part of the SMART Plan and includes the purchase of a semi-vacant parcel of land located immediately south of the Palmetto Metrorail Station for the purpose of constructing the Palmetto Intermodal Terminal. The proposed improvements also include the design and construction of a 1,000-space parking garage including long-term and short-term parking, kiss-and-ride, pool-and-ride, and a minimum of a 12-bus bay terminal.

2.6.1.2.2 Express Bus System

Within the project limits, there are existing services to be improved as part of the SMART plan, as well as new proposed services.


New proposed service routes within the project limits include:

American Dream-MIC Express, Express Bus service to be implemented from proposed American Dream Transit Terminal east of the Homestead Extension of Florida's Turnpike (HEFT) and west of I-75 between NW 170th Street and the intersection of I-75 and HEFT to the Miami Intermodal Center (MIC).

Palmetto Express (East), from the Palmetto Intermodal Terminal to Golden Glades Multimodal Terminal. Express bus service on EL with 10-minute headways during a.m./p.m. peak hours.

Palmetto Express (West), from Tamiami Station (SW 8th St/SW 147th Ave) to Palmetto Intermodal Terminal. Express bus service on EL with 10-minute headways during a.m./p.m. peak hours.


Figure 2-26 | Express Bus System Vision



2.6.1.2.3 Bus Express Rapid Transit (BERT) Network

There is one BERT Network route within the project limits. The N.W. Miami-Dade Express route, running from the Palmetto Metrorail Station to Miami Gardens Drive Park-n-Ride via the Palmetto expressway. This route began service on November 18, 2018, with weekday peak hour service runs every morning from 5:30-9:30 a.m. and every afternoon from 3:30-7:30 p.m. The N.W. Miami-Dade Express route is also a transit project outlined in the Miami-Dade Long Range Transportation Plan. Route location is shown in **Figure 2-21**.

Figure 2-27 | SMART Plan Map



2.6.2 Frontage Roads

Two existing bus stops are within the project limits along the East Frontage Road/W 20th Avenue, serving the City of Hialeah Transit System, Flamingo Route.

NB Bus Stop at W 20th Avenue, north of W 41th Street

- The existing bus stop meets criteria for a sidewalk connection and boarding & alighting area.
- The existing sidewalk connection is missing a detectable warning surface at the edge of pavement.
- The existing unobstructed sidewalk width is sub-standard (less than 4.0 feet) at the existing bus bench.

NB Bus Stop at W 20th Avenue, south of W 44th Place

- The existing bus stop does not meet criteria for a sidewalk connection or boarding & alighting area; there is no sidewalk connection between the existing sidewalk and edge of pavement.

2.6.3 Metrorail

MDT Metrorail Green Line crosses under SR 826 just north of NW 74th Street to a station just west of SR 826.

2.7 Existing Drainage Systems

The existing drainage within the project limits can be divided into three systems based on existing collection and conveyance systems, interconnected stormwater management facilities, and outfalls. The existing drainage systems have been delineated as follows:

2.7.1 Existing Drainage System SR 826

The project is located in northwestern Miami-Dade County, within the City of Hialeah, City of Doral, and The Town of Medley. In addition, the project runs along Unincorporated Miami-Dade County, and is within the jurisdictional boundary of the South Florida Water Management District (SFWMD), USACE, and Miami-Dade Regulatory and Economic Resources (DRER). The proposed roadway improvements are within the SFWMD Miami Canal, Little River Canal, Peter's Pike Canal, and NW 122 St. Canal Basins.

SFWMD and FDOT have established several criteria for water quality, depending on the proposed type of stormwater treatment facility. The existing conditions throughout the project limits generally consist of an open and close drainage system with swale, ditch bottom inlets along both sides of the roadway, French Drains, and Infield retention pond. Existing facilities is providing water quality treatment and attenuation of roadway runoff.

2.7.2 Existing Drainage System Frontage Road East

The project is located in northwestern Miami-Dade County, within the City of Hialeah, and City of Hialeah Gardens, and is within the jurisdictional boundary of the South Florida Water Management District (SFWMD), USACE, and Miami-Dade Regulatory and Economic Resources (DRER). The proposed roadway improvements are within the SFWMD Little River Canal basin.

SFWMD and FDOT have established several criteria for water quality, depending on the proposed type of stormwater treatment facility. The existing conditions throughout the project limits generally consist of an open drainage system with swale and ditch bottom inlets along both sides of the roadway. Existing facilities is not providing water quality treatment or attenuation of roadway runoff.

2.7.3 Existing Drainage System Frontage Road West

The project is located in northwestern Miami-Dade County, within the City of Hialeah, and City of Hialeah Gardens, and is within the jurisdictional boundary of the South Florida Water Management District (SFWMD), USACE, and Miami-Dade Regulatory and Economic Resources (DRER). The proposed roadway improvements are within the SFWMD Little river Canal basin.

SFWMD and FDOT have established several criteria for water quality, depending on the proposed type of stormwater treatment facility. The existing conditions throughout the project limits generally consist of an open drainage system with swale and ditch bottom inlets along both sides of the roadway. The West Frontage Road/NW 77th Avenue has a trench drain along the west side of the roadway from north of NW 98th Street to NW 103'd Street. Existing facilities is not providing water quality treatment or attenuation of roadway runoff.

2.8 Geotechnical Characteristics

Based on the soil data from the United States Department of Agriculture, Natural Resources Conservation Service (NRCS, 2019) for Miami-Dade County, the project study area is comprised of six (6) mapped soil units. According to the Hydric Soils of Florida Handbook (Hurt, 2007), two (2) of the six (6) soil types identified within the project study area are classified as hydric; the remaining four (4) types are not classified as hydric.

2.9 Utilities

Initial utility agency contact for this project has been coordinated through the District's Utility Coordinator. Existing utility owners and their respective contact personnel are provided in **Table 2-9**. Utility Design ticket is attached in **Appendix D**.

Table 2-10 | Existing Utility Owners

| Type | Location | Utility Agency/Owner | Contact Person | Contact Information |
|--------------|----------|---|------------------|---|
| Telephone | | AT&T Florida | Carlos Moreno | O: (305) 929-4597 M: (954) 531-5876 cm8802@att.com |
| CATV, Fiber | | Atlantic BroadBand | Edwin Zambrana | (305) 861-8069 Ext. 5411 EZambrana@atlanticbb.com |
| Electric | | Buckeye Development and Logistics, LLC | Javares Hall | (305) 213-9908 |
| CATV, Fiber | | Lumen (CenturyLink) | Francisco Azuri | Daniel G. Magnum O: (832) 325-1626 M: (832) 541-3946 DMangum@buckeye.com (786) 266-1713 francisco.azuri@lumen.com |
| | | City of North Miami Beach | Karim Rossy | Karim.Rossy@jacobs.com O: (305) 948-2980 D: (305) 947-7581 ext.7962 |
| CATV, Fiber | | Comcast | Mike Connell | (754) 221-1304 Michael_Connell@comcast.com |
| Fiber | | Crown Castle Fibernet – Ancillary Network Under Crown Castle Branding | Danny Haskett | Danny.Haskett@crowncastle.com O: (786) 610-7073 M: (786) 246-7827 |
| Gas | | Florida City Gas | Elio A. Bustos | O: (305) 835-3618 M: (786) 810-8159 Elio.Bustos@NextEraEnergy.com |
| Gas | | Florida Gas Transmission | Joe Sanchez | O: (407) 838-7171 M: (407) 808-4607 joseph.e.sanchez@energytransfer.com Ph: (305) 442-5129 Cell: (305) 495-9253 angel.vargas@fpl.com |
| Electric | | FPL (Distribution) | Angel A. Vargas | O: (561) 904-3640 M: (561) 523-9896 Michael.Foley@fpl.com |
| Electric | | FPL Transmission | Michael Foley | O: (954) 699-0900 M: (954) 248-7396 walter.sancho-davila@hotwirecommunication.com |
| Water, Sewer | | Miami-Dade Water and Sewer Dept. | Patrick Chong | O: (786) 552-4416 PCHON@miamidade.gov |
| Telephone | | MCI/Verizon | Juan Haber | M: (786) 224-8576 juan.haber@verizon.com |
| Gas | | Suburban Propane | Dimitry Pressman | O: (305) 635-4427 F: (305) 891-0834 DPressman@suburbanpropane.com |
| | | Town of Miami Lakes | Carlos Acosta | 305-364-6100 Ext: 1129 acostac@miamilakes-fl.gov CC: publicworks@miamilakes-fl.gov |

2.10 Design and Posted Speeds

The posted speed limits for the roadways within the study limits are as follows:

- SR 826/Palmetto Expressway: 55 miles per hour
- SR 826/Palmetto Expressway Ramps: 30 miles per hour
- SR 826 East Frontage Road: 20-35 miles per hour

The design speed for the roadways within the project limits are as follows:

- SR 826/Palmetto Expressway: 60 miles per hour
- SR 826/Palmetto Expressway ramps: 30-40 miles per hour
- SR 826 East Frontage Road: 30-40 miles per hour

2.11 Traffic Characteristics

2.11.1 Existing Conditions

Within the project limits, SR 826/Palmetto Expressway is classified as 'Principal Arterial-Other Freeways and Expressways' and consists of six to eight general use lanes and zero to four express (managed) lanes; the typical section varies throughout the project segment. The current typical along the SR 826/Palmetto Expressway northbound consists of one express lane throughout the entire study limits with five general purpose lanes from NW 36th Street to Okeechobee Road and four general purpose lanes from Okeechobee Road to I-75 interchange. The current typical along the SR 826/Palmetto Expressway southbound consists of a single express lane and three general purpose lanes from south of NW 54th Street to south of I-75 interchange; two express lanes and four general purpose lanes from south of I-75 Interchange to north of NW 103rd Street interchange; two express lanes and three general purpose lanes carried through the NW 103rd Street interchange; and, two express lanes and four general purpose lanes from south of NW 103rd Street interchange to north of NW 36th Street interchange.

In addition, SR 826/Palmetto Expressway is part of the state's emergency evacuation network and is a designated Strategic Intermodal System (SIS) highway corridor, providing access via SR 934/NW 74th Street (also known as Hialeah Expressway) and surface streets to the Miami Hialeah FEC Intermodal Terminal, an SIS Freight Rail Terminal.

In addition to the SR 826 facility, frontage roads are located throughout the project limits on both the east and west sides of SR 826. The limits and typical sections of The Frontage Roads are discussed in section 2.1.1. The Frontage Roads are an Urban Local facility generally consisting of a two-lane undivided typical section with flush shoulders and some segments with one-way undivided or two-way divided typical sections with curb & gutter.

Please see the Traffic Analysis Methodology Report, Calibration Report, and Traffic Operations Analysis Summary Report for more information.

2.12 Existing Traffic Volumes

2.12.1 Data Collection

Data collection for the study consists of information from various sources. It is comprised of existing information and field collected data. Sources of information collected include, but is not limited to:

- StreetLight Insight Origin-Destination (OD) Data - used to validate the OD matrices developed for the Vissim simulation;
- Traffic Count Information— used to create General Purpose, Ramp, and Express Lane volume targets.
 - Florida Traffic Information (FTI)
 - Traffic Management Center (TMC)
 - Turnpike Transactions (TPK)
 - SunGuide;
- Transit schedules;
- Signal Timing

Traffic Counts:

Due to the ongoing pandemic, current field traffic count data would not best represent the 2019 traffic condition. Traffic count data supplied by FDOT that represented conditions in the Fall of 2019 are used for analysis. Based on the historical data provided by FDOT, sufficient count information does not exist along the crossroads within the limits of our study area.

Field Data:

Field data collected in Fall of 2019 is used for microsimulation calibration purposes including SR 826 and I-75 mainline peak period speeds from the Regional Integrated Transportation Information System (RITIS). Field visits were also conducted to collect information on existing driver behavior and congestion levels and to verify signal phasing information such as protected/permitted left-turn operations, right-turn-on-red restrictions, phasing, etc. Existing signal plans and timing information for signalized intersections will be obtained from Miami-Dade County Transportation and Public Works Department. Due to current conditions, it is not possible to collect any further field data.

2.13 Modeling and Travel Demand

2.13.1 VISSIM Model Development and Calibration

Vissim models using 15-minute flow rates were developed for a 3-hour AM and PM peak period and calibrated to existing conditions. The 2019 update of FHWA's Traffic Analysis Toolbox Volume III: Guidelines for Applying Traffic Microsimulation Modeling Software and 2014 FDOT Traffic Analysis Handbook were used as a guideline for the development of the project Vissim models.

Existing Conditions Vissim Model Development:

- A Vissim model for the SR 826 general purpose lanes, SR 826 express lanes, I-75 mainline, I-75 express lane, as well as these facilities' ramps was developed for existing conditions. The model utilized a 60-minute seeding period and will be calibrated using speed data from RITIS. Observed queue spillback onto the mainline from the ramp terminals will require the addition of a ramp terminal signal in order to calibrate the mainline. Terminal intersection ramp movement flow rates are gathered from FTI and TMC ; these rates emulated the influence of the ramp terminal on the mainline flow by combining the flow rates with signal timing information.
- Existing Vissim models were validated to the 2019 existing year traffic counts provided by FDOT and OD patterns gathered from Streetlight Data.
- The calibration of the existing AM and PM peak period models targeted the thresholds indicated in the FDOT Traffic Analysis Handbook Table 7-7 Classical Model Calibration Targets shown in **Table 2-10**.

Table 2-11 | Vissim Calibration Targets¹

| Calibration Criteria | Calibration Target/Goal |
|----------------------|---|
| Traffic Volume | Simulated and measured link volumes for more than 85% of links to be: <ul style="list-style-type: none"> • Within 100 vph for volumes less than 700 vph • Within 15% for volumes between 700 vph and 2700 vph • Within 400 vph, for volumes greater than 2700 vph. |
| | Simulated and measured link volumes for more than 85% of links to have a GEH statistic value of five (5) or lower. |
| | Sum of link volumes within calibration area to be within 5%. |
| | Sum of link volumes to have a GEH statistic value of 5 or lower. |
| Speed | Modeled average speeds on I-75 to be within +/- 10 mph of field-measured speeds on at least 85% of all RITIS detector locations. |
| Visualization | Check consistency with field conditions of the following: on- and off-ramp queuing; weaving maneuvers; patterns and extent of queue at intersections and congested links; lane utilization/choice; location of bottlenecks; etc. |
| | Verify no unrealistic U-turns or vehicles exiting and reentering the network. |

¹source: FDOT Traffic Analysis Handbook, Table 7-7 Classical Model Calibration Targets.

2.13.2 Selection of Measures of Effectiveness (MOE)

Site-specific MOEs used to evaluate and compare the alternatives were as follows:

- Freeway Segments – Volume, density, travel speed, congestion charts; and
- Off Ramps – Volume, maximum queue lengths.

In addition to the site-specific MOEs mentioned above, network wide MOEs were also evaluated and are described below:

- Total Travel Time;
- Total Delay Time;
- Vehicles Arrived;
- Average Delay Time;
- Latent Delay Time;
- Latent Vehicles; and
- Total Delay plus Latent Delay.

3.0 Design Controls and Criteria

3.1 Design Controls

The project controls that were used in the alternatives development is shown in **Tables 3-1 to 3-3**.

Table 3-1 | Project Design Controls: SR 826

| Design Element | SR 826 (Mainline) |
|---------------------------|--|
| Functional Classification | Freeway/Expressway |
| Context Classification | L.A. Facility |
| Access Class | Freeway |
| Highway System | National Highway System Strategic Intermodal System State Highway System |
| Design Speed (mph) | 60 |

Table 3-2 | Project Design Controls: SR 826 Ramps

| Design Element | SR 826 (Ramps) |
|---------------------------|--|
| Functional Classification | Freeway/Expressway |
| Context Classification | L.A. Facility |
| Access Class | Freeway |
| Highway System | National Highway System Strategic Intermodal System State Highway System |
| Design Speed (mph) | 30-40 |

Table 3-3 | Project Design Controls: SR 826 Frontage Roads

| Design Element | SR 826 (Ramps) |
|---------------------------|---------------------|
| Functional Classification | Local |
| Context Classification | C3C – Suburban Comm |
| Access Class | N/A |
| Highway System | N/A |
| Design Speed (mph) | 30-40 |

3.2 Design Criteria

The SR 826 mainline and ramps design criteria utilized in the design of the alternatives for this project are in conformance with the following publications and shown in **Table 3-4** to **Table 3-6**.

- Florida Design Manual (2021), Florida Department of Transportation, Part 1 and 2
- Drainage Manual, Florida Department of Transportation
- Structures Manual, Florida Department of Transportation
- Standard Plans for Road and Bridge Construction, Florida Department of Transportation

The SR 826 frontage roads design criteria utilized in the design of the alternatives for this project are in conformance with the following publications and shown in **Table 3-7**.

- Florida Design Manual (2021), Florida Department of Transportation, Part 1 and 2
- American Association of State Highway and Transportation Officials (AASHTO) A Policy on Geometric Design of Highways and Streets (2011, 6th edition)
- FDOT Utility Accommodation Manual (UAM), 2017 edition
- United States Department of Justice 2010 Americans with Disabilities Act (ADA) Standards for Accessible Design
- United States Department of Transportation 2006 ADA Standards for Transportation Facilities
- FDOT District 6 Design Handbook (revised October 2017)
- American with Disabilities Act Accessibility Guidelines (ADAAG)
- Public Right-of-Way Accessibility Guidelines (PROWAG)

Table 3-4 | Design Criteria: SR 826

| SR 826/Palmetto Expressway Capacity Improvements from South of NW 36th Street to NW 154th Street FPID: 447165-1-52-01 | | |
|--|--|---------------------------|
| Design Element | Controlling Criteria | |
| Functional Classification | Interstate | |
| Design Speed (mph): | 60 | |
| Lane Width: | 12' | 2021 FDM Table 210.2.1 |
| Shoulder Width: Full (Paved) | Outside | 2021 FDM Table 211.4.1 |
| | Median | 2021 FDM Table 211.4.1 |
| Express Lane Buffer Width: | 4' | 2021 FDM Section 211.3.3 |
| Border Width: | 10' from back of Barrier or Retaining Wall | 2021 FDM Section 211.6.1 |
| Horizontal Alignment: | | |
| Max deflections in alignment without a curve: | 0°45'00" | 2021 FDM Section 211.7.1 |
| Length of Curve - Desirable (Minimum): | 1800' (900') | 2021 FDM Table 211.7.1 |
| Min. Radius: | | |
| $e_{max} = 10\%$ | 1146' | 2021 FDM Table 210.9.1 |
| N.C. | 11709' | 2021 FDM Table 210.9.1 |
| Max Superelevation: | 10% | 2021 FDM Section 211.8 |
| Superelevation Transition Rate: | 1:170 | 2021 FDM Table 210.9.3 |
| Vertical Alignment: | | |
| Maximum Grades: | 3% | 2021 FDM Table 211.9.1 |
| Maximum change in grade without Vertical Curve: | 0.40% | 2021 FDM Table 210.10.2 |
| Minimum Profile Grade | 0.50% | 2021 FDM Section 210.9.1 |
| Min. Curve Length: | | |
| Crest: | 1000' | 2021 FDM Table 211.9.3 |
| Sag: | 800' | 2021 FDM Table 211.9.3 |
| K-Value: | | |
| Crest: | 193 | 2021 FDM Table 211.9.2 |
| Sag: | 157 | 2021 FDM Table 211.9.2 |
| Horizontal Clear Zone - Mainline (Aux. Lanes): | 36' (24') | 2021 FDM Table 215.2.1 |
| Minimum Stopping Sight Distance (grades < 2%): | 820' | 2021 FDM Table 211.10.1 |
| Cross slope: | | |
| First 2 lanes: | 2% | 2021 FDM Figure 211.2.1 |
| Next 2 lanes: | 3% | 2021 FDM Figure 211.2.1 |
| More than 4 Lanes: | 3.5% | 2021 FDM Figure 211.2.1 |
| Vertical Clearance: | | |
| Over Roadways: | 16' | 2021 FDM Table 260.6.1 |
| Overhead Sign Structures: | 17'-6" | 2021 FDM Section 210.10.3 |
| Overhead DMS Sign Trusses: | 19'-6" | 2021 FDM Section 210.10.3 |
| Signals, mast arms, or other structures | 17'-6" | 2021 FDM Section 210.10.3 |
| R/R | 23.5' | 2021 FDM Table 260.6.1 |
| Base Clearance: | 3' | 2021 FDM Section 210.10.3 |

Table 3-5 | Design Criteria: Ramps (30 mph)

| SR 826/Palmetto Expressway Capacity Improvements from South of NW 36th Street to NW 154th Street FPID: 447165-1-52-01 | | | |
|--|------------------|--|-------------------------|
| Design Element | | Controlling Criteria | |
| Functional Classification | | | Interstate - Ramp |
| Design Speed (mph): | | 40 | |
| Lane Width: | | 12' | 2021 FDM Table 211.2.1 |
| Shoulder Width: Full (Paved) | Outside | 10' | 2021 FDM Table 211.4.1 |
| | Median | 8' | 2021 FDM Table 211.4.1 |
| Border Width: | | 10' from back of Barrier or Retaining Wall | 2021 FDM Table 211.6.1 |
| Horizontal Alignment: | | | |
| Max deflections in alignment without a curve: | | 2°00'00" | 2021 FDM Table 211.7.1 |
| Length of Curve - Desirable (Minimum): | | 600' (400') | 2021 FDM Table 211.7.1 |
| Min. Radius: | | | |
| | $e_{max} = 10\%$ | 441' | 2021 FDM Table 210.9.1 |
| | N.C. | 5560' | 2021 FDM Table 210.9.1 |
| Max Superelevation: | | | 10% |
| Superelevation Transition Rate: | | 1:175 | 2021 FDM Table 210.9.3 |
| Vertical Alignment: | | | |
| Maximum Grades: | | 6% | 2021 FDM Table 211.9.1 |
| Maximum change in grade without Vertical Curve: | | 0.80% | 2021 FDM Table 210.10.2 |
| Min. Curve Length: | Crest: | 120' | 2021 FDM Table 211.9.3 |
| | Sag: | 120' | 2021 FDM Table 211.9.3 |
| K-Value: | Crest: | 44 | 2021 FDM Table 211.9.2 |
| | Sag: | 64 | 2021 FDM Table 211.9.2 |
| Horizontal Clear Zone Width: | | 10' | 2021 FDM Table 215.2.1 |
| Minimum Stopping Sight Distance (grades < 2%): | | 305' | 2021 FDM Table 211.10.2 |

Table 3-6 | Design Criteria: Ramps (40 mph)

| SR 826/Palmetto Expressway Capacity Improvements from South of NW 36th Street to NW 154th Street FPID: 447165-1-52-01 | | |
|--|---|-------------------------|
| Design Element | Controlling Criteria | |
| Functional Classification | Interstate - Ramp | |
| Design Speed (mph): | 40 | |
| Lane Width: | 12-15' | 2021 FDM Table 211.2.1 |
| Shoulder Width: Full (Paved) | Outside | 6' |
| | Median | 2021 FDM Table 211.4.1 |
| Border Width: | 10' from back of Barrier or Retaining Wall | 2021 FDM Table 211.6.1 |
| Horizontal Alignment: | | |
| Max deflections in alignment without a curve: | 2°00'00" | 2021 FDM Table 211.7.1 |
| Length of Curve - Desirable (Minimum): | 450' (400') | 2021 FDM Table 211.7.1 |
| Min. Radius: | | |
| | e _{max} = 10% | 239' |
| | N.C. | 3349' |
| Max Superelevation: | 10% | 2021 FDM Table 211.8 |
| Superelevation Transition Rate: | 1:175 | 2021 FDM Table 210.9.3 |
| Vertical Alignment: | | |
| Maximum Grades: | 7% | 2021 FDM Table 211.9.1 |
| Maximum change in grade without Vertical Curve: | 1.00% | 2021 FDM Table 210.10.2 |
| Min. Curve Length: | Crest: | 90' |
| | Sag: | 90' |
| K-Value: | Crest: | 19 |
| | Sag: | 37 |
| Horizontal Clear Zone Width: | | 10' |
| Minimum Stopping Sight Distance (grades < 2%): | 200' | 2021 FDM Table 211.10.2 |
| Vertical Clearance: | | |
| Over Roadways: | 16' | 2021 FDM Table 260.6.1 |

Table 3-7 | Design Criteria: Frontage Roads

| SR 826 Frontage Roads from Okeechobee Road to NW 103 Street (FPID 441830-1-52-01) and SR 826 Frontage Roads from NW 103 Street to NW 122 Street (FPID 441831-1-52-01) | | | | |
|---|--|-----------------------------------|------------------------------|--|
| Design Element | | Controlling Criteria | | |
| Functional Classification | | | | |
| Design Speed (mph): | | | | |
| Lane Width: | Travel Lanes | 12' | 2021 FDM Table 210.2.1 | |
| | Auxiliary Lanes | 12' | 2021 FDM Table 210.2.1 | |
| Cross Slope: | Travel Lanes | Min. | 0.015 | |
| | | Max. | 0.030 | |
| | Outside Shoulder | Min. | 0.015 | |
| | | Max. | 0.080 | |
| | Inside Shoulder | Min. | 0.020 | |
| | | Max. | 0.080 | |
| Median Width | | 15.5' | 2022 FDM Table 210.3.1 | |
| Shoulder Width: | Outside Shoulder | Full Width | 6' | |
| | | Paved Width | 5' | |
| | Inside Shoulder | Full Width | 6' | |
| | | Paved Width | 2' | |
| Border Width: | | | 8' from shoulder point | |
| Horizontal Alignment: | | | | |
| Max. deflections in alignment without a curve: | | 2°00'00" | 2021 FDM Section 210.8.1 | |
| Length of Horizontal Curve | | 400' | 2021 FDM Table 210.8.1 | |
| Min. Radius: | | 223' (DS=30) 332' (DS=35) | 2021 FDM Table 210.8.1 | |
| Max Superelevation: | | | 0.100 | |
| Vertical Alignment: | | | | |
| Max. change in grade without Vertical Curve: | | 1.00% (DS=30) 0.90% (DS=35) | 2021 FDM Table 210.10.2 | |
| Min. distance between VPIs on curbed roadways | | 250' | 2021 FDM Section 210.10.1.1 | |
| Min. grade on curbed roadways | | 0.30% | 2021 FDM Section 210.10.1.1 | |
| K-Value: | Crest: | 19 (DS=30) | 2021 FDM Table 210.10.3 | |
| | | 29 (DS=35) | | |
| Min. Curve Length: | Sag: | 37 (DS=30) | 2021 FDM Table 210.10.4 | |
| | | 49 (DS=35) | | |
| Vertical Clearance: | | | | |
| Signals, mast arms, or other structures | | 17'-6" (new) 17'-0" (existing) | 2021 FDM Section 210.10.3 | |
| Bridges over Roadways: | | 16'-0" (new) 14'-6" (existing) | 2021 FDM Table 260.6.1 | |
| Min. Stopping Sight Distance: (Grades < 2%) | | | 200' (DS=30) 250' (DS=35) | |
| Clear Zone: (flush shoulder section) | RRR | Travel Lanes & Auxiliary Lanes | 6' | |
| | Control Zone | Travel Lanes | 12' (DS=30) 14' (DS=35) | |
| | | Auxiliary Lanes | 10' | |
| Min. Lateral Offset: (curb & gutter section) | Light Poles, Signal Poles, ITS Poles, Trees | 1.5' from face of curb | 2021 FDM Table 215.2.2 | |
| | | 16' from edge of travel | | |
| | Bridge Piers & Abutments | | | |
| Sidewalk Width: | Existing | 4' | 2021 FDM Table 222.2.1 | |
| | Proposed | 6' | | |
| Bicycle Facilities: | | | 4' paved shoulder | |
| Bridge Width: | | | 4' shoulder | |
| | | | 2021 FDM Table 260.9.1 | |

4.0 Alternatives Analysis

Evaluation of transportation projects to select the most desirable alternative is often based on a wide range of criteria (i.e., traffic operations and safety, environmental impacts, construction costs, drainage impacts, right-of-way costs, etc.) that reflect concerns of all the key stakeholders. One improvement build alternative was considered for improving traffic operations and safety throughout the SR 826/Palmetto Expressway corridor. The following sections summarize the No-Action, and TSM&O alternatives and the evaluation and elimination of alternatives.

4.1 No-Build Alternative

The No-Build Alternative assumes that no improvements would be implemented within the project corridor. It serves as a baseline for comparison against the Build Alternative. It will, however, include on-going construction projects and all funded or programmed improvements scheduled to be opened to traffic in the analysis years being considered. These improvements must be part of the FDOT's adopted Five-Year Work Program, Miami-Dade County Metropolitan Planning Organization (MPO), Long Range Transportation Plan (LRTP), transportation elements of Local Government Comprehensive Plans (LGCP), or developer-funded transportation improvements specified in approved development orders. This alternative is considered to be a viable alternative to serve as a comparison to the study's proposed Build Alternative.

The advantage of the No-Build Alternative is that it requires no expenditure of public funds for design, right-of-way acquisition, construction or utility relocation. In addition, there would be no disruptions due to construction from the project and no direct or indirect impacts to the environment and/or the socio-economic characteristics of the project area. However, the No-Build Alternative does not address the purpose and need of the project and operational and safety conditions within the project area will become progressively worse as traffic volumes continue to increase.

4.2 Build Alternative

The proposed improvements evaluated for the SR 826/Palmetto Expressway consisted of three elements:

1. Improvements to the mainline of southbound SR 826 to retrofit the Express Lane ingress/egress points and widening between NW 74th Street and NW 103rd Street
2. Improvements to the mainline of northbound SR 826 is limited to the widening of the inside shoulder at the NW 103rd Street interchange, and
3. Improvements to the frontage roads to preserve and extend the pavement life.

4.2.2 Mainline SR 826 Build Alternative

The SR 826/Palmetto Expressway Capacity Improvement project (FPID 447165-1-52-01) consists of improvements in the southbound direction to retrofit the EL ingress/egress access points, widening of the mainline between NW 74th Street and SR 25 / Okeechobee Road and between SR 25 / Okeechobee Road and NW 103rd Street, widening of the NW 103rd St on/off ramps, widening of bridges over NW 74th Street, Metrorail corridor, FEC corridor, and NW 103rd Street, and a comprehensive milling and resurfacing plan. Modification of the NW 103rd Street westbound flyover on-ramp on to SR 826 southbound is also being conducted to accommodate SR 826 southbound mainline widening.

Improvements in the northbound direction include widening of the mainline at the NW 103rd Street interchange to correct substandard shoulder width created under the Northbound Express Lanes Interim Improvements project, widening along NW 103rd Street off-ramp, widening of bridge over NW 103rd Street, and milling and resurfacing. Furthermore, improvements include the installation of a new Tolling Site along both the northbound and southbound directions that will require a specific pavement design to be implemented 50 feet north/south of the gantry location.

The proposed SR 826/Palmetto Expressway southbound typical section consists of a single express lane and five general purpose lanes from I-75 Interchange to NW 103rd Street interchange and two express lanes and four general purpose lanes from NW 103rd Street interchange to north of NW 36th Street interchange.

There are no changes to the typical section along the SR 826/Palmetto Expressway northbound other than the provision of a wider inside shoulder at the NW 103rd Street interchange.

Project improvements at the intersection of NW 103rd Street/W 49th Street and SR 826 Northbound Off-Ramp/W 20th Avenue East, identified in the Traffic Operations Technical Memorandum, including:

- Signalize the westbound right turn movement at the W 20th Avenue intersection to provide a protected pedestrian phase for pedestrians to safely cross within the marked crosswalk. Note that a new traffic signal controller is required to allow operation of the westbound right turn movement independently from the existing signal at the intersection.
- Expand existing channelization island located on the northeast corner of the intersection to increase the refuge area provided for pedestrians since large groups of students cross at this location.
- Reduce the curb radius at the southeast corner of the intersection and construct a truck apron.
- Install “No Pedestrian Crossing” (R9-3) and “Use Crosswalk” (R9-3P) signs on the east and west sides of W 20th Avenue at approximately 100 feet north of SR 932/NW 103rd Street to discourage pedestrians from crossing midblock and to direct pedestrians to use the existing marked crosswalk at the signalized intersection.
- Remove the pedestrian crossing (W11-2) sign located on the far side of the intersection facing northbound traffic.

The Build Alternative for SR 826 is shown in **Figure 4-1**.

4.2.3 Frontage Road Build Alternative

In conjunction with SR 826/Palmetto Expressway Capacity Improvement project improvements, the Department has included the SR 826 Frontage Road RRR improvements from Okeechobee Road to NW 103rd St (FPID 441830-1-52-01) and from NW 103rd St to NW 122nd St (FPID 441831-1-52-01).


The primary purpose of the 441830-1-52-01 and 441831-1-52-01 RRR Projects is to preserve and extend the service life of the existing pavement. The following improvements are recommended to be included in the overall project scope of work to correct the deficient pavement conditions, meet ADA compliance, upgrade all sub-standard ground-mounted signs and pavement markings, upgrade existing guardrail, construction of new paved shoulders to meet required criteria and improve overall safety of the corridor, and upgrade existing bridge railings at Bridges 870569 and 870570.

Specifically the roadway scope entails milling and resurfacing of the existing pavement with adjustment of the existing storm drain manhole tops, utility manhole tops, and utility valves within the limits of resurfacing; Construction of paved shoulders (5 feet wide) in segments without existing roadside landscaping or utility impacts; Adjustment of the existing ditch-bottom inlets impacted by the proposed shoulder widening and construction of additional ditch-bottom inlets where required along the shoulder widening areas; Upgrade sub-standard pedestrian curb ramps and detectable warning surfaces along W 20th Avenue to meet ADA criteria; Construction of new sidewalk along W 20th Avenue to connect the gaps between existing sidewalk segments and reconstruction of damaged or uneven sidewalks; and upgrade of the guardrail, guardrail terminals, guardrail transition connections to the bridge traffic railings, and guardrail-to-rigid barrier transition connections.

Additionally, the proposed frontage road improvements include signing and pavement marking, signalization, landscaping, structure upgrades, upgrades to pedestrian signalization, crosswalk pavement markings, and lighting at intersections.

The proposed SR 826 southbound mainline widening and modification of the NW 103rd Street westbound flyover on-ramp to continue along SR 826 southbound will require the realignment of the west frontage road / NW 77th Avenue from approximately south of NW 98th Street intersection to south of the NW 103rd Street intersection.

Figure 4-1 | Build Alternative: SR 826 Southbound



4.3 Future Conditions Analysis

Analysis will be conducted for the following scenarios within the project limits:

- Existing (2019)
- Northbound Interim Improvements Build (2020)
- Palmetto Expressway Capacity Improvements Build (2023)

The analysis scenarios are described as follows:

- The Existing scenario represents the existing condition as it was after the opening of the SR 826 Express Lanes in the Fall of 2019 and will be used for developing and calibrating a baseline scenario.
- The Northbound Interim Improvements (FPID 432687-1-52-02) Build scenario is the roadway configuration which opened to traffic in the Fall of 2020. This specifically includes the combining of the Northwest 36th Street NB ingress with the Okeechobee Road NB ingress and shifting the NW 154th Street egress south to NW 103rd Street.
- The Palmetto Expressway Capacity Improvements (FPID 447165-1-52-01) Build scenario is the roadway configuration that is anticipated to open to traffic in the year 2023. This specifically includes all changes from FPID 432687-1-52-02, plus the shifting of the NW 154th Street SB ingress south to W 122nd Street.

For all three scenarios, one set of volumes will be used that was developed based on data supplied by FDOT that represented conditions in the Fall of 2019. Due to current extraordinary circumstances, additional data collection is not possible and sufficient turning movement count information is not available along the crossroads. The demand volumes from 2019 best represent worst case congestion for both 2019 and 2020. It is assumed that traffic conditions will not return to typical congested states until the pandemic and its impacts have subsided, therefore the same data set will be used for the Palmetto Expressway Capacity Improvements Build (2023) scenario.

Please see the Traffic Analysis Methodology Report, Calibration Report, and Traffic Operations Analysis Summary Report for more information.

4.3.1 Build 2023(2040) Peak Hour Traffic Development

A summary of the SR-826 travel speeds during the entire weekday morning and afternoon peak periods for the Palmetto Expressway Capacity Improvement Build scenario is provided in the Traffic Operations Analysis Summary Report. While there will be minor degradations in peak hour level of service with some sections dropping, all sections within the construction improvement area will meet the criteria of no LOS degradation and the average traveling speed throughout the corridor does improve.

It should be noted that this improved traffic flow, compared to existing conditions, is also reflective of increased traffic volumes compared to existing conditions. As stated previously, the existing

capacity of the SR-826 corridor in this area is inadequate to meet the existing demand. Unmet traffic demand, which cannot be accommodated due to inadequate system capacity results in backups along the corridor under 2019 Existing Conditions, which are expected to improve with the Palmetto Expressway Capacity Improvement project, as detailed above. This Build condition can accommodate increased traffic volumes and minimize the unmet demand compared to existing conditions.

4.4 Evaluation and Elimination of Alternatives

The alternatives matrix is developed to compare the alternatives across the breadth of issues affected by the project. It provides a comparative qualitative and quantitative analysis of alternatives for the project. An evaluation matrix, as shown in **Table 4-1**, was developed to help summarize and compare the impacts associated with each alternative.

Table 4-1 | Alternative Comparison Matrix

| SR 826/Palmetto Expressway Alternatives Comparison Matrix | | |
|---|----------------------|--|
| EVALUATION FACTORS | NO-BUILD ALTERNATIVE | ALT 1 - BUILD ALTERNATIVE |
| Meets Purpose and Need | No | Yes |
| Project Cost (\$ in millions) | | |
| Construction Cost | \$0 | \$37.9 million |
| Construction Engineering and Inspection (CEI) | \$0 | \$3.8 million |
| Social and Economic Environment | | |
| Number of Impacted Parcels (Business/Residential) | None | None |
| Number of Relocations (Business/Residential) | None | None |
| Right of Way Impacts | None | The project will not displace any residences or businesses within the community. |
| Social and Neighborhood Impacts | No change | There are no anticipated impacts to existing accessways or routes. Improved sidewalk coverage on the frontage road system will enhance the social environment through neighborhood connectivity. |
| Economic Impacts | No change | The project supports economic development by improving access to businesses through reduced congestion and improved facilities along the frontage road network. |
| Land Use Impacts | No change | No impacts or changes to land use are anticipated by the project. |
| Mobility Impacts | No change | The project improves mobility by providing an additional southbound GP lane and enhanced EL access. Continuous sidewalk coverage on the frontage roads will enhance pedestrian and bicycle safety. |
| Aesthetic Impacts | No change | Viewshed impacts are expected to be limited since the expressway is an existing facility. |
| Community Services and Features Impacts | No change | No impacts to community services (Fire, Police, Hospitals, Churches, Schools, etc.) are anticipated from the project. |
| Cultural Environment | | |
| Cultural/Historic/Archeological Impacts | No impact | The project will have no adverse affect on 2 archeological resources in the area. The 2 National Register-eligible historic resources in the area will not be adversely affected by the project. |
| Parks and Recreational Areas Impacts | No impact | Due to the distance of the improvements from the 9 recreational areas within 0.25 miles of the corridor, no impacts to these recreational areas will occur as a result of the project. |

SR 826/Palmetto Expressway Alternatives Comparison Matrix

| EVALUATION FACTORS | NO-BUILD ALTERNATIVE | ALT 1 - BUILD ALTERNATIVE |
|--|---|--|
| Natural Environment | | |
| Wetlands and Surface Waters Impacts | No change | <p>No impacts to vegetated wetland resources will occur. 0.005 acres of impact to 1 excavated stormwater conveyance feature will occur. The impact will be compensated through the expansion of the drainage feature by approximately 565.4 square feet just to the south of the area of the impact.</p> |
| Protected Species and Habitat Impacts | No Impact | <p>The finding for the project on the West Indian manatee and on the eastern indigo snake is May Affect, Not Likely to Adversely Affect.</p> <p>The project will not adversely affect any federal or state-designated Critical Habitat.</p> |
| Essential Fish Habitat Impacts | No impact | <p>There is no Essential Fish Habitat located within the project area.</p> |
| Water Quality and Water Quantity Impacts | No change | <p>No adverse impacts to the Biscayne Aquifer are anticipated as a result of the project.</p> |
| Floodplains Impacts | No impact | <p>The project is located within the 100 year floodplain; it will not encroach upon the base floodplain.</p> |
| Physical Environment | | |
| Contamination/Hazardous Waste Sites | No change | <p>5 High-Risk Sites 3 Medium-Risk Sites 22 Low-Risk Sites 2 No-Risk Sites</p> |
| Traffic Noise | <p>Minimal potential impacts may occur from increased congestion.</p> <p>Does not add any noise abatement.</p> | <p>Noise sensitive sites (416 residences and 5 non-residential) will be impacted by the improvements.</p> <p>Of the 9 noise barrier locations evaluated for mitigation, none (0) are recommended for the project.</p> |
| Air Quality | <p>The project is located within an attainment area. Minimal potential impacts may occur from increased congestion.</p> | <p>The project is located within an attainment area. No significant air quality impacts are anticipated. Project is anticipated to decrease congestion.</p> |
| Utilities and Railroads | No change | <p>The project will require water and sewer manhole adjustments and power pole relocations.</p> <p>The bridge widening over the FEC Railroad will not have an adverse impact on the railroad.</p> |
| Construction | No impact | <p>Construction activities causing dust will be minimized by adherence to applicable state regulations and specifications.</p> |
| Traffic Operations | | |
| AM Level of Service (LOS) | F | F/E (depending on segment) |
| PM Level of Service (LOS) | F | F/E (depending on segment) |

5.0 Public Involvement/Project Coordination

The public information team is currently engaged in coordination efforts for the January 2021 hybrid Public Hearing. Notifications to Elected Officials and the public are anticipated to be distributed in mid to late December prior to the meeting. The tentative date for this hearing is January 12, 2021.

5.1 MPO Coordination

The public information team coordinated with the Miami-Dade County Transportation Planning Organization (TPO) Board Members and Miami-Dade County to conduct a bus tour of the project, hosted by FDOT. This bus tour was conducted on December 2, 2020.

5.2 Coordination with Elected/Appointed Officials

Notifications to Elected and Appointed Officials occurred prior to the tour and will occur prior to the Public Hearing.

5.3 Public Hearing

A public hearing will be held for this project. It is anticipated to be a hybrid public hearing to be held on Tuesday, January 12, 2021.

6.0 Preferred Alternative

The Preferred Alternative is Build Alternative. The Build Alternative consists of improvements in the southbound direction to retrofit the EL ingress/egress access points and widening to add a General Purpose lane from the exit to NW 103rd Street to the exit to Okeechobee Road. Other improvements include widening in the northbound direction to correct substandard shoulder width created under the Northbound Express Lanes Interim Improvements project, widening of the NW 103rd St on/off ramps, and a comprehensive milling and resurfacing plan. Furthermore, improvements include the installation of a new Tolling Site along both the northbound and southbound directions that will require a specific pavement design to be implemented 50 feet north/south of the gantry location. A detailed description of the development of the Preferred Alternative is included in subsequent sections of this report.

The preferred alternative will improve the frontage road system on both sides of SR 826 between US 27 and NW 122nd Street to correct deficient pavement conditions; upgrade sub-standard ground-mounted signs and pavement markings; comply with the American with Disabilities Act (ADA); replace existing guardrail; upgrade bridge railings; and construct new paved shoulders to meet criteria and improve overall safety of the corridor. Additionally, the proposed frontage road improvements include signalization, lighting, and landscaping upgrades.

The proposed SR 826 southbound mainline widening and the modification of the pier of the NW 103rd Street westbound flyover on-ramp to SR 826 southbound will require the realignment of the West

Frontage Road/NW 77th Avenue. The realignment of this two-way frontage road begins south of the NW 98th Street intersection and ends south of the NW 103rd Street intersection.

6.1 Right-of-Way Needs and Relocation

The proposed improvements of the Preferred Alternative will all be constructed within existing Right-of-Way.

6.2 Typical Sections

The proposed SR 826/Palmetto Expressway southbound typical section consists of a single express lane (11') and five general purpose lanes (11' each) from I-75 Interchange to NW 103rd Street interchange and two express lanes (11' each) and four general purpose lanes (11' each) from NW 103rd Street interchange to north of NW 36th Street interchange. See **Figure 6-2** and **Figure 6-3**.

There are no changes to the typical section along the SR 826/Palmetto Expressway northbound other than the provision of a wider inside shoulder at the NW 103rd Street interchange. See **Figure 6-4**.

The proposed typical section for the frontage road consists of two lanes (11'-12' each), flush paved shoulders (0'-5' each), and a sidewalk (0'-6') on one side. A representative typical section is illustrated in **Figure 6-5** and the entire Typical Section Package can be found in **Appendix B**.

Figure 6-1 | Typical Section: SR 826 Southbound One Express Lane




Figure 6-2 | Typical Section: SR 826 Southbound Two Express Lanes




Figure 6-3 | Typical Section: SR 826 Northbound





Figure 6-4 | Typical Section: Frontage Roads



6.3 Horizontal and Vertical Geometry

Once the preferred alternative was determined, the project team worked to further refine the horizontal and vertical geometry of the proposed improvements along the SR 826 mainline and the east and west frontage roads.

6.3.1 SR 826

The horizontal geometry of the Preferred Alternative along the SR 826 mainline allows for widening in critical areas within the project limits to improve the overall operation and safety. The Preferred Alternative along SR 826 mainline maintains the existing profile along all travel lanes. Details of the horizontal and vertical geometry are summarized in **Table 6-1**.

Table 6-1 | Geometry: SR 826

| SR 826/Palmetto Expressway Capacity Improvements from South of NW 36th Street to NW 154th Street | | | |
|--|---------|--|--|
| FPID: 447165-1-52-01 | | | |
| Design Element | | SR 826 (mainline) | Controlling Criteria |
| Functional Classification | | Interstate | Interstate |
| Design Speed (mph): | | 60 | 60 |
| Lane Width: | | 11' | 12' |
| Shoulder Width: Full (Paved) | Outside | 10'-12' | 12' |
| | Median | 3.5'-12' | 12' |
| Express Lane Buffer Width: | | 2' | 4' |
| Border Width: | | 10' from back of Barrier or Retaining Wall | 10' from back of Barrier or Retaining Wall |
| Horizontal Alignment: | | | |
| Max deflections in alignment without a curve: | | 0°45'00" | 0°45'00" |
| Length of Curve - Desirable (Minimum): | | 410.76' | 1800' (900') |
| Min. Radius: | | | |
| e _{max} = 10% | | N/A | 1146' |
| | N.C. | 18000' | 11709' |
| Max Superelevation: | | NC | 10% |
| Superelevation Transition Rate: | | N/A | 1:170 |
| Vertical Alignment: | | | |
| Maximum Grades: | | N/A | 3% |
| Maximum change in grade without Vertical Curve: | | N/A | 0.40% |
| Minimum Profile Grade | | N/A | 0.50% |
| Min. Curve Length: | Crest: | N/A | 1000' |
| | Sag: | N/A | 800' |
| K-Value: | Crest: | N/A | 193 |
| | Sag: | N/A | 157 |
| Horizontal Clear Zone - Mainline (Aux. Lanes): | | N/A | 36' (24') |
| Minimum Stopping Sight Distance (grades < 2%): | | N/A | 820' |
| Cross slope: | | | |
| First 2 lanes: | | | 2% |
| Next 2 lanes: | | | 3% |
| More than 4 Lanes: | | | 3.5% |
| Vertical Clearance: | | | |
| Over Roadways: | | 16' | 16' |
| Overhead Sign Structures: | | 17'-6" | 17'-6" |
| Overhead DMS Sign Trusses: | | 19'-6" | 19'-6" |
| Signals, mast arms, or other structures | | 17'-6" | 17'-6" |
| R/R | | 18.78 | 23.5' |
| Base Clearance: | | 3' | 3' |

6.3.2 Ramps

In order to accommodate the mainline improvements, the preferred alternative requires adjustments to the geometry of five ramps within the project limits.

6.3.2.1 Ramp A – SR 826 SB Off-Ramp at NW 74th Street

The preferred alternative includes horizontal realignment of Ramp A to accommodate mainline widening. Details of the horizontal and vertical geometry are summarized in **Table 6-2**.

Table 6-2 | Geometry: Ramp A

| SR 826/Palmetto Expressway Capacity Improvements from South of NW 36th Street to NW 154th Street | | | | | |
|--|---------|---|--|---|-------------------------|
| FPID: 447165-1-52-01 | | | | | |
| Design Element | | Freeway Ramps (2 Lanes) (40 MPH) | | Controlling Criteria | |
| Functional Classification | | Interstate - Ramp | | | |
| Design Speed (mph): | | 40 | | | |
| Lane Width: | | 12' | | 12' | 2021 FDM Table 211.2.1 |
| Shoulder Width: Full (Paved) | Outside | 8' | | 10' | 2021 FDM Table 211.4.1 |
| | Median | 6' | | 8' | 2021 FDM Table 211.4.1 |
| Border Width: | | 10' from back of Barrier or Retaining Wall | | 10' from back of Barrier or Retaining Wall | 2021 FDM Table 211.6.1 |
| Horizontal Alignment: | | | | | |
| Max deflections in alignment without a curve: | | 2°00'00" | | 2°00'00" | 2021 FDM Table 211.7.1 |
| Length of Curve - Desirable (Minimum): | | N/A | | 600' (400') | 2021 FDM Table 211.7.1 |
| Min. Radius: | | | | | |
| $e_{max} = 10\%$ | | N/A | | 441' | 2021 FDM Table 210.9.1 |
| | N.C. | N/A | | 5560' | 2021 FDM Table 210.9.1 |
| Max Superelevation: | | NC | | 10% | 2021 FDM Table 211.8 |
| Superelevation Transition Rate: | | N/A | | 1:175 | 2021 FDM Table 210.9.3 |
| Vertical Alignment: | | | | | |
| Maximum Grades: | | N/A | | 6% | 2021 FDM Table 211.9.1 |
| Maximum change in grade without Vertical Curve: | | N/A | | 0.80% | 2021 FDM Table 210.10.2 |
| Min. Curve Length: | Crest: | N/A | | 120' | 2021 FDM Table 211.9.3 |
| | Sag: | N/A | | 120' | 2021 FDM Table 211.9.3 |
| K-Value: | Crest: | N/A | | 44 | 2021 FDM Table 211.9.2 |
| | Sag: | N/A | | 64 | 2021 FDM Table 211.9.2 |
| Horizontal Clear Zone Width: | | N/A | | 10' | 2021 FDM Table 215.2.1 |
| Minimum Stopping Sight Distance (grades < 2%): | | N/A | | 305' | 2021 FDM Table 211.10.2 |

6.3.2.2 Ramp B – SR 826 SB Off-Ramp at NW 103rd Street

The preferred alternative includes Vertical realignment of Ramp B to accommodate mainline widening and gore relocation. Details of the horizontal and vertical geometry are summarized in **Table 6-3**.

Table 6-3 | Geometry: Ramp B

| SR 826/Palmetto Expressway Capacity Improvements from South of NW 36th Street to NW 154th Street | | | | | |
|--|---------|---|--|---|-------------------------|
| FPID: 447165-1-52-01 | | | | | |
| Design Element | | Freeway Ramps (2-4 Lanes) (40 MPH) | | Controlling Criteria | |
| Functional Classification | | Interstate - Ramp | | | |
| Design Speed (mph): | | 40 | | | |
| Lane Width: | | 12' | | 12' | 2021 FDM Table 211.2.1 |
| Shoulder Width: Full (Paved) | Outside | 10' | | 10' | 2021 FDM Table 211.4.1 |
| | Median | 6' | | 8' | 2021 FDM Table 211.4.1 |
| Border Width: | | 10' from back of Barrier or Retaining Wall | | 10' from back of Barrier or Retaining Wall | 2021 FDM Table 211.6.1 |
| Horizontal Alignment: | | | | | |
| Max deflections in alignment without a curve: | | 2°00'00" | | 2°00'00" | 2021 FDM Table 211.7.1 |
| Length of Curve - Desirable (Minimum): | | 484.4' | | 600' (400') | 2021 FDM Table 211.7.1 |
| Min. Radius: | | | | | |
| $e_{max} = 10\%$ | | 441' | | 2021 FDM Table 210.9.1 | |
| | N.C | 5754' | | 5560' | 2021 FDM Table 210.9.1 |
| Max Superelevation: | | NC | | 10% | 2021 FDM Table 211.8 |
| Superelevation Transition Rate: | | | | 1:175 | 2021 FDM Table 210.9.3 |
| Vertical Alignment: | | | | | |
| Maximum Grades: | | 3.7% | | 6% | 2021 FDM Table 211.9.1 |
| Maximum change in grade without Vertical Curve: | | | | 0.80% | 2021 FDM Table 210.10.2 |
| Min. Curve Length: | Crest: | 420' | | 120' | 2021 FDM Table 211.9.3 |
| | Sag: | N/A | | 120' | 2021 FDM Table 211.9.3 |
| K-Value: | Crest: | 71 | | 44 | 2021 FDM Table 211.9.2 |
| | Sag: | N/A | | 64 | 2021 FDM Table 211.9.2 |
| Horizontal Clear Zone Width: | | N/A | | 10' | 2021 FDM Table 215.2.1 |
| Minimum Stopping Sight Distance (grades < 2%): | | N/A | | 305' | 2021 FDM Table 211.10.2 |

6.3.2.3 Ramp C – NW 77th Avenue On-Ramp

The preferred alternative includes horizontal realignment of Ramp C to accommodate mainline widening. Details of the horizontal and vertical geometry are summarized in **Table 6-4**.

Table 6-4 | Geometry: Ramp C

| SR 826/Palmetto Expressway Capacity Improvements from South of NW 36th Street to NW 154th Street | | | | | |
|--|---------|---|--|---|-------------------------|
| FPID: 447165-1-52-01 | | | | | |
| Design Element | | Freeway Ramps (1 Lane) (40 MPH) | | Controlling Criteria | |
| Functional Classification | | Interstate - Ramp | | | |
| Design Speed (mph): | | 40 | | | |
| Lane Width: | | 12' | | 12' | 2021 FDM Table 211.2.1 |
| Shoulder Width: Full (Paved) | Outside | 6' | | 10' | 2021 FDM Table 211.4.1 |
| | Median | 6' | | 8' | 2021 FDM Table 211.4.1 |
| Border Width: | | 10' from back of Barrier or Retaining Wall | | 10' from back of Barrier or Retaining Wall | 2021 FDM Table 211.6.1 |
| Horizontal Alignment: | | | | | |
| Max deflections in alignment without a curve: | | 2°00'00" | | 2°00'00" | 2021 FDM Table 211.7.1 |
| Length of Curve - Desirable (Minimum): | | 319' | | 600' (400') | 2021 FDM Table 211.7.1 |
| Min. Radius: | | | | | |
| $e_{max} = 10\%$ | | 441' | | 2021 FDM Table 210.9.1 | |
| | N.C | 5575' | | 5560' | 2021 FDM Table 210.9.1 |
| Max Superelevation: | | N/A | | 10% | 2021 FDM Table 211.8 |
| Superelevation Transition Rate: | | N/A | | 1:175 | 2021 FDM Table 210.9.3 |
| Vertical Alignment: | | | | | |
| Maximum Grades: | | 1.5% | | 6% | 2021 FDM Table 211.9.1 |
| Maximum change in grade without Vertical Curve: | | N/A | | 0.80% | 2021 FDM Table 210.10.2 |
| Min. Curve Length: | Crest: | 200' | | 120' | 2021 FDM Table 211.9.3 |
| | Sag: | 170' | | 120' | 2021 FDM Table 211.9.3 |
| K-Value: | Crest: | 80 | | 44 | 2021 FDM Table 211.9.2 |
| | Sag: | 83 | | 64 | 2021 FDM Table 211.9.2 |
| Horizontal Clear Zone Width: | | N/A | | 10' | 2021 FDM Table 215.2.1 |
| Minimum Stopping Sight Distance (grades < 2%): | | N/A | | 305' | 2021 FDM Table 211.10.2 |

6.3.2.4 Ramp D – NW 103rd SB Flyover On-Ramp

The preferred alternative includes horizontal realignment of Ramp D due to deck width reduction in order to accommodate mainline widening. Details of the horizontal and vertical geometry are summarized in **Table 6-5**.

Table 6-5 | Geometry: Ramp D

| SR 826/Palmetto Expressway Capacity Improvements from South of NW 36th Street to NW 154th Street | | | | | |
|--|---------|---|--|---|--|
| FPID: 447165-1-52-01 | | | | | |
| Design Element | | Freeway Ramps (1-2 Lanes) (30 MPH) | | Controlling Criteria | |
| Functional Classification | | Interstate - Ramp | | | |
| Design Speed (mph): | | 40 | | | |
| Lane Width: | | 12'-15' | | 12'-15' | |
| Shoulder Width: Full (Paved) | Outside | 6'-10' | | 6' | |
| | Median | 6'-13' | | 6' | |
| Border Width: | | 10' from back of Barrier or Retaining Wall | | 10' from back of Barrier or Retaining Wall | |
| Horizontal Alignment: | | | | | |
| Max deflections in alignment without a curve: | | 2°00'00" | | 2°00'00" | |
| Length of Curve - Desirable (Minimum): | | 436' | | 450' (400') | |
| Min. Radius: | | | | | |
| $e_{max} = 10\%$ | | 326' | | 239' | |
| | N.C. | 3349' | | 2021 FDM Table 210.9.1 | |
| Max Superelevation: | | 9.7% | | 10% | |
| Superelevation Transition Rate: | | | | 1:175 | |
| Vertical Alignment: | | | | | |
| Maximum Grades: | | N/A | | 7% | |
| Maximum change in grade without Vertical Curve: | | N/A | | 1.00% | |
| Min. Curve Length: | Crest: | N/A | | 90' | |
| | Sag: | N/A | | 90' | |
| K-Value: | Crest: | N/A | | 19 | |
| | Sag: | N/A | | 37 | |
| Horizontal Clear Zone Width: | | N/A | | 10' | |
| Minimum Stopping Sight Distance (grades < 2%): | | 222.17' | | 200' | |
| Vertical Clearance: | | | | | |
| Over Roadways: | | N/A | | 16' | |
| | | | | 2021 FDM Table 260.6.1 | |

6.3.2.5 Ramp E – NW 103rd Street NB Off-Ramp

The preferred alternative includes horizontal realignment of Ramp E to accommodate shoulder width increase, the proposed improvements also include a raise in the vertical profile of the ramp. Details of the horizontal and vertical geometry are summarized in **Table 6-6**.

Table 6-6 | Geometry: Ramp E

| SR 826/Palmetto Expressway Capacity Improvements from South of NW 36th Street to NW 154th Street | | | | |
|--|------------------|-------------------------------------|-------------|---|
| FPID: 447165-1-52-01 | | | | |
| Design Element | | Freeway Ramps (2 Lanes) (40 MPH) | | Controlling Criteria |
| Functional Classification | | Interstate - Ramp | | |
| Design Speed (mph): | | 40 | | |
| Lane Width: | | 12' | | 12' 2021 FDM Table 211.2.1 |
| Shoulder Width: Full (Paved) | Outside | 7.9'-10' | 10' | 2021 FDM Table 211.4.1 |
| | Median | 6' | 8' | 2021 FDM Table 211.4.1 |
| Border Width: | | 3.75' MIN | | 10' from back of Barrier or Retaining Wall 2021 FDM Table 211.6.1 |
| Horizontal Alignment: | | | | |
| Max deflections in alignment without a curve: | | 2°00'00" | 2°00'00" | 2021 FDM Table 211.7.1 |
| Length of Curve - Desirable (Minimum): | | 214' | 600' (400') | 2021 FDM Table 211.7.1 |
| Min. Radius: | | | | |
| | $e_{max} = 10\%$ | | 441' | 2021 FDM Table 210.9.1 |
| | N.C | 6012 | 5560' | 2021 FDM Table 210.9.1 |
| Max Superelevation: | | NC | | 10% 2021 FDM Table 211.8 |
| Superelevation Transition Rate: | | | | 1:175 2021 FDM Table 210.9.3 |
| Vertical Alignment: | | | | |
| Maximum Grades: | | 3.9% | 6% | 2021 FDM Table 211.9.1 |
| Maximum change in grade without Vertical Curve: | | N/A | 0.80% | 2021 FDM Table 210.10.2 |
| Min. Curve Length: | Crest: | 460' | 120' | 2021 FDM Table 211.9.3 |
| | Sag: | N/A | 120' | 2021 FDM Table 211.9.3 |
| K-Value: | Crest: | 71 | 44 | 2021 FDM Table 211.9.2 |
| | Sag: | N/A | 64 | 2021 FDM Table 211.9.2 |
| Horizontal Clear Zone Width: | | N/A | 10' | 2021 FDM Table 215.2.1 |
| Minimum Stopping Sight Distance (grades < 2%): | | N/A | 305' | 2021 FDM Table 211.10.2 |

6.3.3 Frontage Roads

The preferred alternative improvements for the frontage roads consist of pavement milling and resurfacing, shoulder widening, and upgrades to drainage systems and pedestrian facilities in order to preserve and extend the life of the project. Details of the horizontal and vertical geometry are summarized in **Table 6-7**.

Table 6-7 | Geometry: Frontage Roads

| SR 826 Frontage Roads from Okeechobee Road to NW 103 Street (FPID 441830-1-52-01) and SR 826 Frontage Roads from NW 103 Street to NW 122 Street (FPID 441831-1-52-01) | | | | | | |
|---|---|--------------------------------|--------------------------|------------------------------|-------------------------|-----------------------------|
| Design Element | | W 20 Ave. (87260151) | NW 77 Ave. (87260152) | W 20 Ave. East (87260298) | NW 77 Ct. (87260506) | W 20 Ave West (87260521) |
| Functional Classification | | Urban Local | Urban Local | Urban Local | Urban Local | Urban Local |
| Design Speed (mph): | | 30 mph | 30 mph | 30 mph | 30 mph | 35 mph |
| Lane Width: | Travel Lanes | 11'-12' | 11'-12' | 11'-12' | 11'-12' | 11'-12' |
| | Auxiliary Lanes | N/A | 11'-15' | 10.5'-15' | 11' | 10'-12' |
| Cross Slope: | Travel Lanes | Min. Max. | 0.009 0.043 | 0.004 0.047 | 0.004 0.045 | 0.005 0.033 |
| | Outside Shoulder | Min. Max. | 0.060 | 0.060 | 0.060 | N/A 0.060 |
| | Inside Shoulder | Min. Max. | N/A | 0.016 0.066 | 0.037 0.065 | N/A N/A |
| | | | | | | |
| Median Width | | N/A | N/A | 16' | N/A | N/A |
| Shoulder Width: | Outside Shoulder | Full Width Paved Width | 2'-6' 0'-2' | 0'-10' 0'-10' | 0'-6' 0'-5' | N/A N/A |
| | Inside Shoulder | Full Width Paved Width | N/A N/A | 2'-6' 1'-5' | 6' 2' | N/A N/A |
| | | | | | | |
| | | | | | | |
| Border Width: | | 0'-46.7' | 0'-22' | 0'-24' | 8'-13' | 6'-8' |
| Horizontal Alignment: | | | | | | |
| Max. deflections in alignment without a curve: | | Max. 0°53'58" | Max. 2°00'00" | Max. 1°09'57" | N/A | Max. 0°46'31" |
| Length of Horizontal Curve | | Min. 56.16' | Min. 111.35' | Min. 111.59' | Min. 75.06' | Min. 114.87' |
| Min. Radius: | | Min. 72' | Min. 175' | Min. 76' | Min. 47' | Min. 75' |
| Max Superelevation: | | 0.086 | 0.080 | 0.070 | RC | 0.100 |
| Vertical Alignment: | | | | | | |
| Max. change in grade without Vertical Curve: | | N/A | 0.504% | N/A | N/A | N/A |
| Min. distance between VPIs on curbed roadways | | N/A | 50' | N/A | N/A | N/A |
| Min. grade on curbed roadways | | N/A | 0.20% | N/A | N/A | N/A |
| K-Value: | Crest: | N/A | N/A | N/A | N/A | N/A |
| | Sag: | N/A | 128 | N/A | N/A | N/A |
| Min. Curve Length: | | Crest/Sag: | N/A | 120 | N/A | N/A |
| Vertical Clearance: | | | | | | |
| Signals, mast arms, or other structures | | N/A | N/A | 17' | N/A | 17' |
| Bridges over Roadways: | | N/A | 17'-11" | N/A | 40'+ | N/A |
| Min. Stopping Sight Distance: (Grades < 2%) | | 121' | 149' | 115' | 109' | 149' |
| Clear Zone: (flush shoulder section) | RRR | Travel Lanes & Auxiliary Lanes | Min. 3' | 6' | Min. 4' | N/A |
| | Control Zone | Travel Lanes | Min. 3' | 12' | Min. 2' | N/A |
| | | Auxiliary Lanes | N/A | 10' | 10' | N/A |
| Min. Lateral Offset: (curb & gutter section) | Light Poles, Signal Poles, ITS Poles, Trees | | 1.5' | 1.5' | 1.5' | 1.5' |
| | Bridge Piers & Abutments | | N/A | 8.4' | 8.7' | N/A |
| Sidewalk Width: | Existing | | 5' | N/A | 5' | 5' |
| | Proposed | | 4'-6' | | 4.7'-6' | 4.2'-6' |
| Bicycle Facilities: | | 0'-2' | 0'-10' | 0'-5' | N/A | 0'-5' |
| Bridge Width: | | N/A | N/A | 6' shoulder | N/A | 1'-4" shoulder |

6.4 Access Management

Access management throughout the study limits will remain the same.

6.5 Design Variations and Exceptions

Design variations and exceptions necessary for the Preferred Alternative, both along SR 826 and the frontage roads include the following:

6.5.1 Design Variations

SR 826:

- Barrier Mounted Fence
 - The locations where the proposed fence is being mounted on top of new concrete barrier wall is from Sta. 497+94.98 to Sta. 503+99.49, and from Sta. 511+10.67 to Sta. 520+98.39. The proposed fence mounted on top of the new concrete barrier wall is a non-crash tested continuous item and does not meet the minimum offset to hazard above top of barrier wall requirement.
- Border Width
 - The NB off ramp to NW 103rd Street is proposed with border width less than the 8-foot FDOT requires for curbed roadway and existing border with of less than 10-feet for existing wall to remain.
- Buffer Width
 - The buffer width throughout the project will be maintained at 2-feet, which is less than the current criteria of 4-feet. The 2-feet buffer width is consistent with the remainder of the corridor.
- Cross Slope
 - Throughout the project, no changes will be made to the existing cross slope. The widening will match adjacent lane cross slope.
- Recovery Area
 - There is one location within the project limits where a 360 feet escape taper or recovery area, as required per Standard Index 525, is not provided for an exit ramp. As such, a design variation is required for the SB exit ramp to NW 103rd Street.
- Weaving Distance
 - There is one location within the project limits where the proposed design provides the required 1000 feet per lane change through the weaving section between the SB EL egress and the SB off-ramp at NW 74th Street, for a total of 4000 feet. However due to space constraints, the additional 1500 feet intended to allow traffic in the outside GP lane to access the exit ramp cannot be provided. Since not providing this additional 1500 feet does not comply with the current 2020 FDM criteria, a design variation is required.

Frontage Roads:

- Bicycle Facilities

- The project limits include 22 segments where bicycle facilities are not proposed, due to the available existing pavement width or other roadside impacts.
- Border Width
 - The project limits include 27 segments with sub-standard Border Width less than FDOT and AASHTO minimum Border Width of 8.0 feet on existing roadways. Median Width
- Cross Slope
 - A Design Variation is required for 29 locations with existing sub-standard cross slopes less than 0.015 or greater than 0.030, in normal-crown segments outside the limits of superelevation transitions or intersection plateaus.
- Horizontal Curve Radius and Length
 - A Design Variation is being requested for 9 horizontal curves with sub-standard radius and 18 horizontal curves with sub-standard length. Some of the existing horizontal curves along the Frontage Roads near intersections were originally designed to meet a design speed of 25 mph or less and do not meet the current FDOT RRR criteria for minimum radius at the proposed design speeds of 30 mph or 35 mph. Most of the existing horizontal curves do not meet the FDOT minimum length of horizontal curve of 400 feet.
- Superelevation Rate
 - A Design Variation is being requested for 6 horizontal curves with sub-standard superelevation rate. Some of the existing horizontal curves along the Frontage Roads near intersections were originally designed to meet a design speed of 20 mph or less and do not meet the current FDOT criteria for superelevation rate at the proposed design speeds of 30 mph or 35 mph.
- Horizontal Stopping Sight Distance
 - A Design Variation is being requested for 6 horizontal curves with sub-standard stopping sight distance due to roadside objections at the right of way line. Some of the existing horizontal curves along the Frontage Roads were originally designed to meet a design speed of 20 mph or less and do not meet the current FDOT criteria for stopping sight distance at the proposed design speeds of 30 mph or 35 mph.
- Lane Width
 - The project limits include 19 locations with sub-standard lane widths, including travel lanes less than 12 feet wide in undivided two-lane sections and turn lanes less than 11 feet wide in divided sections.
- Lateral offset
 - The project limits include existing roadside objects located inside the clear zone; including 57 trees, 2 ITS poles, and 3 rock boulders.
- Shoulder Width
 - The project limits include 15 segments with sub-standard shoulder widths, either full-width shoulders less than 6 feet, paved shoulders less than 5 feet wide.
- Bridge Width
 - The project limits include two bridges with sub-standard bridge widths and outside shoulders less than 4.0 feet wide. At Bridge 870570, the existing shoulder widths are proposed to be reduced on LT & RT sides to provide a raised sidewalk (6' wide) on the RT side while matching

the existing bridge deck width. At Bridge 870569, the existing LT shoulder width and lane width are proposed to be reduced to provide a raised sidewalk (4' wide) on the LT side while matching the existing bridge deck width.

- Guardrail Lateral Offset
 - The project limits include four segments with sub-standard guardrail lateral offset from the shoulder break point.
- Sidewalk Width
 - There are three locations with proposed new sidewalks less than 6 feet wide due to lack of available right of way.
- Sight Triangles
 - A Design Variation is being requested for 64 locations with existing obstructions to the clear sight triangle. The 14.5 foot required driver-eye setback encroaches outside the FDOT right of way at many existing driveways within the project limits where the distance to the right of way line is 14 feet or less from the travel lane and the fencing, landscaping, or walls on the private property create an obstruction to the clear sight distance.

6.5.2 Design Exceptions

SR 826:

- Lane Width
 - Exception for lane width consistent with the existing conditions within the PD&E study limits, 11-feet provided, 12-feet required.
- Shoulder Width
 - Exception for shoulder width consistent with the existing conditions within the PD&E study limits. Multiple locations in the southbound direction have existing shoulders less than the 10-feet required will be maintained by the project.
- Vertical Clearance
 - Exception for vertical clearance consistent with the existing conditions. The bridge widenings of the SR 826 mainline over the Metrorail and FEC Railroad will maintain the existing substandard vertical clearance.

6.6 Lighting

SR 826 southbound and northbound mainline and ramps existing conventional lighting assemblies with HPS luminaires are proposed to be replaced with LED luminaires throughout the widening of the mainline and proposed outside barrier walls due to the following reasons:

- The proposed roadway improvements will impact the locations of several light poles mounted on the outside barrier walls
- The existing median mounted conventional lighting system will not have the necessary intensity to illuminate the widened roadway segments from shoulder break to shoulder break

- HPS luminaires are obsolete, consume more energy and require more maintenance than the LED type

The proposed mainline and ramps conventional lighting assemblies will consist of FDOT standard aluminum light poles, single and double bracket arms and LED cobra head type luminaires. All proposed luminaires will be mounted with zero degrees tilt and will have zero up light (Full Cutoff) to minimize the sky glow (light pollution).

The existing conventional lighting assemblies with HPS luminaires at SR 826 Frontage Road/W 20th Avenue East and West at the intersections with NW 103rd Street and W 60th Street are proposed to be retrofitted with LED luminaires and additional lighting assemblies to be installed due to the following reasons:

- The proposed roadway improvements will change the overall layout/alignment at the intersections which will require the intersection lighting to be analyzed to ensure proper coverage
- Ensure that crosswalks are illuminated in accordance with current signalized intersection horizontal and vertical FDM lighting criteria to improve pedestrian safety
- HPS luminaires are obsolete, consume more energy and require more maintenance than the LED type

Underdeck lighting will be required to be analyzed due to the widening of SR 826 bridge over NW 103rd Street to ensure widen areas are properly illuminated. The existing underdeck lighting pendant mounted luminaires which are HPS will be replaced with more efficient and sustainable LED wall/pier cap mounted luminaires. Also, in accordance with the 2020 FDM the only luminaire to be used for underdeck lighting is wall mount fixture located on the pier or pier cap.

SR 826 Frontage Roads East and West which include, NW 77th Avenue, W 20th Avenue West, W 20th Avenue East (East Frontage Road) and W 67th Place roadway segments excluding the intersections at NW 103rd Street and W 60th Street conventional lighting assemblies with HPS luminaires impacted by the proposed shoulder widening and sidewalk construction are proposed to be replaced with LED luminaires due to the following reasons:

- The existing lighting assemblies on SR 826 west barrier wall adjacent and along NW 77th Avenue will be impacted by the widening of SR 826 southbound
- Four Concrete light poles, three along W 67th Place (West Frontage Road) and one at W 20th Avenue East will be impacted by the proposed sidewalk and shoulder lanes widening
- HPS luminaires are obsolete, consume more energy and require more maintenance than the LED type

6.7 Utilities

The Preferred Alternative will require the manhole adjustments for Miami Dade Water and Sewer District water and sewer manholes as well as the relocation of FPL Distribution poles.

6.8 Preliminary Drainage Analysis

For the allowable spread, design speed for the expressway is greater than 55 mile per hour (mph). Therefore, no encroachment is allowed in the travel lane. For Frontage Road, design speed is less than 45 mph; spread is allowed to encroach a ½ of lane.

In addition to the above standards, for sections with a shoulder gutter, the spread resulting from a 10-year frequency storm shall not exceed 1'-3" outside the gutter in the direction toward the front slope. The distance limits the spread to the face of guardrail posts.

The SR 826 project falls within the limits of the Community Panels 12086C0144L, 12086C0277L and 12086C0279L of the FEMA FIRM Maps of Miami-Dade County. The project is located within the Flood Zones AH, AE, and X. There is very negligible flood impact due to proposed improvements

6.8.1 Proposed Drainage Systems

The proposed drainage design consists of adjust the existing ditch-bottom inlets impacted by the proposed shoulder widening. Construct a drainage system with additional ditch-bottom inlets and French drains where required along the shoulder widening areas. It is noted that proposed storm sewer systems shall meet FDOT wall zone requirements however in some areas pipe running along MSE wall are shown to tie existing systems or avoid extensive pipe installations. These locations J-Bottom are proposed to offset pipe and meet wall strap requirement. Re-grade the sod at locations with existing ponding to improve the drainage pattern. All proposed stormwater management facilities will provide the necessary water quality treatment volume and limit the post-development peak discharge rate into the Little Canal to the pre-development peak discharge rate. Water quality treatment and discharge attenuation will be provided via existing trench drain and proposed French Drains. Additional French drain is being proposed where widening is proposed in the project in order to compensate for the additional impervious area along SR 826. The existing weirs in some of the basins will be modified in order to ensure that post-development discharge requirements are met for all receiving surface water bodies.

6.9 Structures

6.9.1 Horizontal and Vertical Clearance

The primary function of vertical clearance to structures going over roadways or railroads consists of providing safe passage to tall design vehicles and rail cars beneath these structures. The FDOT Florida Design Manual (FDM) specifies that the highest point on the roadway below a bridge structure must measure a minimum of 16.5-feet to the lowest point (low member) beneath the structure. This includes provisions for a future underpass resurfacing of 6 inches over the existing pavement elevation. The FDM also states to provide 23.5-ft of vertical clearance for Roadway or Pedestrian Bridge over Railroad, and 24.25-ft of vertical clearance for Roadway or Pedestrian bridge over Electrified Railroad. According to the Miami Dade Transit manual, vertical clearance, guideway structure under a fixed structure, shall be 13'-0" minimum, measured from top of rail to the nearest point of the obstruction.

AASHTO requires a minimum vertical clearance of 16-feet for structures passing over roadways including auxiliary lanes and the usable width of shoulders. Further guidance allows a minimum vertical clearance of 14-feet in highly urbanized areas provided there is an alternate facility with the minimum 16-feet clearance. For railroad underpasses, AASHTO recommends a minimum vertical clearance of 23-feet.

The vertical clearance for all the bridges along SR 826 over roadways meet the design criteria. The bridges over Metrorail and FEC will maintain the existing substandard vertical clearances.

The horizontal clearance underneath the existing bridges is the lateral distance from the roadway edge of travel lane to the bridge abutment or piers. The horizontal clearance requirements for most roadside features and objects are based on providing the required clear zone. Both the FDOT FDM and AASHTO require bridge piers and abutment walls to be placed outside the clear zone unless shielded by a crash worthy barrier.

The following sections provide descriptions of proposed modifications to the bridge structures. There are five (5) bridges throughout the corridor that have no modifications.


6.9.2 Flyover Bridge from SR 932/NW 103rd westbound to SR 826 southbound

6.9.2.1 Bridge Analysis

The proposed improvements require the bridge to be modified to accommodate the proposed new roadway typical section. Major modifications are necessary to pier 5 and modifications are necessary to both piers 2 and 3 as well as the existing bridge deck. Additionally, girder 5 will be removed with the bridge deck removal

Figure 6-5 shows the proposed bridge typical section for the flyover bridge.

Figure 6-5 | Typical Section: Flyover Bridge from SR 932/NW 103rd WB to SR 826 SB, Bridge No. 870856




6.9.2.2 Construction Sequence

To construct the Pier 5 modifications, the steps below will be followed:

1. Construct new column in front of existing column.
2. Construct new right and left cap.
3. Construct integral cap with post-tensioning.
4. Shift loads to temporary bearings on new right and left cap.
5. Demolish existing column and cap.
6. Build new middle cap
7. Shift loads to permanent bearings on new middle cap.

The construction sequence is illustrated in **Figure 6-6**.

Figure 6-6 | Construction Sequence




6.9.3 Southbound 826 over Metrorail

The SR 826 over Metrorail bridge is proposed to be widened in the Southbound direction to accommodate an additional lane.

Figure 6-7 shows the proposed bridge typical section


Figure 6-7 | Typical Section: SB 826 over Metrorail, Bridge No. 870257



6.9.4 West Frontage Road over Little River Canal

The West Frontage Road over the Little River Canal improvements consist of barrier replacement, slab replacement, and adding sidewalk on one side. These improvements will take place without widening the bridge. The bridge typical section is shown in **Figure 6-8**.


Figure 6-8 | Typical Section: West Frontage Road over Little River Canal, Bridge No. 870569



6.9.5 East Frontage Road over Little River Canal

The East Frontage Road over the Little River Canal improvements consist of barrier replacement, expansion joint header replacement, resurfacing of the asphalt surface, and adding sidewalk on one side. These improvements will take place without widening the bridge. The bridge typical section is shown in Figure 6-9.


Figure 6-9 | Typical Section: East Frontage Road over Little River Canal, Bridge No. 870570



6.9.6 Southbound SR 826 over FEC Railroad

The SR 826 over FEC Railroad is proposed to be widened in the Southbound direction to accommodate an additional lane.


Figure 6-10 shows the proposed bridge typical section

Figure 6-10 | Typical Section: SB SR 826 over FEC Railroad, Bridge No. 870258

6.9.7 Southbound SR 826 at SR934/NW 74th Street

The SR 826 over SR 934/NW 74th Street is proposed to be widened in the Southbound direction to accommodate an additional lane.

Figure 6-11 shows the proposed bridge typical section


Figure 6-11 | Typical Section: SB SR 826 over NW 74th Street, Bridge No. 870964

6.9.8 Southbound SR 826 at SR 932/NW 103rd Street

The SR 826 over SR 932/NW 103rd Street is proposed to be widened in the Southbound direction to accommodate an additional lane.

Figure 6-12 shows the proposed bridge typical section

Figure 6-12 | Typical Section: SB SR 826 over NW 103rd Street, Bridge No. 870757




6.9.9 Northbound SR 826 at SR 932/NW 103rd Street

The SR 826 over SR 932/NW 103rd Street is proposed to be widened in the Northbound direction to provide shoulders that meet FDOT standards.

Figure 6-13 shows the proposed bridge typical section

Figure 6-13 | Typical Section: NB SR 826 over NW 103rd Street, Bridge No. 870995



6.9.10 Retaining Wall Modifications

Retaining walls within the construction limits will be modified to accommodate the necessary bridge widenings as noted above.

6.9.11 Aesthetics

The bridges and retaining walls within the construction limits shall meet the requirements of Level One aesthetic criteria, as defined by FDM Section 121.9.3.

6.9.12 ITS Features

Within the project limits, the Intelligent Transportation System (ITS) will be adjusted to support the earlier mentioned roadway changes. ITS improvements include the installation of a new tolling site along both the northbound and southbound directions that will require a specific pavement design to be implemented 50 feet north and south of the gantry location. The project will also include the installation and replacement of impacted Closed-Circuit Television (CCTV) cameras, Dynamic Message Signs (DMS), Microwave Vehicle Detection Systems (MVDS), and Ramp Signal Systems as necessary.

6.10 Maintenance of Traffic

6.10.1 Southbound SR 826

The construction of southbound SR 826 segment consists of three phases. Phase one consists of relocating the SR 826 southbound express lane ingress to the vicinity of NW 103rd Street. Phase two consists of the outside widening to provide the additional lane of capacity in the southbound direction. The third phase consists of milling and resurfacing and the final striping configuration will be placed.

6.10.2 Northbound SR 826

The construction for the northbound SR 826 segment consists of two phases. Phase one consists of outside widening in order to bring shoulders to standard. The second phase consists of milling and resurfacing and the final striping configuration will be placed.

6.10.3 Frontage Roads

The majority of the proposed work on the Frontage Roads can be performed without impacting traffic. For the milling and resurfacing of the roadway full nighttime closures with detours will be needed.

6.10.4 Miscellaneous Overhead Structures

For construction of overhead structures (bridges, sign panels) intermittent detours, lane shifts, lane closures and traffic pacing will be needed. It is recommended to follow techniques described in the FDM Chapter 240.7.1.1.

6.11 Cost Estimates

A construction cost estimate for the Preferred Alternative was prepared both the SR 826 improvements and the frontage road improvements. Please refer to **Appendix C** for the construction cost estimates,

6.12 Environmental Analysis

An environmental analysis was conducted for this PD&E through detailed studies of the Social, Economic, Cultural, Natural, and Physical environments. A detailed discussion of all subjects summarized below and more can be found in the State Environmental Impact Report and the individual corresponding environmental reports.

6.12.1 Existing and Future Land Use

Existing and future land use was assessed through review of statewide generalized land use files. Geographic Information Systems (GIS) shapefiles were downloaded from the Florida Geographic Data Library (FGDL) and compared to the SCE study area. **Table 6-8** reports generalized existing land use by zoning description found within the study area. The predominant land use present is Industrial (29.71%), followed by Residential (20.26%), and Retail Office (19.10%).

Table 6-8 | SCE Study Area Existing Land Use

| Existing Land Use | Acres | Percent |
|-----------------------------------|--------|---------|
| Acreage Not Zoned for Agriculture | 81.59 | 2.93% |
| Agricultural | 9.73 | 0.35% |
| Centrally Assessed | 6.74 | 0.24% |
| Industrial | 827.02 | 29.71% |
| Institutional | 87.83 | 3.15% |
| Parcels with No Values | 3.47 | 0.12% |
| Public/Semi-Public | 149.45 | 5.37% |
| Recreation | 71.32 | 2.56% |
| Residential | 563.91 | 20.26% |
| Retail/Office | 531.67 | 19.10% |
| Right-Of-Way | 0.07 | 0.00% |
| Vacant Nonresidential | 102.88 | 3.70% |
| Vacant Residential | 326.13 | 11.71% |
| Water | 22.22 | 0.80% |

According to **Table 6-9**, which reports generalized future land use, the study area is expected to see an increase in industrial uses. Occurring well within the Miami-Dade urban growth boundary, SR 826, a limited access expressway, is consistent with the character and intensity of surrounding development. This project is not expected to affect the current or future land use of the area. No additional right-of-way will be required. Therefore, the acreage per land use type is not expected to change as a direct result of the project. Furthermore, no impacts to recreation and open space are expected by the Build Alternative.

Table 6-9 | SCE Study Area Future Land Use

| Future Land Use Description | Acres | Percent |
|--------------------------------------|---------|---------|
| Commercial | 296.11 | 12.17% |
| Industrial | 1268.80 | 52.13% |
| Institutional | 29.67 | 1.22% |
| Mixed Use - General | 23.27 | 0.96% |
| Recreation | 94.50 | 3.88% |
| Residential High (> 12 DU/AC) | 403.89 | 16.59% |
| Residential Medium (5.01 - 12 DU/AC) | 211.70 | 8.70% |
| Transportation/Utilities | 24.39 | 1.00% |
| Water | 81.72 | 3.36% |

A population and employment analysis conducted by the Miami-Dade TPO for the 2045 LRTP shows that between 2015 and 2045 population is expected to grow by approximately 920,000 (34%) and employment is expected to grow by over 500,000 (38%) within the County. Traversing two (2) of the seven (7) transportation planning areas (Central and Northwest) the greatest employment growth within the County is expected to occur within the Northwest transportation planning area. This area expects an employment increase of 44.1 percent and a modest increase in population of 27.1 percent. The Central transportation planning area expects a lower rate of population and employment growth (32.7% and 36.6% respectively) when compared to the countywide averages. The projected growth in the area will result in a significant increase in travel demand and further deteriorate the conditions on the already congested SR 826 corridor.

Due to the project improvements taking place within existing right-of-way no impacts are expected to adjacent use. Access to residential, employment and community features will likely be enhanced due to reduced congestion and improved traffic flow within the general-purpose lanes.

6.12.2 Cultural Resource Assessment Survey

A Cultural Resource Assessment Survey (CRAS) was prepared as part of the Project Development and Environment (PD&E) Study for the State Road (SR) 826/Palmetto Expressway from South of NW 36th Street (MP 8.355) to North of NW 154th Street (MP 17.950), in the towns of Miami Lakes and Medley and the cities of Doral, Hialeah and Hialeah Gardens, as well as unincorporated Miami-Dade County, Florida (Financial Project ID [FPID] Nos. 447165-1-22-01,

441830-1-22-01, and 441831-1-22-01). The purpose of this CRAS was to locate and evaluate archaeological and historic resources within the area of potential effect (APE) and to assess their eligibility for inclusion in the National Register of Historic Places (National Register) according to the criteria set forth in 36 CFR Section 60.4.

This assessment complies with the revised Chapter 267, Florida Statutes (F.S.); and standards embodied in the Florida Division of Historical Resources (FDHR) Cultural Resource Management Standards and Operational Manual (February 2003), and Chapter 1A-46 (Archaeological and Historical Report Standards and Guidelines), Florida Administrative Code. In addition, this report was prepared in conformity with standards set forth in Part 2, Chapter 8 (Archaeological and Historical Resources) of the FDOT Project Development and Environment (PD&E) Manual (effective July 1, 2020). All work also conforms to professional guidelines set forth in the Secretary of Interior's Standards and Guidelines for Archaeology and Historic Preservation (48 FR 44716, as amended and annotated).

The current study area has been surveyed and evaluated during several recent studies. In 2010, Janus Research conducted a CRAS of the I-75 PD&E Study from SR 826 (Palmetto Expressway) to North of Florida's Turnpike (HEFT), Miami-Dade County, Florida, FM No. 420669-1-22-01 [Florida Master Site File (FMSF) Manuscript No. 17998] as part of a PD&E study that included the evaluation of proposed improvements along SR 826/Palmetto Expressway from NW 103rd Street to NW 154th Street. The State Historic Preservation Officer (SHPO) concurred with the determinations and findings of this survey on February 15, 2011. In 2012, Janus Research conducted a CRAS of the SR 826/Palmetto Expressway Managed Lanes PD&E Study, FM No. 418423-3-22-01 (FMSF Manuscript No. 19276) as part of another PD&E study that included the evaluation of proposed improvements along SR 826/Palmetto Expressway from south of SR 836/Dolphin Expressway to NW 103rd Street. The SHPO concurred with the relevant determinations and findings of this survey on August 3, 2012.

In 2016, Janus Research conducted the CRAS Reevaluation for the SR 826 (Palmetto Expressway) from Flagler Street to NW 154th Street and SR 93/I-75 from SR 826 to NW 170th Street, Miami-Dade County, Florida (FPID Nos. 432687-1-52-01 and 432687-1-52-01; FMSF Manuscript No. 23335). This survey was an update to the 2010 and 2012 CRAS reports conducted due to design changes to the Design Build project to construct improvements evaluated during both the above referenced 2010 PD&E study, as well as the 2012 PD&E study for SR 826 (Palmetto Expressway) from NW 103rd Street to NW 154th Street (432687-3-22-01). This project converted an existing general purpose (GP) lane that was originally built to be operated as a High Occupancy Vehicle (HOV) lane, into an express lane (EL). The project also provided a second EL through widening and reduced lane width, shoulder width, and EL buffer width for the majority of the project limits. The SHPO concurred with the determinations and findings of this survey on November 2, 2016.

After the Palmetto ELs were opened to traffic in August 2019 and toll collection in September 2019, additional congestion and large differential between EL higher speeds and GP lanes lower speeds were observed in both the northbound (NB) and southbound (SB) directions during peak

travel times. Janus Research prepared two CRAS updates, Palmetto Express Lanes Modification – Interim Solution: Cultural Resource Assessment Survey Update to SR 826/Palmetto Expressway Project Development and Environment (PD&E) Study from South of SR 836 to North of SR 93/I-75 (FPID No. 418423-3-22-01), Miami-Dade County, Florida and Palmetto Express Lanes Modification – Interim Solution: Cultural Resource Assessment Survey Update to SR 93/I-75 Project Development and Environment (PD&E) Study from State Road (SR) 826/Palmetto Expressway to North of Florida's Turnpike (FPID No. 420669-1-22-01), Miami-Dade County, Florida (2020a; 2020b) to coordinate an interim solution for the NB lanes to be implemented immediately and to provide measurable improvements without the need to acquire right-of-way (ROW) and to avoid impacts to adjacent Florida Gas Transmission lines. The SHPO concurred with the findings of each of these reports on April 2, 2020.

The current survey is being conducted for the PD&E study to address a permanent solution for both the NB and SB lanes. This survey focused on identifying archaeological resources within the current APE as well as identifying historic resources which have become historic since the time of the previous studies and confirming there are no changes to the eligibility status of the previously identified National Register-eligible historic resources.

Two archaeological resources (8DA40 and 8DA75) were identified within the archaeological APE during the background research. The pedestrian survey did not identify any remains of these sites and confirmed the disturbed nature of the corridor. Subsurface testing within the corridor was not possible due to the extent of hardscape, underground utilities and drainage, and land modification. Previous archaeological monitoring conducted by Archaeological and Historical Conservancy, Inc. during the construction of the improvements for the most recent PD&E in the area documented the presence of fill and extremely disturbed soils within the limits of the previously recorded archaeological sites. The desktop analysis and pedestrian survey determined that the portion of the archaeological APE that was not previously comprehensively surveyed exhibited a low potential for containing intact archaeological sites. No Miami-Dade County-designated archaeological sites or zones are located within the APE.

The historic resources survey resulted in the identification of 49 historic resources within the historic resources APE. The resources include 15 previously recorded historic resources and 34 newly recorded historic resources. The 15 previously recorded historic resources include: six historic linear resources, six historic structures, two historic bridges, and one designed historic landscape. Two of these previously recorded historic resources have been determined eligible for listing in the National Register by the SHPO: the Miami Canal (8DA6525) and the FEC Railway (8DA10107). Twelve previously recorded historic resources were determined ineligible for listing in the National Register by the SHPO (8DA6352, 8DA11420, 8DA11680-8DA11683, 8DA12380-8DA12382, 8DA12389, 8DA12390, and 8DA15160). The one remaining previously recorded historic resource, 8DA12383, was determined to have insufficient information for an evaluation of National Register-eligibility by the SHPO.

FMSF forms were updated for two previously recorded historic resources: 8DA12382 and 8DA12383. The FMSF form for 8DA12382 was updated to correct the address, which is

incorrectly listed in the FMSF, but no changes to the resource since it was last recorded were observed, and it is still considered National Register-ineligible. The FMSF form for 8DA12383 was updated to correct the address, which is also incorrectly listed in the FMSF, and to update the evaluation of significance since it was first recorded since the SHPO did not provide a determination of eligibility. 8DA12383 exhibits a common architectural style found in South Florida, and limited research did not reveal any historical associations with significant people or events. Therefore, 8DA12383 is considered ineligible for listing in the National Register, either individually or as part of a historic district.

The 34 newly recorded resources within the historic resources APE include 27 historic structures (8DA19117-8DA19143), four historic resource groups (8DA19147-8DA19150), and three historic bridges (8DA19154-8DA19156). The four newly recorded resource groups include one industrial complex and three condominium complexes located on parcels that are partially within the historic resources APE. The 31 newly recorded historic resources are considered ineligible for listing in the National Register, either individually or as part of a historic district.

The three bridges identified during this study (8DA19154-8DA19156) are common bridge types, reinforced concrete slab and prestressed concrete multi-beam, and meet the criteria for the 2012 Program Comment issued by the Advisory Council on Historic Preservation (ACHP), Streamlining Section 106 Review for Actions Affecting Post-1945 Concrete and Steel Bridges (ACHP 2012). All three bridges are exempt from Section 106 consideration and were not evaluated for eligibility for the National Register; however, they were recorded and documented in the FMSF.

As previously noted, two resources in the APE have been determined eligible for listing in the National Register by the SHPO: the Miami Canal (8DA6525) and the FEC Railway (8DA10107). At the Miami Canal location, there are no improvements to the facility's bridge structure that crosses over the Miami Canal. At the FEC Railway, the southbound SR 826 bridge will be widened by 22 feet over the railroad to provide an additional lane of capacity. The widening will include all substructure and superstructure work necessary to complete the widening and the construction of crash walls adjacent to the railroad. However, ROW will be required from the railroad corridor for the new piers and the crash walls, but no materials or features will be impacted and the historic linear resource will continue to convey its significance. Based on the improvements proposed at these two locations, the Miami Canal and the FEC Railway will not be adversely affected by the project. Although this project is being conducted under Chapter 267, F.S., this effects evaluation acknowledges the guidance provided by Section 106 of the National Historic Preservation Act.

6.12.3 Community Facilities

Community features are public or private facilities, organizations, or locations that often hold special importance to local residents. **Figure 4-2** and **Figure 4-3** depict the facility location and corresponds with the tables listed in the section. **Tables 4-7** through **4-16** describe the community focal points present within the quarter-mile SCE study area. These types of facilities include:

- Cemetery
- Civic Center
- Cultural Center
- Existing Recreational Trail
- Fire Station
- Law Enforcement Facility
- Government Building
- Group Care Facility
- HealthCare Facility
- Hospital
- Parks and Recreational Facility
- School
- Social Services Facility
- Religious Facility

No community features will be displaced as a result of the proposed improvements. No negative impacts to community feature access have been identified.

Figure 6-14 | Community Features Key Sheet




Figure 6-15 | Community Features (1 of 6)




Figure 6-16 | Community Features (2 of 6)




Figure 6-17 | Community Features (3 of 6)




Figure 6-18 | Community Features (4 of 6)




Figure 6-19 | Community Features (5 of 6)




Figure 6-20 | Community Features (6 of 6)




Table 6-10 | Group Care Facilities in SCE Study Area

| MAP ID # | Map # | Facility | Address |
|----------|-------|--|--------------------|
| 1 | 6 | Golden Palm A.L.F. Inc. | 7280 NW 169 Street |
| 2 | 3 | Citrus Health Network - Adult Crisis Unit | 4175 W 20 Avenue |
| 2 | 3 | Citrus Health Network - Children's Crisis Unit | 4175 W 20 Avenue |
| 3 | 4 | Sweet Paradise ALF | 5991 W 20 Lane |
| 4 | 4 | Our Loving Mother | 1635 W 65 Street |
| 5 | 5 | New World ALF | 8184 W 18 Avenue |

Table 6-11 | Park and Recreational Facilities in SCE Study Area

| MAP ID # | Map # | Facility | Address |
|----------|-------|------------------------------|------------------------|
| 1 | 6 | Miami Lakes Mini Park (P-86) | 6851 Main Street |
| 2 | 6 | Miami Lakes Mini Park (P-56) | 16331 Ravenwood Place |
| 3 | 5 | Miami Lakes Mini Park (P-28) | 7350 Sabal Drive |
| 4 | 6 | Miami Lakes Mini Park (P-55) | 16695 NW 67 Avenue |
| 5 | 6 | Miami Lakes Mini Park (P-50) | 7599 Loch Ness Drive |
| 6 | 6 | Miami Lakes Mini Park (P-52) | 6700 Loch Ness Drive |
| 7 | 6 | Miami Lakes Mini Park (P-51) | 6970 Loch Ness Drive |
| 8 | 4 | Garden of The Arts Park | 1850 W 76 Street |
| 9 | 6 | Don Shula's Golf Club | 7601 Miami Lakes Drive |

Table 6-12 | Law Enforcement Facilities in SCE Study Area

| MAP ID # | Map # | Facility | Address |
|----------|-------|---|----------------------------|
| 1 | 3 | Miami-Dade College Police Department - Hialeah Campus | 1780 W 49 Street (Rm 1114) |

Table 6-13 | Hospitals in SCE Study Area

| MAP ID # | Map # | Facility | Address |
|----------|-------|---------------------------|------------------|
| 1 | 3 | Southern Winds Hospital | 4225 W 20 Avenue |
| 2 | 4 | Palmetto General Hospital | 2001 W 68 Street |

Table 6-14 | Healthcare Facilities in SCE Study Area

| MAP ID # | Map # | Facility | Address |
|----------|-------|--|-------------------------------|
| 1 | 4 | Perez D.O. Pa Gerardo C. | 5355 W 20 Avenue |
| 2 | 2 | Leah Medical Center Inc. | 6917 NW 77 Avenue |
| 2 | 2 | Mdd Medical Center | 6905-07 NW 77 Avenue |
| 3 | 3 | Mora Elba M.D. P.A. | 1840 W 49 Street, Suite 516 |
| 3 | 3 | Luis Lugo-Arrendell M.D. P.A. | 1840 W 49 Street, Suite 510 |
| 3 | 3 | Esperanza Arce- Nunez M.D. | 1840 W 49 Street, Suite 420 |
| 3 | 3 | Multimed Care Inc | 1840 W 49 Street, Suite 700 |
| 3 | 3 | International Research Associates, LLC | 1840 W 49th Street, Suite 103 |
| 3 | 3 | American Family Health Center | 1840 W 49 Street, Suite 425 |
| 3 | 3 | Savin Medical Group/ Carlos Aguilar | 1840 W 49 Street, Suite 229 |
| 3 | 3 | Isabel C. Gomez, M.D. | 1840 W 49 Street, Suite 517 |
| 3 | 3 | Luzmed Clinical Research Institute | 1840 W 49 Street, Suite 605 |
| 3 | 3 | Spera, Carlos, M.D., P.A. | 1840 W 49 Street, Suite 411 |
| 3 | 3 | Vicente A. Chavarria Md | 1840 W 49 Street, Suite 103 |
| 3 | 3 | Eduardo G. Gomez M.D., P.A. | 1840 W 49 Street, Suite 607 |
| 3 | 3 | Rodrigo Belacazar, M.D., P.L.L.C. | 1840 W 49 Street, Suite 601 |
| 3 | 3 | Community Clinical Center Inc | 1840 W 49 Street, Suite 105 |
| 3 | 3 | Faith Medical Group Inc | 1840 W 49 Street 514a |
| 4 | 4 | Nuconcept Clinic LLC | 10550 NW 77 Court, Suite 312 |
| 4 | 4 | Centro De Terapia Avanzada Inc. | 10550 NW 77 Court, Suite 308 |
| 4 | 4 | Context Medical Group | 10550 NW 77 Court, Suite 305 |
| 5 | 4 | Fraga Pediatrics & Associates Dba/Prime Care Fc | 5590 W 20 Avenue, Suite 100 |
| 5 | 4 | South Florida Pediatrics Inc. | 5590 W 20 Avenue, Suite 300 |
| 5 | 4 | Eduardo A Reyes M.D. P.A | 5590 W 20 Avenue, Suite 401 |
| 5 | 4 | Yanssel Delgado DPM | 5590 W 20 Avenue, Suite 404 |
| 6 | 4 | Maria T. Pol-Carballo M.D. P.A. | 6450 W 21 Court, Suite 301 |
| 6 | 4 | Victores Md Pa Lorenzo | 6450 W 21 Court, Suite 205 |
| 6 | 4 | Power Pediatrics Inc | 6450 W 21 Court, Suite 306 |
| 6 | 4 | Cordoves M.D. Lourdes A. | 6450 W 21 Court, Suite 305 |
| 6 | 4 | 21 st Century Oncology, LLC Dba Southeast Florida | 6450 W 21 Court, Stop 205 |
| 7 | 4 | Miguel A. Chamah M.D. Pa. | 1800 W 68 Street, Suite 127 |

| MAP ID # | Map # | Facility | Address |
|----------|-------|--|-------------------------------|
| 7 | 4 | John A. Serpa MD PA | 1800 W 68 Street, Suite 115 |
| 8 | 4 | Mt. Sinai Cardiac | 2150 W 68 Street, Suite 115 |
| 8 | 4 | Chen Medical Hialeah | 2150 W 68 Street, Suite 200 |
| 9 | 4 | Urology Specialists LLC | 2140 W 68 Street, Suite 200 |
| 9 | 4 | Tenet Florida Physician Services, LLC | 2140 W 68 Street, Suite 403 |
| 9 | 4 | Moya M.D. Pa Roberto A. | 2140 W 68 Street, Suite 201 |
| 9 | 4 | Fernandez M.D. P.A. Benedicto | 2140 W 68 Street, Suite 406 |
| 9 | 4 | Digestive Medicine Assoc. | 2140 W 68 Street, Suite 300 |
| 9 | 4 | Ravelo Jorge E. | 2140 W 68 Street, Suite 307 |
| 9 | 4 | Julian Marquez MD PA | 2140 W 68 Street, Suite 401A |
| 9 | 4 | Carrillo Pedro L. Jr. M.D. | 2140 W 68 Street, Suite 308 |
| 9 | 4 | Imaging Center The | 2140 W 68 Street 103 |
| 9 | 4 | Palmetto ASC L.P. The | 2140 W 68 Street, Suite 102 |
| 9 | 4 | Aran Eye Association | 2140 W 68 Street, Suite 405 |
| 9 | 4 | America Mobile Health Service Inc. | 2134 W 68 Street |
| 9 | 4 | Urology Specialists, LLC | 2140 W 68 Street, Suite 302 |
| 10 | 4 | Siguanea LLC | 7100 W 20 Avenue, Suite 312 |
| 10 | 4 | Allergy and Asthma Center of Miami P.A. | 7100 W 20 Avenue, Suite 706 |
| 10 | 4 | Rovira, M.D. Juan J. | 7100 W 20 Avenue, Suite 404 |
| 10 | 4 | Jorge L. Diaz Do Pa | 7100 W 20 Avenue, Suite 403 |
| 10 | 4 | Salinas M.D. Pa Hugo | 7100 W 20 Avenue, Suite 516 |
| 10 | 4 | Uro-Medix Inc. | 7100 W 20 Avenue, Suite 703 |
| 10 | 4 | Orthopedic Specialists of South Fl | 7100 W 20 Avenue, Suite 101 |
| 10 | 4 | Torres M.D. Julio D. | 7100 W 20 Avenue, Suite 105 |
| 10 | 4 | Pagan Luis M.D. | 7100 W 20 Avenue, Suite G-176 |
| 10 | 4 | Fernandez & Molina M.D. | 7100 W 20 Avenue, Suite 602 |
| 10 | 4 | Halperin, Scott B. M.D. | 7100 W 20 Avenue, Suite 213 |
| 10 | 4 | Shalhub M.D. Don | 7100 W 20 Avenue, Suite 414 |
| 10 | 4 | Alhambra Medical Group Inc. | 7100 W 20 Avenue, Suite 506 |
| 10 | 4 | Campos M.D. Pa Jaime E. | 7100 W 20 Avenue, Suite 303 |
| 10 | 4 | Tenet Florida Physician Services/Dr. Sangita Gogat | 7100 W 20 Avenue, Suite 107 |
| 10 | 4 | Jose Pinero, Md | 7100 W 20 Avenue, Suite 314 |
| 10 | 4 | J.V. Ferreira M.D. P.A. | 7100 W 20 Avenue, Suite 801 |

| MAP ID # | Map # | Facility | Address |
|----------|-------|---|-------------------------------|
| 10 | 4 | Advanced Gastroenterology of South Florida, P.A. | 7100 W 20 Avenue, Suite 301 |
| 10 | 4 | West Dade Pediatrics Inc. | 7100 W 20 Avenue, Suite 411 |
| 10 | 4 | Font Jose M.D. P.A. | 7100 W 20 Avenue, Suite 806 |
| 10 | 4 | Reyes Md Franklin A. | 7100 W 20 Avenue, Suite 616 |
| 10 | 4 | Andres Vega M.D. P.A. | 7100 W 20 Avenue, Suite 601 |
| 10 | 4 | Alvarez M.D. Pa Hernando | 7100 W 20 Avenue, Suite 304 |
| 10 | 4 | Kenneth Strubbe, MD | 7100 W 20 Avenue, Suite 107 |
| 10 | 4 | Physicians' Management GP. Of Dade, Inc. | 7100 W 20 Avenue, Suite 110 |
| 10 | 4 | Inpatient Healthcare Group | 7100 W 20 Avenue, Suite G-126 |
| 10 | 4 | Miami Ob/Gyn Dreams | 7100 W 20 Avenue, Suite 803 |
| 10 | 4 | Jose Rodriguez-Valdes M.D. | 7100 W 20 Avenue, Suite 401 |
| 10 | 4 | Steven Fields M.D. P.A | 7100 W 20 Avenue, Suite 311 |
| 10 | 4 | Northwest Center for Infertility and Reproductive | 7100 W 20 Avenue, Suite 205 |
| 10 | 4 | Neurology-Neurosurgery of Dade And Broward Inc. | 7100 W 20 Avenue, Suite 702 |
| 10 | 4 | Miami Interventional Spine Specialists | 7100 W 20 Avenue, Suite 210 |
| 10 | 4 | Martinez-Alba Jr M.D. Jose R. | 7100 W 20 Avenue, Suite 514 |
| 10 | 4 | Ason M.D. Rafael | 7100 W 20 Avenue, Suite 501 |
| 10 | 4 | C & C Medical | 7100 W 20 Avenue, Suite 412 |
| 10 | 4 | Martinez-Catinchi MD PA Fernando | 7100 W 20 Avenue, Suite 402 |
| 10 | 4 | Vidal Angel F. M.D. P.A. | 7100 W 20 Avenue, Suite 703 |
| 10 | 4 | Gilberto Concepcion MD PA | 7100 W 20 Avenue, Suite 806 |
| 10 | 4 | Sofia E. Vasquez - Solomon M.D | 7100 W 20 Avenue, Suite 214 |
| 10 | 4 | Cesar A. O'phelan M.D. | 7100 W 20 Avenue, Suite 201 |
| 11 | 4 | Jaraki Medical Care, P.A. | 7150 W 20 Avenue, Suite 318 |
| 11 | 4 | Alvarez Pedro G. D.O. P.A. | 7150 W 20 Avenue, Suite 607 |
| 11 | 4 | Tenet Florida Physician Services LLC | 7150 W 20 Avenue, Suite 615 |
| 11 | 4 | Gonzalez Abreu &Fernandez MD. PA. | 7150 W 20 Avenue, Suite 202 |
| 11 | 4 | Shuman Md Pa Joseph | 7150 W 20 Avenue, Suite 408 |
| 11 | 4 | Dr. Victoria Garcia And Associates LLC | 7150 W 20 Avenue, Suite 501 |
| 11 | 4 | South Florida Eye Associates | 7150 W 20 Avenue, Suite 411 |
| 11 | 4 | Florida Center for Allergy & Asthma | 7150 W 20 Avenue, Suite 106 |
| 11 | 4 | Hamady Ghassan T. M.D. | 7150 W 20 Avenue, Suite 406 |

| MAP ID # | Map # | Facility | Address |
|----------|-------|---|-------------------------------|
| 11 | 4 | Miami Lakes Medical Center Assoc. PA | 7150 W 20 Avenue, Suite 615 |
| 11 | 4 | Oncology & Radiation Assoc. Pa. | 7150 W 20 Avenue, Suite 214 |
| 11 | 4 | Pombo, Md, Hector | 7150 W 20 Avenue, Suite 313 |
| 11 | 4 | Rodriguez M.D. J. Ramon | 7150 W 20 Avenue, Suite 402 |
| 11 | 4 | Palmetto Artificial Kidney Center | 7150 W 20 Avenue, Suite 109 |
| 11 | 4 | Rodolfo A. Perez, M.D | 7150 W 20 Avenue, Suite 304 |
| 11 | 4 | South Florida Gyn\Oncology | 7150 W 20 Avenue, Suite 313 |
| 11 | 4 | Robert O'Neill MD | 7150 W 20 Avenue, Suite 612 |
| 11 | 4 | Miami Spine Care | 7150 W 20 Avenue, Suite 209 |
| 12 | 4 | Karelia Ruiz | 7600 W 20 Avenue, Suite 106 |
| 12 | 4 | Dr. Mary Jo Villar | 7600 W 20 Avenue, Suite 104 |
| 13 | 5 | Canton Enrique J. MD. | 14505 Commerce Way, Suite 800 |
| 13 | 5 | Renovation of Life Dialysis | 14505 Commerce Way, Suite 600 |
| 13 | 5 | De Quesada Gonzalo Md | 14505 Commerce Way, Suite 800 |
| 13 | 5 | Rives Elvira J. MD. PA. | 14505 Commerce Way, Suite 800 |
| 13 | 5 | Diamond Health Medical Care Center Inc | 14505 Commerce Way, Suite 750 |
| 14 | 5 | B & C Family Health Group P.A | 7761 NW 146 Street |
| 14 | 5 | Lysette Iglesias M.D. PA. | 7761 NW 146 Street |
| 15 | 3 | Community Medical Group of Hialeah | 3805 W 20 Avenue, Suite 105 |
| 16 | 5 | Baptist Medical Plaza Miami Lakes Urgent Care | 14701 NW 77 Avenue |
| 17 | 1 | Tenet Florida Physician Services | 3901 NW 79 Avenue, Suite 222 |
| 18 | 5 | Power G Medical Center Corp | 14411 Commerce Way, Suite 305 |
| 19 | 3 | Dynamic Medical Services | 1685 W 49 Street, Suite 1104 |
| 20 | 4 | Hialeah Diagnostic Inc. | 1991 W 60 Street |
| 21 | 1 | Doral Kidney Center | 7755 NW 48 Street, Suite 120 |
| 22 | 4 | University Health Care Hialeah, Inc | 1700 W 68 Street |
| 23 | 5 & 6 | Miami Children's Hospital, Miami Lakes Outpatient | 15025 NW 77 Avenue |
| 24 | 5 & 6 | Interamerican Medical Center | 15105 NW 77 Avenue, Floor 4 |
| 25 | 4 | Carlos L. Delgado | 1957 W 60 Street |
| 26 | 5 | South Fl Pediatric Partners | 14400 NW 77 Court, Suite 102 |
| 27 | 5 | Universal Imaging and Radiology | 14462 Commerce Way |
| 28 | 4 | Westland Medical Center | 2150 W 76 Street, Suite 110 |

| MAP ID # | Map # | Facility | Address |
|----------|-------|-------------------------------------|--------------------------------|
| 29 | 4 | All M.D. Medical Center LLC | 2100 W 68 Street |
| 30 | 3 | IQuest Surgery Center Inc | 1738 W 49 Street, Suite 8,9,10 |
| 31 | 4 | BMA Of Hialeah | 7170 W 20 Avenue |
| 32 | 2 | Life Medical Center & Research | 6801 NW 77 Avenue, Suite 105 |
| 33 | 1 | Concentra Medical Center | 7800 NW 25 Street |
| 34 | 4 | Palmetto Lakes Surgical Center | 2100 W 76 Street, Suite 101 |
| 35 | 4 | A Woman's Option | 1933 W 60 Street |
| 36 | 3 | The Medical City | 1905 W 35 Street, Suite 105 |
| 37 | 4 | Palmetto Rehab and Health Center | 6750 W 22 Court |
| 38 | 3 | Florida Health Solution Center | 1779 W 37 Street, Suite 1 |
| 39 | 4 | Elite Health & Rehabilitation Ctr. | 1949 W 68 Street, Suite 200 |
| 40 | 6 | Palm Plaza Medical Center, LLC | 16795 NW 67 Avenue |
| 41 | 4 | Perez Pediatrics P.A. | 7100 W 20 Avenue, Suite G154 |
| 42 | 6 | Bridgewater Women Center LLC | 16782 NW 67 Avenue |
| 43 | 3 | Citrus Health Network Inc | 4125 W 20 Avenue |
| 44 | 4 | Cardiology Diagnostic Serv. So. Fl. | 6450 W 21 Court, Suite 201 |
| 45 | 1 | Doral Imaging Institute LLC. | 7775 NW 48 Street, Suite 150 |
| 46 | 5 | Barry M.D. Patrick J. | 7850 NW 146 Street, Suite 508 |
| 47 | 4 | Leon Medical Centers Inc | 2020 W 64 Street |

Table 6-15 | Government Buildings in SCE Study Area

| MAP ID # | Map # | Facility | Address |
|----------|-------|--|-------------------|
| 1 | 4 | U S Post Office - Hialeah Annex | 7000 W 19 Court |
| 2 | 1 | U S Post Office - Miami Periodical Annex | 7499 NW 31 Street |
| 3 | 3 | U S Post Office - Promenade | 3690 W 18 Avenue |
| 4 | 4 | Florida Department of Highway Safety and Motor Vehicles Service Center | 1923 W 60 Street |

Table 6-16 | Fire Stations in SCE Study Area

| MAP ID # | Map # | Facility | Address |
|----------|-------|--|------------------|
| 1 | 4 | Hialeah Fire Department and Rescue Station 8 | 5405 W 18 Avenue |

| | | | |
|---|-------|--|--------------------|
| 2 | 6 | Miami-Dade County Fire Department and Rescue Station 1 (Miami Lakes) | 16699 NW 67 Avenue |
| 3 | 5 & 6 | Miami Lakes West Fire Department Station 64 | 15325 NW 77 Court |

Table 6-17 | Cultural Centers in SCE Study Area

| MAP ID # | Map # | Facility | Address |
|----------|-------|---|--------------------------|
| 1 | 3 | Florida National College Library | 4425 Jose Regueiro Ave |
| 2 | 3 | Miami Dade College - Hialeah Campus Library | 1780 W 49 Street |
| 3 | 6 | Miami Lakes Library | 6699 Windmill Gate Road |
| 4 | 5 & 6 | Jay I Kislak Foundation Inc | 7900 Miami Lakes Drive W |

Table 6-18 | Schools in SCE Study Area

| MAP ID # | Map # | Facility | Address |
|----------|-------|---|------------------------------|
| 1 | 4 | Mater Academy | 7700 NW 98 Street |
| 2 | 3 | Florida Career College-Hialeah | 3750 West 18 Avenue |
| 3 | 4 | Acceleration Academies LLC Hialeah | 1665 W 68 Street, Suite 109 |
| 4 | 3 | Florida National College | 4425 W 20 Avenue |
| 5 | 3 | Miami Dade College - Hialeah Campus | 1776 W 49 Street |
| 6 | 4 | Mater Performing Arts & Entertainment Academy | 7901 NW 103 Street |
| 7 | 5 | Youth Co-Op Charter School | 7700 West 20 Avenue |
| 8 | 5 | Youth Co-Op Preparatory High School | 7700 West 20 Avenue |
| 9 | 6 | Bob Graham Education Center | 15901 NW 79 Avenue |
| 10 | 3 | Westland Hialeah Senior High School | 4000 W 18 Avenue |
| 11 | 4 | Mater Academy Charter Middle | 7901 NW 103 Street |
| 12 | 4 | American Advanced Technicians Institute | 6801 W 20 Street |
| 13 | 3 | Our Lady of Charity Private School | 1900 W 44 Place |
| 14 | 4 | Mater Academy Elementary | 8003 NW 103 Street |
| 15 | 6 | Little College at Ludlam C. Corp. | 6545 NW 169 Street |
| 16 | 5 & 6 | Little College at Royal Oaks Plaza | 15225 NW 77 Avenue |
| 17 | 5 & 6 | Children's Paradise Learning Center #5 | 15520 NW 77 Court Rear |
| 18 | 4 | Happy Children Academy | 1937 West 68 Street |
| 19 | 2 | Blessed Pediatric Care | 7500 NW 52 Street, Suite 100 |

| | | | |
|----|---|--|---------------------------------|
| 20 | 3 | Petite World | 4680 W 17 Court 5 |
| 21 | 4 | Tiny Smile Learning Center | 10550 NW 77 Court, Unit 208-212 |
| 22 | 4 | Little Children's Learning Academy | 1917 W 60 Street |
| 23 | 6 | America's Christian Future Child Care Learning Ctr | 16931 NW 67 Avenue |
| 24 | 4 | Paradise Christian School | 6184 W 21 Court |
| 25 | 4 | American Christian School & Art | 5888 W 20 Avenue |
| 26 | 3 | Miss Carusi Learning Center | 1905 W 35 Street |
| 27 | 4 | Steps for Learning Preschool Center | 2150 W 76 Street, Suite 101 |
| 28 | 4 | Gratigny Day Care Center Corporation | 1800 W 68 Street |

Table 6-19 | Religious Centers in SCE Study Area

| MAP ID # | Map # | Facility | Address |
|----------|-------|---|---------------------------|
| 1 | 3 | Centro Cristiano Internacional | 7540 NW 82 Street |
| 2 | 4 | Church of Jesus Christ The Almighty | 6050 W 20 Avenue |
| 3 | 5 | Church of Christ Hialeah | 7700 W 20 Avenue |
| 4 | 3 | San Lazaro Parish | 4400 W 18 Avenue |
| 5 | 6 | Orthodox Cathedral of Christ The Savior | 16601 NW 77 Court |
| 6 | 4 | Iglesia Cristiano Del Alma | 7306 W 20 Avenue |
| 7 | 1 | Comunidad Servicios De Cristo | 3100 NW 77 Court |
| 8 | 3 | Iglesia Bautista | 8551 NW South River Drive |
| 9 | 4 | Primera Hispana Iglesia | 1650 W 68 Street |
| 10 | 2 | Bezerra De Menezes Kardec Spiritist Association | 6450 NW 77 Court |

6.12.4 Parks and Recreational Facilities

Several park and recreational features exist within the study area as shown in **Table X**. This includes one private golf course and eight parks. Of the nine recreational features eight are located in Miami Lakes and one (Garden of the Arts Park) is located in Hialeah, Florida. Additionally, one Office of Greenways and Trails (OGT) multi-use trail opportunity/hiking trail priority [Miami River Greenway - also a part of the Shared Use Nonmotorized (SUN) trail network]. This project involves no additional right-of-way, therefore recreational features within the study area are expected to see minimal to no impacts.

Table 6-20 | Park and Recreational Facilities in SCE Study Area

| MAP ID # | Map # | Facility | Address |
|----------|-------|------------------------------|------------------------|
| 1 | 6 | Miami Lakes Mini Park (P-86) | 6851 Main Street |
| 2 | 6 | Miami Lakes Mini Park (P-56) | 16331 Ravenwood Place |
| 3 | 5 | Miami Lakes Mini Park (P-28) | 7350 Sabal Drive |
| 4 | 6 | Miami Lakes Mini Park (P-55) | 16695 NW 67 Avenue |
| 5 | 6 | Miami Lakes Mini Park (P-50) | 7599 Loch Ness Drive |
| 6 | 6 | Miami Lakes Mini Park (P-52) | 6700 Loch Ness Drive |
| 7 | 6 | Miami Lakes Mini Park (P-51) | 6970 Loch Ness Drive |
| 8 | 4 | Garden of The Arts Park | 1850 W 76 Street |
| 9 | 6 | Don Shula's Golf Club | 7601 Miami Lakes Drive |

6.12.5 Wetlands

In accordance with Presidential Executive Order (EO) 11990 entitled "Protection of Wetlands" and United States Department of Transportation Order 5660.1A, "Preservation of the Nation's Wetlands" and Part 2, Chapter 9 (Wetlands and Other Surface Waters) of the FDOT PD&E Manual, the project study area was reviewed to identify, quantify, and map wetland communities that are located within the proposed project boundaries. In order to protect, preserve, and enhance wetlands to the fullest extent possible, the FDOT has assessed wetlands that may be affected by proposed roadway improvements.

The water habitats within the Build Alternative consist primarily of stormwater drainage conveyance features, stormwater detention/retention features, wetlands, canals, and surface water features. Based on in-house reviews and field verification, eight (8) stormwater drainage conveyance features, 34 stormwater drainage detention/retention features, six (6) wetlands, three (3) SFWMD-owned canals, five (5) Miami Dade County-owned canals, and three (3) surface water features, comprising a total of 83.59

acres, were identified within the limits of the project study area. Table X-X lists the individual surface water habitats present within the project study area, by FLUCFCS code, FWS classification, and acreage. Descriptions of each surface water habitat are also provided below.

No impacts will result from the No-Build Alternative. The viable Build Alternative will result in approximately 0.16 acre of impacts to permitted drainage feature 19 (DD19) (stormwater drainage detention/retention feature). The impacts are a result of the addition of a new ITS structure and parking area, which is required for roadway operations. The proposed impacts to this feature will be compensated for through the design and construction of the new stormwater management system. As such, compensatory mitigation is not proposed, and a wetland functional assessment was not conducted. No impacts to the identified wetland features in the vicinity of the I-75 interchange will occur as part of the project. In addition, no new impacts to surface water features, including the Miami Canal (C-6), Little River Canal (C-7), and Biscayne Canal (C-8), as well as the Miami-Dade County owned canals, will occur. The existing features within the project study area all provide low quality habitat due to their location with a densely developed urban area and proximity to the existing roadway corridor.

The proposed project will have no significant short-term or long-term adverse impacts to wetlands or surface waters. In accordance with EO 11990, the FDOT has undertaken all actions to avoid and minimize the destruction, loss or degradation of wetlands and surface waters, and to preserve and enhance the natural and beneficial values of wetlands/surface waters in carrying out the agency's responsibilities.

Table 6-21 | Summary of Individual Water Features

| ID | Type | FLUCFCS Description | FLUCFCS Code | FWS Classification | Acres in Study Area |
|------|---|--------------------------------|--------------|--------------------|---------------------|
| DC02 | Stormwater Drainage Conveyance Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.14 |
| DC03 | Stormwater Drainage Conveyance Feature | Vegetated Non-forested Wetland | 640 | PEM1A/C | 0.14 |
| DC04 | Stormwater Drainage Conveyance Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.12 |
| DC05 | Stormwater Drainage Conveyance Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.05 |
| DC06 | Stormwater Drainage Conveyance Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.05 |
| DC07 | Stormwater Drainage Conveyance Feature | Vegetated Non-forested Wetland | 640 | PSS3/EM1A/C | 0.26 |
| DC08 | Stormwater Drainage Conveyance Feature | Vegetated Non-forested Wetland | 640 | PSS3/EM1A/C | 0.04 |
| DC09 | Stormwater Drainage Conveyance Feature | Vegetated Non-forested Wetland | 640 | PEM1A/C | 0.12 |
| DD01 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.82 |
| DD02 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.28 |
| DD03 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 1.42 |
| DD04 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.84 |
| DD05 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.52 |
| DD06 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.52 |
| DD07 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.35 |
| DD08 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.33 |
| DD09 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A/C | 1.20 |
| DD10 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.14 |
| DD11 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 1.40 |
| DD12 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 1.98 |
| DD13 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PSS1C | 0.19 |
| DD14 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.18 |

| ID | Type | FLUCFCS Description | FLUCFCS Code | FWS Classification | Acres in Study Area |
|------|---|--------------------------------|--------------|--------------------|---------------------|
| DD15 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 1.63 |
| DD16 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.49 |
| DD17 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.44 |
| DD18 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.69 |
| DD19 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.82 |
| DD20 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.47 |
| DD21 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.06 |
| DD22 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.37 |
| DD23 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 1.89 |
| DD24 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.27 |
| DD25 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.45 |
| DD26 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.11 |
| DD27 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.30 |
| DD28 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.40 |
| DD29 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.46 |
| DD30 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 1.09 |
| DD31 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.11 |
| DD32 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.84 |
| DD33 | Stormwater Drainage Detention/Retention Feature | Vegetated Non-forested Wetland | 640 | PEM1A | 0.24 |
| DD34 | Stormwater Drainage Detention/Retention Feature | Freshwater Cattail Marsh | 6411 | PEM1A | 3.10 |
| W01 | Forested Wetland | Cypress, Wetland Shrub | 621,631 | PFO2/SS3E | 1.12 |
| W02 | Shrub Wetland | Wetland Shrub | 631 | PSS3E | 0.17 |
| W03 | Forested Wetland | Cypress, Wetland Shrub | 621,631 | PFO2/SS3E | 1.00 |

| ID | Type | FLUCFCS Description | FLUCFCS Code | FWS Classification | Acres in Study Area |
|--------------|--|-------------------------------|--------------|--------------------|---------------------|
| W04 | Forested Wetland | Cypress | 621 | PFO2E | 0.24 |
| W05 | Forested Wetland | Cypress | 621 | PFO2E | 0.43 |
| W06 | Forested Wetland | Cypress | 621 | PFO2E | 0.37 |
| SW03 | Surface Water Feature [Dressels Dairy Canal] | Streams and Waterways | 510 | R2UBHx | 4.13 |
| SW04 | Surface Water Feature [NW 58 th Street Canal] | Streams and Waterways | 510 | R2UBHx | 1.70 |
| SW05 | Surface Water Feature [Miami Canal (C-6)] | Streams and Waterways | 510 | R2UBHx | 4.88 |
| SW06 | Surface Water Feature [Little River Canal (C-7)] | Streams and Waterways | 510 | R2UBHx | 1.14 |
| SW07 | Surface Water Feature [Gratigny Canal] | Streams and Waterways | 510 | R2UBHx | 2.75 |
| SW08 | Surface Water Feature (Wet Pond) | Reservoirs Less Than 10 Acres | 534 | PUBHx | 2.82 |
| SW09 | Surface Water Feature [Grahams Dairy Canal] | Streams and Waterways | 510 | R2UBHx | 3.02 |
| SW10 | Surface Water Feature (Wet Pond) | Reservoirs Less Than 10 Acres | 534 | PUBHx | 0.34 |
| SW11 | Surface Water Feature [Biscayne Canal (C-8)] | Streams and Waterways | 510 | R2UBHx | 3.28 |
| SW12 | Surface Water Feature (Peter's Pike Canal) | Streams and Waterways | 510 | R2UBHx | 27.81 |
| SW13 | Surface Water Feature (Wet Pond) | Reservoirs Less Than 10 Acres | 534 | PUBHx | 3.07 |
| TOTAL | | | | | 83.59 |

***FWS Wetland Descriptions:**

PEM1A: Palustrine, Emergent, Persistent, Temporarily Flooded

PEM1A/C: Palustrine, Emergent, Persistent, Temporarily Flooded/Seasonally Flooded

PSS3/EM1A/C: Palustrine, Emergent, Persistent/Palustrine, Scrub-Shrub, Broad-Leaved Evergreen, Temporarily Flooded/Seasonally Flooded

PSS1C: Palustrine, Scrub-Shrub, Broad-Leaved Deciduous, Seasonally Flooded

PFO2E: Palustrine, Forested, Needle-leaved Deciduous, Seasonally Flooded/Saturated

R2UBHx: Riverine, Lower Perennial, Unconsolidated Bottom, Permanently Flooded, Excavated

PUBHx: Palustrine Unconsolidated Bottom, Permanently Flooded, Excavated

6.12.6 Essential Fish Habitat

The Magnuson-Stevens Fishery Conservation and Management Act (Magnuson-Stevens Act) (MSFCMA), as amended by the Sustainable Fisheries Act of 1996 (Public Law 104-267), established procedures designed to identify, conserve, and enhance EFH for those species regulated under a federal fisheries management plan (FMP). Section 305(b)(2) of the MSFCMA requires federal action agencies to consult with NOAA's NMFS on all actions or proposed actions, authorized, funded, or undertaken by the agency, that may adversely affect EFH. EFH is defined in the MSFCMA as "...those waters and substrate necessary to fish for spawning, breeding, feeding, or growth to maturity."

In accordance with Part 2, Chapter 17 (Essential Fish Habitat) of the FDOT PD&E Manual, coordination with NMFS occurred through the ETDM Screening Tool. The ETDM response stated that the proposed project would not impact areas that support NMFS trust resources. Therefore, an EFH Assessment is not required for this project as the surface waters within the project limits are not tidally influenced and do not contain EFH. Based on the project location and the biological field review, it was confirmed that EFH resources do not exist within the project corridor.

No action is required pursuant to the EFH requirements of the MSFCMA.

6.12.7 Wildlife and Habitat Survey

The project study area was evaluated for potential occurrences of federally listed and state listed plant and animal species in accordance with Section 7 of the Endangered Species Act (ESA) of 1973, as amended; the Fish and Wildlife Conservation Act; the Migratory Bird Treaty Act (MBTA); Part 2, Chapter 16 (Protected Species and Habitat) of the FDOT PD&E Manual; and Chapters 5B-40 and 68A-27, Florida Administrative Code (FAC). It is important to note that all federally listed species are also considered state listed species. Based on this evaluation, a total of ten (10) federally listed animal species, seven (7) state listed animal species, and six (6) state listed plant species, were identified as potentially occurring within the limits of the viable Build Alternative. Additionally, while not state or federally listed under the ESA, the bald eagle (*Haliaeetus leucocephalus*) was included in the protected species analysis due to the regulatory protections associated with this species. **Table 6-22** provides a summary of the federally listed and state listed animal and plant species with potential to occur within the limits of the viable Build Alternative, along with their corresponding effect determinations.

The project study area was also evaluated for the presence of federally-designated Critical Habitat as defined by Congress in 50 Code of Federal Regulations (CFR) 17. Based on this evaluation, it was determined that state-designated Critical Habitat exists for the West Indian manatee (*Trichechus manatus latirostris*) within the Miami Canal (C-6), NW 25th Street Canal, and Northline Canal. Based on the availability of habitat, including designated Critical Habitat, the potential for occurrence of this species

within the study area is High. The project is also located within the FWS Consultation Areas for the Everglade snail kite (*Rostrhamus sociabilis plumbeus*), American Crocodile (*Crocodylus acutus*), and the Florida bonneted bat (*Eumops floridanus*).

Table 6-22 | Summary of Listed Species and Effect Determinations

| | Common Name | Scientific Name | Federal Status | State Status | Occurrence Potential | Effect Determination |
|--------------------------------|--|------------------|----------------|--------------|--|----------------------|
| Mammals | | | | | | |
| Florida Bonneted Bat | <i>Eumops floridanus</i> | E | FE | Low | No Effect | |
| West Indian Manatee | <i>Trichechus manatus latirostris</i> | T | FT | High | May affect, not likely to adversely affect | |
| Reptiles | | | | | | |
| American Crocodile | <i>Crocodylus acutus</i> | T | FT | Low | No Effect | |
| Eastern Indigo Snake | <i>Drymarchon corais couperi</i> | T | FT | Low | May affect, not likely to adversely affect | |
| Birds | | | | | | |
| Bachman's Warbler | <i>Vermivora bachmanii</i> | E | FE | Low | No Effect | |
| Everglade Snail Kite | <i>Rostrhamus sociabilis plumbeus</i> | E | FE | Low | No Effect | |
| Wood Stork | <i>Mycteria americana</i> | T | FT | High | May affect, not likely to adversely affect | |
| Insects | | | | | | |
| Bartram's Hairstreak Butterfly | <i>Strymon acis bartrami</i> | E | FE | None | No Effect | |
| Florida Leafwing Butterfly | <i>Anaea troglodyta floridalis</i> | E | FE | None | No Effect | |
| Miami Blue Butterfly | <i>Cyclargus thomasi bethunebakeri</i> | E | FE | None | No Effect | |
| Reptiles | | | | | | |
| Gopher Tortoise | <i>Gopherus polyphemus</i> | C ⁽¹⁾ | ST | Low | No Effect Anticipated | |
| Birds | | | | | | |
| Florida Burrowing Owl | <i>Athene cunicularia floridana</i> | NL | ST | Low | No Effect Anticipated | |

| | Little Blue Heron | <i>Egretta caerulea</i> | NL | ST | Moderate | No Adverse Effect Anticipated |
|----------------------------|-------------------------------|---------------------------------|----|----|------------------------------------|-------------------------------|
| | Roseate Spoonbill | <i>Platalea ajaja</i> | NL | ST | Low | No Effect Anticipated |
| | Southeastern American Kestrel | <i>Falco sparverius paulus</i> | NL | ST | Low | No Effect Anticipated |
| | Tricolored Heron | <i>Egretta tricolor</i> | NL | ST | High | No Adverse Effect Anticipated |
| | Least Tern | <i>Sternula antillarum</i> | NL | ST | Low | No Effect Anticipated |
| | Bald Eagle ⁽²⁾ | <i>Haliaeetus leucocephalus</i> | NL | NL | Low | N/A |
| State Listed Plant Species | Plants | | | | | |
| | Golden Leather Fern | <i>Acrostichum aureum</i> | NL | ST | Planted within ROW for landscaping | No Effect Anticipated |
| | Everglades Palm | <i>Acoelorraphe wrightii</i> | NL | ST | Planted within ROW for landscaping | No Effect Anticipated |
| | Satin-Leaf | <i>Chrysophyllum oliviforme</i> | NL | ST | Planted within ROW for landscaping | No Effect Anticipated |
| | Simpson's Stopper | <i>Myrcianthes fragrans</i> | NL | ST | Planted within ROW for landscaping | No Effect Anticipated |
| | Royal Palm | <i>Roystonea elata</i> | NL | SE | Planted within ROW for landscaping | No Effect Anticipated |
| | West Indian Mahogany | <i>Swietenia mahagoni</i> | NL | ST | Planted within ROW for landscaping | No Effect Anticipated |

F = Federally Listed / S = State Listed / E = Endangered / T = Threatened / NL = Not Listed

(1) The gopher tortoise is currently a candidate species for federal protection under the ESA.

(2) The bald eagle is neither state nor federally listed; however, this species is federally protected by the Bald and Golden Eagle Act. The bald eagle is also managed in Florida by the FWC's bald eagle rule (FAC 68A-16.002).

6.12.8 Floodplains/Floodways

Based on a review of available Geographic Information System (GIS) data and the Miami-Dade County Flood Zone data, the project corridor is located within Zone AH and Zone X of the 100-year floodplain. However, this project will not: 1) affect flood heights or base floodplain limits, 2) result in increased or new adverse environmental impacts, 3) increase flood risks or damage, or 4) significantly change the potential for interruption or termination of emergency service or emergency evacuation routes. Therefore,

this project will not encroach upon the base floodplain, as defined in Part 2, Chapter 13 (Floodplains) of the FDOT PD&E Manual.

6.12.9 Noise

A traffic noise analysis was conducted in accordance with Title 23 Code of Federal Regulations (CFR) 772, Procedures for Abatement of Highway Traffic Noise and Construction Noise (July 13, 2010) and Part 2, Chapter 18 (Highway Traffic Noise) of the FDOT PD&E Manual. Traffic noise levels were predicted for noise sensitive locations along the project corridor for the existing conditions and the design year (2040) No-Build and recommended Build Alternative. Build Alternative traffic noise levels are expected to range from approximately 37.2 to 79.0 dB(A) during the project's design year. Worst-case design year traffic noise levels with the Build Alternative are predicted to be no more than 1.9 dB(A) greater than existing traffic noise levels.

Design year traffic noise levels with the planned improvements are predicted to approach or exceed the Federal Highway Administration (FHWA) Noise Abatement Criteria (NAC) for residential use [67 dB(A)] at 416 residences and five (5) special use/non-residential sites. Therefore, planned improvements were determined to generate noise impacts at noise sensitive sites within the project study area. In accordance with traffic noise study requirements set forth by both the FHWA and FDOT, noise barriers were considered for all noise sensitive receptor sites where design year Build Alternative traffic noise levels were predicted to equal or exceed the NAC. Noise barriers were evaluated at nine (9) locations to mitigate these predicted noise impacts.

Due to the limited scope of the project's improvements, limited available right-of-way and poor abatement performance, none of the noise barriers evaluated for the nine (9) impacted Common Noise Environments (CNE) are recommended for construction at this time. Based on the noise analyses performed to date, there are no apparent solutions available to mitigate the noise impacts at any of 416 impacted residences and five (5) impacted special land use sites. The traffic noise impacts to these noise sensitive sites are considered to be an unavoidable consequence of the project.

6.12.10 Contamination

In accordance with Volume 2, Chapter 20 of the FDOT PD&E Manual, potential contamination impacts in the area surrounding the project corridor were assessed for the viable Build Alternative as well as the No-Build Alternative.

After a review of all available data, such as agency file reviews at FDEP, the EDR database report, aerial photography, and confirmed by site reconnaissance, contamination of soil and groundwater has been documented in the vicinity of the project corridor. A total of 31 sites of potential environmental concern were identified for the project corridor; of these, five (5) sites are rated as High risk, two (2) sites are rated

as Medium risk, 19 sites are rated as Low risk and five (5) sites are rated as No risk. The status of the sites will be updated accordingly at each future design phase. Remaining sites identified in the above-referenced sources are not considered to pose potential contamination concerns because of the current regulatory status of the site and/or the distance from the project corridor.

The FDOT District VI Planning and Environmental Management Office will utilize the information contained in this report to determine the need for additional investigation during the design phase of the Project. The Level II Contamination Assessment investigation may be conducted prior to any right-of-way acquisition and/or prior to the design phase, should any become necessary. Based on the findings of updated future review and Level II investigation, the design engineers may be instructed to avoid the areas of concern or to include special provisions with the plans to require that the construction activities performed in the areas of concern be performed or supervised by a contamination assessment and remediation contractor specified by the FDOT.

It must be recognized that the possibility exists that some contaminated substances, petroleum products, or environmental contamination not identified during this assessment may exist on or in the immediate vicinity of the project. This is because regulatory agency records are not always complete; not all leaks, spills, and discharges are reported; not all USTs and ASTs are registered. It is unknown if any registered substances were illegally dumped or were deposited during past construction activities.

If construction dewatering will be necessary during construction, a Water Use Permit from SFWMD may be required. The contractor will be held responsible for ensuring compliance with any necessary dewatering permit(s). The dewatering plan will need to consider the radius of influence of any dewatering activity on nearby contamination plumes to avoid potential contamination plume exacerbation. The status of the sites will be updated accordingly at each future design phase. All permits will be obtained in accordance with Federal, State, and local laws and regulations.

6.12.11 Right-of-Way

Existing right-of-way along the SR 826 corridor ranges from approximately 235 feet to 455 feet or more in width near the existing interchanges. The existing right-of-way along the frontage road systems is typically 50 feet, with a minimum of 46.4 feet on the East Frontage Road/W 20th Avenue at W 64th Street and maximum of 108.9 feet on the West Frontage Road/NW 77th Avenue at NW 122nd Street.

6.12.12 Value Engineering Review

A Value Engineering review was not conducted on this project.

7.0 List of Technical Reports Completed for the Project

- Air Quality Report
- Natural Resources Evaluation
- Water Quality Impact Evaluation
- Contamination Screening Evaluation Report
- Socio-Cultural Effects Evaluation
- Noise Study Report
- Cultural Resource Assessment Survey
- Drainage Report
- Traffic Analysis Methodology Report
- Calibration Report
- Traffic Operations Analysis Summary Report

Appendix A

Concept Plans (under separate cover)

Appendix B

Typical Section Package

STATE OF FLORIDA
DEPARTMENT OF TRANSPORTATION

THIS TYPICAL SECTION PACKAGE INCLUDES
FINANCIAL PROJECT ID(S):
441830-1-52-01 AND 441831-1-52-01

TYPICAL SECTION PACKAGE


FINANCIAL PROJECT ID 447165-1-52-01

MIAMI-DADE COUNTY (87260)

STATE ROAD NO. 826

FROM SOUTH OF NW 36TH ST. TO NW 154TH ST.

APPROVED BY:



THIS ITEM HAS BEEN DIGITALLY
SIGNED AND SEALED BY:

Javier Manso
2020.09.28 14:06:38-04'00'

ON THE DATE ADJACENT TO THE SEAL


PRINTED COPIES OF THIS DOCUMENT ARE
NOT CONSIDERED SIGNED AND SEALED.
THE SIGNATURE MUST BE VERIFIED
ON ANY ELECTRONIC COPIES.

HDR ENGINEERING, INC.
15450 NEW BARN ROAD, SUITE 304
MIAMI LAKES, FLORIDA 33014
CERTIFICATE OF AUTHORIZATION 4213
JAVIER MANSO, P.E. NO. 69183

THE ABOVE NAMED PROFESSIONAL ENGINEER SHALL BE RESPONSIBLE FOR THE
FOLLOWING SHEETS IN ACCORDANCE WITH RULE 61G15-23.004, F.A.C.

TYPICAL SECTION PACKAGE

| SHEET NO | SHEET DESCRIPTION |
|-----------|---|
| 1 2-37 | COVER SHEET TYPICAL SECTION NO. 1 - NO. 36 |



TYPICAL SECTION CONCURRENCE

Digitally signed by: Karina Fuentes
Date: 2020.09.30 09:57:39 -04'00'

FDOT DISTRICT DESIGN ENGINEER

FDOT DISTRICT STRUCTURES
DESIGN ENGINEER

FHWA TRANSPORTATION ENGINEER

DESIGN SPEED AND POSTED
SPEED CONCURRENCE:

Digitally signed by: omar.

meitin@dot.state.fl.us

Date: 2020.10.08 15:56:36 -

05'00'

FDOT DISTRICT TRAFFIC OPERATIONS
ENGINEER

Digitally signed by: Karina Fuentes

Date: 2020.09.30 09:58:07 -04'00'

FDOT DISTRICT DESIGN ENGINEER


CONTEXT CLASSIFICATION
CONCURRENCE:


Digitally signed by: Calvin R Mason
Date: 2020.10.08 14:17:39 -04'00'

FDOT DISTRICT PLANNING AND
ENVIRONMENTAL ADMINISTRATOR

| BRIDGE NO. | CROSSING | STATION | | MILEPOST | | BRIDGE NO. | CROSSING | STATION | | MILEPOST | |
|------------|--|-----------|-----------|----------|--------|------------|---|-----------|-----------|----------|--------|
| | | BEGIN | END | BEGIN | END | | | BEGIN | END | BEGIN | END |
| 870964 | SR 826 OVER NW 74TH STREET | 435+50.81 | 437+29.87 | 11.346 | 11.379 | 870856 | NW 103RD ST. SB FYLOVER ON-RAMP | 100+00.00 | 110+84.70 | 13.213 | 13.224 |
| 870257 | SR 826 OVER METRORAIL | 445+72.21 | 446+98.06 | 11.541 | 11.574 | 870570 | W 20TH AVE E OVER LITTLE RIVER CANAL | 310+26.79 | 311+36.42 | 0.197 | 0.214 |
| 870258 | SR 826 OVER FEC RR | 462+17.94 | 463+67.36 | 11.835 | 11.877 | 870569 | W 20TH AVE W OVER LITTLE RIVER CANAL | 411+81.83 | 412+71.84 | 0.222 | 0.239 |
| 870975 | SR 826 OVER S. RIVER DR./MIAMI CANAL /OKEECHOBEE ROAD | 481+20.39 | 485+91.26 | 12.197 | 12.288 | 870758 | SR 826 OVER LITTLE RIVER CANAL | 540+84.25 | 541+69.15 | 13.335 | 13.359 |
| 870995 | SR 826 NB OVER NW 103RD STREET | 529+96.72 | 532+28.78 | 13.129 | 13.179 | 870766 | SR 826 OVER NW 122ND STREET | 593+16.24 | 594+71.22 | 14.324 | 14.362 |
| 870757 | SR 826 SB OVER NW 103RD STREET | 529+96.72 | 532+28.78 | 13.129 | 13.179 | 870467 | SR 826 OVER NW 138TH STREET | 757+71.93 | 758+67.78 | 15.332 | 15.363 |


SHEET
NO.











































| PROJECT CONTROLS | | TYPICAL SECTION No. 4 | | | | | |
|---|-----------|---|--|----------------------|-----------|----------------|---|
| <u>CONTEXT CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> C1 : NATURAL <input type="checkbox"/> C3C : SUBURBAN COMM. <input type="checkbox"/> C2 : RURAL <input type="checkbox"/> C4 : URBAN GENERAL <input type="checkbox"/> C2T : RURAL TOWN <input type="checkbox"/> C5 : URBAN CENTER <input type="checkbox"/> C3R : SUBURBAN RES. <input type="checkbox"/> C6 : URBAN CORE <input checked="" type="checkbox"/> N/A : L.A. FACILITY | | | | | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> INTERSTATE <input type="checkbox"/> MAJOR COLLECTOR <input checked="" type="checkbox"/> FREEWAY/EXPWY. <input type="checkbox"/> MINOR COLLECTOR <input type="checkbox"/> PRINCIPAL ARTERIAL <input type="checkbox"/> LOCAL <input type="checkbox"/> MINOR ARTERIAL | | | | | | | |
| <u>HIGHWAY SYSTEM</u> | | | | | | | |
| <input checked="" type="checkbox"/> NATIONAL HIGHWAY SYSTEM <input checked="" type="checkbox"/> STRATEGIC INTERMODAL SYSTEM <input checked="" type="checkbox"/> STATE HIGHWAY SYSTEM <input type="checkbox"/> OFF-STATE HIGHWAY SYSTEM | | | | | | | |
| <u>ACCESS CLASSIFICATION</u> | | | | | | | |
| <input checked="" type="checkbox"/> 1 - FREEWAY <input type="checkbox"/> 2 - RESTRICTIVE w/Service Roads <input type="checkbox"/> 3 - RESTRICTIVE w/660 ft. Connection Spacing <input type="checkbox"/> 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing <input type="checkbox"/> 5 - RESTRICTIVE w/440 ft. Connection Spacing <input type="checkbox"/> 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing <input type="checkbox"/> 7 - BOTH MEDIAN TYPES | | | | | | | |
| <u>CRITERIA</u> | | | | | | | |
| <input checked="" type="checkbox"/> NEW CONSTRUCTION / RECONSTRUCTION <input type="checkbox"/> RESURFACING (LA FACILITIES) <input type="checkbox"/> RRR (ARTERIALS & COLLECTORS) | | | | | | | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | | | | | | | |
| <u>DESIGN EXCEPTION</u> 1. LANE & SHOULDER WIDTH <u>DESIGN VARIATION</u> 1. CROSS SLOPE 2. EXPRESS LANE BUFFER SEPARATION WIDTH 3. BORDER WIDTH 4. EXPRESS LANES TUBULAR MARKER COLOR | | TRAFFIC DATA <p>CURRENT YEAR = 2020 AADT = 52,280 - 127,060 ESTIMATED OPENING YEAR = 2022 AADT = N/A ESTIMATED DESIGN YEAR = 2036 AADT = 381,000 $K = 7.59\%$ $D = 50.0\%$ $T = 6.6\%$ (24 HOUR) DESIGN HOUR T = 6.6% DESIGN SPEED = 60 MPH POSTED SPEED = 55 MPH</p> | | | | | |
| | | <p>SR 826 (SOUTHBOUND ONLY) STA. 518+41.90 TO STA. 541+65.30</p> <p>NOT TO SCALE</p> <p>LEGEND: EL = EXPRESS LANES GUL = GENERAL USE LANES AUX = AUXILIARY LANES</p> <p>NOTES:</p> <p>[1] MATCH EXISTING CROSS SLOPES (VALUE RANGE IS SHOWN) [2] MATCH ADJACENT LANE CROSS SLOPES. VALUE RANGE IS SHOWN</p> | | | | | |
| | | <table border="1"> <tr> <td>FINANCIAL PROJECT ID</td> <td>SHEET NO.</td> </tr> <tr> <td>447165-1-52-01</td> <td>5</td> </tr> </table> | | FINANCIAL PROJECT ID | SHEET NO. | 447165-1-52-01 | 5 |
| FINANCIAL PROJECT ID | SHEET NO. | | | | | | |
| 447165-1-52-01 | 5 | | | | | | |

| PROJECT CONTROLS | | TYPICAL SECTION No. 5 | | | | | |
|---|-----------|--|--|----------------------|-----------|----------------|---|
| <u>CONTEXT CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> C1 : NATURAL <input type="checkbox"/> C3C : SUBURBAN COMM. <input type="checkbox"/> C2 : RURAL <input type="checkbox"/> C4 : URBAN GENERAL <input type="checkbox"/> C2T : RURAL TOWN <input type="checkbox"/> C5 : URBAN CENTER <input type="checkbox"/> C3R : SUBURBAN RES. <input type="checkbox"/> C6 : URBAN CORE <input checked="" type="checkbox"/> N/A : L.A. FACILITY | | | | | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> INTERSTATE <input type="checkbox"/> MAJOR COLLECTOR <input checked="" type="checkbox"/> FREEWAY/EXPWY. <input type="checkbox"/> MINOR COLLECTOR <input type="checkbox"/> PRINCIPAL ARTERIAL <input type="checkbox"/> LOCAL <input type="checkbox"/> MINOR ARTERIAL | | | | | | | |
| <u>HIGHWAY SYSTEM</u> | | | | | | | |
| <input checked="" type="checkbox"/> NATIONAL HIGHWAY SYSTEM <input checked="" type="checkbox"/> STRATEGIC INTERMODAL SYSTEM <input checked="" type="checkbox"/> STATE HIGHWAY SYSTEM <input type="checkbox"/> OFF-STATE HIGHWAY SYSTEM | | | | | | | |
| <u>ACCESS CLASSIFICATION</u> | | | | | | | |
| <input checked="" type="checkbox"/> 1 - FREEWAY <input type="checkbox"/> 2 - RESTRICTIVE w/Service Roads <input type="checkbox"/> 3 - RESTRICTIVE w/660 ft. Connection Spacing <input type="checkbox"/> 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing <input type="checkbox"/> 5 - RESTRICTIVE w/440 ft. Connection Spacing <input type="checkbox"/> 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing <input type="checkbox"/> 7 - BOTH MEDIAN TYPES | | | | | | | |
| <u>CRITERIA</u> | | | | | | | |
| <input checked="" type="checkbox"/> NEW CONSTRUCTION / RECONSTRUCTION <input type="checkbox"/> RESURFACING (LA FACILITIES) <input type="checkbox"/> RRR (ARTERIALS & COLLECTORS) | | <p style="text-align: center;">SR 826 (NORTHBOUND ONLY) STA. 520+08.96 TO STA. 538+48.37</p> <p style="text-align: right;">NOT TO SCALE</p> | | | | | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | | | | | | | |
| <u>DESIGN EXCEPTION</u> 1. LANE WIDTH <u>DESIGN VARIATION</u> 1. SHOULDER WIDTH 2. CROSS SLOPE 3. EXPRESS LANE BUFFER SEPARATION WIDTH 4. BORDER WIDTH 5. EXPRESS LANES TUBULAR MARKER COLOR | | <p style="text-align: center;">TRAFFIC DATA</p> <p>CURRENT YEAR = 2020 AADT = 52,280 - 127,060 ESTIMATED OPENING YEAR = 2022 AADT = N/A ESTIMATED DESIGN YEAR = 2036 AADT = 381,000 $K = 7.59\%$ $D = 50.0\%$ $T = 6.6\%$ (24 HOUR) DESIGN HOUR T = 6.6% DESIGN SPEED = 60 MPH POSTED SPEED = 55 MPH</p> | | | | | |
| | | <p style="text-align: right;">LEGEND:</p> <p>EL = EXPRESS LANES GUL = GENERAL USE LANES AUX = AUXILIARY LANES</p> <p style="text-align: right;">NOTES:</p> <p>[1] MATCH EXISTING CROSS SLOPES (VALUE RANGE IS SHOWN) [2] MATCH ADJACENT LANE CROSS SLOPE. VALUE RANGE IS SHOWN</p> | | | | | |
| | | <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 80%;">FINANCIAL PROJECT ID</td> <td style="width: 20%;">SHEET NO.</td> </tr> <tr> <td>447165-1-52-01</td> <td>6</td> </tr> </table> | | FINANCIAL PROJECT ID | SHEET NO. | 447165-1-52-01 | 6 |
| FINANCIAL PROJECT ID | SHEET NO. | | | | | | |
| 447165-1-52-01 | 6 | | | | | | |



| PROJECT CONTROLS | | TYPICAL SECTION No. 7 | | | | | |
|---|-----------|--|--|----------------------|-----------|----------------|---|
| <u>CONTEXT CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> C1 : NATURAL <input type="checkbox"/> C3C : SUBURBAN COMM. <input type="checkbox"/> C2 : RURAL <input type="checkbox"/> C4 : URBAN GENERAL <input type="checkbox"/> C2T : RURAL TOWN <input type="checkbox"/> C5 : URBAN CENTER <input type="checkbox"/> C3R : SUBURBAN RES. <input type="checkbox"/> C6 : URBAN CORE <input checked="" type="checkbox"/> N/A : L.A. FACILITY | | | | | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> INTERSTATE <input type="checkbox"/> MAJOR COLLECTOR <input checked="" type="checkbox"/> FREEWAY/EXPWY. <input type="checkbox"/> MINOR COLLECTOR <input type="checkbox"/> PRINCIPAL ARTERIAL <input type="checkbox"/> LOCAL <input type="checkbox"/> MINOR ARTERIAL | | | | | | | |
| <u>HIGHWAY SYSTEM</u> | | | | | | | |
| <input checked="" type="checkbox"/> NATIONAL HIGHWAY SYSTEM <input checked="" type="checkbox"/> STRATEGIC INTERMODAL SYSTEM <input checked="" type="checkbox"/> STATE HIGHWAY SYSTEM <input type="checkbox"/> OFF-STATE HIGHWAY SYSTEM | | | | | | | |
| <u>ACCESS CLASSIFICATION</u> | | | | | | | |
| <input checked="" type="checkbox"/> 1 - FREEWAY <input type="checkbox"/> 2 - RESTRICTIVE w/Service Roads <input type="checkbox"/> 3 - RESTRICTIVE w/660 ft. Connection Spacing <input type="checkbox"/> 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing <input type="checkbox"/> 5 - RESTRICTIVE w/440 ft. Connection Spacing <input type="checkbox"/> 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing <input type="checkbox"/> 7 - BOTH MEDIAN TYPES | | | | | | | |
| <u>CRITERIA</u> | | | | | | | |
| <input checked="" type="checkbox"/> NEW CONSTRUCTION / RECONSTRUCTION <input type="checkbox"/> RESURFACING (LA FACILITIES) <input type="checkbox"/> RRR (ARTERIALS & COLLECTORS) | | | | | | | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | | | | | | | |
| <u>DESIGN VARIATION</u> 1. BORDER WIDTH 2. SHOULDER WIDTH | | <u>TRAFFIC DATA</u> <p>CURRENT YEAR = 2020 AADT = 52,280 - 127,060 ESTIMATED OPENING YEAR = 2022 AADT = N/A ESTIMATED DESIGN YEAR = 2036 AADT = 381,000 $K = 7.59\%$ $D = 50.0\%$ $T = 6.6\%$ (24 HOUR) DESIGN HOUR T = 6.6% DESIGN SPEED = 40 MPH POSTED SPEED = 30 MPH</p> | | | | | |
| | | <p>NOT TO SCALE</p> <p>LEGEND: EL = EXPRESS LANES GUL = GENERAL USE LANES AUX = AUXILIARY LANES</p> <p>NOTES; [1] MATCH EXISTING CROSS SLOPES (VALUE RANGE IS SHOWN) [2] MATCH ADJACENT LANE CROSS SLOPES. VALUE RANGE IS SHOWN</p> | | | | | |
| | | <table border="1"> <tr> <td>FINANCIAL PROJECT ID</td> <td>SHEET NO.</td> </tr> <tr> <td>447165-1-52-01</td> <td>8</td> </tr> </table> | | FINANCIAL PROJECT ID | SHEET NO. | 447165-1-52-01 | 8 |
| FINANCIAL PROJECT ID | SHEET NO. | | | | | | |
| 447165-1-52-01 | 8 | | | | | | |




| PROJECT CONTROLS | | TYPICAL SECTION No. 9 | |
|---|--|---|--|
| <u>CONTEXT CLASSIFICATION</u> | |  | |
| <input type="checkbox"/> C1 : NATURAL <input type="checkbox"/> C3C : SUBURBAN COMM. <input type="checkbox"/> C2 : RURAL <input type="checkbox"/> C4 : URBAN GENERAL <input type="checkbox"/> C2T : RURAL TOWN <input type="checkbox"/> C5 : URBAN CENTER <input type="checkbox"/> C3R : SUBURBAN RES. <input type="checkbox"/> C6 : URBAN CORE <input checked="" type="checkbox"/> N/A : L.A. FACILITY | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | |  | |
| <input type="checkbox"/> INTERSTATE <input type="checkbox"/> MAJOR COLLECTOR <input checked="" type="checkbox"/> FREEWAY/EXPWY. <input type="checkbox"/> MINOR COLLECTOR <input type="checkbox"/> PRINCIPAL ARTERIAL <input type="checkbox"/> LOCAL <input type="checkbox"/> MINOR ARTERIAL | | | |
| <u>HIGHWAY SYSTEM</u> | |  | |
| <input checked="" type="checkbox"/> NATIONAL HIGHWAY SYSTEM <input checked="" type="checkbox"/> STRATEGIC INTERMODAL SYSTEM <input checked="" type="checkbox"/> STATE HIGHWAY SYSTEM <input type="checkbox"/> OFF-STATE HIGHWAY SYSTEM | | | |
| <u>ACCESS CLASSIFICATION</u> | |  | |
| <input checked="" type="checkbox"/> 1 - FREEWAY <input type="checkbox"/> 2 - RESTRICTIVE w/Service Roads <input type="checkbox"/> 3 - RESTRICTIVE w/660 ft. Connection Spacing <input type="checkbox"/> 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing <input type="checkbox"/> 5 - RESTRICTIVE w/440 ft. Connection Spacing <input type="checkbox"/> 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing <input type="checkbox"/> 7 - BOTH MEDIAN TYPES | |  | |
| <u>CRITERIA</u> | |  | |
| <input checked="" type="checkbox"/> NEW CONSTRUCTION / RECONSTRUCTION <input type="checkbox"/> RESURFACING (LA FACILITIES) <input type="checkbox"/> RRR (ARTERIALS & COLLECTORS) | |  | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | |  | |
| <u>DESIGN VARIATION</u> 1. BORDER WIDTH 2. SHOULDER WIDTH | |  | |
| <u>TRAFFIC DATA</u> CURRENT YEAR = 2020 AADT = 52,280 - 127,060 ESTIMATED OPENING YEAR = 2022 AADT = N/A ESTIMATED DESIGN YEAR = 2036 AADT = 381,000 $K = 7.59\%$ $D = 50.0\%$ $T = 6.6\%$ (24 HOUR) DESIGN HOUR T = 6.6% DESIGN SPEED = 40 MPH POSTED SPEED = 30 MPH | |  | |
| | |  | |
| | |  | |
| | |  | |
| | |  | |
| | |  | |
| | |  | |
| | |  | |
| | |  | |
| | |  | |
| | |  | |
| | |  | |
| | |  | |
| | |  | |
| | |  | |
| | |  | |
| | |  | |
| | |  | |
| | |  | |
| | |  | |
| | |  | |
| | |  | |
| | |  | |
| | |  | |
| | |  | |
| | |  | |
| | |  | |
| | |  | |
| | | <img alt="Typical Section No. 9 diagram showing a highway ramp transition. The diagram illustrates the layout of lanes, shoulders, and barriers. Key features include a 'WALL SHIELDING BARRIER INDEX 521-001' on the left, a 'MILLING & RESURFACING' area, and a 'RAMP E | |

| PROJECT CONTROLS | | TYPICAL SECTION No. 10 | | | | | |
|---|-----------|--|--|----------------------|-----------|----------------|----|
| <u>CONTEXT CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> C1 : NATURAL <input type="checkbox"/> C3C : SUBURBAN COMM. <input type="checkbox"/> C2 : RURAL <input type="checkbox"/> C4 : URBAN GENERAL <input type="checkbox"/> C2T : RURAL TOWN <input type="checkbox"/> C5 : URBAN CENTER <input type="checkbox"/> C3R : SUBURBAN RES. <input type="checkbox"/> C6 : URBAN CORE <input checked="" type="checkbox"/> N/A : L.A. FACILITY | | | | | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> INTERSTATE <input type="checkbox"/> MAJOR COLLECTOR <input checked="" type="checkbox"/> FREEWAY/EXPWY. <input type="checkbox"/> MINOR COLLECTOR <input type="checkbox"/> PRINCIPAL ARTERIAL <input type="checkbox"/> LOCAL <input type="checkbox"/> MINOR ARTERIAL | | | | | | | |
| <u>HIGHWAY SYSTEM</u> | | | | | | | |
| <input checked="" type="checkbox"/> NATIONAL HIGHWAY SYSTEM <input checked="" type="checkbox"/> STRATEGIC INTERMODAL SYSTEM <input checked="" type="checkbox"/> STATE HIGHWAY SYSTEM <input type="checkbox"/> OFF-STATE HIGHWAY SYSTEM | | | | | | | |
| <u>ACCESS CLASSIFICATION</u> | | | | | | | |
| <input checked="" type="checkbox"/> 1 - FREEWAY <input type="checkbox"/> 2 - RESTRICTIVE w/Service Roads <input type="checkbox"/> 3 - RESTRICTIVE w/660 ft. Connection Spacing <input type="checkbox"/> 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing <input type="checkbox"/> 5 - RESTRICTIVE w/440 ft. Connection Spacing <input type="checkbox"/> 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing <input type="checkbox"/> 7 - BOTH MEDIAN TYPES | | | | | | | |
| <u>CRITERIA</u> | | | | | | | |
| <input checked="" type="checkbox"/> NEW CONSTRUCTION / RECONSTRUCTION <input type="checkbox"/> RESURFACING (LA FACILITIES) <input type="checkbox"/> RRR (ARTERIALS & COLLECTORS) | | STA. 435+50.81 TO STA. 437+29.87 APPROACH SLABS STA 435+20.55 TO STA 435+50.81 STA 437+29.87 TO STA 437+54.21 | | | | | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | | | | | | | |
| <u>DESIGN EXCEPTION:</u> 1. LANE WIDTH | | NOT TO SCALE TRAFFIC DATA CURRENT YEAR = 2020 AADT = 52,280 - 127,060 ESTIMATED OPENING YEAR = 2022 AADT = N/A ESTIMATED DESIGN YEAR = 2036 AADT = 381,000 $K = 7.59\%$ $D = 50.0\%$ $T = 6.6\%$ (24 HOUR) DESIGN HOUR T = 6.6% DESIGN SPEED = 60 MPH POSTED SPEED = 55 MPH | | | | | |
| <u>DESIGN VARIATION:</u> 1. EXPRESS LANE BUFFER SEPARATION WIDTH 2. EXPRESS LANES TUBULAR MARKER COLOR | | LEGEND: EL = EXPRESS LANES GUL = GENERAL USE LANES AUX = AUXILIARY LANES NOTES: 1. MATCH EXISTING CROSS SLOPES. CROSS SLOPES OBTAINED FROM FPID 432687-1-52-01 2. MATCH ADJACENT LANE CROSS SLOPE. VALUE IS SHOWN | | | | | |
| | | <table border="1"> <tr> <td>FINANCIAL PROJECT ID</td><td>SHEET NO.</td></tr> <tr> <td>447165-1-52-01</td><td>11</td></tr> </table> | | FINANCIAL PROJECT ID | SHEET NO. | 447165-1-52-01 | 11 |
| FINANCIAL PROJECT ID | SHEET NO. | | | | | | |
| 447165-1-52-01 | 11 | | | | | | |

| PROJECT CONTROLS | | TYPICAL SECTION No. 11 | | | | | |
|---|-----------|---|--|----------------------|-----------|----------------|----|
| <u>CONTEXT CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> C1 : NATURAL <input type="checkbox"/> C3C : SUBURBAN COMM. <input type="checkbox"/> C2 : RURAL <input type="checkbox"/> C4 : URBAN GENERAL <input type="checkbox"/> C2T : RURAL TOWN <input type="checkbox"/> C5 : URBAN CENTER <input type="checkbox"/> C3R : SUBURBAN RES. <input type="checkbox"/> C6 : URBAN CORE <input checked="" type="checkbox"/> N/A : L.A. FACILITY | | | | | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> INTERSTATE <input type="checkbox"/> MAJOR COLLECTOR <input checked="" type="checkbox"/> FREEWAY/EXPWY. <input type="checkbox"/> MINOR COLLECTOR <input type="checkbox"/> PRINCIPAL ARTERIAL <input type="checkbox"/> LOCAL <input type="checkbox"/> MINOR ARTERIAL | | | | | | | |
| <u>HIGHWAY SYSTEM</u> | | | | | | | |
| <input checked="" type="checkbox"/> NATIONAL HIGHWAY SYSTEM <input checked="" type="checkbox"/> STRATEGIC INTERMODAL SYSTEM <input checked="" type="checkbox"/> STATE HIGHWAY SYSTEM <input type="checkbox"/> OFF-STATE HIGHWAY SYSTEM | | | | | | | |
| <u>ACCESS CLASSIFICATION</u> | | | | | | | |
| <input checked="" type="checkbox"/> 1 - FREEWAY <input type="checkbox"/> 2 - RESTRICTIVE w/Service Roads <input type="checkbox"/> 3 - RESTRICTIVE w/660 ft. Connection Spacing <input type="checkbox"/> 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing <input type="checkbox"/> 5 - RESTRICTIVE w/440 ft. Connection Spacing <input type="checkbox"/> 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing <input type="checkbox"/> 7 - BOTH MEDIAN TYPES | | | | | | | |
| <u>CRITERIA</u> | | | | | | | |
| <input checked="" type="checkbox"/> NEW CONSTRUCTION / RECONSTRUCTION <input type="checkbox"/> RESURFACING (LA FACILITIES) <input type="checkbox"/> RRR (ARTERIALS & COLLECTORS) | | STA. 446+07.24 TO STA. 446+63.81 APPROACH SLABS STA 445+72.21 TO STA 446+07.24 STA 446+63.81 TO STA 446+98.06 | | | | | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | | NOT TO SCALE LEGEND: EL = EXPRESS LANES GUL = GENERAL USE LANES AUX = AUXILIARY LANES NOTES: 1. MATCH EXISTING CROSS SLOPES. CROSS SLOPES OBTAINED FROM FPID 432687-1-52-01 2. MATCH ADJACENT LANE CROSS SLOPE. VALUE IS SHOWN | | | | | |
| <u>DESIGN EXCEPTION:</u> 1. LANE WIDTH & SHOULDER WIDTH | | <u>TRAFFIC DATA</u> CURRENT YEAR = 2020 AADT = 52,280 - 127,060 ESTIMATED OPENING YEAR = 2022 AADT = N/A ESTIMATED DESIGN YEAR = 2036 AADT = 381,000 K = 7.59% D = 50.0% T = 6.6% (24 HOUR) DESIGN HOUR T = 6.6% DESIGN SPEED = 60 MPH POSTED SPEED = 55 MPH | | | | | |
| <u>DESIGN VARIATION:</u> 1. VERTICAL CLEARANCE 2. EXPRESS LANE BUFFER SEPARATION WIDTH 3. EXPRESS LANES TUBULAR MARKER COLOR | | <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">FINANCIAL PROJECT ID</td><td style="width: 50%;">SHEET NO.</td></tr> <tr> <td>447165-1-52-01</td><td>12</td></tr> </table> | | FINANCIAL PROJECT ID | SHEET NO. | 447165-1-52-01 | 12 |
| FINANCIAL PROJECT ID | SHEET NO. | | | | | | |
| 447165-1-52-01 | 12 | | | | | | |

| PROJECT CONTROLS | | TYPICAL SECTION No. 12 | | | | | |
|--|-----------|--|--|----------------------|-----------|----------------|----|
| <u>CONTEXT CLASSIFICATION</u> | | | | | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> INTERSTATE <input type="checkbox"/> MAJOR COLLECTOR <input checked="" type="checkbox"/> FREEWAY/EXPWY. <input type="checkbox"/> MINOR COLLECTOR <input type="checkbox"/> PRINCIPAL ARTERIAL <input type="checkbox"/> LOCAL <input type="checkbox"/> MINOR ARTERIAL | | | | | | | |
| <u>HIGHWAY SYSTEM</u> | | | | | | | |
| <input checked="" type="checkbox"/> NATIONAL HIGHWAY SYSTEM <input checked="" type="checkbox"/> STRATEGIC INTERMODAL SYSTEM <input checked="" type="checkbox"/> STATE HIGHWAY SYSTEM <input type="checkbox"/> OFF-STATE HIGHWAY SYSTEM | | | | | | | |
| <u>ACCESS CLASSIFICATION</u> | | <p style="text-align: center;">SR 826 SB OVER FEC RR, BRIDGE NO. 870258</p> <p style="text-align: center;">STA. 462+17.94 TO STA. 463+67.36</p> | | | | | |
| <u>CRITERIA</u> | | <p style="text-align: center;">APPROACH SLABS</p> <p style="text-align: center;">STA 461+91.73 TO STA 462+17.94</p> <p style="text-align: center;">STA 463+67.36 TO STA 463+93.73</p> | | | | | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | | <p style="text-align: center;">NOT TO SCALE</p> <p>LEGEND: EL = EXPRESS LANES GUL = GENERAL USE LANES AUX = AUXILIARY LANES</p> <p>NOTES:</p> <p>[1] MATCH EXISTING CROSS SLOPES. CROSS SLOPES OBTAINED FROM FPID 432687-1-52-01</p> <p>[2] MATCH ADJACENT LANE CROSS SLOPE. VALUE IS SHOWN</p> | | | | | |
| <u>DESIGN EXCEPTION:</u> 1. LANE WIDTH & SHOULDER WIDTH 2. VERTICAL CLERANCE | | <p style="text-align: center;">TRAFFIC DATA</p> <p>CURRENT YEAR = 2020 AADT = 52,280 - 127,060 ESTIMATED OPENING YEAR = 2022 AADT = N/A ESTIMATED DESIGN YEAR = 2036 AADT = 381,000 $K = 7.59\%$ $D = 50.0\%$ $T = 6.6\%$ (24 HOUR) DESIGN HOUR T = 6.6% DESIGN SPEED = 60 MPH POSTED SPEED = 55 MPH</p> | | | | | |
| <u>DESIGN VARIATION:</u> 1. EXPRESS LANE BUFFER SEPARATION WIDTH 2. EXPRESS LANES TUBULAR MARKER COLOR | | <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 80%;">FINANCIAL PROJECT ID</td> <td style="width: 20%;">SHEET NO.</td> </tr> <tr> <td>447165-1-52-01</td> <td>13</td> </tr> </table> | | FINANCIAL PROJECT ID | SHEET NO. | 447165-1-52-01 | 13 |
| FINANCIAL PROJECT ID | SHEET NO. | | | | | | |
| 447165-1-52-01 | 13 | | | | | | |

| PROJECT CONTROLS | | TYPICAL SECTION No. 13 | | | | | |
|--|-----------|---|--|----------------------|-----------|----------------|----|
| <u>CONTEXT CLASSIFICATION</u> | |  | | | | | |
| <input type="checkbox"/> C1 : NATURAL <input type="checkbox"/> C3C : SUBURBAN COMM. <input type="checkbox"/> C2 : RURAL <input type="checkbox"/> C4 : URBAN GENERAL <input type="checkbox"/> C2T : RURAL TOWN <input type="checkbox"/> C5 : URBAN CENTER <input type="checkbox"/> C3R : SUBURBAN RES. <input type="checkbox"/> C6 : URBAN CORE <input checked="" type="checkbox"/> N/A : L.A. FACILITY | | | | | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | | <input type="checkbox"/> INTERSTATE <input type="checkbox"/> MAJOR COLLECTOR <input checked="" type="checkbox"/> FREEWAY/EXPWY. <input type="checkbox"/> MINOR COLLECTOR <input type="checkbox"/> PRINCIPAL ARTERIAL <input type="checkbox"/> LOCAL <input type="checkbox"/> MINOR ARTERIAL | | | | | |
| <u>HIGHWAY SYSTEM</u> | | <input checked="" type="checkbox"/> NATIONAL HIGHWAY SYSTEM <input checked="" type="checkbox"/> STRATEGIC INTERMODAL SYSTEM <input checked="" type="checkbox"/> STATE HIGHWAY SYSTEM <input type="checkbox"/> OFF-STATE HIGHWAY SYSTEM | | | | | |
| <u>ACCESS CLASSIFICATION</u> | | <input checked="" type="checkbox"/> 1 - FREEWAY <input type="checkbox"/> 2 - RESTRICTIVE w/Service Roads <input type="checkbox"/> 3 - RESTRICTIVE w/660 ft. Connection Spacing <input type="checkbox"/> 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing <input type="checkbox"/> 5 - RESTRICTIVE w/440 ft. Connection Spacing <input type="checkbox"/> 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing <input type="checkbox"/> 7 - BOTH MEDIAN TYPES | | | | | |
| <u>CRITERIA</u> | | <input checked="" type="checkbox"/> NEW CONSTRUCTION / RECONSTRUCTION <input type="checkbox"/> RESURFACING (LA FACILITIES) <input type="checkbox"/> RRR (ARTERIALS & COLLECTORS) | | | | | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | | <p>TRAFFIC DATA</p> <p>CURRENT YEAR = 2020 AADT = 52,280 - 127,060 ESTIMATED OPENING YEAR = 2022 AADT = N/A ESTIMATED DESIGN YEAR = 2036 AADT = 381,000 $K = 7.59\%$ $D = 50.0\%$ $T = 6.6\%$ (24 HOUR) DESIGN HOUR T = 6.6% DESIGN SPEED = 60 MPH POSTED SPEED = 55 MPH</p> <p>APPROACH SLABS</p> <p>STA 481+20.25 TO STA 481+20.39 STA 485+91.26 TO STA 485+91.42</p> | | | | | |
| <u>DESIGN EXCEPTION:</u> 1. LANE WIDTH | | <p>NOT TO SCALE</p> <p>LEGEND: EL = EXPRESS LANES GUL = GENERAL USE LANES AUX = AUXILIARY LANES</p> <p>NOTES: \square MATCH EXISTING CROSS SLOPES. CROSS SLOPES OBTAINED FROM FPID 432687-1-52-01. VALUE IS SHOWN</p> | | | | | |
| <u>DESIGN VARIATION:</u> 1. EXPRESS LANE BUFFER SEPARATION WIDTH 2. EXPRESS LANES TUBULAR MARKER COLOR | | <table border="1" data-bbox="2709 1879 3100 2027"> <tr> <td>FINANCIAL PROJECT ID</td> <td>SHEET NO.</td> </tr> <tr> <td>447165-1-52-01</td> <td>14</td> </tr> </table> | | FINANCIAL PROJECT ID | SHEET NO. | 447165-1-52-01 | 14 |
| FINANCIAL PROJECT ID | SHEET NO. | | | | | | |
| 447165-1-52-01 | 14 | | | | | | |

| PROJECT CONTROLS | | TYPICAL SECTION No. 14 | | | | | |
|---|-----------|--|--|----------------------|-----------|----------------|----|
| <u>CONTEXT CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> C1 : NATURAL <input type="checkbox"/> C3C : SUBURBAN COMM. <input type="checkbox"/> C2 : RURAL <input type="checkbox"/> C4 : URBAN GENERAL <input type="checkbox"/> C2T : RURAL TOWN <input type="checkbox"/> C5 : URBAN CENTER <input type="checkbox"/> C3R : SUBURBAN RES. <input type="checkbox"/> C6 : URBAN CORE <input checked="" type="checkbox"/> N/A : L.A. FACILITY | | | | | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> INTERSTATE <input type="checkbox"/> MAJOR COLLECTOR <input checked="" type="checkbox"/> FREEWAY/EXPWY. <input type="checkbox"/> MINOR COLLECTOR <input type="checkbox"/> PRINCIPAL ARTERIAL <input type="checkbox"/> LOCAL <input type="checkbox"/> MINOR ARTERIAL | | | | | | | |
| <u>HIGHWAY SYSTEM</u> | | | | | | | |
| <input checked="" type="checkbox"/> NATIONAL HIGHWAY SYSTEM <input checked="" type="checkbox"/> STRATEGIC INTERMODAL SYSTEM <input checked="" type="checkbox"/> STATE HIGHWAY SYSTEM <input type="checkbox"/> OFF-STATE HIGHWAY SYSTEM | | | | | | | |
| <u>ACCESS CLASSIFICATION</u> | | | | | | | |
| <input checked="" type="checkbox"/> 1 - FREEWAY <input type="checkbox"/> 2 - RESTRICTIVE w/Service Roads <input type="checkbox"/> 3 - RESTRICTIVE w/660 ft. Connection Spacing <input type="checkbox"/> 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing <input type="checkbox"/> 5 - RESTRICTIVE w/440 ft. Connection Spacing <input type="checkbox"/> 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing <input type="checkbox"/> 7 - BOTH MEDIAN TYPES | | | | | | | |
| <u>CRITERIA</u> | | | | | | | |
| <input checked="" type="checkbox"/> NEW CONSTRUCTION / RECONSTRUCTION <input type="checkbox"/> RESURFACING (LA FACILITIES) <input type="checkbox"/> RRR (ARTERIALS & COLLECTORS) | | | | | | | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | | | | | | | |
| <u>DESIGN EXCEPTION:</u> 1. LANE WIDTH & SHOULDER WIDTH | | | | | | | |
| <u>DESIGN VARIATION:</u> 1. SHOULDER WIDTH 2. EXPRESS LANE BUFFER SEPARATION WIDTH 3. EXPRESS LANES TUBULAR MARKER COLOR | | | | | | | |
| | | | | | | | |
| | | <p>SR 826 SB OVER NW 103RD STREET, BRIDGE NO. 870757</p> <p>STA. 529+96.72 TO STA. 532+28.78</p> <p>APPROACH SLABS</p> <p>STA 529+70.69 TO STA 529+96.72</p> <p>STA 532+28.78 TO STA 532+48.86</p> <p>NOT TO SCALE</p> <p>LEGEND: EL = EXPRESS LANES GUL = GENERAL USE LANES AUX = AUXILIARY LANES</p> <p>NOTES: 1. MATCH EXISTING CROSS SLOPES. CROSS SLOPES OBTAINED FROM FPID 432687-1-52-01 2. MATCH ADJACENT LANE CROSS SLOPE. VALUE IS SHOWN</p> | | | | | |
| | | <p>TRAFFIC DATA</p> <p>CURRENT YEAR = 2020 AADT = 52,280 - 127,060 ESTIMATED OPENING YEAR = 2022 AADT = N/A ESTIMATED DESIGN YEAR = 2036 AADT = 381,000 $K = 7.59\%$ $D = 50.0\%$ $T = 6.6\%$ (24 HOUR) DESIGN HOUR T = 6.6% DESIGN SPEED = 60 MPH POSTED SPEED = 55 MPH</p> | | | | | |
| | | <table border="1"> <tr> <td>FINANCIAL PROJECT ID</td> <td>SHEET NO.</td> </tr> <tr> <td>447165-1-52-01</td> <td>15</td> </tr> </table> | | FINANCIAL PROJECT ID | SHEET NO. | 447165-1-52-01 | 15 |
| FINANCIAL PROJECT ID | SHEET NO. | | | | | | |
| 447165-1-52-01 | 15 | | | | | | |


| PROJECT CONTROLS | | TYPICAL SECTION No. 15 | | | | | |
|---|-----------|---|--|----------------------|-----------|----------------|----|
| <u>CONTEXT CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> C1 : NATURAL <input type="checkbox"/> C3C : SUBURBAN COMM. <input type="checkbox"/> C2 : RURAL <input type="checkbox"/> C4 : URBAN GENERAL <input type="checkbox"/> C2T : RURAL TOWN <input type="checkbox"/> C5 : URBAN CENTER <input type="checkbox"/> C3R : SUBURBAN RES. <input type="checkbox"/> C6 : URBAN CORE <input checked="" type="checkbox"/> N/A : L.A. FACILITY | | | | | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> INTERSTATE <input type="checkbox"/> MAJOR COLLECTOR <input checked="" type="checkbox"/> FREEWAY/EXPWY. <input type="checkbox"/> MINOR COLLECTOR <input type="checkbox"/> PRINCIPAL ARTERIAL <input type="checkbox"/> LOCAL <input type="checkbox"/> MINOR ARTERIAL | | | | | | | |
| <u>HIGHWAY SYSTEM</u> | | | | | | | |
| <input checked="" type="checkbox"/> NATIONAL HIGHWAY SYSTEM <input checked="" type="checkbox"/> STRATEGIC INTERMODAL SYSTEM <input checked="" type="checkbox"/> STATE HIGHWAY SYSTEM <input type="checkbox"/> OFF-STATE HIGHWAY SYSTEM | | | | | | | |
| <u>ACCESS CLASSIFICATION</u> | | | | | | | |
| <input checked="" type="checkbox"/> 1 - FREEWAY <input type="checkbox"/> 2 - RESTRICTIVE w/Service Roads <input type="checkbox"/> 3 - RESTRICTIVE w/660 ft. Connection Spacing <input type="checkbox"/> 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing <input type="checkbox"/> 5 - RESTRICTIVE w/440 ft. Connection Spacing <input type="checkbox"/> 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing <input type="checkbox"/> 7 - BOTH MEDIAN TYPES | | | | | | | |
| <u>CRITERIA</u> | | | | | | | |
| <input checked="" type="checkbox"/> NEW CONSTRUCTION / RECONSTRUCTION <input type="checkbox"/> RESURFACING (LA FACILITIES) <input type="checkbox"/> RRR (ARTERIALS & COLLECTORS) | | | | | | | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | | | | | | | |
| <u>DESIGN EXCEPTION:</u> 1. LANE WIDTH | | | | | | | |
| <u>DESIGN VARIATION:</u> 1. EXPRESS LANE BUFFER SEPARATION WIDTH 2. EXPRESS LANES TUBULAR MARKER COLOR | | | | | | | |
| | | | | | | | |
| | | <p>SR 826 NB OVER NW 103RD STREET, BRIDGE NO. 870995</p> <p>STA. 529+96.72 TO STA. 532+28.78 ℓ SR 826</p> <p>NOT TO SCALE</p> <p>APPROACH SLABS</p> <p>STA 529+70.69 TO STA 529+96.72</p> <p>STA 532+28.78 TO STA 532+48.86</p> <p>LEGEND: EL = EXPRESS LANES GUL = GENERAL USE LANES AUX = AUXILIARY LANES</p> <p>NOTES: 1. MATCH EXISTING CROSS SLOPES. CROSS SLOPES OBTAINED FROM FPID 432687-1-52-01 2. MATCH ADJACENT LANE CROSS SLOPE. VALUE IS SHOWN</p> | | | | | |
| | | <p><u>TRAFFIC DATA</u></p> <p>CURRENT YEAR = 2020 AADT = 52,280 - 127,060 ESTIMATED OPENING YEAR = 2022 AADT = N/A ESTIMATED DESIGN YEAR = 2036 AADT = 381,000 K = 7.59% D = 50.0% T = 6.6% (24 HOUR) DESIGN HOUR T = 6.6% DESIGN SPEED = 60 MPH POSTED SPEED = 55 MPH</p> | | | | | |
| | | <table border="1"> <tr> <td>FINANCIAL PROJECT ID</td> <td>SHEET NO.</td> </tr> <tr> <td>447165-1-52-01</td> <td>16</td> </tr> </table> | | FINANCIAL PROJECT ID | SHEET NO. | 447165-1-52-01 | 16 |
| FINANCIAL PROJECT ID | SHEET NO. | | | | | | |
| 447165-1-52-01 | 16 | | | | | | |

| PROJECT CONTROLS | | TYPICAL SECTION No. 16 | |
|--|--------------------------|------------------------|--|
| <u>CONTEXT CLASSIFICATION</u> | | | |
| () C1 : NATURAL | () C3C : SUBURBAN COMM. | | |
| () C2 : RURAL | () C4 : URBAN GENERAL | | |
| () C2T : RURAL TOWN | () C5 : URBAN CENTER | | |
| () C3R : SUBURBAN RES. | () C6 : URBAN CORE | | |
| (X) N/A : L.A. FACILITY | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | | | |
| () INTERSTATE | () MAJOR COLLECTOR | | |
| (X) FREEWAY/EXPWY. | () MINOR COLLECTOR | | |
| () PRINCIPAL ARTERIAL | () LOCAL | | |
| () MINOR ARTERIAL | | | |
| <u>HIGHWAY SYSTEM</u> | | | |
| (X) NATIONAL HIGHWAY SYSTEM | | | |
| (X) STRATEGIC INTERMODAL SYSTEM | | | |
| (X) STATE HIGHWAY SYSTEM | | | |
| () OFF-STATE HIGHWAY SYSTEM | | | |
| <u>ACCESS CLASSIFICATION</u> | | | |
| (X) 1 - FREEWAY | | | |
| () 2 - RESTRICTIVE w/Service Roads | | | |
| () 3 - RESTRICTIVE w/660 ft. Connection Spacing | | | |
| () 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing | | | |
| () 5 - RESTRICTIVE w/440 ft. Connection Spacing | | | |
| () 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing | | | |
| () 7 - BOTH MEDIAN TYPES | | | |
| <u>CRITERIA</u> | | | |
| (X) NEW CONSTRUCTION / RECONSTRUCTION | | | |
| () RESURFACING (LA FACILITIES) | | | |
| () RRR (ARTERIALS & COLLECTORS) | | | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | | | |
| | | | |
| <u>TRAFFIC DATA</u> | | | |
| CURRENT YEAR = 2020 AADT = 52,280 - 127,060 | | | |
| ESTIMATED OPENING YEAR = 2022 AADT = N/A | | | |
| ESTIMATED DESIGN YEAR = 2036 AADT = 381,000 | | | |
| K = 7.59% D = 50.0% T = 6.6% (24 HOUR) | | | |
| DESIGN HOUR T = 6.6% | | | |
| DESIGN SPEED = 30 MPH | | | |
| POSTED SPEED = 30 MPH (25 MPH ADVISORY) | | | |
| | | | |
| NOT TO SCALE | | | |
| NOTE: | | | |
| [1] MATCH EXISTING CROSS SLOPES. | | | |
| CROSS SLOPES OBTAINED FROM FPID | | | |
| 432687-1-52-01. VALUE RANGE IS SHOWN | | | |
| [2] BRIDGE IS SUPERELEVATED | | | |
| [3] SHOULDER WIDTH NEEDED TO MEET | | | |
| STOPPING SIGHT DISTANCE | | | |
| | | | |
| FINANCIAL PROJECT ID | | | |
| SHEET NO. | | | |
| 447165-1-52-01 | | | |
| 17 | | | |


| PROJECT CONTROLS | | TYPICAL SECTION No. 17 | | | | | |
|---|-----------|--|--|----------------------|-----------|----------------|----|
| <u>CONTEXT CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> C1 : NATURAL <input type="checkbox"/> C3C : SUBURBAN COMM. <input type="checkbox"/> C2 : RURAL <input type="checkbox"/> C4 : URBAN GENERAL <input type="checkbox"/> C2T : RURAL TOWN <input type="checkbox"/> C5 : URBAN CENTER <input type="checkbox"/> C3R : SUBURBAN RES. <input type="checkbox"/> C6 : URBAN CORE <input checked="" type="checkbox"/> N/A : L.A. FACILITY | | | | | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> INTERSTATE <input type="checkbox"/> MAJOR COLLECTOR <input checked="" type="checkbox"/> FREEWAY/EXPWY. <input type="checkbox"/> MINOR COLLECTOR <input type="checkbox"/> PRINCIPAL ARTERIAL <input type="checkbox"/> LOCAL <input type="checkbox"/> MINOR ARTERIAL | | | | | | | |
| <u>HIGHWAY SYSTEM</u> | | | | | | | |
| <input checked="" type="checkbox"/> NATIONAL HIGHWAY SYSTEM <input checked="" type="checkbox"/> STRATEGIC INTERMODAL SYSTEM <input checked="" type="checkbox"/> STATE HIGHWAY SYSTEM <input type="checkbox"/> OFF-STATE HIGHWAY SYSTEM | | | | | | | |
| <u>ACCESS CLASSIFICATION</u> | | | | | | | |
| <input checked="" type="checkbox"/> 1 - FREEWAY <input type="checkbox"/> 2 - RESTRICTIVE w/Service Roads <input type="checkbox"/> 3 - RESTRICTIVE w/660 ft. Connection Spacing <input type="checkbox"/> 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing <input type="checkbox"/> 5 - RESTRICTIVE w/440 ft. Connection Spacing <input type="checkbox"/> 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing <input type="checkbox"/> 7 - BOTH MEDIAN TYPES | | | | | | | |
| <u>CRITERIA</u> | | | | | | | |
| <input checked="" type="checkbox"/> NEW CONSTRUCTION / RECONSTRUCTION <input type="checkbox"/> RESURFACING (LA FACILITIES) <input type="checkbox"/> RRR (ARTERIALS & COLLECTORS) | | | | | | | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | | | | | | | |
| | | | | | | | |
| | | <p>NW 103RD ST. SB FLYOVER ON-RAMP, BRIDGE NO. 870757</p> <p>STA 4538+08.15 TO STA 4546+20.21</p> <p>NOT TO SCALE</p> | | | | | |
| | | <p>NOTE:</p> <p>[1] MATCH EXISTING CROSS SLOPES. CROSS SLOPES OBTAINED FROM FPD 432687-1-52-01. VALUE RANGE IS SHOWN</p> <p>[2] BRIDGE IS SUPERELEVATED</p> <p>[3] SHOULDER WIDTH NEEDED TO MEET STOPPING SIGHT DISTANCE</p> | | | | | |
| <u>TRAFFIC DATA</u> | | | | | | | |
| <p>CURRENT YEAR = 2020 AADT = 52,280 - 127,060 ESTIMATED OPENING YEAR = 2022 AADT = N/A ESTIMATED DESIGN YEAR = 2036 AADT = 381,000 K = 7.59% D = 50.0% T = 6.6% (24 HOUR) DESIGN HOUR T = 6.6% DESIGN SPEED = 30 MPH POSTED SPEED = 30 MPH (25 MPH ADVISORY)</p> | | | | | | | |
| | | <table border="1"> <tr> <td>FINANCIAL PROJECT ID</td> <td>SHEET NO.</td> </tr> <tr> <td>447165-1-52-01</td> <td>18</td> </tr> </table> | | FINANCIAL PROJECT ID | SHEET NO. | 447165-1-52-01 | 18 |
| FINANCIAL PROJECT ID | SHEET NO. | | | | | | |
| 447165-1-52-01 | 18 | | | | | | |

| PROJECT CONTROLS | | TYPICAL SECTION No. 18 | | | | | |
|--|-----------|--|--|----------------------|-----------|----------------|----|
| <u>CONTEXT CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> C1 : NATURAL <input type="checkbox"/> C3C : SUBURBAN COMM. <input type="checkbox"/> C2 : RURAL <input type="checkbox"/> C4 : URBAN GENERAL <input type="checkbox"/> C2T : RURAL TOWN <input type="checkbox"/> C5 : URBAN CENTER <input type="checkbox"/> C3R : SUBURBAN RES. <input type="checkbox"/> C6 : URBAN CORE <input checked="" type="checkbox"/> N/A : L.A. FACILITY | | | | | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> INTERSTATE <input type="checkbox"/> MAJOR COLLECTOR <input checked="" type="checkbox"/> FREEWAY/EXPWY. <input type="checkbox"/> MINOR COLLECTOR <input type="checkbox"/> PRINCIPAL ARTERIAL <input type="checkbox"/> LOCAL <input type="checkbox"/> MINOR ARTERIAL | | | | | | | |
| <u>HIGHWAY SYSTEM</u> | | | | | | | |
| <u>ACCESS CLASSIFICATION</u> | | <p>SR 826 SB OVER LITTLE RIVER CANAL, BRIDGE NO. 870758</p> <p>STA. 540+84.25 TO STA. 541+69.15</p> <p>APPROACH SLABS</p> <p>STA 540+64.30 TO STA 540+84.25</p> <p>STA 541+69.15 TO STA 541+89.18</p> | | | | | |
| <u>CRITERIA</u> | | <p>NOT TO SCALE</p> <p>LEGEND:</p> <ul style="list-style-type: none"> EL = EXPRESS LANES GUL = GENERAL USE LANES AUX = AUXILIARY LANES <p>NOTES:</p> <p>[1] MATCH EXISTING CROSS SLOPES. CROSS SLOPES OBTAINED FROM FPID 432687-1-52-01. VALUE IS SHOWN</p> | | | | | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | | <p><u>TRAFFIC DATA</u></p> <p>CURRENT YEAR = 2020 AADT = 52,280 - 127,060 ESTIMATED OPENING YEAR = 2022 AADT = N/A ESTIMATED DESIGN YEAR = 2036 AADT = 381,000 $K = 7.59\%$ $D = 50.0\%$ $T = 6.6\%$ (24 HOUR) DESIGN HOUR T = 6.6% DESIGN SPEED = 60 MPH POSTED SPEED = 55 MPH</p> | | | | | |
| | | <table border="1"> <tr> <td>FINANCIAL PROJECT ID</td> <td>SHEET NO.</td> </tr> <tr> <td>447165-1-52-01</td> <td>19</td> </tr> </table> | | FINANCIAL PROJECT ID | SHEET NO. | 447165-1-52-01 | 19 |
| FINANCIAL PROJECT ID | SHEET NO. | | | | | | |
| 447165-1-52-01 | 19 | | | | | | |

| PROJECT CONTROLS | | TYPICAL SECTION No. 19 | | | | | |
|--|-----------|---|--|----------------------|-----------|----------------|----|
| <u>CONTEXT CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> C1 : NATURAL <input type="checkbox"/> C3C : SUBURBAN COMM. <input type="checkbox"/> C2 : RURAL <input type="checkbox"/> C4 : URBAN GENERAL <input type="checkbox"/> C2T : RURAL TOWN <input type="checkbox"/> C5 : URBAN CENTER <input type="checkbox"/> C3R : SUBURBAN RES. <input type="checkbox"/> C6 : URBAN CORE <input checked="" type="checkbox"/> N/A : L.A. FACILITY | | | | | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> INTERSTATE <input type="checkbox"/> MAJOR COLLECTOR <input checked="" type="checkbox"/> FREEWAY/EXPWY. <input type="checkbox"/> MINOR COLLECTOR <input type="checkbox"/> PRINCIPAL ARTERIAL <input type="checkbox"/> LOCAL <input type="checkbox"/> MINOR ARTERIAL | | | | | | | |
| <u>HIGHWAY SYSTEM</u> | | | | | | | |
| <u>ACCESS CLASSIFICATION</u> | | <p>SR 826 SB OVER W 60TH STREET, BRIDGE NO. 870957</p> <p>STA. 567+82.06 TO STA. 568+87.97</p> <p>NOT TO SCALE</p> <p>APPROACH SLABS</p> <p>STA 567+62.08 TO STA 567+82.06</p> <p>STA 568+87.97 TO STA 569+07.96</p> | | | | | |
| <u>CRITERIA</u> | | <p>LEGEND:</p> <p>EL = EXPRESS LANES</p> <p>GUL = GENERAL USE LANES</p> <p>AUX = AUXILIARY LANES</p> <p>NOTES:</p> <p>1. MATCH EXISTING CROSS SLOPES. CROSS SLOPES OBTAINED FROM FPID 432687-1-52-01. VALUE IS SHOWN</p> | | | | | |
| <input checked="" type="checkbox"/> NEW CONSTRUCTION / RECONSTRUCTION <input type="checkbox"/> RESURFACING (LA FACILITIES) <input type="checkbox"/> RRR (ARTERIALS & COLLECTORS) | | | | | | | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | | <p><u>DESIGN EXCEPTION</u></p> <p>1. LANE WIDTH</p> <p><u>DESIGN VARIATION</u></p> <p>1. EXPRESS LANE BUFFER SEPARATION WIDTH</p> <p>2. EXPRESS LANES TUBULAR MARKER COLOR</p> <p><u>TRAFFIC DATA</u></p> <p>CURRENT YEAR = 2020 AADT = 52,280 - 127,060 ESTIMATED OPENING YEAR = 2022 AADT = N/A ESTIMATED DESIGN YEAR = 2036 AADT = 381,000 K = 7.59% D = 50.0% T = 6.6% (24 HOUR) DESIGN HOUR T = 6.6% DESIGN SPEED = 60 MPH POSTED SPEED = 55 MPH</p> | | | | | |
| | | <table border="1"> <tr> <td>FINANCIAL PROJECT ID</td> <td>SHEET NO.</td> </tr> <tr> <td>447165-1-52-01</td> <td>20</td> </tr> </table> | | FINANCIAL PROJECT ID | SHEET NO. | 447165-1-52-01 | 20 |
| FINANCIAL PROJECT ID | SHEET NO. | | | | | | |
| 447165-1-52-01 | 20 | | | | | | |

| PROJECT CONTROLS | | TYPICAL SECTION No. 20 | | | | | |
|---|-----------|--|--|----------------------|-----------|----------------|----|
| <u>CONTEXT CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> C1 : NATURAL <input type="checkbox"/> C3C : SUBURBAN COMM. <input type="checkbox"/> C2 : RURAL <input type="checkbox"/> C4 : URBAN GENERAL <input type="checkbox"/> C2T : RURAL TOWN <input type="checkbox"/> C5 : URBAN CENTER <input type="checkbox"/> C3R : SUBURBAN RES. <input type="checkbox"/> C6 : URBAN CORE <input checked="" type="checkbox"/> N/A : L.A. FACILITY | | | | | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> INTERSTATE <input type="checkbox"/> MAJOR COLLECTOR <input checked="" type="checkbox"/> FREEWAY/EXPWY. <input type="checkbox"/> MINOR COLLECTOR <input type="checkbox"/> PRINCIPAL ARTERIAL <input type="checkbox"/> LOCAL <input type="checkbox"/> MINOR ARTERIAL | | | | | | | |
| <u>HIGHWAY SYSTEM</u> | | | | | | | |
| <input checked="" type="checkbox"/> NATIONAL HIGHWAY SYSTEM <input checked="" type="checkbox"/> STRATEGIC INTERMODAL SYSTEM <input checked="" type="checkbox"/> STATE HIGHWAY SYSTEM <input type="checkbox"/> OFF-STATE HIGHWAY SYSTEM | | | | | | | |
| <u>ACCESS CLASSIFICATION</u> | | | | | | | |
| <input checked="" type="checkbox"/> 1 - FREEWAY <input type="checkbox"/> 2 - RESTRICTIVE w/Service Roads <input type="checkbox"/> 3 - RESTRICTIVE w/660 ft. Connection Spacing <input type="checkbox"/> 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing <input type="checkbox"/> 5 - RESTRICTIVE w/440 ft. Connection Spacing <input type="checkbox"/> 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing <input type="checkbox"/> 7 - BOTH MEDIAN TYPES | | | | | | | |
| <u>CRITERIA</u> | | | | | | | |
| <input checked="" type="checkbox"/> NEW CONSTRUCTION / RECONSTRUCTION <input type="checkbox"/> RESURFACING (LA FACILITIES) <input type="checkbox"/> RRR (ARTERIALS & COLLECTORS) | | | | | | | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | | | | | | | |
| <u>DESIGN EXCEPTION:</u> 1. LANE WIDTH | | | | | | | |
| <u>DESIGN VARIATION:</u> 1. EXPRESS LANE BUFFER SEPARATION WIDTH 2. EXPRESS LANES TUBULAR MARKER COLOR | | | | | | | |
| | |  <p>SR 826 SB OVER NW 122ND STREET, BRIDGE NO. 870766</p> <p>STA. 593+16.24 TO STA. 594+71.22</p> <p>APPROACH SLABS</p> <p>STA 592+96.23 TO STA 593+16.24</p> <p>STA 594+71.22 TO STA 594+91.41</p> <p>NOT TO SCALE</p> <p>LEGEND: EL = EXPRESS LANES GUL = GENERAL USE LANES AUX = AUXILIARY LANES</p> <p>NOTES: 1. MATCH EXISTING CROSS SLOPES. CROSS SLOPES OBTAINED FROM FPID 432687-1-52-01. VALUE IS SHOWN</p> | | | | | |
| | | <table border="1"> <tr> <td>FINANCIAL PROJECT ID</td> <td>SHEET NO.</td> </tr> <tr> <td>447165-1-52-01</td> <td>21</td> </tr> </table> | | FINANCIAL PROJECT ID | SHEET NO. | 447165-1-52-01 | 21 |
| FINANCIAL PROJECT ID | SHEET NO. | | | | | | |
| 447165-1-52-01 | 21 | | | | | | |

| PROJECT CONTROLS | | TYPICAL SECTION No. 21 | | | | | |
|---|-----------|--|--|----------------------|-----------|----------------|----|
| <u>CONTEXT CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> C1 : NATURAL <input type="checkbox"/> C3C : SUBURBAN COMM. <input type="checkbox"/> C2 : RURAL <input type="checkbox"/> C4 : URBAN GENERAL <input type="checkbox"/> C2T : RURAL TOWN <input type="checkbox"/> C5 : URBAN CENTER <input type="checkbox"/> C3R : SUBURBAN RES. <input type="checkbox"/> C6 : URBAN CORE <input checked="" type="checkbox"/> N/A : L.A. FACILITY | | | | | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> INTERSTATE <input type="checkbox"/> MAJOR COLLECTOR <input checked="" type="checkbox"/> FREEWAY/EXPWY. <input type="checkbox"/> MINOR COLLECTOR <input type="checkbox"/> PRINCIPAL ARTERIAL <input type="checkbox"/> LOCAL <input type="checkbox"/> MINOR ARTERIAL | | | | | | | |
| <u>HIGHWAY SYSTEM</u> | | | | | | | |
| <input checked="" type="checkbox"/> NATIONAL HIGHWAY SYSTEM <input checked="" type="checkbox"/> STRATEGIC INTERMODAL SYSTEM <input checked="" type="checkbox"/> STATE HIGHWAY SYSTEM <input type="checkbox"/> OFF-STATE HIGHWAY SYSTEM | | | | | | | |
| <u>ACCESS CLASSIFICATION</u> | | | | | | | |
| <input checked="" type="checkbox"/> 1 - FREEWAY <input type="checkbox"/> 2 - RESTRICTIVE w/Service Roads <input type="checkbox"/> 3 - RESTRICTIVE w/660 ft. Connection Spacing <input type="checkbox"/> 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing <input type="checkbox"/> 5 - RESTRICTIVE w/440 ft. Connection Spacing <input type="checkbox"/> 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing <input type="checkbox"/> 7 - BOTH MEDIAN TYPES | | | | | | | |
| <u>CRITERIA</u> | | | | | | | |
| <input checked="" type="checkbox"/> NEW CONSTRUCTION / RECONSTRUCTION <input type="checkbox"/> RESURFACING (LA FACILITIES) <input type="checkbox"/> RRR (ARTERIALS & COLLECTORS) | | | | | | | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | | | | | | | |
| <u>DESIGN EXCEPTION</u> 1. LANE WIDTH <u>DESIGN VARIATION</u> 1. EXPRESS LANE BUFFER SEPARATION WIDTH | | <p>TRAFFIC DATA</p> <p>CURRENT YEAR = 2020 AADT = 52,280 - 127,060 ESTIMATED OPENING YEAR = 2022 AADT = N/A ESTIMATED DESIGN YEAR = 2036 AADT = 381,000 $K = 7.59\%$ $D = 50.0\%$ $T = 6.6\%$ (24 HOUR) DESIGN HOUR T = 6.6% DESIGN SPEED = 60 MPH POSTED SPEED = 55 MPH</p> | | | | | |
| | | <p>SR 826 SB OVER NW 138TH STREET, BRIDGE NO. 870467</p> <p>STA. 757+71.93 TO STA. 758+67.78 $\#$ SR 826 SB</p> <p>APPROACH SLABS</p> <p>STA 757+36.72 TO STA 757+71.93 $\#$ SR 826 SB STA 758+67.78 TO STA 759+02.99 $\#$ SR 826 SB</p> | | | | | |
| | | <p>NOT TO SCALE</p> <p>LEGEND: $\#$ = EXPRESS LANES GUL = GENERAL USE LANES AUX = AUXILIARY LANES</p> <p>NOTES: 1. MATCH EXISTING CROSS SLOPES. CROSS SLOPES OBTAINED FROM FPID 432687-1-52-01. VALUE IS SHOWN</p> | | | | | |
| | | <table border="1"> <tr> <td>FINANCIAL PROJECT ID</td> <td>SHEET NO.</td> </tr> <tr> <td>447165-1-52-01</td> <td>22</td> </tr> </table> | | FINANCIAL PROJECT ID | SHEET NO. | 447165-1-52-01 | 22 |
| FINANCIAL PROJECT ID | SHEET NO. | | | | | | |
| 447165-1-52-01 | 22 | | | | | | |

| PROJECT CONTROLS | | TYPICAL SECTION No. 22 | | | | | |
|--|-----------|--|--|----------------------|-----------|----------------|----|
| <u>CONTEXT CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> C1 : NATURAL <input checked="" type="checkbox"/> C3C : SUBURBAN COMM. <input type="checkbox"/> C2 : RURAL <input type="checkbox"/> C4 : URBAN GENERAL <input type="checkbox"/> C2T : RURAL TOWN <input type="checkbox"/> C5 : URBAN CENTER <input type="checkbox"/> C3R : SUBURBAN RES. <input type="checkbox"/> C6 : URBAN CORE <input type="checkbox"/> N/A : L.A. FACILITY | | | | | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> INTERSTATE <input type="checkbox"/> MAJOR COLLECTOR <input type="checkbox"/> FREEWAY/EXPWY. <input type="checkbox"/> MINOR COLLECTOR <input type="checkbox"/> PRINCIPAL ARTERIAL <input checked="" type="checkbox"/> LOCAL <input type="checkbox"/> MINOR ARTERIAL | | | | | | | |
| <u>HIGHWAY SYSTEM</u> | | | | | | | |
| <input type="checkbox"/> NATIONAL HIGHWAY SYSTEM <input type="checkbox"/> STRATEGIC INTERMODAL SYSTEM <input checked="" type="checkbox"/> STATE HIGHWAY SYSTEM <input type="checkbox"/> OFF-STATE HIGHWAY SYSTEM | | | | | | | |
| <u>ACCESS CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> 1 - FREEWAY <input type="checkbox"/> 2 - RESTRICTIVE w/Service Roads <input type="checkbox"/> 3 - RESTRICTIVE w/660 ft. Connection Spacing <input type="checkbox"/> 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing <input type="checkbox"/> 5 - RESTRICTIVE w/440 ft. Connection Spacing <input type="checkbox"/> 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing <input type="checkbox"/> 7 - BOTH MEDIAN TYPES | | | | | | | |
| <u>CRITERIA</u> | | | | | | | |
| <input type="checkbox"/> NEW CONSTRUCTION / RECONSTRUCTION <input type="checkbox"/> RESURFACING (LA FACILITIES) <input checked="" type="checkbox"/> RRR (ARTERIALS & COLLECTORS) | | | | | | | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | | | | | | | |
| <u>DESIGN VARIATION</u> 1. CROSS SLOPE 2. BORDER WIDTH 3. HORIZONTAL CURVE RADIUS, HORIZONTAL CURVE LENGTH AND SUPERELEVATION 4. GUARDRAIL LATERAL OFFSET | |  <p>EAST FRONTAGE ROAD/W 20TH AVENUE (SECTION 87260151) STA. 200+12.23 TO STA. 214+41.08</p> <p>* MATCH EXISTING CROSS SLOPE; APPROX. VALUE RANGE IS SHOWN. MAX. CROSS SLOPE AT SUPERELEVATED SECTIONS: - 0.091 (RIGHT LANE) - 0.095 (LEFT LANE)</p> <p>NOT TO SCALE</p> | | | | | |
| <u>TRAFFIC DATA</u> CURRENT YEAR = 2019 AADT = 2,028 ESTIMATED OPENING YEAR = 2024 AADT = 2,100 ESTIMATED DESIGN YEAR = 2044 AADT = 2,500 K = 10.21% D = 64.5% T = 5.47% (24 HOUR) DESIGN HOUR T = 5.47% DESIGN SPEED = 30 MPH POSTED SPEED = 30 MPH | | | | | | | |
| | | <table border="1"> <tr> <td>FINANCIAL PROJECT ID</td><td>SHEET NO.</td></tr> <tr> <td>441830-1-52-01</td><td>23</td></tr> </table> | | FINANCIAL PROJECT ID | SHEET NO. | 441830-1-52-01 | 23 |
| FINANCIAL PROJECT ID | SHEET NO. | | | | | | |
| 441830-1-52-01 | 23 | | | | | | |

PROJECT CONTROLS

TYPICAL SECTION No. 23

CONTEXT CLASSIFICATION

- () C1 : NATURAL (X) C3C : SUBURBAN COMM.
- () C2 : RURAL () C4 : URBAN GENERAL
- () C2T : RURAL TOWN () C5 : URBAN CENTER
- () C3R : SUBURBAN RES. () C6 : URBAN CORE
- () N/A : L.A. FACILITY

FUNCTIONAL CLASSIFICATION

- () INTERSTATE () MAJOR COLLECTOR
- () FREEWAY/EXPWY. () MINOR COLLECTOR
- () PRINCIPAL ARTERIAL (X) LOCAL
- () MINOR ARTERIAL

HIGHWAY SYSTEM

- () NATIONAL HIGHWAY SYSTEM
- () STRATEGIC INTERMODAL SYSTEM
- (X) STATE HIGHWAY SYSTEM
- () OFF-STATE HIGHWAY SYSTEM

ACCESS CLASSIFICATION

- () 1 - FREEWAY
- () 2 - RESTRICTIVE w/Service Roads
- () 3 - RESTRICTIVE w/660 ft. Connection Spacing
- () 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing
- () 5 - RESTRICTIVE w/440 ft. Connection Spacing
- () 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing
- () 7 - BOTH MEDIAN TYPES

CRITERIA

- () NEW CONSTRUCTION / RECONSTRUCTION
- () RESURFACING (LA FACILITIES)
- (X) RRR (ARTERIALS & COLLECTORS)


POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:

DESIGN VARIATION

1. LANE WIDTH
2. CROSS SLOPE
3. SHOULDER WIDTH
4. BORDER WIDTH
5. HORIZONTAL CURVE RADIUS, HORIZONTAL CURVE LENGTH AND SUPERELEVATION
6. BICYCLE FACILITIES
7. SIDEWALK WIDTH

TRAFFIC DATA

CURRENT YEAR = 2019 AADT = 2,028
 ESTIMATED OPENING YEAR = 2024 AADT = 2,100
 ESTIMATED DESIGN YEAR = 2044 AADT = 2,500
 K = 10.21% D = 64.5% T = 5.47% (24 HOUR)
 DESIGN HOUR T = 5.47%
 DESIGN SPEED = 30 MPH
 POSTED SPEED = 30 MPH



* MATCH EXISTING CROSS SLOPE;
 APPROX. VALUE RANGE SHOWN.
 MAX. CROSS SLOPE AT
 SUPERELEVATED SECTIONS:
 - 0.088 (RIGHT LANE)
 - 0.096 (LEFT LANE)

EAST FRONTAGE ROAD/W 20TH AVENUE (SECTION 87260151)
 STA. 214+41.08 TO STA. 220+88.21 LT,
 STA. 214+41.08 TO STA. 223+61.91 RT

NOT TO SCALE

| FINANCIAL PROJECT ID | SHEET NO. |
|----------------------|-----------|
| 441830-1-52-01 | 24 |

| PROJECT CONTROLS | | TYPICAL SECTION No. 24 | | | | | |
|--|-----------|---|--|----------------------|-----------|----------------|----|
| <u>CONTEXT CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> C1 : NATURAL <input checked="" type="checkbox"/> C3C : SUBURBAN COMM. <input type="checkbox"/> C2 : RURAL <input type="checkbox"/> C4 : URBAN GENERAL <input type="checkbox"/> C2T : RURAL TOWN <input type="checkbox"/> C5 : URBAN CENTER <input type="checkbox"/> C3R : SUBURBAN RES. <input type="checkbox"/> C6 : URBAN CORE <input type="checkbox"/> N/A : L.A. FACILITY | | | | | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> INTERSTATE <input type="checkbox"/> MAJOR COLLECTOR <input type="checkbox"/> FREEWAY/EXPWY. <input type="checkbox"/> MINOR COLLECTOR <input type="checkbox"/> PRINCIPAL ARTERIAL <input checked="" type="checkbox"/> LOCAL <input type="checkbox"/> MINOR ARTERIAL | | | | | | | |
| <u>HIGHWAY SYSTEM</u> | | | | | | | |
| <input type="checkbox"/> NATIONAL HIGHWAY SYSTEM <input type="checkbox"/> STRATEGIC INTERMODAL SYSTEM <input checked="" type="checkbox"/> STATE HIGHWAY SYSTEM <input type="checkbox"/> OFF-STATE HIGHWAY SYSTEM | | | | | | | |
| <u>ACCESS CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> 1 - FREEWAY <input type="checkbox"/> 2 - RESTRICTIVE w/Service Roads <input type="checkbox"/> 3 - RESTRICTIVE w/660 ft. Connection Spacing <input type="checkbox"/> 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing <input type="checkbox"/> 5 - RESTRICTIVE w/440 ft. Connection Spacing <input type="checkbox"/> 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing <input type="checkbox"/> 7 - BOTH MEDIAN TYPES | | | | | | | |
| <u>CRITERIA</u> | | | | | | | |
| <input type="checkbox"/> NEW CONSTRUCTION / RECONSTRUCTION <input type="checkbox"/> RESURFACING (LA FACILITIES) <input checked="" type="checkbox"/> RRR (ARTERIALS & COLLECTORS) | | | | | | | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | | | | | | | |
| <u>DESIGN VARIATION</u> 1. LANE WIDTH 2. CROSS SLOPE 3. SHOULDER WIDTH 4. BICYCLE FACILITIES 5. LATERAL OFFSET | | TRAFFIC DATA CURRENT YEAR = 2019 AADT = 2,028 ESTIMATED OPENING YEAR = 2024 AADT = 2,100 ESTIMATED DESIGN YEAR = 2044 AADT = 2,500 K = 10.21% D = 64.5% T = 5.47% (24 HOUR) DESIGN HOUR T = 5.47% DESIGN SPEED = 30 MPH POSTED SPEED = 30 MPH | | | | | |
| | | EAST FRONTAGE ROAD/W 20TH AVENUE (SECTION 87260151) STA. 220+88.21 TO STA. 237+40.00 LT, STA. 223+61.91 TO STA. 237+40.00 RT | | | | | |
| | | <small>* MATCH EXISTING CROSS SLOPE; APPROX. VALUE RANGE SHOWN.</small> | | | | | |
| | | <small>NOT TO SCALE</small> | | | | | |
| | | <table border="1"> <tr> <td>FINANCIAL PROJECT ID</td> <td>SHEET NO.</td> </tr> <tr> <td>441830-1-52-01</td> <td>25</td> </tr> </table> | | FINANCIAL PROJECT ID | SHEET NO. | 441830-1-52-01 | 25 |
| FINANCIAL PROJECT ID | SHEET NO. | | | | | | |
| 441830-1-52-01 | 25 | | | | | | |

| PROJECT CONTROLS | | TYPICAL SECTION No. 25 | | | | | |
|--|-----------|--|--|----------------------|-----------|----------------|----|
| <u>CONTEXT CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> C1 : NATURAL <input checked="" type="checkbox"/> C3C : SUBURBAN COMM. <input type="checkbox"/> C2 : RURAL <input type="checkbox"/> C4 : URBAN GENERAL <input type="checkbox"/> C2T : RURAL TOWN <input type="checkbox"/> C5 : URBAN CENTER <input type="checkbox"/> C3R : SUBURBAN RES. <input type="checkbox"/> C6 : URBAN CORE <input type="checkbox"/> N/A : L.A. FACILITY | | | | | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> INTERSTATE <input type="checkbox"/> MAJOR COLLECTOR <input type="checkbox"/> FREEWAY/EXPWY. <input type="checkbox"/> MINOR COLLECTOR <input type="checkbox"/> PRINCIPAL ARTERIAL <input checked="" type="checkbox"/> LOCAL <input type="checkbox"/> MINOR ARTERIAL | | | | | | | |
| <u>HIGHWAY SYSTEM</u> | | | | | | | |
| <input type="checkbox"/> NATIONAL HIGHWAY SYSTEM <input type="checkbox"/> STRATEGIC INTERMODAL SYSTEM <input checked="" type="checkbox"/> STATE HIGHWAY SYSTEM <input type="checkbox"/> OFF-STATE HIGHWAY SYSTEM | | | | | | | |
| <u>ACCESS CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> 1 - FREEWAY <input type="checkbox"/> 2 - RESTRICTIVE w/Service Roads <input type="checkbox"/> 3 - RESTRICTIVE w/660 ft. Connection Spacing <input type="checkbox"/> 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing <input type="checkbox"/> 5 - RESTRICTIVE w/440 ft. Connection Spacing <input type="checkbox"/> 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing <input type="checkbox"/> 7 - BOTH MEDIAN TYPES | | | | | | | |
| <u>CRITERIA</u> | | | | | | | |
| <input type="checkbox"/> NEW CONSTRUCTION / RECONSTRUCTION <input type="checkbox"/> RESURFACING (LA FACILITIES) <input checked="" type="checkbox"/> RRR (ARTERIALS & COLLECTORS) | | | | | | | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | | | | | | | |
| <u>DESIGN VARIATION</u> 1. LANE WIDTH 2. SHOULDER WIDTH 3. CROSS SLOPE 4. BORDER WIDTH 5. HORIZONTAL CURVE RADIUS, HORIZONTAL CURVE LENGTH AND SUPERELEVATION 6. GUARDRAIL LATERAL OFFSET | | <p>TRAFFIC DATA</p> <p>CURRENT YEAR = 2019 AADT = 3,621 ESTIMATED OPENING YEAR = 2024 AADT = 4,600 ESTIMATED DESIGN YEAR = 2044 AADT = 5,400 K = 8.38% D = 76.4% T = 4.64% (24 HOUR) DESIGN HOUR T = 4.64% DESIGN SPEED = 30 MPH POSTED SPEED = 30 MPH***</p> <p>*** NO EXISTING SPEED LIMIT SIGNS.</p> | | | | | |
| | | <p>WEST FRONTAGE ROAD/NW 77TH AVENUE (SECTION 87260152) STA. 700+00.00 TO STA. 705+66.18 LT, STA. 700+00.00 TO STA. 705+47.86 RT</p> <p>NOT TO SCALE</p> | | | | | |
| | | <p>* MATCH EXISTING CROSS SLOPE; APPROX. VALUE RANGE SHOWN. MAX. CROSS SLOPE AT SUPERELEVATED SECTIONS: - 0.075 (RIGHT LANE) - 0.093 (LEFT LANE)</p> | | | | | |
| | | <table border="1"> <tr> <td>FINANCIAL PROJECT ID</td> <td>SHEET NO.</td> </tr> <tr> <td>441830-1-52-01</td> <td>26</td> </tr> </table> | | FINANCIAL PROJECT ID | SHEET NO. | 441830-1-52-01 | 26 |
| FINANCIAL PROJECT ID | SHEET NO. | | | | | | |
| 441830-1-52-01 | 26 | | | | | | |

| PROJECT CONTROLS | | TYPICAL SECTION No. 26 | | | | | |
|--|-----------|--|--|----------------------|-----------|----------------|----|
| <u>CONTEXT CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> C1 : NATURAL <input checked="" type="checkbox"/> C3C : SUBURBAN COMM. <input type="checkbox"/> C2 : RURAL <input type="checkbox"/> C4 : URBAN GENERAL <input type="checkbox"/> C2T : RURAL TOWN <input type="checkbox"/> C5 : URBAN CENTER <input type="checkbox"/> C3R : SUBURBAN RES. <input type="checkbox"/> C6 : URBAN CORE <input type="checkbox"/> N/A : L.A. FACILITY | | | | | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> INTERSTATE <input type="checkbox"/> MAJOR COLLECTOR <input type="checkbox"/> FREEWAY/EXPWY. <input type="checkbox"/> MINOR COLLECTOR <input type="checkbox"/> PRINCIPAL ARTERIAL <input checked="" type="checkbox"/> LOCAL <input type="checkbox"/> MINOR ARTERIAL | | | | | | | |
| <u>HIGHWAY SYSTEM</u> | | | | | | | |
| <input type="checkbox"/> NATIONAL HIGHWAY SYSTEM <input type="checkbox"/> STRATEGIC INTERMODAL SYSTEM <input checked="" type="checkbox"/> STATE HIGHWAY SYSTEM <input type="checkbox"/> OFF-STATE HIGHWAY SYSTEM | | | | | | | |
| <u>ACCESS CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> 1 - FREEWAY <input type="checkbox"/> 2 - RESTRICTIVE w/Service Roads <input type="checkbox"/> 3 - RESTRICTIVE w/660 ft. Connection Spacing <input type="checkbox"/> 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing <input type="checkbox"/> 5 - RESTRICTIVE w/440 ft. Connection Spacing <input type="checkbox"/> 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing <input type="checkbox"/> 7 - BOTH MEDIAN TYPES | | | | | | | |
| <u>CRITERIA</u> | | <p>WEST FRONTAGE ROAD/NW 77TH AVENUE (SECTION 87260152) STA. 705+66.18 TO STA. 730+58.27 LT, STA. 705+47.86 TO STA. 727+87.77 RT</p> | | | | | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | | | | | | | |
| <u>DESIGN VARIATION</u> 1. LANE WIDTH 2. SHOULDER WIDTH 3. BORDER WIDTH 4. BICYCLE FACILITIES 5. MINIMUM OFFSET TO HAZARD ON TOP OF BARRIER WALL | | <u>TRAFFIC DATA</u> <p>CURRENT YEAR = 2019 AADT = 3,621 ESTIMATED OPENING YEAR = 2024 AADT = 4,600 ESTIMATED DESIGN YEAR = 2044 AADT = 5,400 $K = 8.38\%$ $D = 76.4\%$ $T = 4.64\%$ (24 HOUR) DESIGN HOUR T = 4.64% DESIGN SPEED = 30 MPH POSTED SPEED = 30 MPH***</p> <p>*** NO EXISTING SPEED LIMIT SIGNS.</p> | | | | | |
| | | NOT TO SCALE | | | | | |
| | | <table border="1"> <tr> <td>FINANCIAL PROJECT ID</td> <td>SHEET NO.</td> </tr> <tr> <td>441830-1-52-01</td> <td>27</td> </tr> </table> | | FINANCIAL PROJECT ID | SHEET NO. | 441830-1-52-01 | 27 |
| FINANCIAL PROJECT ID | SHEET NO. | | | | | | |
| 441830-1-52-01 | 27 | | | | | | |

| PROJECT CONTROLS | | TYPICAL SECTION No. 27 | | | | | |
|--|-----------|---|--|----------------------|-----------|----------------|----|
| <u>CONTEXT CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> C1 : NATURAL <input checked="" type="checkbox"/> C3C : SUBURBAN COMM. <input type="checkbox"/> C2 : RURAL <input type="checkbox"/> C4 : URBAN GENERAL <input type="checkbox"/> C2T : RURAL TOWN <input type="checkbox"/> C5 : URBAN CENTER <input type="checkbox"/> C3R : SUBURBAN RES. <input type="checkbox"/> C6 : URBAN CORE <input type="checkbox"/> N/A : L.A. FACILITY | | | | | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> INTERSTATE <input type="checkbox"/> MAJOR COLLECTOR <input type="checkbox"/> FREEWAY/EXPWY. <input type="checkbox"/> MINOR COLLECTOR <input type="checkbox"/> PRINCIPAL ARTERIAL <input checked="" type="checkbox"/> LOCAL <input type="checkbox"/> MINOR ARTERIAL | | | | | | | |
| <u>HIGHWAY SYSTEM</u> | | | | | | | |
| <input type="checkbox"/> NATIONAL HIGHWAY SYSTEM <input type="checkbox"/> STRATEGIC INTERMODAL SYSTEM <input checked="" type="checkbox"/> STATE HIGHWAY SYSTEM <input type="checkbox"/> OFF-STATE HIGHWAY SYSTEM | | | | | | | |
| <u>ACCESS CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> 1 - FREEWAY <input type="checkbox"/> 2 - RESTRICTIVE w/Service Roads <input type="checkbox"/> 3 - RESTRICTIVE w/660 ft. Connection Spacing <input type="checkbox"/> 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing <input type="checkbox"/> 5 - RESTRICTIVE w/440 ft. Connection Spacing <input type="checkbox"/> 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing <input type="checkbox"/> 7 - BOTH MEDIAN TYPES | | | | | | | |
| <u>CRITERIA</u> | | | | | | | |
| <input type="checkbox"/> NEW CONSTRUCTION / RECONSTRUCTION <input type="checkbox"/> RESURFACING (LA FACILITIES) <input checked="" type="checkbox"/> RRR (ARTERIALS & COLLECTORS) | | | | | | | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | | | | | | | |
| <u>DESIGN VARIATION</u> 1. CROSS SLOPE 2. SHOULDER WIDTH 3. BORDER WIDTH 4. BICYCLE FACILITIES | | | | | | | |
| <u>TRAFFIC DATA</u> CURRENT YEAR = 2019 AADT = 3,621 ESTIMATED OPENING YEAR = 2024 AADT = 4,600 ESTIMATED DESIGN YEAR = 2044 AADT = 5,400 K = 8.38% D = 76.4% T = 4.64% (24 HOUR) DESIGN HOUR T = 4.64% DESIGN SPEED = 40 MPH POSTED SPEED = 30 MPH*** *** NO EXISTING SPEED LIMIT SIGNS. | | <p>WEST FRONTAGE ROAD/NW 77TH AVENUE (SECTION 87260152) STA. 727+87.77 TO STA. 737+12.00 RT, STA. 730+58.27 TO STA. 737+12.00 LT</p> <p>NOT TO SCALE</p> <table border="1"> <tr> <td>FINANCIAL PROJECT ID</td> <td>SHEET NO.</td> </tr> <tr> <td>441830-1-52-01</td> <td>28</td> </tr> </table> | | FINANCIAL PROJECT ID | SHEET NO. | 441830-1-52-01 | 28 |
| FINANCIAL PROJECT ID | SHEET NO. | | | | | | |
| 441830-1-52-01 | 28 | | | | | | |

PROJECT CONTROLS

TYPICAL SECTION No. 28

CONTEXT CLASSIFICATION

- () C1 : NATURAL (X) C3C : SUBURBAN COMM.
- () C2 : RURAL () C4 : URBAN GENERAL
- () C2T : RURAL TOWN () C5 : URBAN CENTER
- () C3R : SUBURBAN RES. () C6 : URBAN CORE
- () N/A : L.A. FACILITY

FUNCTIONAL CLASSIFICATION

- () INTERSTATE () MAJOR COLLECTOR
- () FREEWAY/EXPWY. () MINOR COLLECTOR
- () PRINCIPAL ARTERIAL (X) LOCAL
- () MINOR ARTERIAL

HIGHWAY SYSTEM

- () NATIONAL HIGHWAY SYSTEM
- () STRATEGIC INTERMODAL SYSTEM
- (X) STATE HIGHWAY SYSTEM
- () OFF-STATE HIGHWAY SYSTEM

ACCESS CLASSIFICATION

- () 1 - FREEWAY
- () 2 - RESTRICTIVE w/Service Roads
- () 3 - RESTRICTIVE w/660 ft. Connection Spacing
- () 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing
- () 5 - RESTRICTIVE w/440 ft. Connection Spacing
- () 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing
- () 7 - BOTH MEDIAN TYPES


CRITERIA

- () NEW CONSTRUCTION / RECONSTRUCTION
- () RESURFACING (LA FACILITIES)
- (X) RRR (ARTERIALS & COLLECTORS)

POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:

DESIGN VARIATION

1. CROSS SLOPE
2. BORDER WIDTH
3. BICYCLE FACILITIES



EAST FRONTAGE ROAD/W 20TH AVENUE EAST (SECTION 87260298)
 STA 300+65.28 TO STA. 308+00.00 LT,
 STA 300+65.28 TO STA. 310+26.79 RT

* MATCH EXISTING CROSS SLOPE;
 APPROX. VALUE RANGE SHOWN.

TRAFFIC DATA

CURRENT YEAR = 2019 AADT = 13,422
 ESTIMATED OPENING YEAR = 2024 AADT = 14,000
 ESTIMATED DESIGN YEAR = 2044 AADT = 16,600
 K = 7.61% D = 71.2% T = 1.30% (24 HOUR)
 DESIGN HOUR T = 1.30%
 DESIGN SPEED = 30 MPH
 POSTED SPEED = 30 MPH

NOT TO SCALE

| FINANCIAL PROJECT ID | SHEET NO. |
|----------------------|-----------|
| 441831-1-52-01 | 29 |

PROJECT CONTROLS

TYPICAL SECTION No. 29

CONTEXT CLASSIFICATION

- () C1 : NATURAL (X) C3C : SUBURBAN COMM.
- () C2 : RURAL () C4 : URBAN GENERAL
- () C2T : RURAL TOWN () C5 : URBAN CENTER
- () C3R : SUBURBAN RES. () C6 : URBAN CORE
- () N/A : L.A. FACILITY

FUNCTIONAL CLASSIFICATION

- () INTERSTATE () MAJOR COLLECTOR
- () FREEWAY/EXPWY. () MINOR COLLECTOR
- () PRINCIPAL ARTERIAL (X) LOCAL
- () MINOR ARTERIAL

HIGHWAY SYSTEM

- () NATIONAL HIGHWAY SYSTEM
- () STRATEGIC INTERMODAL SYSTEM
- (X) STATE HIGHWAY SYSTEM
- () OFF-STATE HIGHWAY SYSTEM

ACCESS CLASSIFICATION

- () 1 - FREEWAY
- () 2 - RESTRICTIVE w/Service Roads
- () 3 - RESTRICTIVE w/660 ft. Connection Spacing
- () 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing
- () 5 - RESTRICTIVE w/440 ft. Connection Spacing
- () 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing
- () 7 - BOTH MEDIAN TYPES

CRITERIA

- () NEW CONSTRUCTION / RECONSTRUCTION
- () RESURFACING (LA FACILITIES)
- (X) RRR (ARTERIALS & COLLECTORS)

POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:

DESIGN VARIATION

1. LANE WIDTH
2. CROSS SLOPE
3. SHOULDER WIDTH
4. BORDER WIDTH
5. HORIZONTAL CURVE RADIUS, HORIZONTAL CURVE LENGTH AND SUPERELEVATION
6. BICYCLE FACILITIES
7. LATERAL OFFSET
8. GUARDRAIL LATERAL OFFSET
9. SIDEWALK WIDTH

TRAFFIC DATA

CURRENT YEAR = 2019 AADT = 13,422
 ESTIMATED OPENING YEAR = 2024 AADT = 14,000
 ESTIMATED DESIGN YEAR = 2044 AADT = 16,600
 K = 7.61% D = 71.2% T = 1.30% (24 HOUR)
 DESIGN HOUR T = 1.30%
 DESIGN SPEED = 30 MPH
 POSTED SPEED = 30 MPH

***DETAIL G STA. 351+18.17 TO STA. 352+45.76 LT

REFER TO DETAIL G***

12' LANE

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

0.06

1.6

| PROJECT CONTROLS | | TYPICAL SECTION No. 30 | | | | | |
|--|-----------|--|--|----------------------|-----------|----------------|----|
| <u>CONTEXT CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> C1 : NATURAL <input checked="" type="checkbox"/> C3C : SUBURBAN COMM. <input type="checkbox"/> C2 : RURAL <input type="checkbox"/> C4 : URBAN GENERAL <input type="checkbox"/> C2T : RURAL TOWN <input type="checkbox"/> C5 : URBAN CENTER <input type="checkbox"/> C3R : SUBURBAN RES. <input type="checkbox"/> C6 : URBAN CORE <input type="checkbox"/> N/A : L.A. FACILITY | | | | | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> INTERSTATE <input type="checkbox"/> MAJOR COLLECTOR <input type="checkbox"/> FREEWAY/EXPWY. <input type="checkbox"/> MINOR COLLECTOR <input type="checkbox"/> PRINCIPAL ARTERIAL <input checked="" type="checkbox"/> LOCAL <input type="checkbox"/> MINOR ARTERIAL | | | | | | | |
| <u>HIGHWAY SYSTEM</u> | | | | | | | |
| <input type="checkbox"/> NATIONAL HIGHWAY SYSTEM <input type="checkbox"/> STRATEGIC INTERMODAL SYSTEM <input checked="" type="checkbox"/> STATE HIGHWAY SYSTEM <input type="checkbox"/> OFF-STATE HIGHWAY SYSTEM | | | | | | | |
| <u>ACCESS CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> 1 - FREEWAY <input type="checkbox"/> 2 - RESTRICTIVE w/Service Roads <input type="checkbox"/> 3 - RESTRICTIVE w/660 ft. Connection Spacing <input type="checkbox"/> 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing <input type="checkbox"/> 5 - RESTRICTIVE w/440 ft. Connection Spacing <input type="checkbox"/> 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing <input type="checkbox"/> 7 - BOTH MEDIAN TYPES | | | | | | | |
| <u>CRITERIA</u> | | | | | | | |
| <input type="checkbox"/> NEW CONSTRUCTION / RECONSTRUCTION <input type="checkbox"/> RESURFACING (LA FACILITIES) <input checked="" type="checkbox"/> RRR (ARTERIALS & COLLECTORS) | | | | | | | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | | | | | | | |
| <u>DESIGN VARIATION</u> 1. CROSS SLOPE 2. BICYCLE FACILITIES | | <p>TRAFFIC DATA</p> <p>CURRENT YEAR = 2019 AADT = 13,422 ESTIMATED OPENING YEAR = 2024 AADT = 14,000 ESTIMATED DESIGN YEAR = 2044 AADT = 16,600 $K = 7.61\%$ $D = 71.2\%$ $T = 1.30\%$ (24 HOUR) DESIGN HOUR T = 1.30% DESIGN SPEED = 30 MPH POSTED SPEED = 30 MPH</p> | | | | | |
| | | <p>EAST FRONTAGE ROAD/W 20TH AVENUE EAST (SECTION 87260298) STA. 336+06.51 TO STA. 339+47.22</p> <p>NOT TO SCALE</p> | | | | | |
| | | <table border="1"> <tr> <td>FINANCIAL PROJECT ID</td> <td>SHEET NO.</td> </tr> <tr> <td>441831-1-52-01</td> <td>31</td> </tr> </table> | | FINANCIAL PROJECT ID | SHEET NO. | 441831-1-52-01 | 31 |
| FINANCIAL PROJECT ID | SHEET NO. | | | | | | |
| 441831-1-52-01 | 31 | | | | | | |

| PROJECT CONTROLS | | TYPICAL SECTION No. 31 | | | | | |
|--|-----------|--|--|----------------------|-----------|----------------|----|
| <u>CONTEXT CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> C1 : NATURAL <input checked="" type="checkbox"/> C3C : SUBURBAN COMM. <input type="checkbox"/> C2 : RURAL <input type="checkbox"/> C4 : URBAN GENERAL <input type="checkbox"/> C2T : RURAL TOWN <input type="checkbox"/> C5 : URBAN CENTER <input type="checkbox"/> C3R : SUBURBAN RES. <input type="checkbox"/> C6 : URBAN CORE <input type="checkbox"/> N/A : L.A. FACILITY | | | | | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> INTERSTATE <input type="checkbox"/> MAJOR COLLECTOR <input type="checkbox"/> FREEWAY/EXPWY. <input type="checkbox"/> MINOR COLLECTOR <input type="checkbox"/> PRINCIPAL ARTERIAL <input checked="" type="checkbox"/> LOCAL <input type="checkbox"/> MINOR ARTERIAL | | | | | | | |
| <u>HIGHWAY SYSTEM</u> | | | | | | | |
| <input type="checkbox"/> NATIONAL HIGHWAY SYSTEM <input type="checkbox"/> STRATEGIC INTERMODAL SYSTEM <input checked="" type="checkbox"/> STATE HIGHWAY SYSTEM <input type="checkbox"/> OFF-STATE HIGHWAY SYSTEM | | | | | | | |
| <u>ACCESS CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> 1 - FREEWAY <input type="checkbox"/> 2 - RESTRICTIVE w/Service Roads <input type="checkbox"/> 3 - RESTRICTIVE w/660 ft. Connection Spacing <input type="checkbox"/> 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing <input type="checkbox"/> 5 - RESTRICTIVE w/440 ft. Connection Spacing <input type="checkbox"/> 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing <input type="checkbox"/> 7 - BOTH MEDIAN TYPES | | | | | | | |
| <u>CRITERIA</u> | | | | | | | |
| <input type="checkbox"/> NEW CONSTRUCTION / RECONSTRUCTION <input type="checkbox"/> RESURFACING (LA FACILITIES) <input checked="" type="checkbox"/> RRR (ARTERIALS & COLLECTORS) | | | | | | | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | | | | | | | |
| <u>DESIGN VARIATION</u> | | | | | | | |
| 1. LANE WIDTH 2. CROSS SLOPE 3. HORIZONTAL CURVE RADIUS, HORIZONTAL CURVE LENGTH AND SUPERELEVATION 4. BICYCLE FACILITIES | | | | | | | |
| <u>TRAFFIC DATA</u> | | | | | | | |
| CURRENT YEAR = 2019 AADT = 13,422 ESTIMATED OPENING YEAR = 2024 AADT = 14,000 ESTIMATED DESIGN YEAR = 2044 AADT = 16,600 K = 7.61% D = 71.2% T = 1.30% (24 HOUR) DESIGN HOUR T = 1.30% DESIGN SPEED = 30 MPH POSTED SPEED = 30 MPH*** *** NO EXISTING SPEED LIMIT SIGNS. ADVISORY SPEED 20 MPH. | | EAST FRONTAGE ROAD/W 67TH PLACE (SECTION 87260298) STA. 363+26.20 TO STA. 373+34.04 | | | | | |
| | | * MATCH EXISTING CROSS SLOPE; APPROX. VALUE RANGE SHOWN. | | | | | |
| | | NOT TO SCALE | | | | | |
| | | <table border="1"> <tr> <td>FINANCIAL PROJECT ID</td> <td>SHEET NO.</td> </tr> <tr> <td>441831-1-52-01</td> <td>32</td> </tr> </table> | | FINANCIAL PROJECT ID | SHEET NO. | 441831-1-52-01 | 32 |
| FINANCIAL PROJECT ID | SHEET NO. | | | | | | |
| 441831-1-52-01 | 32 | | | | | | |

| PROJECT CONTROLS | | TYPICAL SECTION No. 32 | | | | | |
|--|-----------|--|--|----------------------|-----------|----------------|----|
| <u>CONTEXT CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> C1 : NATURAL <input checked="" type="checkbox"/> C3C : SUBURBAN COMM. <input type="checkbox"/> C2 : RURAL <input type="checkbox"/> C4 : URBAN GENERAL <input type="checkbox"/> C2T : RURAL TOWN <input type="checkbox"/> C5 : URBAN CENTER <input type="checkbox"/> C3R : SUBURBAN RES. <input type="checkbox"/> C6 : URBAN CORE <input type="checkbox"/> N/A : L.A. FACILITY | | | | | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> INTERSTATE <input type="checkbox"/> MAJOR COLLECTOR <input type="checkbox"/> FREEWAY/EXPWY. <input type="checkbox"/> MINOR COLLECTOR <input type="checkbox"/> PRINCIPAL ARTERIAL <input checked="" type="checkbox"/> LOCAL <input type="checkbox"/> MINOR ARTERIAL | | | | | | | |
| <u>HIGHWAY SYSTEM</u> | | | | | | | |
| <input type="checkbox"/> NATIONAL HIGHWAY SYSTEM <input type="checkbox"/> STRATEGIC INTERMODAL SYSTEM <input checked="" type="checkbox"/> STATE HIGHWAY SYSTEM <input type="checkbox"/> OFF-STATE HIGHWAY SYSTEM | | | | | | | |
| <u>ACCESS CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> 1 - FREEWAY <input type="checkbox"/> 2 - RESTRICTIVE w/Service Roads <input type="checkbox"/> 3 - RESTRICTIVE w/660 ft. Connection Spacing <input type="checkbox"/> 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing <input type="checkbox"/> 5 - RESTRICTIVE w/440 ft. Connection Spacing <input type="checkbox"/> 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing <input type="checkbox"/> 7 - BOTH MEDIAN TYPES | | | | | | | |
| <u>CRITERIA</u> | | | | | | | |
| <input type="checkbox"/> NEW CONSTRUCTION / RECONSTRUCTION <input type="checkbox"/> RESURFACING (LA FACILITIES) <input checked="" type="checkbox"/> RRR (ARTERIALS & COLLECTORS) | | | | | | | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | | | | | | | |
| <u>DESIGN VARIATION</u> 1. SHOULDER WIDTH 2. BICYCLE FACILITIES 3. BRIDGE WIDTH | | <p style="text-align: center;">TRAFFIC DATA</p> <p>CURRENT YEAR = 2019 AADT = 13,422 ESTIMATED OPENING YEAR = 2024 AADT = 14,000 ESTIMATED DESIGN YEAR = 2044 AADT = 16,600 K = 7.61% D = 71.2% T = 1.30% (24 HOUR) DESIGN HOUR T = 1.30% DESIGN SPEED = 30 MPH POSTED SPEED = 30 MPH</p> | | | | | |
| | | <p style="text-align: center;">EAST FRONTAGE ROAD/W 20TH AVENUE EAST (SECTION 87260298) BRIDGE NO. 870570 OVER LITTLE RIVER CANAL (C-7) STA. 310+26.79 TO STA. 311+36.42</p> <p style="text-align: right;">NOT TO SCALE</p> | | | | | |
| | | <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 80%;">FINANCIAL PROJECT ID</td> <td style="width: 20%;">SHEET NO.</td> </tr> <tr> <td>441831-1-52-01</td> <td>33</td> </tr> </table> | | FINANCIAL PROJECT ID | SHEET NO. | 441831-1-52-01 | 33 |
| FINANCIAL PROJECT ID | SHEET NO. | | | | | | |
| 441831-1-52-01 | 33 | | | | | | |

PROJECT CONTROLS

TYPICAL SECTION No. 33

CONTEXT CLASSIFICATION

- C1 : NATURAL C3C : SUBURBAN COMM.
- C2 : RURAL C4 : URBAN GENERAL
- C2T : RURAL TOWN C5 : URBAN CENTER
- C3R : SUBURBAN RES. C6 : URBAN CORE
- N/A : L.A. FACILITY

FUNCTIONAL CLASSIFICATION

- INTERSTATE MAJOR COLLECTOR
- FREEWAY/EXPWY. MINOR COLLECTOR
- PRINCIPAL ARTERIAL LOCAL
- MINOR ARTERIAL

HIGHWAY SYSTEM

- NATIONAL HIGHWAY SYSTEM
- STRATEGIC INTERMODAL SYSTEM
- STATE HIGHWAY SYSTEM
- OFF-STATE HIGHWAY SYSTEM

ACCESS CLASSIFICATION

- 1 - FREEWAY
- 2 - RESTRICTIVE w/Service Roads
- 3 - RESTRICTIVE w/660 ft. Connection Spacing
- 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing
- 5 - RESTRICTIVE w/440 ft. Connection Spacing
- 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing
- 7 - BOTH MEDIAN TYPES


CRITERIA

- NEW CONSTRUCTION / RECONSTRUCTION
- RESURFACING (LA FACILITIES)
- RRR (ARTERIALS & COLLECTORS)

POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:

DESIGN VARIATION

1. CROSS SLOPE
2. HORIZONTAL CURVE RADIUS,
HORIZONTAL CURVE LENGTH AND SUPERELEVATION
3. BICYCLE FACILITIES



WEST FRONTAGE ROAD/NW 77TH COURT (SECTION 87260506)

STA. 400+91.32 TO STA. 411+81.83 LT,
STA. 400+91.32 TO STA. 409+55.73 RT

TRAFFIC DATA

CURRENT YEAR = 2019 AADT = 9,322
ESTIMATED OPENING YEAR = 2024 AADT = 10,100
ESTIMATED DESIGN YEAR = 2044 AADT = 13,800
K = 8.30% D = 61.6% T = 2.54% (24 HOUR)
DESIGN HOUR T = 2.54%
DESIGN SPEED = 30 MPH
POSTED SPEED = 20 MPH

NOT TO SCALE

| FINANCIAL PROJECT ID | SHEET NO. |
|----------------------|-----------|
| 441831-1-52-01 | 34 |

| PROJECT CONTROLS | | TYPICAL SECTION No. 34 | | | | | |
|--|-----------|--|--|----------------------|-----------|----------------|----|
| <u>CONTEXT CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> C1 : NATURAL <input checked="" type="checkbox"/> C3C : SUBURBAN COMM. <input type="checkbox"/> C2 : RURAL <input type="checkbox"/> C4 : URBAN GENERAL <input type="checkbox"/> C2T : RURAL TOWN <input type="checkbox"/> C5 : URBAN CENTER <input type="checkbox"/> C3R : SUBURBAN RES. <input type="checkbox"/> C6 : URBAN CORE <input type="checkbox"/> N/A : L.A. FACILITY | | | | | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> INTERSTATE <input type="checkbox"/> MAJOR COLLECTOR <input type="checkbox"/> FREEWAY/EXPWY. <input type="checkbox"/> MINOR COLLECTOR <input type="checkbox"/> PRINCIPAL ARTERIAL <input checked="" type="checkbox"/> LOCAL <input type="checkbox"/> MINOR ARTERIAL | | | | | | | |
| <u>HIGHWAY SYSTEM</u> | | | | | | | |
| <input type="checkbox"/> NATIONAL HIGHWAY SYSTEM <input type="checkbox"/> STRATEGIC INTERMODAL SYSTEM <input checked="" type="checkbox"/> STATE HIGHWAY SYSTEM <input type="checkbox"/> OFF-STATE HIGHWAY SYSTEM | | | | | | | |
| <u>ACCESS CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> 1 - FREEWAY <input type="checkbox"/> 2 - RESTRICTIVE w/Service Roads <input type="checkbox"/> 3 - RESTRICTIVE w/660 ft. Connection Spacing <input type="checkbox"/> 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing <input type="checkbox"/> 5 - RESTRICTIVE w/440 ft. Connection Spacing <input type="checkbox"/> 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing <input type="checkbox"/> 7 - BOTH MEDIAN TYPES | | | | | | | |
| <u>CRITERIA</u> | | | | | | | |
| <input type="checkbox"/> NEW CONSTRUCTION / RECONSTRUCTION <input type="checkbox"/> RESURFACING (LA FACILITIES) <input checked="" type="checkbox"/> RRR (ARTERIALS & COLLECTORS) | | | | | | | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | | | | | | | |
| <u>DESIGN VARIATION</u> 1. LANE WIDTH 2. CROSS SLOPE 3. SHOULDER WIDTH 4. BORDER WIDTH 5. HORIZONTAL CURVE RADIUS, HORIZONTAL CURVE LENGTH AND SUPERELEVATION 6. BICYCLE FACILITIES 7. GUARDRAIL LATERAL OFFSET | | <u>TRAFFIC DATA</u> CURRENT YEAR = 2019 AADT = 9,322 ESTIMATED OPENING YEAR = 2024 AADT = 10,100 ESTIMATED DESIGN YEAR = 2044 AADT = 13,800 K = 8.30% D = 61.6% T = 2.54% (24 HOUR) DESIGN HOUR T = 2.54% DESIGN SPEED = 35 MPH POSTED SPEED = 35 MPH | | | | | |
| | | NOT TO SCALE | | | | | |
| | | <table border="1"> <tr> <td>FINANCIAL PROJECT ID</td><td>SHEET NO.</td></tr> <tr> <td>441831-1-52-01</td><td>35</td></tr> </table> | | FINANCIAL PROJECT ID | SHEET NO. | 441831-1-52-01 | 35 |
| FINANCIAL PROJECT ID | SHEET NO. | | | | | | |
| 441831-1-52-01 | 35 | | | | | | |

| PROJECT CONTROLS | | TYPICAL SECTION No. 35 | | | | | |
|--|-----------|--|--|----------------------|-----------|----------------|----|
| <u>CONTEXT CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> C1 : NATURAL <input checked="" type="checkbox"/> C3C : SUBURBAN COMM. <input type="checkbox"/> C2 : RURAL <input type="checkbox"/> C4 : URBAN GENERAL <input type="checkbox"/> C2T : RURAL TOWN <input type="checkbox"/> C5 : URBAN CENTER <input type="checkbox"/> C3R : SUBURBAN RES. <input type="checkbox"/> C6 : URBAN CORE <input type="checkbox"/> N/A : L.A. FACILITY | | | | | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> INTERSTATE <input type="checkbox"/> MAJOR COLLECTOR <input type="checkbox"/> FREEWAY/EXPWY. <input type="checkbox"/> MINOR COLLECTOR <input type="checkbox"/> PRINCIPAL ARTERIAL <input checked="" type="checkbox"/> LOCAL <input type="checkbox"/> MINOR ARTERIAL | | | | | | | |
| <u>HIGHWAY SYSTEM</u> | | | | | | | |
| <input type="checkbox"/> NATIONAL HIGHWAY SYSTEM <input type="checkbox"/> STRATEGIC INTERMODAL SYSTEM <input checked="" type="checkbox"/> STATE HIGHWAY SYSTEM <input type="checkbox"/> OFF-STATE HIGHWAY SYSTEM | | | | | | | |
| <u>ACCESS CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> 1 - FREEWAY <input type="checkbox"/> 2 - RESTRICTIVE w/Service Roads <input type="checkbox"/> 3 - RESTRICTIVE w/660 ft. Connection Spacing <input type="checkbox"/> 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing <input type="checkbox"/> 5 - RESTRICTIVE w/440 ft. Connection Spacing <input type="checkbox"/> 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing <input type="checkbox"/> 7 - BOTH MEDIAN TYPES | | | | | | | |
| <u>CRITERIA</u> | | | | | | | |
| <input type="checkbox"/> NEW CONSTRUCTION / RECONSTRUCTION <input type="checkbox"/> RESURFACING (LA FACILITIES) <input checked="" type="checkbox"/> RRR (ARTERIALS & COLLECTORS) | | | | | | | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | | | | | | | |
| <u>DESIGN VARIATION</u> 1. CROSS SLOPE 2. SHOULDER WIDTH 3. BORDER WIDTH 4. BICYCLE FACILITIES 5. LATERAL OFFSET | | <p style="text-align: center;">WEST FRONTAGE ROAD/W 20TH AVENUE WEST (SECTION 87260521) STA. 436+30.54 TO STA. 442+32.45</p> <p style="text-align: right;">* MATCH EXISTING CROSS SLOPE; APPROX. VALUE RANGE SHOWN.</p> <p style="text-align: right;">NOT TO SCALE</p> <p>TRAFFIC DATA</p> <p>CURRENT YEAR = 2019 AADT = 9,322 ESTIMATED OPENING YEAR = 2024 AADT = 10,100 ESTIMATED DESIGN YEAR = 2044 AADT = 13,800 K = 8.30% D = 61.6% T = 2.54% (24 HOUR) DESIGN HOUR T = 2.54% DESIGN SPEED = 35 MPH POSTED SPEED = 35 MPH</p> | | | | | |
| | | <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 80%;">FINANCIAL PROJECT ID</td> <td style="width: 20%;">SHEET NO.</td> </tr> <tr> <td>441831-1-52-01</td> <td>36</td> </tr> </table> | | FINANCIAL PROJECT ID | SHEET NO. | 441831-1-52-01 | 36 |
| FINANCIAL PROJECT ID | SHEET NO. | | | | | | |
| 441831-1-52-01 | 36 | | | | | | |

| PROJECT CONTROLS | | TYPICAL SECTION No. 36 | | | | | |
|--|-----------|---|--|----------------------|-----------|----------------|----|
| <u>CONTEXT CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> C1 : NATURAL <input checked="" type="checkbox"/> C3C : SUBURBAN COMM. <input type="checkbox"/> C2 : RURAL <input type="checkbox"/> C4 : URBAN GENERAL <input type="checkbox"/> C2T : RURAL TOWN <input type="checkbox"/> C5 : URBAN CENTER <input type="checkbox"/> C3R : SUBURBAN RES. <input type="checkbox"/> C6 : URBAN CORE <input type="checkbox"/> N/A : L.A. FACILITY | | | | | | | |
| <u>FUNCTIONAL CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> INTERSTATE <input type="checkbox"/> MAJOR COLLECTOR <input type="checkbox"/> FREEWAY/EXPWY. <input type="checkbox"/> MINOR COLLECTOR <input type="checkbox"/> PRINCIPAL ARTERIAL <input checked="" type="checkbox"/> LOCAL <input type="checkbox"/> MINOR ARTERIAL | | | | | | | |
| <u>HIGHWAY SYSTEM</u> | | | | | | | |
| <input type="checkbox"/> NATIONAL HIGHWAY SYSTEM <input type="checkbox"/> STRATEGIC INTERMODAL SYSTEM <input checked="" type="checkbox"/> STATE HIGHWAY SYSTEM <input type="checkbox"/> OFF-STATE HIGHWAY SYSTEM | | | | | | | |
| <u>ACCESS CLASSIFICATION</u> | | | | | | | |
| <input type="checkbox"/> 1 - FREEWAY <input type="checkbox"/> 2 - RESTRICTIVE w/Service Roads <input type="checkbox"/> 3 - RESTRICTIVE w/660 ft. Connection Spacing <input type="checkbox"/> 4 - NON-RESTRICTIVE w/2640 ft. Signal Spacing <input type="checkbox"/> 5 - RESTRICTIVE w/440 ft. Connection Spacing <input type="checkbox"/> 6 - NON-RESTRICTIVE w/1320 ft. Signal Spacing <input type="checkbox"/> 7 - BOTH MEDIAN TYPES | | | | | | | |
| <u>CRITERIA</u> | | | | | | | |
| <input type="checkbox"/> NEW CONSTRUCTION / RECONSTRUCTION <input type="checkbox"/> RESURFACING (LA FACILITIES) <input checked="" type="checkbox"/> RRR (ARTERIALS & COLLECTORS) | | | | | | | |
| <u>POTENTIAL EXCEPTIONS AND VARIATIONS RELATED TO TYPICAL SECTION:</u> | | | | | | | |
| <u>DESIGN VARIATION</u> 1. LANE WIDTH 2. CROSS SLOPE 3. SHOULDER WIDTH 4. BICYCLE FACILITIES 5. BRIDGE WIDTH 6. SIDEWALK WIDTH | | <p>WEST FRONTAGE ROAD/W 20TH AVENUE WEST (SECTION 87260521) BRIDGE NO. 870569 OVER LITTLE RIVER CANAL (C-7) STA. 411+81.83 TO STA. 412+71.84</p> <p>* MATCH EXISTING CROSS SLOPE; APPROX. VALUE RANGE SHOWN.</p> | | | | | |
| <u>TRAFFIC DATA</u> CURRENT YEAR = 2019 AADT = 9,322 ESTIMATED OPENING YEAR = 2024 AADT = 10,100 ESTIMATED DESIGN YEAR = 2044 AADT = 13,800 K = 8.30% D = 61.6% T = 2.54% (24 HOUR) DESIGN HOUR T = 2.54% DESIGN SPEED = 35 MPH POSTED SPEED = 35 MPH | | <p>NOT TO SCALE</p> <table border="1"> <tr> <td>FINANCIAL PROJECT ID</td> <td>SHEET NO.</td> </tr> <tr> <td>441831-1-52-01</td> <td>37</td> </tr> </table> | | FINANCIAL PROJECT ID | SHEET NO. | 441831-1-52-01 | 37 |
| FINANCIAL PROJECT ID | SHEET NO. | | | | | | |
| 441831-1-52-01 | 37 | | | | | | |

Appendix C

Cost Estimates

FM 447165-1 - SR 826 Express Lanes Modifications

| | | | | | |
|---|---|------------------------------|----|-----------|----------------------|
| 0100 - Structures | | Structures Sub-total: | | | \$ 5,473,962 |
| 0101 - Structures, Bridge 870856 (Ramp D Flyover over SR 826 & NW 103 St) | | Bridge 870856 Sub-total: | | | \$ 2,667,373 |
| 0102 - Structures, Bridge 870964 (SR 826 over SR 934/NW 74th Street) | | Bridge 870964 Sub-total: | | | \$ 204,092 |
| 0103 - Structures, Bridge 870257 (SR 826 over Metrorail) | | Bridge 870257 Sub-total: | | | \$ 663,379 |
| 0104 - Structures, Bridge 870258 (SR 826 over FEC RR) | | Bridge 870258 Sub-total: | | | \$ 573,001 |
| 0105 - Structures, Bridge 870757 (SR 826 SB over SR 932/NW 103rd Street) | | Bridge 870757 Sub-total: | | | \$ 607,034 |
| 0106 - Structures, Bridge 870995 (SR 826 NB over SR 932/NW 103rd Street) | | Bridge 870995 Sub-total: | | | \$ 759,082 |
| 0200 - Roadway | | Roadway Sub-total: | | | \$ 17,177,973 |
| 0300 - Signing and Pavement Markings | | Signing Sub-total: | | | \$ 1,969,454 |
| 0400 - Lighting | | Lighting Sub-total: | | | \$ 524,529 |
| 0500 - Signalization | | Signal Sub-total: | | | \$ 246,746 |
| 0550 - Intelligent Transportation System | | ITS Sub-total: | | | \$ 3,585,662 |
| | | Sub-total | | | \$ 28,978,326 |
| 999-16 | PARTNERING, DO NOT BID | 1 | LS | \$ 30,000 | \$ 30,000 |
| 999-20-1 | DISPUTES REVIEW BOARD, MEETING- DO NOT BID | 24 | DA | \$ 3,500 | \$ 84,000 |
| 999-20-2 | DISPUTES REVIEW BOARD, HEARING- DO NOT BID | 2 | EA | \$ 4,000 | \$ 8,000 |
| 999-25 | INITIAL CONTINGENCY AMOUNT, DO NOT BID | 1 | LS | | \$ 150,000 |
| 0-30-1 | DESIGN COST FOR DESIGN BUILD PROJECTS: ESTIMATES USE ONLY (44716515201DB) | 1 | LS | 10% | \$ 2,925,033 |
| FM 447165-1 | | Grand Total | | | \$ 32,175,359 |

FM 447165-1 - SR 826 Express Lanes Modifications, Phase 2 (Ultimate)

| Pay Item | Description | Quantity | Unit | Unit Price | Total |
|--|---|----------|------|---------------------------------|---------------------|
| 0100 - Structures | | | | | |
| 0101 - Structures, Bridge 870856 (Ramp D Flyover over SR 826 & NW 103 St) | | | | | |
| 101-1 | MOBILIZATION | 1 | LS | \$ 289,940.92 | \$ 289,941 |
| 110-3 | REMOVAL OF EXISTING STRUCTURES/BRIDGES | 6,440 | SF | \$ 120.00 | \$ 772,800 |
| 400-4-4 | CONCRETE CLASS IV, SUPERSTRUCTURE | 43.6 | CY | \$ 1,300.00 | \$ 56,680 |
| 400-4-5 | CONCRETE CLASS IV, BRIDGE SUBSTRUCTURE | 516.3 | CY | \$ 1,000.00 | \$ 516,300 |
| 400-147 | COMPOSITE NEOPRENE PADS | 2.4 | CF | \$ 1,500.00 | \$ 3,600 |
| 415-1-4 | REINFORCING STEEL - BRIDGE SUPERSTRUCTURE | 13,089 | LB | \$ 1.65 | \$ 21,597 |
| 415-1-5 | REINFORCING STEEL- BRIDGE SUBSTRUCTURE | 132,075 | LB | \$ 1.10 | \$ 145,283 |
| 455-35-22 | STEEL PILING, 24" DIA. PIPE | 960 | LF | \$ 145.00 | \$ 139,200 |
| 455-133-3 | SHEET PILING STEEL, F&I PERMANENT | 12,000 | SF | \$ 16.00 | \$ 192,000 |
| 462-2-13 | POST TENSIONING TENDONS, SUBSTRUCTURE STRAND WITH GROUT | 6,525 | LB | \$ 5.00 | \$ 32,625 |
| 521-5-13 | CONCRETE TRAFFIC RAILING- BRIDGE, 36" SINGLE-SLOPE | 621 | LF | \$ 85.00 | \$ 52,785 |
| | | | | Bridge 870856 Sub-total: | \$ 2,667,373 |
| 0102 - Structures, Bridge 870964 (SR 826 over SR 934/NW 74th Street) | | | | | |
| 110-3 | REMOVAL OF EXISTING STRUCTURES/BRIDGES | 551 | SF | \$ 35.00 | \$ 19,285 |
| 400-2-4 | CONC CLASS II, BRIDGE SUPERSTRUCTURE | 29.7 | CY | \$ 750.00 | \$ 22,275 |
| 400-2-10 | CONCRETE CLASS II, APPROACH SLABS | 14.4 | CY | \$ 400.00 | \$ 5,760 |
| 400-4-5 | CONCRETE CLASS IV, BRIDGE SUBSTRUCTURE | 4.4 | CY | \$ 950.00 | \$ 4,180 |
| 400-9-1 | BRIDGE DECK PLANING | 126 | SY | \$ 5.00 | \$ 630 |
| 400-148 | PLAIN NEOPRENE BEARING PADS | 1.1 | CF | \$ 1,000.00 | \$ 1,100 |
| 415-1-4 | REINFORCING STEEL - BRIDGE SUPERSTRUCTURE | 6,079 | LB | \$ 1.05 | \$ 6,383 |
| 415-1-5 | REINFORCING STEEL- BRIDGE SUBSTRUCTURE | 638 | LB | \$ 1.00 | \$ 638 |
| 415-1-9 | REINFORCING STEEL- APPROACH SLABS | 2,889 | LB | \$ 1.05 | \$ 3,033 |
| 455-34-5 | PRESTRESSED CONCRETE PILING, 24" SQ | 200 | LF | \$ 140.00 | \$ 28,000 |
| 458-1-11 | BRIDGE DECK EXPANSION JOINT, NEW CONSTRUCTION, F&I Poured JOINT WITH BACKER ROD | 13 | LF | \$ 45.00 | \$ 585 |
| 460-2-2 | STRUCT STEEL, LOW ALLOY | 35,798 | LB | \$ 1.65 | \$ 59,067 |
| 521-5-13 | CONCRETE TRAFFIC RAILING- BRIDGE, 36" SINGLE-SLOPE | 174 | LF | \$ 110.00 | \$ 19,140 |
| | | | | Bridge 870964 Sub-total: | \$ 204,092 |
| 0103 - Structures, Bridge 870257 (SR 826 over Metrorail) | | | | | |
| 110-3 | REMOVAL OF EXISTING STRUCTURES/BRIDGES | 1,166 | SF | \$ 68.95 | \$ 80,398 |
| 400-1-25 | CONC CLASS I, MASS SUBSTRUCTURE | 15.1 | CY | \$ 625.00 | \$ 9,438 |
| 400-2-10 | CONCRETE CLASS II, APPROACH SLABS | 25.7 | CY | \$ 400.00 | \$ 10,280 |
| 400-4-4 | CONCRETE CLASS IV, SUPERSTRUCTURE | 50.3 | CY | \$ 1,200.00 | \$ 60,360 |
| 400-4-5 | CONCRETE CLASS IV, BRIDGE SUBSTRUCTURE | 87.5 | CY | \$ 950.00 | \$ 83,125 |
| 400-148 | PLAIN NEOPRENE BEARING PADS | 4.3 | CF | \$ 1,000.00 | \$ 4,300 |
| 415-1-4 | REINFORCING STEEL - BRIDGE SUPERSTRUCTURE | 9,800 | LB | \$ 1.05 | \$ 10,290 |
| 415-1-5 | REINFORCING STEEL- BRIDGE SUBSTRUCTURE | 6,442 | LB | \$ 1.00 | \$ 6,442 |
| 415-1-9 | REINFORCING STEEL- APPROACH SLABS | 2,574 | LB | \$ 1.05 | \$ 2,703 |
| 450-1-1 | PRESTRESSED BEAMS, TYPE II | 378 | LF | \$ 275.00 | \$ 103,950 |
| 455-14-3 | CONCRETE SHEET PILING, 10"X30" | 195 | LF | \$ 110.00 | \$ 21,450 |
| 455-34-3 | PRESTRESSED CONCRETE PILING, 18" SQ | 402 | LF | \$ 125.00 | \$ 50,250 |
| 455-88-4 | DRILLED SHAFT, 42" DIA | 120 | LF | \$ 550.00 | \$ 66,000 |
| 458-1-11 | BRIDGE DECK EXPANSION JOINT, NEW CONSTRUCTION, F&I Poured JOINT WITH BACKER ROD | 64 | LF | \$ 45.00 | \$ 2,880 |
| 521-5-13 | CONCRETE TRAFFIC RAILING- BRIDGE, 36" SINGLE-SLOPE | 126 | LF | \$ 110.00 | \$ 13,860 |
| 550-10-334 | FENCING, TYPE R, 6.1-7.0', PARTIAL ENCLOSURE | 126 | LF | \$ 215.00 | \$ 27,090 |
| | | | | Bridge 870257 Sub-total: | \$ 663,379 |
| 0104 - Structures, Bridge 870258 (SR 826 over FEC RR) | | | | | |
| 110-3 | REMOVAL OF EXISTING STRUCTURES/BRIDGES | 1,181 | SF | \$ 62.43 | \$ 73,734 |
| 400-1-25 | CONC CLASS I, MASS SUBSTRUCTURE | 44.4 | CY | \$ 625.00 | \$ 27,750 |
| 400-2-10 | CONCRETE CLASS II, APPROACH SLABS | 25.2 | CY | \$ 400.00 | \$ 10,080 |
| 400-4-4 | CONCRETE CLASS IV, SUPERSTRUCTURE | 50.4 | CY | \$ 1,200.00 | \$ 60,480 |
| 400-4-5 | CONCRETE CLASS IV, BRIDGE SUBSTRUCTURE | 54.7 | CY | \$ 950.00 | \$ 51,965 |
| 400-148 | PLAIN NEOPRENE BEARING PADS | 2.8 | CF | \$ 1,000.00 | \$ 2,800 |
| 415-1-4 | REINFORCING STEEL - BRIDGE SUPERSTRUCTURE | 9,999 | LB | \$ 1.05 | \$ 10,499 |
| 415-1-5 | REINFORCING STEEL- BRIDGE SUBSTRUCTURE | 4,006 | LB | \$ 1.00 | \$ 4,006 |
| 415-1-9 | REINFORCING STEEL- APPROACH SLABS | 2,520 | LB | \$ 1.05 | \$ 2,646 |
| 450-1-1 | PRESTRESSED BEAMS, TYPE II | 300 | LF | \$ 275.00 | \$ 82,500 |
| 455-34-3 | PRESTRESSED CONCRETE PILING, 18" SQ | 268 | LF | \$ 125.00 | \$ 33,500 |
| 455-88-4 | DRILLED SHAFT, 42" DIA | 120 | LF | \$ 550.00 | \$ 66,000 |
| 458-1-11 | BRIDGE DECK EXPANSION JOINT, NEW CONSTRUCTION, F&I Poured JOINT WITH BACKER ROD | 62 | LF | \$ 45.00 | \$ 2,790 |
| 521-5-13 | CONCRETE TRAFFIC RAILING- BRIDGE, 36" SINGLE-SLOPE | 150 | LF | \$ 110.00 | \$ 16,500 |
| 550-10-334 | FENCING, TYPE R, 6.1-7.0', PARTIAL ENCLOSURE | 150 | LF | \$ 215.00 | \$ 32,250 |
| | | | | Bridge 870258 Sub-total: | \$ 573,001 |

FM 447165-1 - SR 826 Express Lanes Modifications, Phase 2 (Ultimate)

| Pay Item | Description | Quantity | Unit | Unit Price | Total |
|---|---|----------|------|-------------|--|
| 0105 - Structures, Bridge 870757 (SR 826 SB over SR 932/NW 103rd Street) | | | | | |
| 110-3 | REMOVAL OF EXISTING STRUCTURES/BRIDGES | 648 | SF | \$ 120.00 | \$ 77,760 |
| 400-2-10 | CONCRETE CLASS II, APPROACH SLABS | 20.1 | CY | \$ 400.00 | \$ 8,040 |
| 400-4-4 | CONCRETE CLASS IV, SUPERSTRUCTURE | 86.4 | CY | \$ 1,200.00 | \$ 103,680 |
| 400-4-5 | CONCRETE CLASS IV, BRIDGE SUBSTRUCTURE | 32.6 | CY | \$ 950.00 | \$ 30,970 |
| 400-148 | PLAIN NEOPRENE BEARING PADS | 1.9 | CF | \$ 1,000.00 | \$ 1,900 |
| 415-1-4 | REINFORCING STEEL - BRIDGE SUPERSTRUCTURE | 16,179 | LB | \$ 1.05 | \$ 16,988 |
| 415-1-5 | REINFORCING STEEL- BRIDGE SUBSTRUCTURE | 3,802 | LB | \$ 1.00 | \$ 3,802 |
| 415-1-9 | REINFORCING STEEL- APPROACH SLABS | 2,012 | LB | \$ 1.05 | \$ 2,113 |
| 450-2-72 | PREST BEAMS: FLORIDA-I BEAM 72" | 464 | LF | \$ 320.00 | \$ 148,480 |
| 455-34-5 | PRESTRESSED CONCRETE PILING, 24" SQ | 268 | LF | \$ 140.00 | \$ 37,520 |
| 455-88-6 | DRILLED SHAFT, 60" DIA | 60 | LF | \$ 600.00 | \$ 36,000 |
| 458-1-11 | BRIDGE DECK EXPANSION JOINT, NEW CONSTRUCTION, F&I Poured JOINT WITH BACKER ROD | 37 | LF | \$ 45.00 | \$ 1,665 |
| 521-5-13 | CONCRETE TRAFFIC RAILING- BRIDGE, 36" SINGLE-SLOPE | 232 | LF | \$ 110.00 | \$ 25,520 |
| 548-12 | RETAINING WALL SYSTEM, PERMANENT, EXCLUDING BARRIER | 357 | SF | \$ 32.00 | \$ 11,424 |
| | | | | | Bridge 870757 Sub-total: \$ 607,034 |
| 0106 - Structures, Bridge 870995 (SR 826 NB over SR 932/NW 103rd Street) | | | | | |
| 110-3 | REMOVAL OF EXISTING STRUCTURES/BRIDGES | 1,161 | SF | \$ 120.00 | \$ 139,320 |
| 400-2-10 | CONCRETE CLASS II, APPROACH SLABS | 25.9 | CY | \$ 400.00 | \$ 10,360 |
| 400-4-4 | CONCRETE CLASS IV, SUPERSTRUCTURE | 110.2 | CY | \$ 1,200.00 | \$ 132,240 |
| 400-4-5 | CONCRETE CLASS IV, BRIDGE SUBSTRUCTURE | 59.3 | CY | \$ 950.00 | \$ 56,335 |
| 400-148 | PLAIN NEOPRENE BEARING PADS | 1.9 | CF | \$ 1,000.00 | \$ 1,900 |
| 415-1-4 | REINFORCING STEEL - BRIDGE SUPERSTRUCTURE | 20,814 | LB | \$ 1.05 | \$ 21,855 |
| 415-1-5 | REINFORCING STEEL- BRIDGE SUBSTRUCTURE | 7,134 | LB | \$ 1.00 | \$ 7,134 |
| 415-1-9 | REINFORCING STEEL- APPROACH SLABS | 2,593 | LB | \$ 1.05 | \$ 2,723 |
| 450-2-72 | PREST BEAMS: FLORIDA-I BEAM 72" | 464 | LF | \$ 320.00 | \$ 148,480 |
| 455-34-5 | PRESTRESSED CONCRETE PILING, 24" SQ | 476 | LF | \$ 140.00 | \$ 66,640 |
| 458-1-11 | BRIDGE DECK EXPANSION JOINT, NEW CONSTRUCTION, F&I Poured JOINT WITH BACKER ROD | 49 | LF | \$ 45.00 | \$ 2,205 |
| 521-5-13 | CONCRETE TRAFFIC RAILING- BRIDGE, 36" SINGLE-SLOPE | 232 | LF | \$ 110.00 | \$ 25,520 |
| 548-12 | RETAINING WALL SYSTEM, PERMANENT, EXCLUDING BARRIER | 558 | SF | \$ 32.00 | \$ 17,856 |
| | | | | | Bridge 870995 Sub-total: \$ 759,082 |
| | | | | | Structures Sub-total: \$ 5,473,962 |

FM 447165-1 - SR 826 Express Lanes Modifications, Phase 2 (Ultimate)

| Pay Item | Description | Quantity | Unit | Unit Price | Total |
|---------------------------|--|----------|------|--------------|----------------------|
| 0200 - Roadway | | | | | |
| 101-1 | MOBILIZATION | 1 | LS | 8% | \$ 1,456,000 |
| 102-1 | MAINTENANCE OF TRAFFIC | 650 | DA | 20% | \$ 3,639,000 |
| 102-14 | TRAFFIC CONTROL OFFICER | 288 | HR | \$ 27.09 | \$ 7,802 |
| 102-60 | WORK ZONE SIGN | 21,585 | ED | \$ 0.32 | \$ 6,907 |
| 102-71-15 | TEMPORARY BARRIER, F&I, ANCHORED | 1,500 | LF | \$ 5.15 | \$ 7,725 |
| 102-71-16 | TEMPORARY BARRIER, F&I, FREE STANDING | 1,400 | LF | \$ 10.82 | \$ 15,148 |
| 102-74-1 | CHANNELIZING DEVICE- TYPES I, II, DI, VP, DRUM, OR LCD | 243,222 | ED | \$ 0.21 | \$ 51,077 |
| 102-76 | ARROW BOARD / ADVANCE WARNING ARROW PANEL | 2,608 | ED | \$ 6.20 | \$ 16,170 |
| 102-89-1 | TEMPORARY CRASH CUSHION, REDIRECTIVE OPTION | 5 | LO | \$ 932.61 | \$ 4,663 |
| 102-99 | PORTABLE CHANGEABLE MESSAGE SIGN, TEMPORARY | 1,856 | ED | \$ 11.76 | \$ 21,827 |
| 102-115 | TYPE III BARRICADE | 5,184 | ED | \$ 0.32 | \$ 1,659 |
| 102-150-1 | PORTABLE REGULATORY, SIGN | 1,730 | ED | \$ 6.30 | \$ 10,899 |
| 102-150-2 | RADAR SPEED DISPLAY UNIT | 1,730 | ED | \$ 6.30 | \$ 10,899 |
| 110-1-1 | CLEARING & GRUBBING | 5,140 | AC | \$ 20,000.00 | \$ 102,800 |
| 120-1 | REGULAR EXCAVATION | 22,357 | CY | \$ 13.97 | \$ 312,331 |
| 120-6 | EMBANKMENT | 45,185 | CY | \$ 16.49 | \$ 745,105 |
| 160-4 | TYPE B STABILIZATION | 18,526 | SY | \$ 5.04 | \$ 93,373 |
| 285-704 | OPTIONAL BASE, BASE GROUP 04 | 7,356 | SY | \$ 16.80 | \$ 123,576 |
| 285-706 | OPTIONAL BASE, BASE GROUP 06 | 3,624 | SY | \$ 51.45 | \$ 186,453 |
| 285-711 | OPTIONAL BASE, BASE GROUP 11 | 3,693 | SY | \$ 15.86 | \$ 58,573 |
| 285-712 | OPTIONAL BASE, BASE GROUP 12 | 5,510 | SY | \$ 32.03 | \$ 176,485 |
| 327-70-6 | MILLING EXIST ASPH PAVT, 1 1/2" AVG DEPTH | 11,360 | SY | \$ 2.94 | \$ 33,398 |
| 327-70-11 | MILLING EXIST ASPH PAVT, 2 1/4" AVG DEPTH | 129,722 | SY | \$ 2.52 | \$ 326,900 |
| 334-1-14 | SUPERPAVE ASPHALTIC CONC, TRAFFIC D | 1,702.9 | TN | \$ 109.20 | \$ 185,957 |
| 334-1-54 | SUPERPAVE ASPHALTIC CONCRETE, TRAFFIC D, PG76-22 | 12,641.2 | TN | \$ 125.16 | \$ 1,582,173 |
| 337-7-25 | ASPHALT CONCRETE FRICTION COURSE, INC BIT, FC-5, PG 76-22 | 5,557.0 | TN | \$ 148.58 | \$ 825,663 |
| 339-1 | MISCELLANEOUS ASPHALT PAVEMENT | 154.8 | TN | \$ 159.92 | \$ 24,756 |
| 425-1-541 | INLETS, DT BOT, TYPE D, <10' | 4 | EA | \$ 4,410.00 | \$ 17,640 |
| 425-1-701 | INLETS, GUTTER, TYPE S, <10' | 2 | EA | \$ 4,683.32 | \$ 9,367 |
| 425-1-883 | INLETS, BARRIER WALL, RIGID, CURB & GUTTER, J BOT<10' | 1 | EA | \$ 7,888.65 | \$ 7,889 |
| 425-1-921 | INLETS, ADJACENT BARRIER, <=10' | 13 | EA | \$ 7,410.90 | \$ 96,342 |
| 425-1-923 | INLETS, ADJACENT BARRIER, J BOTTOM, < 10' | 27 | EA | \$ 8,893.08 | \$ 240,113 |
| 425-2-41 | MANHOLES, P-7, <10' | 23 | EA | \$ 5,055.23 | \$ 116,270 |
| 425-2-72 | MANHOLES, J-7, >10' | 2 | EA | \$ 8,168.16 | \$ 16,336 |
| 430-174-118 | PIPE CULVERT, OPTIONAL MATERIAL, ROUND, 18"SD | 2,146 | LF | \$ 74.97 | \$ 160,886 |
| 430-174-124 | PIPE CULVERT, OPTIONAL MATERIAL, ROUND, 24"SD | 158 | LF | \$ 88.20 | \$ 13,936 |
| 430-174-130 | PIPE CULVERT, OPTIONAL MATERIAL, ROUND, 30"SD | 445 | LF | \$ 148.79 | \$ 66,212 |
| 430-611-125 | U-ENDWALL WITH BAFFLES, INDEX 261/430-011, 1:4 SLOPE, 18"PIPE | 7 | EA | \$ 3,887.10 | \$ 27,210 |
| 436-1-1 | TRENCH DRAIN, STANDARD | 479 | LF | \$ 273.42 | \$ 130,968 |
| 443-70-4 | FRENCH DRAIN, 24" | 1,285 | LF | \$ 158.24 | \$ 203,338 |
| 443-70-5 | FRENCH DRAIN, 30" | 454 | LF | \$ 173.99 | \$ 78,991 |
| 520-6 | SHOULDER GUTTER- CONCRETE | 366 | LF | \$ 21.00 | \$ 7,686 |
| 521-1-11 | MEDIAN CONCRETE BARRIER, 38" HEIGHT | 291 | LF | \$ 166.74 | \$ 48,521 |
| 521-1-12 | MEDIAN CONCRETE BARRIER, SHORT GRADE-SEPARATED | 1,534 | LF | \$ 141.12 | \$ 216,478 |
| 521-5-13 | CONCRETE TRAFFIC RAILING- BRIDGE, 36" SINGLE-SLOPE | 1,126 | LF | \$ 132.20 | \$ 148,791 |
| 521-8-7 | CONCRETE BARRIER, WITH JUNCTION SLAB, 36" SINGLE SLOPE | 5,118 | LF | \$ 265.65 | \$ 1,359,570 |
| 536-1-1 | GUARDRAIL -ROADWAY, GENERAL TL-3 | 516 | LF | \$ 17.43 | \$ 8,994 |
| 536-8-112 | GUARDRAIL TRANSITION CONNECTION TO RIGID BARRIER, FURNISH AND INSTALL, NEW BRIDGE OR CONCRETE BARRIER, APPROACH TL-3 | 1 | EA | \$ 2,940.00 | \$ 2,940 |
| 536-8-113 | GUARDRAIL TRANSITION CONNECTION TO RIGID BARRIER, FURNISH AND INSTALL, NEW BRIDGE OR CONCRETE BARRIER, TRAILING | 2 | EA | \$ 2,525.25 | \$ 5,051 |
| 536-73 | GUARDRAIL REMOVAL | 516 | LF | \$ 2.31 | \$ 1,192 |
| 544-3-2 | CRASH CUSHION, TL-3, WIDE | 4 | EA | \$ 34,884.58 | \$ 139,538 |
| 548-12 | RETAINING WALL SYSTEM, PERMANENT, EXCLUDING BARRIER | 123,820 | SF | \$ 32.00 | \$ 3,962,240 |
| 630-2-12 | CONDUIT, FURNISH & INSTALL, DIRECTIONAL BORE | 180 | LF | \$ 19.85 | \$ 3,573 |
| 695-1-1 | TRAFFIC MONITORING SITE VEHICLE SENSOR-NON-WEIGHT, FURNISH & INSTALL | 18 | EA | \$ 1,659.00 | \$ 29,862 |
| 695-6-12 | TRAFFIC MONITORING SITE INDUCTIVE LOOP ASSEMBLY, FURNISH & INSTALL, 2 LOOPS | 18 | EA | \$ 1,706.78 | \$ 30,722 |
| Roadway Sub-total: | | | | | \$ 17,177,973 |

FM 447165-1 - SR 826 Express Lanes Modifications, Phase 2 (Ultimate)

| Pay Item | Description | Quantity | Unit | Unit Price | Total |
|---|---|----------|------|---------------|------------|
| 0300 - Signing and Pavement Markings | | | | | |
| 700-1-11 | SINGLE POST SIGN, F&I GROUND MOUNT, UP TO 12 SF | 1 | AS | \$ 308.81 | \$ 309 |
| 700-1-12 | SINGLE POST SIGN, F&I GROUND MOUNT, 12-20 SF | 2 | AS | \$ 955.82 | \$ 1,912 |
| 700-1-13 | SINGLE POST SIGN, F&I GROUND MOUNT, 21-30 SF | 2 | AS | \$ 1,230.81 | \$ 2,462 |
| 700-1-31 | SINGLE POST SIGN, F&I BRIDGE MOUNT INDEX 11870/700-012, UP TO 12 SF | 1 | AS | \$ 1,569.75 | \$ 1,570 |
| 700-1-60 | SINGLE POST SIGN, REMOVE | 7 | AS | \$ 24.78 | \$ 173 |
| 700-3-206 | SIGN PANEL, FURNISH & INSTALL OVERHEAD MOUNT, 101-200 SF | 2 | EA | \$ 5,260.50 | \$ 10,521 |
| 700-3-207 | SIGN PANEL, FURNISH & INSTALL OVERHEAD MOUNT, 201-300 SF | 2 | EA | \$ 5,197.50 | \$ 10,395 |
| 700-3-208 | SIGN PANEL, FURNISH & INSTALL OVERHEAD MOUNT, 301-400 SF | 5 | EA | \$ 7,035.00 | \$ 35,175 |
| 700-3-209 | SIGN PANEL, FURNISH & INSTALL OVERHEAD MOUNT, 401-500 SF | 1 | EA | \$ 17,520.28 | \$ 17,520 |
| 700-3-211 | SIGN PANEL, FURNISH & INSTALL OVERHEAD MOUNT, 601 SF AND GREATER | 3 | EA | \$ 18,375.00 | \$ 55,125 |
| 700-3-505 | SIGN PANEL, RELOCATE, 51-100 SF | 2 | EA | \$ 693.97 | \$ 1,388 |
| 700-3-506 | SIGN PANEL, RELOCATE, 101-200 SF | 2 | EA | \$ 1,601.78 | \$ 3,204 |
| 700-3-507 | SIGN PANEL, RELOCATE, 201-300 SF | 6 | EA | \$ 1,522.50 | \$ 9,135 |
| 700-3-508 | SIGN PANEL, RELOCATE, 301-400 SF | 2 | EA | \$ 2,257.50 | \$ 4,515 |
| 700-3-605 | SIGN PANEL, REMOVE, 51-100 SF | 1 | EA | \$ 262.19 | \$ 262 |
| 700-3-606 | SIGN PANEL, REMOVE, 101-200 SF | 3 | EA | \$ 609.00 | \$ 1,827 |
| 700-3-607 | SIGN PANEL, REMOVE, 201-300 SF | 1 | EA | \$ 521.54 | \$ 522 |
| 700-3-608 | SIGN PANEL, REMOVE, 301-400 SF | 7 | EA | \$ 649.69 | \$ 4,548 |
| 700-3-611 | SIGN PANEL, REMOVE, 601 SF AND GREATER | 2 | EA | \$ 2,509.50 | \$ 5,019 |
| 700-4-112 | OVERHEAD STATIC SIGN STRUCTURE, FURNISH & INSTALL, CANTILEVER, 21-30 FT | 1 | EA | \$ 62,055.00 | \$ 62,055 |
| 700-4-113 | OVERHEAD STATIC SIGN STRUCTURE, FURNISH & INSTALL, CANTILEVER, 31-40 FT | 1 | EA | \$ 91,875.00 | \$ 91,875 |
| 700-4-114 | OVERHEAD STATIC SIGN STRUCTURE, FURNISH & INSTALL, CANTILEVER, 41-50 FT | 2 | EA | \$ 99,876.00 | \$ 199,752 |
| 700-4-126 | OVERHEAD STATIC SIGN STRUCTURE, FURNISH & INSTALL, SPAN, 101-150 FT | 6 | EA | \$ 146,618.85 | \$ 879,713 |
| 700-4-610 | OVERHEAD STATIC SIGN STRUCTURE, REMOVE CANTILEVER | 7 | EA | \$ 6,063.23 | \$ 42,443 |
| 700-4-620 | OVERHEAD STATIC SIGN STRUCTURE, REMOVE SPAN | 7 | EA | \$ 9,975.00 | \$ 69,825 |
| 701-18-101 | PROFILED THERMOPLASTIC, STANDARD- ASPHALT SURFACES, WHITE, SOLID, 6" | 0.293 | GM | \$ 6,300.00 | \$ 1,846 |
| 701-18-201 | PROFILED THERMOPLASTIC, STANDARD- ASPHALT SURFACES, YELLOW, SOLID, 6" | 1.347 | GM | \$ 6,300.00 | \$ 8,486 |
| 704-1-2 | TUBULAR MARKER, DURABLE, 36" YELLOW POST | 4,500 | EA | \$ 52.50 | \$ 236,250 |
| 710-90 | PAINTED PAVEMENT MARKINGS, FINAL SURFACE | 1 | LS | \$ 41,853.80 | \$ 41,854 |
| 711-11-103 | THERMOPLASTIC, STANDARD, WHITE, SOLID, 12" FOR INTERCHANGE MARKINGS | 1.364 | GM | \$ 8,820.00 | \$ 12,030 |
| 711-11-124 | THERMOPLASTIC, STANDARD, WHITE, SOLID, 18" FOR DIAGONALS AND CHEVRONS | 674 | LF | \$ 2.42 | \$ 1,631 |
| 711-11-125 | THERMOPLASTIC, STANDARD, WHITE, SOLID, 24" FOR STOP LINE AND CROSSWALK | 73 | LF | \$ 3.57 | \$ 261 |
| 711-11-160 | THERMOPLASTIC, STANDARD, WHITE, MESSAGE OR SYMBOL | 12 | EA | \$ 101.64 | \$ 1,220 |
| 711-11-170 | THERMOPLASTIC, STANDARD, WHITE, ARROW | 39 | EA | \$ 58.38 | \$ 2,277 |
| 711-11-224 | THERMOPLASTIC, STANDARD, YELLOW, SOLID, 18" FOR DIAGONAL OR CHEVRON | 1,252 | LF | \$ 2.63 | \$ 3,293 |
| 711-14-125 | THERMOPLASTIC, PREFORMED, WHITE, SOLID, 24" FOR CROSSWALK | 182 | LF | \$ 16.38 | \$ 2,981 |
| 711-14-560 | THERMOPLASTIC, PREFORMED, WHITE WITH BLACK CONTRAST ON CONCRETE PAVEMENT, MESSAGE OR SYMBOL | 2 | EA | \$ 672.95 | \$ 1,346 |
| 711-14-570 | THERMOPLASTIC, PREFORMED, WHITE WITH BLACK CONTRAST, ARROW ON CONCRETE SURFACE | 2 | EA | \$ 829.50 | \$ 1,659 |
| 711-15-101 | THERMOPLASTIC, STANDARD-OPEN GRADED ASPHALT SURFACES WHITE, SOLID, 6" | 1.923 | GM | \$ 4,305.00 | \$ 8,279 |
| 711-15-102 | THERMOPLASTIC, STANDARD-OPEN GRADED ASPHALT SURFACES, WHITE, SOLID, 8" | 8.061 | GM | \$ 5,355.00 | \$ 43,167 |
| 711-15-131 | THERMOPLASTIC, STANDARD-OPEN GRADED ASPHALT SURFACES, WHITE, SKIP, 6",10-30 SKIP OR 3-9 LANE DROP | 11.349 | GM | \$ 1,732.50 | \$ 19,662 |
| 711-15-133 | THERMOPLASTIC, STANDARD-OPEN GRADED ASPHALT SURFACES, WHITE, SKIP, 12"- APPROACH TO TOLL PLAZA OR 3-9 LANE DROP | 1.783 | GM | \$ 3,043.74 | \$ 5,427 |
| 711-15-201 | THERMOPLASTIC, STANDARD-OPEN GRADED ASPHALT SURFACES, YELLOW, SOLID, 6" | 1.036 | GM | \$ 4,305.00 | \$ 4,460 |
| 711-16-101 | THERMOPLASTIC, STANDARD-OTHER SURFACES, WHITE, SOLID, 6" | 1.178 | GM | \$ 4,168.92 | \$ 4,911 |
| 711-16-102 | THERMOPLASTIC, STANDARD-OTHER SURFACES, WHITE, SOLID, 8" | 0.070 | GM | \$ 4,969.55 | \$ 348 |
| 711-16-131 | THERMOPLASTIC, STANDARD-OTHER SURFACES, WHITE, SKIP, 6",10-30 SKIP OR 3-9 LANE DROP | 0.523 | GM | \$ 1,234.28 | \$ 646 |
| 711-16-201 | THERMOPLASTIC, STANDARD-OTHER SURFACES, YELLOW, SOLID, 6" | 0.566 | GM | \$ 4,178.79 | \$ 2,365 |
| 713-103-101 | PERMANENT TAPE, WHITE, SOLID, 6" FOR CONCRETE BRIDGES | 0.459 | GM | \$ 23,633.09 | \$ 10,848 |
| 713-103-102 | PERMANENT TAPE, WHITE, SOLID, 8" EXIT LANE AT INTERCHANGE ON CONCRETE PAVEMENT | 0.498 | GM | \$ 33,366.48 | \$ 16,617 |
| 713-103-103 | PERMANENT TAPE, WHITE, SOLID LANE DROP MARKING, 12" FOR CONCRETE BRIDGES | 0.039 | GM | \$ 54,030.06 | \$ 2,107 |
| 713-103-131 | PERMANENT TAPE, WHITE, SKIP/DOTTED, 6" FOR CONCRETE SURFACES | 0.889 | GM | \$ 7,225.37 | \$ 6,423 |

FM 447165-1 - SR 826 Express Lanes Modifications, Phase 2 (Ultimate)

| Pay Item | Description | Quantity | Unit | Unit Price | Total |
|---|---|----------|------|--------------|---------------------|
| 713-103-133 | PERMANENT TAPE, WHITE, SKIP, 12" WIDE 3'-9' DROP LANE ON CONCRETE SURFACES | 0.076 | GM | \$ 14,871.05 | \$ 1,130 |
| 713-103-201 | PERMANENT TAPE, YELLOW, SOLID, 6" FOR CONCRETE BRIDGES | 0.400 | GM | \$ 24,038.60 | \$ 9,615 |
| 713-103-331 | PERMANENT TAPE, BLACK, SKIP/DOTTED, 6" FOR CONCRETE SURFACES | 0.890 | GM | \$ 6,237.00 | \$ 5,551 |
| 713-103-333 | PERMANENT TAPE, BLACK, 3'-9' DROP LANE, 12" ON CONCRETE SURFACES | 0.076 | GM | \$ 20,034.00 | \$ 1,523 |
| Sub-total Signing and Pavement Markings | | | | | \$ 1,969,454 |
| Lump Sum Pay Item 710-90, Painted Pavement Markings, Final Surface | | | | | \$ 41,854 |
| 706-1-1 | RAISED PAVEMENT MARKER, TYPE B WITHOUT FINAL SURFACE MARKINGS | 3,108 | EA | \$ 4.31 | \$ 13,395 |
| 710-11-101 | PAINTED PAVEMENT MARKINGS, STANDARD, WHITE, SOLID, 6" | 3.326 | GM | \$ 775.95 | \$ 2,581 |
| 710-11-102 | PAINTED PAVEMENT MARKINGS, STANDARD, WHITE, SOLID FOR INTERCHANGE AND URBAN ISLAND, 8" | 8.131 | GM | \$ 1,029.11 | \$ 8,368 |
| 710-11-103 | PAINTED PAVEMENT MARKINGS, STANDARD, WHITE, SOLID FOR INTERCHANGE MARKINGS, 12" | 1.364 | GM | \$ 1,470.00 | \$ 2,005 |
| 710-11-124 | PAINTED PAVEMENT MARKINGS, STANDARD, WHITE, SOLID FOR DIAGONAL OR CHEVRON, 18" | 674 | LF | \$ 0.84 | \$ 566 |
| 710-11-125 | PAINTED PAVEMENT MARKINGS, STANDARD, WHITE, SOLID FOR STOP LINE OR CROSSWALK, 24" | 73 | LF | \$ 1.05 | \$ 77 |
| 710-11-131 | PAINTED PAVEMENT MARKINGS, STANDARD, WHITE, SKIP, 10-30 OR 3-9 SKIP, 6" WIDE | 21.715 | GM | \$ 351.86 | \$ 7,641 |
| 710-11-133 | PAINTED PAVEMENT MARKING, STANDARD, WHITE, 3'-9' SKIP DROP LINE AND APPROACH TO TOLL PLAZA, 12" WIDE, | 1.783 | GM | \$ 1,151.96 | \$ 2,054 |
| 710-11-160 | PAINTED PAVEMENT MARKINGS, STANDARD, WHITE, MESSAGE OR SYMBOL | 12 | EA | \$ 50.61 | \$ 607 |
| 710-11-170 | PAINTED PAVEMENT MARKINGS, STANDARD, WHITE, ARROWS | 39 | EA | \$ 26.25 | \$ 1,024 |
| 710-11-201 | PAINTED PAVEMENT MARKINGS, STANDARD, YELLOW, SOLID, 6" | 2.910 | GM | \$ 763.46 | \$ 2,222 |
| 710-11-224 | PAINTED PAVEMENT MARKINGS, STANDARD, YELLOW, SOLID FOR DIAGONAL OR CHEVRON, 18" | 1,252 | LF | \$ 1.05 | \$ 1,315 |

FM 447165-1 - SR 826 Express Lanes Modifications, Phase 2 (Ultimate)

| Pay Item | Description | Quantity | Unit | Unit Price | Total |
|---------------------------------------|---|----------|------|--------------|------------|
| 0400 - Lighting | | | | | |
| 630-2-12 | CONDUIT, FURNISH & INSTALL, DIRECTIONAL BORE | 500 | LF | \$ 19.85 | \$ 9,925 |
| 630-2-15 | CONDUIT, FURNISH & INSTALL, BRIDGE MOUNT | 800 | LF | \$ 30.45 | \$ 24,360 |
| 630-2-16 | CONDUIT, FURNISH & INSTALL, EMBEDDED CONCRETE BARRIERS AND TRAFFIC RAILINGS | 18,408 | LF | \$ 10.08 | \$ 185,553 |
| 635-2-11 | PULL & SPLICE BOX, F&I, 13" x 24" COVER SIZE | 16 | EA | \$ 711.59 | \$ 11,385 |
| 635-3-12 | JUNCTION BOX, FURNISH & INSTALL, MOUNTED | 10 | EA | \$ 472.50 | \$ 4,725 |
| 635-3-13 | JUNCTION BOX, FURNISH & INSTALL, EMBEDDED | 45 | EA | \$ 392.07 | \$ 17,643 |
| 715-1-13 | LIGHTING CONDUCTORS, F&I, INSULATED, NO 4 TO NO 2 | 21,492 | LF | \$ 2.42 | \$ 52,011 |
| 715-4-12 | LIGHT POLE COMPLETE, FURNISH & INSTALL STANDARD POLE STANDARD FOUNDATION, 35' MOUNTING HEIGHT | 15 | EA | \$ 5,202.96 | \$ 78,044 |
| 715-4-14 | LIGHT POLE COMPLETE, FURNISH & INSTALL STANDARD POLE STANDARD FOUNDATION, 45' MOUNTING HEIGHT | 1 | EA | \$ 7,218.23 | \$ 7,218 |
| 715-4-71 | LIGHT POLE COMPLETE, REMOVE POLE, FOUNDATION REMAINS | 9 | EA | \$ 735.00 | \$ 6,615 |
| 715-7-21 | LOAD CENTER, REWORK, SECONDARY VOLTAGE | 1 | EA | \$ 1,693.86 | \$ 1,694 |
| 715-11-125 | LUMINAIRE, F&I, UNDER DECK, WALL MOUNT | 9 | EA | \$ 942.59 | \$ 8,483 |
| 715-11-211 | LUMINAIRE, F&I- REPLACE EXISTING LUMINAIRE ON EXISTING POLE/ARM, ROADWAY, COBRA HEAD | 62 | EA | \$ 1,422.96 | \$ 88,224 |
| 715-500-3 | POLE CABLE DISTRIBUTION SYSTEM, WALL MOUNT | 78 | EA | \$ 367.29 | \$ 28,649 |
| Lighting Sub-total: \$ 524,529 | | | | | |
| 0500 - Signalization | | | | | |
| 630-2-12 | CONDUIT, FURNISH & INSTALL, DIRECTIONAL BORE | 387 | LF | \$ 19.85 | \$ 7,682 |
| 630-2-65 | CONDUIT, REMOVE, BRIDGE MOUNT | 100 | LF | \$ 5.78 | \$ 578 |
| 632-7-1 | SIGNAL CABLE- NEW OR RECONSTRUCTED INTERSECTION, FURNISH & INSTALL | 2 | PI | \$ 5,245.07 | \$ 10,490 |
| 635-2-11 | PULL & SPLICE BOX, F&I, 13" x 24" COVER SIZE | 18 | EA | \$ 711.59 | \$ 12,809 |
| 635-2-12 | PULL & SPLICE BOX, F&I, 24" X 36" COVER SIZE | 1 | EA | \$ 1,421.91 | \$ 1,422 |
| 639-1-122 | ELECTRICAL POWER SERVICE, F&I, UNDERGROUND, METER PURCHASED BY CONTRACTOR | 1 | AS | \$ 3,485.27 | \$ 3,485 |
| 639-2-1 | ELECTRICAL SERVICE WIRE, FURNISH & INSTALL | 100 | LF | \$ 4.83 | \$ 483 |
| 641-2-12 | PRESTRESSED CONCRETE POLE, F&I, TYPE P-II SERVICE POLE | 1 | EA | \$ 1,657.64 | \$ 1,658 |
| 646-1-11 | ALUMINUM SIGNALS POLE, PEDESTAL | 2 | EA | \$ 1,219.79 | \$ 2,440 |
| 646-1-40 | ALUMINUM SIGNALS POLE, RELOCATE | 1 | EA | \$ 1,201.73 | \$ 1,202 |
| 649-21-11 | STEEL MAST ARM ASSEMBLY, FURNISH AND INSTALL, DOUBLE ARM 60'-30' | 1 | EA | \$ 55,650.00 | \$ 55,650 |
| 649-21-13 | STEEL MAST ARM ASSEMBLY, FURNISH AND INSTALL, DOUBLE ARM 60'-50' | 1 | EA | \$ 68,176.19 | \$ 68,176 |
| 649-26-3 | STEEL MAST ARM ASSEMBLY, REMOVE, SHALLOW FOUNDATION-BOLT ON ATTACHMENT | 2 | EA | \$ 2,696.51 | \$ 5,393 |
| 650-1-14 | VEHICULAR TRAFFIC SIGNAL, FURNISH & INSTALL ALUMINUM, 3 SECTION, 1 WAY | 12 | AS | \$ 1,022.81 | \$ 12,274 |
| 650-1-16 | VEHICULAR TRAFFIC SIGNAL, FURNISH & INSTALL ALUMINUM, 4 SECTION, 1 WAY | 2 | AS | \$ 1,350.83 | \$ 2,702 |
| 653-1-11 | PEDESTRIAN SIGNAL, FURNISH & INSTALL LED COUNTDOWN, 1 WAY | 2 | AS | \$ 849.87 | \$ 1,700 |
| 660-2-101 | LOOP ASSEMBLY- F&I, TYPE A | 6 | AS | \$ 1,124.97 | \$ 6,750 |
| 665-1-11 | PEDESTRIAN DETECTOR, FURNISH & INSTALL, STANDARD | 2 | EA | \$ 301.77 | \$ 604 |
| 670-5-140 | TRAFFIC CONTROLLER ASSEMBLY, FURNISH & INSTALL MODEL 2070 | 1 | AS | \$ 27,877.61 | \$ 27,878 |
| 670-5-400 | TRAFFIC CONTROLLER ASSEMBLY, MODIFY | 2 | AS | \$ 2,456.69 | \$ 4,913 |
| 700-3-201 | SIGN PANEL, FURNISH & INSTALL OVERHEAD MOUNT, UP TO 12 SF | 2 | EA | \$ 585.48 | \$ 1,171 |
| 700-4-640 | OVERHEAD STATIC SIGN STRUCTURE, REMOVE BRIDGE MOUNT | 2 | EA | \$ 2,814.00 | \$ 5,628 |
| 700-5-21 | INTERNAL ILLUMINATED SIGN, FURNISH & INSTALL OVERHEAD MOUNT, UP TO 12 SF | 4 | EA | \$ 2,914.91 | \$ 11,660 |
| Signal Sub-total: \$ 246,746 | | | | | |

FM 447165-1 - SR 826 Express Lanes Modifications, Phase 2 (Ultimate)

| Pay Item | Description | Quantity | Unit | Unit Price | Total |
|---|--|----------|------|---------------|--------------|
| 0550 - Intelligent Transportation System | | | | | |
| 630-2-11 | CONDUIT, FURNISH & INSTALL, OPEN TRENCH | 2,680 | LF | \$ 9.07 | \$ 24,308 |
| 630-2-12 | CONDUIT, FURNISH & INSTALL, DIRECTIONAL BORE | 4,285 | LF | \$ 18.84 | \$ 80,729 |
| 630-2-15 | CONDUIT, FURNISH & INSTALL, BRIDGE MOUNT | 2,910 | LF | \$ 28.94 | \$ 84,215 |
| 633-1-121 | FIBER OPTIC CABLE, F&I, UNDERGROUND,2-12 FIBERS | 12,315 | LF | \$ 2.55 | \$ 31,403 |
| 633-1-122 | FIBER OPTIC CABLE, F&I, UNDERGROUND,13-48 FIBERS | 525 | LF | \$ 2.46 | \$ 1,292 |
| 633-1-123 | FIBER OPTIC CABLE, F&I, UNDERGROUND,49-96 FIBERS | 11,355 | LF | \$ 3.39 | \$ 38,493 |
| 633-2-31 | FIBER OPTIC CONNECTION, INSTALL, SPLICE | 288 | EA | \$ 39.50 | \$ 11,376 |
| 633-3-11 | FIBER OPTIC CONNECTION HARDWARE, F&I, SPLICE ENCLOSURE | 2 | EA | \$ 887.72 | \$ 1,775 |
| 633-4-1 | SIGNALS COMMUNICATION CABLE- TWISTED PAIR CABLE, FURNISH & INSTALL | 1,050 | LF | \$ 5.22 | \$ 5,481 |
| 635-2-11 | PULL & SPLICE BOX, F&I, 13" x 24" COVER SIZE | 32 | EA | \$ 677.62 | \$ 21,684 |
| 635-2-12 | PULL & SPLICE BOX, F&I, 24" X 36" COVER SIZE | 25 | EA | \$ 1,354.19 | \$ 33,855 |
| 635-3-13 | JUNCTION BOX, FURNISH & INSTALL, EMBEDDED | 20 | EA | \$ 373.40 | \$ 7,468 |
| 639-2-1 | ELECTRICAL SERVICE WIRE, FURNISH & INSTALL | 10,295 | LF | \$ 4.51 | \$ 46,430 |
| 641-2-13 | PRESTRESSED CONCRETE POLE, F&I, TYPE P-III | 2 | EA | \$ 12,290.41 | \$ 24,581 |
| 641-3-175 | CONCRETE CCTV POLE, FURNISH & INSTALL WITH LOWERING DEVICE, 75' | 5 | EA | \$ 24,103.79 | \$ 120,519 |
| 650-1-13 | VEHICULAR TRAFFIC SIGNAL, FURNISH & INSTALL ALUMINUM, 2 SECTION, 1-2 WAYS | 2 | AS | \$ 790.00 | \$ 1,580 |
| 650-1-60 | VEHICULAR TRAFFIC SIGNAL, REMOVE- POLES TO REMAIN | 2 | AS | \$ 91.36 | \$ 183 |
| 660-3-12 | VEHICLE DETECTION SYSTEM- MICROWAVE, FURNISH & INSTALL, ABOVE GROUND EQUIPMENT | 8 | EA | \$ 8,241.82 | \$ 65,935 |
| 660-3-52 | VEHICLE DETECTION SYSTEM - MICROWAVE, ADJUST & MODIFY, ABOVE GROUND EQUIPMENT | 37 | EA | \$ 769.32 | \$ 28,465 |
| 660-3-60 | VEHICLE DETECTION SYSTEM - MICROWAVE, REMOVE, COMPLETE SYSTEM | 8 | EA | \$ 332.73 | \$ 2,662 |
| 670-5-300 | TRAFFIC CONTROLLER ASSEMBLY, INSTALL | 2 | AS | \$ 3,800.00 | \$ 7,600 |
| 676-2-122 | ITS CABINET, FURNISH & INSTALL, POLE MOUNT WITH SUNSHIELD, 336S, 24" W X 46" H X 22" D | 1 | EA | \$ 5,632.75 | \$ 5,633 |
| 676-2-143 | ITS CABINET, FURNISH & INSTALL, BASE MOUNT, 334, 24" W X 66" H X 30" D | 13 | EA | \$ 6,404.72 | \$ 83,261 |
| 682-1-133 | ITS CCTV CAMERA, F&I, DOME ENCLOSURE - NON-PRESSURIZED, IP, HIGH DEFINITION | 13 | EA | \$ 5,006.45 | \$ 65,084 |
| 682-1-600 | ITS CCTV CAMERA,, REMOVE & DISPOSAL | 6 | EA | \$ 305.00 | \$ 1,830 |
| 684-6-11 | WIRELESS COMMUNICATION DEVICE, FURNISH & INSTALL ETHERNET ACCESS POINT | 2 | EA | \$ 3,415.00 | \$ 6,830 |
| 684-6-60 | WIRELESS COMMUNICATION DEVICE, REMOVE | 2 | EA | \$ 257.00 | \$ 514 |
| 700-7-132 | EMBEDDED DYNAMIC MESSAGE SIGN, FURNISH & INSTALL- WITH UPS, FULL COLOR, 12-20 SF | 10 | EA | \$ 21,980.00 | \$ 219,800 |
| 700-7-600 | EMBEDDED DYNAMIC MESSAGE SIGN, REMOVE | 8 | EA | \$ 1,247.40 | \$ 9,979 |
| 700-8-135 | FRONT ACCESS DYNAMIC MESSAGE SIGN, FURNISH & INSTALL- WITH UPS, FULL COLOR, 51-100 SF | 6 | EA | \$ 80,000.00 | \$ 480,000 |
| 700-8-600 | FRONT ACCESS DYNAMIC MESSAGE SIGN, REMOVE | 6 | EA | \$ 3,746.71 | \$ 22,480 |
| 700-9-137 | WALK-IN DYNAMIC MESSAGE SIGN, FURNISH & INSTALL- WITH UPS FULL COLOR, 201-300 SF | 1 | EA | \$ 118,619.66 | \$ 118,620 |
| 700-9-600 | WALK-IN DYNAMIC MESSAGE SIGN, REMOVE | 1 | EA | \$ 3,782.22 | \$ 3,782 |
| 700-10-116 | DMS SUPPORT STRUCTURE, FURNISH & INSTALL, SPAN, 101-150 FT | 1 | EA | \$ 222,000.00 | \$ 222,000 |
| 700-10-600 | DMS SUPPORT STRUCTURE, REMOVE | 1 | EA | \$ 5,813.92 | \$ 5,814 |
| | TOLL GANTRY | 1 | LS | \$ 1,700,000 | \$ 1,700,000 |
| ITS Sub-total: \$ 3,585,662 | | | | | |

| | | | SUBTOTAL | | \$ 28,978,326 |
|--------------------|---|----|--------------------|-----------|----------------------|
| 999-16 | PARTNERING, DO NOT BID | 1 | LS | \$ 30,000 | \$ 30,000 |
| 999-20-1 | DISPUTES REVIEW BOARD, MEETING- DO NOT BID | 24 | DA | \$ 3,500 | \$ 84,000 |
| 999-20-2 | DISPUTES REVIEW BOARD, HEARING- DO NOT BID | 2 | EA | \$ 4,000 | \$ 8,000 |
| 999-25 | INITIAL CONTINGENCY AMOUNT, DO NOT BID | 1 | LS | | \$ 150,000 |
| 0-30-1 | DESIGN COST FOR DESIGN BUILD PROJECTS: ESTIMATES USE ONLY (44716515201DB) | 1 | LS | 10% | \$ 2,925,033 |
| FM 447165-1 | | | Grand Total | | \$ 32,175,359 |

Preliminary Construction Cost Estimate

Revised 11/25/2020

| FM 441831-1, SR 826 Frontage Roads From NW 103rd Street to NW 122nd Street | | | | | | |
|--|--|----------|------|-------------------|--------------|--|
| Pay Item | Description | Quantity | Unit | Unit Price | Total | |
| Roadway | | | | | | |
| 0-30-1 | DESIGN COST FOR DESIGN BUILD PROJECTS: ESTIMATES USE ONLY (44183115201DB) | 1 | LS | 10% | \$ 361,825 | |
| 101-1 | MOBILIZATION | 1 | LS | 8% | \$ 241,915 | |
| 102-1 | MAINTENANCE OF TRAFFIC | 150 | DA | 10% | \$ 302,394 | |
| 102-14 | TRAFFIC CONTROL OFFICER | 88 | HR | \$ 27.10 | \$ 2,385 | |
| 102-60 | WORK ZONE SIGN | 12,000 | ED | \$ 0.30 | \$ 3,600 | |
| 102-71-16 | TEMPORARY BARRIER, F&I, FREE STANDING | 1,400 | LF | \$ 10.80 | \$ 15,120 | |
| 102-71-26 | TEMPORARY BARRIER, RELOCATE, FREE STANDING | 2,800 | LF | \$ 4.30 | \$ 12,040 | |
| 102-74-1 | CHANNELIZING DEVICE- TYPES I, II, DI, VP, DRUM, OR LCD | 38,000 | ED | \$ 0.20 | \$ 7,600 | |
| 102-74-8 | CHANNELIZING DEVICE- PEDESTRIAN LCD (LONGITUDINAL CHANNELIZING DEVICE) | 60,000 | FD | \$ 0.20 | \$ 12,000 | |
| 102-76 | ARROW BOARD / ADVANCE WARNING ARROW PANEL | 240 | ED | \$ 6.20 | \$ 1,488 | |
| 102-89-1 | TEMPORARY CRASH CUSHION, REDIRECTIVE OPTION | 24 | LO | \$ 932.60 | \$ 22,382 | |
| 102-99 | PORTABLE CHANGEABLE MESSAGE SIGN, TEMPORARY | 1,956 | ED | \$ 11.70 | \$ 22,885 | |
| 102-104 | TEMPORARY SIGNALIZATION AND MAINTENANCE, INTERSECTION | 600 | ED | \$ 5.30 | \$ 3,180 | |
| 102-107-1 | TEMPORARY TRAFFIC DETECTION AND MAINTENANCE, INTERSECTION | 600 | ED | \$ 5.30 | \$ 3,180 | |
| 102-115 | TYPE III BARRICADE | 1,400 | ED | \$ 0.40 | \$ 560 | |
| 104-18 | INLET PROTECTION SYSTEM | 110 | EA | \$ 137.20 | \$ 15,092 | |
| 107-1 | LITTER REMOVAL | 1.94 | AC | \$ 11.70 | \$ 23 | |
| 107-2 | MOWING | 0.72 | AC | \$ 19.80 | \$ 14 | |
| 110-1-1 | CLEARING & GRUBBING | 4.62 | AC | \$ 20,000.00 | \$ 92,400 | |
| 110-2-2 | SELECTIVE CLEARING AND GRUBBING, AREAS WITH TREES TO REMAIN | 0.57 | AC | \$ 37,129.60 | \$ 21,164 | |
| 110-21 | TREE PROTECTION BARRIER | 2,100 | LF | \$ 1.90 | \$ 3,990 | |
| 110-4-10 | REMOVAL OF EXISTING CONCRETE | 1,380 | SY | \$ 16.40 | \$ 22,632 | |
| 120-1 | REGULAR EXCAVATION | 3,213 | CY | \$ 14.00 | \$ 44,982 | |
| 120-6 | EMBANKMENT | 946 | CY | \$ 16.50 | \$ 15,609 | |
| 160-4 | TYPE B STABILIZATION | 10,415 | SY | \$ 5.10 | \$ 53,117 | |
| 285-701 | OPTIONAL BASE, BASE GROUP 01 | 8,280 | SY | \$ 5.30 | \$ 43,884 | |
| 285-706 | OPTIONAL BASE, BASE GROUP 06 | 42 | SY | \$ 51.50 | \$ 2,163 | |
| 327-70-6 | MILLING EXIST ASPH PAVT, 1 1/2" AVG DEPTH | 51,622 | SY | \$ 2.90 | \$ 149,704 | |
| 334-1-12 | SUPERPAVE ASPHALTIC CONC, TRAFFIC B | 4 | TN | \$ 110.60 | \$ 442 | |
| 337-7-81 | ASPHALT CONCRETE FRICTION COURSE, TRAFFIC B, FC-12.5, PG 76-22 | 4,944 | TN | \$ 148.70 | \$ 735,173 | |
| 339-1 | MISCELLANEOUS ASPHALT PAVEMENT | 206 | TN | \$ 159.90 | \$ 32,939 | |
| 350-30-13 | CONCRETE PAVEMENT FOR ROUNDABOUT APRON, 12" DEPTH | 62 | SY | \$ 281.70 | \$ 17,465 | |
| 425-1-211 | INLETS, CURB, TYPE 10, <10' | 37 | EA | \$ 7,123.40 | \$ 263,566 | |
| 425-1-351 | INLETS, CURB, TYPE P-5, <10' | 3 | EA | \$ 6,461.10 | \$ 19,383 | |
| 425-1-352 | INLETS, CURB, TYPE P-5, >10' | 1 | EA | \$ 7,466.60 | \$ 7,467 | |
| 425-1-361 | INLETS, CURB, TYPE P-6, <10' | 2 | EA | \$ 4,967.80 | \$ 9,936 | |
| 425-1-521 | INLETS, DT BOT, TYPE C,<10' | 6 | EA | \$ 3,118.50 | \$ 18,711 | |
| 425-1-523 | INLETS, DT BOT, TYPE C,JBOT, <10' | 8 | EA | \$ 5,609.10 | \$ 44,873 | |
| 425-1-541 | INLETS, DT BOT, TYPE D, <10' | 1 | EA | \$ 4,410.00 | \$ 4,410 | |
| 425-1-701 | INLETS, GUTTER, TYPE S, <10' | 1 | EA | \$ 4,683.30 | \$ 4,683 | |
| 425-1-910 | INLETS, CLOSED FLUME | 2 | EA | \$ 4,677.60 | \$ 9,355 | |
| 425-2-41 | MANHOLES, P-7, <10' | 4 | EA | \$ 5,055.20 | \$ 20,221 | |
| 425-5 | MANHOLE, ADJUST | 11 | EA | \$ 812.90 | \$ 8,942 | |
| 430-174-118 | PIPE CULVERT, OPTIONAL MATERIAL, ROUND, 18"SD | 429 | LF | \$ 75.00 | \$ 32,175 | |
| 443-70-4 | FRENCH DRAIN, 24" | 1,301 | LF | \$ 158.20 | \$ 205,818 | |
| 515-1-2 | PIPE HANDRAIL - GUIDERAIL, ALUMINUM | 535 | LF | \$ 25.20 | \$ 13,482 | |
| 520-1-7 | CONCRETE CURB & GUTTER, TYPE E | 216 | LF | \$ 22.10 | \$ 4,774 | |
| 520-1-10 | CONCRETE CURB & GUTTER, TYPE F | 1,850 | LF | \$ 17.20 | \$ 31,820 | |
| 520-2-4 | CONCRETE CURB, TYPE D | 120 | LF | \$ 33.10 | \$ 3,972 | |
| 522-1 | CONCRETE SIDEWALK AND DRIVEWAYS, 4" THICK | 2,049 | SY | \$ 36.60 | \$ 74,994 | |
| 522-2 | CONCRETE SIDEWALK AND DRIVEWAYS, 6" THICK | 909 | SY | \$ 53.90 | \$ 48,999 | |
| 527-2 | DETECTABLE WARNINGS | 854 | SF | \$ 25.40 | \$ 21,692 | |
| 536-1-0 | GUARDRAIL -ROADWAY, GENERAL/LOW SPEED TL-2 | 4,260 | LF | \$ 15.80 | \$ 67,308 | |
| 536-1-1 | GUARDRAIL -ROADWAY, GENERAL TL-3 | 750 | LF | \$ 17.40 | \$ 13,050 | |
| 536-7-1 | SPECIAL GUARDRAIL POST- DEEP POST FOR SLOPE BREAK CONDITION- TIMBER OR STEEL | 336 | EA | \$ 53.20 | \$ 17,875 | |
| 536-7-2 | SPECIAL GUARDRAIL POST- SPECIAL STEEL POST FOR CONCRETE STRUCTURE MOUNT | 40 | EA | \$ 307.70 | \$ 12,308 | |
| 536-8-111 | GUARDRAIL TRANSITION CONNECTION TO RIGID BARRIER, FURNISH AND INSTALL, NEW BRIDGE OR CONCRETE BARRIER, APPROACH , TL-2 | 3 | EA | \$ 2,800.00 | \$ 8,400 | |
| 536-8-112 | GUARDRAIL TRANSITION CONNECTION TO RIGID BARRIER, FURNISH AND INSTALL, NEW BRIDGE OR CONCRETE BARRIER, APPROACH TL-3 | 1 | EA | \$ 2,800.00 | \$ 2,800 | |
| 536-8-113 | GUARDRAIL TRANSITION CONNECTION TO RIGID BARRIER, FURNISH AND INSTALL, NEW BRIDGE OR CONCRETE BARRIER, TRAILING | 2 | EA | \$ 2,405.00 | \$ 4,810 | |
| 536-8-122 | GUARDRAIL TRANSITION CONNECTION TO RIGID BARRIER, FURNISH AND INSTALL, EXISTING BRIDGE APPROACH TL-3 | 2 | EA | \$ 2,800.00 | \$ 5,600 | |
| 536-8-123 | GUARDRAIL TRANSITION CONNECTION TO RIGID BARRIER, FURNISH AND INSTALL, EXISTING BRIDGE, TRAILING | 1 | EA | \$ 2,405.00 | \$ 2,405 | |
| 536-73 | GUARDRAIL REMOVAL | 4,778 | LF | \$ 2.30 | \$ 10,989 | |
| 536-85-20 | GUARDRAIL END TREATMENT- TRAILING ANCHORAGE | 1 | EA | \$ 1,115.00 | \$ 1,115 | |
| 536-85-24 | GUARDRAIL END TREATMENT- PARALLEL APPROACH TERMINAL | 6 | EA | \$ 2,963.40 | \$ 17,780 | |
| 544-2-2 | CRASH CUSHION, TL-2, WIDE | 1 | EA | \$ 27,031.50 | \$ 27,032 | |
| 550-10-220 | FENCING, TYPE B, 5.1-6.0', STANDARD | 125 | LF | \$ 20.90 | \$ 2,613 | |
| 550-60-212 | FENCE GATE, TYPE B, SINGLE, 6.1 - 12.0' OPENING | 1 | EA | \$ 539.10 | \$ 539 | |
| 570-1-2 | PERFORMANCE TURF, SOD | 9,433 | SY | \$ 4.10 | \$ 38,677 | |
| 999-25 | INITIAL CONTINGENCY AMOUNT, DO NOT BID | 1 | LS | \$ 50,000 | | |
| | | | | Sub-total Roadway | \$ 3,395,921 | |

Preliminary Construction Cost Estimate

Revised 11/25/2020

| FM 441831-1, SR 826 Frontage Roads From NW 103rd Street to NW 122nd Street | | | | | |
|--|--|-------|----|--------------|-------------------|
| Signing and Pavement Markings | | | | | |
| 700-1-11 | SINGLE POST SIGN, F&I GROUND MOUNT, UP TO 12 SF | 168 | AS | \$ 308.80 | \$ 51,878 |
| 700-1-12 | SINGLE POST SIGN, F&I GROUND MOUNT, 12-20 SF | 1 | AS | \$ 955.80 | \$ 956 |
| 700-1-60 | SINGLE POST SIGN, REMOVE | 167 | AS | \$ 24.70 | \$ 4,125 |
| 700-2-60 | MULTI- POST SIGN, REMOVE | 1 | AS | \$ 481.90 | \$ 482 |
| 700-3-501 | SIGN PANEL, RELOCATE, UP TO 12 SF | 44 | EA | \$ 154.80 | \$ 6,811 |
| 705-10-1 | OBJECT MARKER, TYPE 1 | 28 | EA | \$ 213.20 | \$ 5,970 |
| 705-10-2 | OBJECT MARKER, TYPE 2 | 1 | EA | \$ 126.80 | \$ 127 |
| 710-11-290 | PAINTED PAVEMENT MARKINGS, STANDARD, YELLOW, ISLAND NOSE | 25 | SF | \$ 1.80 | \$ 45 |
| 710-90 | PAINTED PAVEMENT MARKINGS, FINAL SURFACE | 1 | LS | \$ 16,363.66 | \$ 16,364 |
| 711-11-123 | THERMOPLASTIC, STANDARD, WHITE, SOLID, 12" FOR CROSSWALK AND ROUNDABOUT | 3,732 | LF | \$ 1.70 | \$ 6,344 |
| 711-11-124 | THERMOPLASTIC, STANDARD, WHITE, SOLID, 18" FOR DIAGONALS AND CHEVRONS | 27 | LF | \$ 2.50 | \$ 68 |
| 711-11-125 | THERMOPLASTIC, STANDARD, WHITE, SOLID, 24" FOR STOP LINE AND CROSSWALK | 600 | LF | \$ 3.50 | \$ 2,100 |
| 711-11-141 | THERMOPLASTIC, STANDARD, WHITE, 2-4 DOTTED GUIDELINE/ 6-10 GAP EXTENSION, 6" | 0.015 | GM | \$ 1,145.20 | \$ 17 |
| 711-11-160 | THERMOPLASTIC, STANDARD, WHITE, MESSAGE OR SYMBOL | 9 | EA | \$ 101.70 | \$ 915 |
| 711-11-170 | THERMOPLASTIC, STANDARD, WHITE, ARROW | 40 | EA | \$ 58.40 | \$ 2,336 |
| 711-11-180 | THERMOPLASTIC, STANDARD, WHITE, YIELD LINE | 26 | LF | \$ 2.70 | \$ 70 |
| 711-11-224 | THERMOPLASTIC, STANDARD, YELLOW, SOLID, 18" FOR DIAGONAL OR CHEVRON | 858 | LF | \$ 2.60 | \$ 2,231 |
| 711-14-125 | THERMOPLASTIC, PREFORMED, WHITE, SOLID, 24" FOR CROSSWALK | 759 | LF | \$ 16.40 | \$ 12,448 |
| 711-16-101 | THERMOPLASTIC, STANDARD-OTHER SURFACES, WHITE, SOLID, 6" | 5.529 | GM | \$ 4,168.90 | \$ 23,050 |
| 711-16-102 | THERMOPLASTIC, STANDARD-OTHER SURFACES, WHITE, SOLID, 8" | 0.153 | GM | \$ 4,969.50 | \$ 760 |
| 711-16-131 | THERMOPLASTIC, STANDARD-OTHER SURFACES, WHITE, SKIP, 6",10-30 SKIP OR 3-9 LANE DROP | 0.152 | GM | \$ 1,234.30 | \$ 188 |
| 711-16-133 | THERMOPLASTIC, STANDARD-OTHER SURFACES WHITE, SKIP, 12"- APPROACH TO TOLL PLAZA OR 3-9 LANE DROP | 0.049 | GM | \$ 1,907.60 | \$ 93 |
| 711-16-201 | THERMOPLASTIC, STANDARD-OTHER SURFACES, YELLOW, SOLID, 6" | 3.659 | GM | \$ 4,178.80 | \$ 15,288 |
| 711-16-231 | THERMOPLASTIC, STANDARD-OTHER SURFACES, YELLOW, SKIP, 6" | 0.966 | GM | \$ 1,400.60 | \$ 1,353 |
| 711-17-1 | THERMOPLASTIC, REMOVE EXISTING THERMOPLASTIC PAVEMENT MARKINGS- SURFACE TO REMAIN | 180 | SF | \$ 2.20 | \$ 396 |
| 713-103-101 | PERMANENT TAPE, WHITE, SOLID, 6" FOR CONCRETE BRIDGES | 0.034 | GM | \$ 23,633.10 | \$ 806 |
| 713-103-201 | PERMANENT TAPE, YELLOW, SOLID, 6" FOR CONCRETE BRIDGES | 0.034 | GM | \$ 24,038.60 | \$ 819 |
| Sub-total Signing and Pavement Markings | | | | | \$ 156,040 |
| Lump Sum Pay Item 710-90, Painted Pavement Markings, Final Surface | | | | | |
| 706-1-1 | RAISED PAVEMENT MARKER, TYPE B WITHOUT FINAL SURFACE MARKINGS | 1,180 | EA | \$ 4.30 | \$ 5,074 |
| 710-11-101 | PAINTED PAVEMENT MARKINGS, STANDARD, WHITE, SOLID, 6" | 5.544 | GM | \$ 775.90 | \$ 4,302 |
| 710-11-102 | PAINTED PAVEMENT MARKINGS, STANDARD, WHITE, SOLID FOR INTERCHANGE AND URBAN ISLAND, 8" | 0.153 | GM | \$ 1,029.10 | \$ 157 |
| 710-11-123 | PAINTED PAVEMENT MARKINGS, STANDARD, WHITE, SOLID FOR CROSSWALK AND ROUNDABOUT, 12" | 3,732 | LF | \$ 0.50 | \$ 1,866 |
| 710-11-124 | PAINTED PAVEMENT MARKINGS, STANDARD, WHITE, SOLID FOR DIAGONAL OR CHEVRON, 18" | 27 | LF | \$ 0.80 | \$ 22 |
| 710-11-125 | PAINTED PAVEMENT MARKINGS, STANDARD, WHITE, SOLID FOR STOP LINE OR CROSSWALK, 24" | 600 | LF | \$ 1.10 | \$ 660 |
| 710-11-131 | PAINTED PAVEMENT MARKINGS, STANDARD, WHITE, SKIP, 10-30 OR 3-9 SKIP, 6" WIDE | 0.152 | GM | \$ 351.80 | \$ 53 |
| 710-11-133 | PAINTED PAVEMENT MARKING, STANDARD,WHITE, 3'-9' SKIP DROP LINE AND APPROACH TO TOLL PLAZA, 12" WIDE, | 0.049 | GM | \$ 1,151.90 | \$ 56 |
| 710-11-141 | PAINTED PAVEMENT MARKINGS, STANDARD, WHITE, 2-4 DOTTED GUIDELINE/ 6-10 DOTTED EXTENSION, 6" | 0.015 | GM | \$ 495.20 | \$ 7 |
| 710-11-180 | PAINTED PAVEMENT MARKINGS, STANDARD, WHITE, YIELD LINE | 22 | LF | \$ 3.70 | \$ 81 |
| 710-11-224 | PAINTED PAVEMENT MARKINGS, STANDARD, YELLOW, SOLID FOR DIAGONAL OR CHEVRON, 18" | 858 | LF | \$ 1.00 | \$ 858 |
| 710-11-201 | PAINTED PAVEMENT MARKINGS, STANDARD, YELLOW, SOLID, 6" | 3.697 | GM | \$ 763.40 | \$ 2,822 |
| 710-11-231 | PAINTED PAVEMENT MARKINGS, STANDARD, YELLOW, SKIP, 6" | 0.966 | GM | \$ 418.20 | \$ 404 |

Preliminary Construction Cost Estimate

Revised 11/25/2020

| FM 441831-1, SR 826 Frontage Roads From NW 103rd Street to NW 122nd Street | | | | | |
|--|---|-------|----|-------------|---------------------|
| Signalization | | | | | |
| 630-2-12 | CONDUIT, FURNISH & INSTALL, DIRECTIONAL BORE | 925 | LF | \$ 19.80 | \$ 18,315 |
| 632-7-1 | SIGNAL CABLE- NEW OR RECONSTRUCTED INTERSECTION, FURNISH & INSTALL | 2 | PI | \$ 5,245.10 | \$ 10,490 |
| 635-2-11 | PULL & SPLICE BOX, F&I, 13" x 24" COVER SIZE | 22 | EA | \$ 711.60 | \$ 15,655 |
| 646-1-11 | ALUMINUM SIGNALS POLE, PEDESTAL | 8 | EA | \$ 1,219.80 | \$ 9,758 |
| 653-1-11 | PEDESTRIAN SIGNAL, FURNISH & INSTALL LED COUNTDOWN, 1 WAY | 4 | AS | \$ 849.90 | \$ 3,400 |
| 653-1-12 | PEDESTRIAN SIGNAL, FURNISH & INSTALL LED COUNTDOWN, 2 WAYS | 4 | AS | \$ 1,204.10 | \$ 4,816 |
| 653-1-60 | PEDESTRIAN SIGNAL, REMOVE PED SIGNAL- POLE/PEDESTAL TO REMAIN | 2 | AS | \$ 67.50 | \$ 135 |
| 660-2-106 | LOOP ASSEMBLY, F&I, TYPE F | 5 | AS | \$ 1,203.50 | \$ 6,018 |
| 660-4-11 | VEHICLE DETECTION SYSTEM- VIDEO, FURNISH & INSTALL CABINET EQUIPMENT | 6 | EA | \$ 6,720.00 | \$ 40,320 |
| 660-4-12 | VEHICLE DETECTION SYSTEM- VIDEO, FURNISH & INSTALL ABOVE GROUND EQUIPMENT | 8 | EA | \$ 2,679.80 | \$ 21,438 |
| 665-1-11 | PEDESTRIAN DETECTOR, FURNISH & INSTALL, STANDARD | 10 | EA | \$ 301.80 | \$ 3,018 |
| 665-1-60 | PEDESTRIAN DETECTOR, REMOVE- POLE/PEDESTAL TO REMAIN | 8 | EA | \$ 65.00 | \$ 520 |
| 670-5-400 | TRAFFIC CONTROLLER ASSEMBLY, MODIFY | 2 | AS | \$ 2,456.70 | \$ 4,913 |
| Sub-total Signalization | | | | | \$ 138,797 |
| Lighting | | | | | |
| 630-2-12 | CONDUIT, FURNISH & INSTALL, DIRECTIONAL BORE | 2,350 | LF | \$ 19.80 | \$ 46,530 |
| 635-2-11 | PULL & SPLICE BOX, F&I, 13" x 24" COVER SIZE | 15 | EA | \$ 711.60 | \$ 10,674 |
| 715-1-13 | LIGHTING CONDUCTORS, F&I, INSULATED, NO 4 TO NO 2 | 8,334 | LF | \$ 2.50 | \$ 20,835 |
| 715-4-12 | LIGHT POLE COMPLETE, FURNISH & INSTALL STANDARD POLE STANDARD FOUNDATION, 35' MOUNTING HEIGHT | 8 | EA | \$ 5,203.00 | \$ 41,624 |
| 715-4-14 | LIGHT POLE COMPLETE, FURNISH & INSTALL STANDARD POLE STANDARD FOUNDATION, 45' MOUNTING HEIGHT | 1 | EA | \$ 7,218.20 | \$ 7,218 |
| 715-5-21 | LUMINAIRE & BRACKET ARM, REPLACE LUMINAIRE AND ARM ON EXISTING POLE | 3 | EA | \$ 1,890.00 | \$ 5,670 |
| 715-11-211 | LUMINAIRE, F&I- REPLACE EXISTING LUMINAIRE ON EXISTING POLE/ARM, ROADWAY, COBRA HEAD | 4 | EA | \$ 1,422.90 | \$ 5,692 |
| 715-500-1 | POLE CABLE DISTRIBUTION SYSTEM, FURNISH AND INSTALL, CONVENTIONAL | 13 | EA | \$ 822.30 | \$ 10,690 |
| Sub-total Lighting | | | | | \$ 148,933 |
| Landscape | | | | | |
| 581-1-2 | RELOCATE TREES AND PALMS, PALM, >=14' OF CLEAR TRUNK | 9 | EA | \$ 1,149.60 | \$ 10,346 |
| Sub-total Landscape | | | | | \$ 10,346 |
| Structures - Bridge 870569 (West) | | | | | |
| 104-11 | FLOATING TURBIDITY BARRIER | 150 | LF | \$ 17.20 | \$ 2,580 |
| 110-3 | REMOVAL OF EXISTING STRUCTURES/BRIDGES | 323 | SF | \$ 31.70 | \$ 10,239 |
| 400-2-4 | CONC CLASS II, BRIDGE SUPERSTRUCTURE | 18 | CY | \$ 813.80 | \$ 14,648 |
| 400-2-10 | CONCRETE CLASS II, APPROACH SLABS | 6 | CY | \$ 2,205.00 | \$ 12,392 |
| 415-1-4 | REINFORCING STEEL - BRIDGE SUPERSTRUCTURE | 3,560 | LB | \$ 10.50 | \$ 37,380 |
| 415-1-9 | REINFORCING STEEL- APPROACH SLABS | 1,123 | LB | \$ 7.90 | \$ 8,872 |
| 458-1-11 | BRIDGE DECK EXPANSION JOINT, NEW CONSTRUCTION, F&I POURED JOINT WITH BACKER ROD | 8 | LF | \$ 92.30 | \$ 738 |
| 515-4-1 | BULLET RAIL, SINGLE RAIL | 90 | LF | \$ 30.60 | \$ 2,754 |
| 521-5-4 | CONCRETE TRAFFIC RAILING- BRIDGE, 32" VERTICAL FACE | 174 | LF | \$ 118.60 | \$ 20,636 |
| 521-5-8 | CONCRETE TRAFFIC RAILING- BRIDGE, RETROFIT- VERTICAL FACE | 90 | LF | \$ 63.00 | \$ 5,670 |
| Sub-total Structures - Bridge 870569 (West) | | | | | \$ 115,910 |
| Structures - Bridge 870570 (East) | | | | | |
| 458-1-11 | BRIDGE DECK EXPANSION JOINT, NEW CONSTRUCTION, F&I POURED JOINT WITH BACKER ROD | 76 | LF | \$ 92.30 | \$ 7,015 |
| 521-5-4 | CONCRETE TRAFFIC RAILING- BRIDGE, 32" VERTICAL FACE | 60 | LF | \$ 118.60 | \$ 7,116 |
| Sub-total Structures - Bridge 870570 (East) | | | | | \$ 14,131 |
| Grand Total | | | | | \$ 3,980,078 |
| Unit Prices from FDOT Item Average Unit Costs, either Area 13 or Statewide Averages (10/2019-9/2020) | | | | | |

Preliminary Construction Cost Estimate

Revised 11/25/2020

| FM 441830-1, SR 826 Frontage Roads From Okeechobee Road to NW 103rd Street | | | | | |
|--|--|----------|------|-------------------|--------------|
| Pay Item | Description | Quantity | Unit | Unit Price | Total |
| Roadway | | | | | |
| 0-30-1 | DESIGN COST FOR DESIGN BUILD PROJECTS: ESTIMATES USE ONLY (44183015201DB) | 1 | LS | 10% | \$ 142,885 |
| 101-1 | MOBILIZATION | 1 | LS | 8% | \$ 91,369 |
| 102-1 | MAINTENANCE OF TRAFFIC | 100 | DA | 10% | \$ 114,211 |
| 102-60 | WORK ZONE SIGN | 8,000 | ED | \$ 0.30 | \$ 2,400 |
| 102-71-16 | TEMPORARY BARRIER, F&I, FREE STANDING | 570 | LF | \$ 10.80 | \$ 6,156 |
| 102-71-26 | TEMPORARY BARRIER, RELOCATE, FREE STANDING | 1,140 | LF | \$ 4.30 | \$ 4,902 |
| 102-74-1 | CHANNELIZING DEVICE- TYPES I, II, DI, VP, DRUM, OR LCD | 23,000 | ED | \$ 0.20 | \$ 4,600 |
| 102-74-8 | CHANNELIZING DEVICE- PEDESTRIAN LCD (LONGITUDINAL CHANNELIZING DEVICE) | 40,000 | FD | \$ 0.20 | \$ 8,000 |
| 102-76 | ARROW BOARD / ADVANCE WARNING ARROW PANEL | 770 | ED | \$ 6.20 | \$ 4,774 |
| 102-89-1 | TEMPORARY CRASH CUSHION, REDIRECTIVE OPTION | 12 | LO | \$ 932.60 | \$ 11,191 |
| 102-99 | PORTABLE CHANGEABLE MESSAGE SIGN, TEMPORARY | 1,416 | ED | \$ 11.70 | \$ 16,567 |
| 102-115 | TYPE III BARRICADE | 1,200 | ED | \$ 0.40 | \$ 480 |
| 104-18 | INLET PROTECTION SYSTEM | 52 | EA | \$ 137.20 | \$ 7,134 |
| 107-1 | LITTER REMOVAL | 1.33 | AC | \$ 11.70 | \$ 16 |
| 107-2 | MOWING | 0.51 | AC | \$ 19.80 | \$ 10 |
| 110-1-1 | CLEARING & GRUBBING | 2.38 | AC | \$ 20,000.00 | \$ 47,600 |
| 110-2-2 | SELECTIVE CLEARING AND GRUBBING, AREAS WITH TREES TO REMAIN | 0.08 | AC | \$ 37,129.60 | \$ 2,970 |
| 110-4-10 | REMOVAL OF EXISTING CONCRETE | 465 | SY | \$ 16.40 | \$ 7,626 |
| 110-21 | TREE PROTECTION BARRIER | 1,920 | LF | \$ 1.90 | \$ 3,648 |
| 120-1 | REGULAR EXCAVATION | 1,876 | CY | \$ 14.00 | \$ 26,264 |
| 120-6 | EMBANKMENT | 552 | CY | \$ 16.50 | \$ 9,108 |
| 160-4 | TYPE B STABILIZATION | 4,853 | SY | \$ 5.10 | \$ 24,750 |
| 285-701 | OPTIONAL BASE, BASE GROUP 01 | 3,693 | SY | \$ 5.30 | \$ 19,573 |
| 285-706 | OPTIONAL BASE, BASE GROUP 06 | 594 | SY | \$ 51.50 | \$ 30,591 |
| 327-70-6 | MILLING EXIST ASPH PAVT, 1 1/2" AVG DEPTH | 21,317 | SY | \$ 2.90 | \$ 61,819 |
| 334-1-12 | SUPERPAVE ASPHALTIC CONC, TRAFFIC B | 157 | TN | \$ 110.60 | \$ 17,364 |
| 337-7-81 | ASPHALT CONCRETE FRICTION COURSE, TRAFFIC B, FC-12.5, PG 76-22 | 2,113 | TN | \$ 148.70 | \$ 314,203 |
| 339-1 | MISCELLANEOUS ASPHALT PAVEMENT | 8 | TN | \$ 159.90 | \$ 1,279 |
| 425-1-351 | INLETS, CURB, TYPE P-5, <10' | 2 | EA | \$ 6,461.10 | \$ 12,922 |
| 425-1-523 | INLETS, DT BOT, TYPE C, JBOT, <10' | 5 | EA | \$ 5,609.10 | \$ 28,046 |
| 425-1-541 | INLETS, DT BOT, TYPE D, <10' | 10 | EA | \$ 4,410.00 | \$ 44,100 |
| 425-1-701 | INLETS, GUTTER, TYPE S, <10' | 2 | EA | \$ 4,683.30 | \$ 9,367 |
| 425-1-921 | INLETS, ADJACENT BARRIER, <=10' | 1 | EA | \$ 7,410.90 | \$ 7,411 |
| 425-2-41 | MANHOLES, P-7, <10' | 1 | EA | \$ 5,055.20 | \$ 5,055 |
| 425-5 | MANHOLE, ADJUST | 10 | EA | \$ 812.90 | \$ 8,129 |
| 430-174-118 | PIPE CULVERT, OPTIONAL MATERIAL, ROUND, 18"SD | 4 | LF | \$ 75.00 | \$ 300 |
| 436-1-1 | TRENCH DRAIN, STANDARD | 396 | LF | \$ 273.40 | \$ 108,266 |
| 443-70-4 | FRENCH DRAIN, 24" | 465 | LF | \$ 158.20 | \$ 73,563 |
| 515-1-2 | PIPE HANDRAIL - GUIDERAIL, ALUMINUM | 20 | LF | \$ 25.20 | \$ 504 |
| 520-1-7 | CONCRETE CURB & GUTTER, TYPE E | 57 | LF | \$ 22.10 | \$ 1,260 |
| 520-1-10 | CONCRETE CURB & GUTTER, TYPE F | 1,067 | LF | \$ 17.20 | \$ 18,352 |
| 522-1 | CONCRETE SIDEWALK AND DRIVEWAYS, 4" THICK | 934 | SY | \$ 36.60 | \$ 34,181 |
| 522-2 | CONCRETE SIDEWALK AND DRIVEWAYS, 6" THICK | 547 | SY | \$ 53.90 | \$ 29,505 |
| 527-2 | DETECTABLE WARNINGS | 334 | SF | \$ 25.40 | \$ 8,484 |
| 536-1-1 | GUARDRAIL -ROADWAY, GENERAL TL-3 | 205 | LF | \$ 17.40 | \$ 3,567 |
| 536-8-122 | GUARDRAIL TRANSITION CONNECTION TO RIGID BARRIER, FURNISH AND INSTALL, EXISTING BRIDGE APPROACH TL-3 | 1 | EA | \$ 2,800.00 | \$ 2,800 |
| 536-73 | GUARDRAIL REMOVAL | 57 | LF | \$ 2.30 | \$ 131 |
| 536-85-24 | GUARDRAIL END TREATMENT- PARALLEL APPROACH TERMINAL | 1 | EA | \$ 2,963.40 | \$ 2,963 |
| 544-2-2 | CRASH CUSHION, TL-2, WIDE | 1 | EA | \$ 27,031.50 | \$ 27,032 |
| 570-1-2 | PERFORMANCE TURF, SOD | 6,780 | SY | \$ 4.10 | \$ 27,800 |
| 999-25 | INITIAL CONTINGENCY AMOUNT, DO NOT BID | 1 | LS | \$ 50,000 | |
| | | | | Sub-total Roadway | \$ 1,485,229 |

Preliminary Construction Cost Estimate

Revised 11/25/2020

FM 441830-1, SR 826 Frontage Roads From Okeechobee Road to NW 103rd Street

| Signing and Pavement Markings | | | | | | |
|--|---|-------|----|-------------|-----------|---------------------|
| 700-1-11 | SINGLE POST SIGN, F&I GROUND MOUNT, UP TO 12 SF | 36 | AS | \$ 308.80 | \$ 11,117 | |
| 700-1-12 | SINGLE POST SIGN, F&I GROUND MOUNT, 12-20 SF | 8 | AS | \$ 955.80 | \$ 7,646 | |
| 700-1-60 | SINGLE POST SIGN, REMOVE | 22 | AS | \$ 24.70 | \$ 543 | |
| 700-2-60 | MULTI- POST SIGN, REMOVE | 2 | AS | \$ 481.90 | \$ 964 | |
| 700-3-501 | SIGN PANEL, RELOCATE, UP TO 12 SF | 18 | EA | \$ 154.80 | \$ 2,786 | |
| 700-3-601 | SIGN PANEL, REMOVE, UP TO 12 SF | 1 | EA | \$ 75.80 | \$ 76 | |
| 705-10-1 | OBJECT MARKER, TYPE 1 | 1 | EA | \$ 213.20 | \$ 213 | |
| 710-90 | PAINTED PAVEMENT MARKINGS, FINAL SURFACE | 1 | LS | \$ 6,207.10 | \$ 6,207 | |
| 711-11-123 | THERMOPLASTIC, STANDARD, WHITE, SOLID, 12" FOR CROSSWALK AND ROUNDABOUT | 1,910 | LF | \$ 1.70 | \$ 3,247 | |
| 711-11-124 | THERMOPLASTIC, STANDARD, WHITE, SOLID, 18" FOR DIAGONALS AND CHEVRONS | 42 | LF | \$ 2.50 | \$ 105 | |
| 711-11-125 | THERMOPLASTIC, STANDARD, WHITE, SOLID, 24" FOR STOP LINE AND CROSSWALK | 191 | LF | \$ 3.50 | \$ 669 | |
| 711-11-141 | THERMOPLASTIC, STANDARD, WHITE, 2-4 DOTTED GUIDELINE/ 6-10 GAP EXTENSION, 6" | 0.007 | GM | \$ 1,145.20 | \$ 8 | |
| 711-11-160 | THERMOPLASTIC, STANDARD, WHITE, MESSAGE OR SYMBOL | 5 | EA | \$ 101.70 | \$ 509 | |
| 711-11-170 | THERMOPLASTIC, STANDARD, WHITE, ARROW | 5 | EA | \$ 58.40 | \$ 292 | |
| 711-11-224 | THERMOPLASTIC, STANDARD, YELLOW, SOLID, 18" FOR DIAGONAL OR CHEVRON | 146 | LF | \$ 2.60 | \$ 380 | |
| 711-11-241 | THERMOPLASTIC, STANDARD, YELLOW, 2-4 DOTTED GUIDE LINE /6-10 DOTTED EXTENSION LINE, 6" | 0.015 | GM | \$ 1,086.70 | \$ 16 | |
| 711-14-125 | THERMOPLASTIC, PREFORMED, WHITE, SOLID, 24" FOR CROSSWALK | 140 | LF | \$ 16.40 | \$ 2,296 | |
| 711-16-101 | THERMOPLASTIC, STANDARD-OTHER SURFACES, WHITE, SOLID, 6" | 2.476 | GM | \$ 4,168.90 | \$ 10,322 | |
| 711-16-131 | THERMOPLASTIC, STANDARD-OTHER SURFACES, WHITE, SKIP, 6",10-30 SKIP OR 3-9 LANE DROP | 0.107 | GM | \$ 1,234.30 | \$ 132 | |
| 711-16-201 | THERMOPLASTIC, STANDARD-OTHER SURFACES, YELLOW, SOLID, 6" | 1.782 | GM | \$ 4,178.80 | \$ 7,447 | |
| 711-16-231 | THERMOPLASTIC, STANDARD-OTHER SURFACES, YELLOW, SKIP, 6" | 0.266 | GM | \$ 1,400.60 | \$ 373 | |
| Sub-total Signing and Pavement Markings | | | | | | \$ 55,347 |
| Lump Sum Pay Item 710-90, Painted Pavement Markings, Final Surface | | | | | | |
| 706-1-1 | RAISED PAVEMENT MARKER, TYPE B WITHOUT FINAL SURFACE MARKINGS | 331 | EA | \$ 4.30 | \$ 1,423 | |
| 710-11-101 | PAINTED PAVEMENT MARKINGS, STANDARD, WHITE, SOLID, 6" | 2.476 | GM | \$ 775.90 | \$ 1,921 | |
| 710-11-123 | PAINTED PAVEMENT MARKINGS, STANDARD, WHITE, SOLID FOR CROSSWALK AND ROUNDABOUT, 12" | 1,910 | LF | \$ 0.50 | \$ 955 | |
| 710-11-124 | PAINTED PAVEMENT MARKINGS, STANDARD, WHITE, SOLID FOR DIAGONAL OR CHEVRON, 18" | 42 | LF | \$ 0.80 | \$ 34 | |
| 710-11-125 | PAINTED PAVEMENT MARKINGS, STANDARD, WHITE, SOLID FOR STOP LINE OR CROSSWALK, 24" | 191 | LF | \$ 1.10 | \$ 210 | |
| 710-11-131 | PAINTED PAVEMENT MARKINGS, STANDARD, WHITE, SKIP, 10-30 OR 3-9 SKIP, 6" WIDE | 0.107 | GM | \$ 351.80 | \$ 38 | |
| 710-11-141 | PAINTED PAVEMENT MARKINGS, STANDARD, WHITE, 2-4 DOTTED GUIDELINE/ 6-10 DOTTED EXTENSION, 6" | 0.007 | GM | \$ 495.20 | \$ 3 | |
| 710-11-201 | PAINTED PAVEMENT MARKINGS, STANDARD, YELLOW, SOLID, 6" | 1.782 | GM | \$ 763.40 | \$ 1,360 | |
| 710-11-224 | PAINTED PAVEMENT MARKINGS, STANDARD, YELLOW, SOLID FOR DIAGONAL OR CHEVRON, 18" | 146 | LF | \$ 1.00 | \$ 146 | |
| 710-11-231 | PAINTED PAVEMENT MARKINGS, STANDARD, YELLOW, SKIP, 6" | 0.266 | GM | \$ 418.20 | \$ 111 | |
| 710-11-241 | PAINTED PAVEMENT MARKINGS, STANDARD, YELLOW, 2-4 DOTTED GUIDELINE/6-10 DOTTED EXTENSION, 6" | 0.015 | GM | \$ 349.60 | \$ 5 | |
| Sub-total Painting Markings | | | | | | \$ 26,557 |
| Lighting | | | | | | |
| 630-2-12 | CONDUIT, FURNISH & INSTALL, DIRECTIONAL BORE | 180 | LF | \$ 19.80 | \$ 3,564 | |
| 635-2-11 | PULL & SPLICING BOX, F&I, 13" x 24" COVER SIZE | 4 | EA | \$ 711.60 | \$ 2,846 | |
| 715-1-13 | LIGHTING CONDUCTORS, F&I, INSULATED, NO 4 TO NO 2 | 636 | LF | \$ 2.50 | \$ 1,590 | |
| 715-4-12 | LIGHT POLE COMPLETE, FURNISH & INSTALL STANDARD POLE STANDARD FOUNDATION, 35' MOUNTING HEIGHT | 1 | EA | \$ 5,203.00 | \$ 5,203 | |
| 715-4-14 | LIGHT POLE COMPLETE, FURNISH & INSTALL STANDARD POLE STANDARD FOUNDATION, 45' MOUNTING HEIGHT | 1 | EA | \$ 7,218.20 | \$ 7,218 | |
| 715-11-211 | LUMINAIRE, F&I- REPLACE EXISTING LUMINAIRE ON EXISTING POLE/ARM, ROADWAY, COBRA HEAD | 2 | EA | \$ 1,422.90 | \$ 2,846 | |
| 715-500-1 | POLE CABLE DISTRIBUTION SYSTEM, FURNISH AND INSTALL, CONVENTIONAL | 4 | EA | \$ 822.30 | \$ 3,289 | |
| Sub-total Lighting | | | | | | \$ 26,557 |
| Landscape | | | | | | |
| 581-1-2 | RELOCATE TREES AND PALMS, PALM, >=14' OF CLEAR TRUNK | 4 | EA | \$ 1,149.60 | \$ 4,598 | |
| Sub-total Landscape | | | | | | \$ 4,598 |
| Grand Total | | | | | | |
| Unit Prices from FDOT Item Average Unit Costs, either Area 13 or Statewide Averages (10/2019-9/2020) | | | | | | \$ 1,571,731 |

Appendix D

Utility Design Ticket

Ticket : 253006766 Rev:000 Taken: 09/09/20 16:03ET

State: FL Cnty: DADE GeoPlace: HIALEAH
CallerPlace: HIALEAH
Subdivision:

Address :
Street : SR 826
Cross 1 : NW 35TH TER
Within 1/4 mile: Y
Cross 2 : NW 154TH ST

Locat: LOCATE BOTH SIDES OF SR 826 FROM NW 35TH TER TO NW 154TH ST

:
Remarks : IN RESPONSE TO RECEIPT OF A DESIGN TICKET, SSOCOF PROVIDES THE ORIGINATOR OF THE DESIGN TICKET WITH A LIST OF SSOCOF MEMBERS IN THE VICINITY OF THE DESIGN PROJECT. SSOCOF DOES NOT NOTIFY SSOCOF MEMBERS OF THE RECEIPT BY SSOCOF OF A DESIGN TICKET. IT IS THE SOLE RESPONSIBILITY OF THE DESIGN ENGINEER TO CONTACT SSOCOF MEMBERS TO REQUEST INFORMATION ABOUT THE LOCATION OF SSOCOF MEMBERS' UNDERGROUND FACILITIES. SUBMISSION OF A DESIGN TICKET WILL NOT SATISFY THE REQUIREMENT OF CHAPTER 556, FLORIDA STATUTES, TO NOTIFY SSOCOF OF AN INTENT TO EXCAVATE OR DEMOLISH. THAT INTENT MUST BE MADE KNOWN SPECIFICALLY TO SSOCOF IN THE MANNER REQUIRED BY LAW. IN AN EFFORT TO SAVE TIME ON FUTURE CALLS, SAVE YOUR DESIGN TICKET NUMBER IF YOU INTEND TO BEGIN EXCAVATION WITHIN 90 DAYS OF YOUR DESIGN REQUEST. THE DESIGN TICKET CAN BE REFERENCED, AND THE INFORMATION ON IT CAN BE USED TO SAVE TIME WHEN YOU CALL IN THE EXCAVATION REQUEST.

*** LOOKUP BY MANUAL ***

:
Grids : 2554A8019B 2554A8019C 2554B8019B 2554B8019C 2555B8014A
Grids : 2555B8015A 2555B8015B 2555B8015C 2555B8015D 2555B8016A
Grids : 2555B8016B 2555B8016C 2555B8016D 2555B8017A 2555B8017B
Grids : 2555B8017C 2555B8017D 2555B8018A 2555B8018B 2555B8018C
Grids : 2555B8018D 2555B8019C 2555B8019D 2555C8017A 2555C8017B
Grids : 2555C8017C 2555C8018A 2555C8018B 2555C8018C 2555C8018D
Grids : 2555C8019B 2555C8019C 2555C8019D 2555D8019B 2555D8019C

Work date: 09/09/20 Time: 15:56ET Hrs notc: 000 Category: 6 Duration: UNKNOWN

Due Date : 09/11/20 Time: 23:59ET Exp Date : 10/09/20 Time: 23:59ET

Work type: DESIGN Boring: N White-lined: N

Ug/Oh/Both: U Machinery: N Depth: UNK Permits: N N/A

Done for : DESIGN

Company : FDOT Type: MEMB
Co addr : 1000 NW 111TH AVE
City : MIAMI State: FL Zip: 33172
Caller : LISANDRA FUENTES Phone: 305-470-5232
BestTime: 8-5
Email : LISANDRA.FUENTES@DOT.STATE.FL.US

Submitted: 09/09/20 16:03ET Oper: EVE

Mbrs : ALLIN1 AMTV01 AT1931 CC1279 CC2356 CITYGS DCPWT EVGPPPL FDOT06 FGT01

Mbrs : FPLDAD HC1660 L3C900 MC2278 MCIU01 MDWS ML1426 NMBPU NN1882 SBF23

Mbrs : SP1898

| <u>Service Area</u> | <u>Utility Type(s)</u> | <u>Contact</u> | <u>Alt. Contact</u> | <u>Emergency Contact</u> | <u>Positive Response</u> |
|--|-----------------------------------|---|---|--|--|
| SSOCOF TEST CODE - DO NOT READ TO CALLER ALLIN1 * Test/In-House | SSOCOF TEST CODE | | | | Call Center Test Destination - The member code affiliated with this code is a test code - please disregard this response |
| ATLANTIC BROADBAND AMTV01 | CABLE | PETE FREYTAG (305) 861-8069 x5208 | PETE FREYTAG (305) 861-8069 x5208 | PETE FREYTAG (305) 861-8069 x5208 | |
| AMERICAN TRAFFIC SOLUTIONS AT1931 | COMMUNICATION LINES, ELECTRIC | VICTORIA GRASSER (480) 596-4559 | IT HELP DESK (866) 382-8689 | IT HELP DESK (866) 382-8689 | |
| COMCAST CABLE CC1279 | CATV, FIBER | LEONARD MAXWELL- NEWBOLD (754) 221-1254 | | USIC DISPATCH (800) 778-9140 | |
| CCI MONITOR CC2356 * New | FIBER | FIBER DIG TEAM (888) 632-0931 x2 | | FIBER NOC (855) 933-4237 x1 | |
| FLORIDA CITY GAS CITYGS | NATURAL GAS | GUSTAVO PENA (305) 835-3624 | RICHARD WILLIAMS (772) 359-1184 | ALEX FARIAS (305) 835-3603 | |
| DADE COUNTY PUBLIC WORKS AND TRAFFIC DCPWT | STREET LIGHTS, TRAFFIC SIGNALS | OCTAVIO VIDAL (305) 412-0891 x102 | OCTAVIO VIDAL (305) 412-0891 x102 | FRANK AIRA P.E. (305) 592-3580 x233 | |
| BUCKEYE PIPELINE CO EVGPL | GAS | DANIEL MANGUM (832) 541-3946 | TRACI MCCLERNON (610) 904-4475 | GARY WURSTER (954) 522-8464 | |
| FLORIDA DEPARTMENT OF TRANSPORTATION VI ITS FDOT06 | FIBER | THOMAS MILLER (305) 470-5757 x7352 | IT ADMIN (305) 470-5757 x7340 | ANTONIO VALLADARES (561) 703-1113 | |
| FLORIDA GAS TRANSMISSION FGT01 | GAS | JOSEPH E. SANCHEZ (407) 838-7171 | LORENZO MENENDEZ (954) 214-5446 | LYNN E IRVIN (407) 838-7656 | |
| FLORIDA POWER & LIGHT--DADE FPLDAD | ELECTRIC | EDGAR AGUILAR (386) 586-6403 | | USIC DISPATCH CENTER (800) 778-9140 | |
| HOTWIRE COMMUNICATIONS HC1660 | CATV, FIBER, TELEPHONE | WALTER DAVILA (954) 699-0900 | RALPH HERRERA (954) 628-7023 | NOC / OAIS HASSANZADA (CALL IF NO RESPONSE FROM NOC) (561) 288-9188 x6 | |
| CENTURYLINK L3C900 | FIBER | NETWORK RELATIONS (877) 366-8344 x2 | TECH ON DUTY (877) 366-8344 x3 | TECH ON DUTY (877) 366-8344 x3 | |
| MASTEC INC MC2278 | FIBER | RICKIE QUINN | | JULIO OLEA (305) 803-0346 | |
| MCI MCIU01 | COMMUNICATION LINES, FIBER | MCIU01 INVESTIGATIONS (469) 886-4091 | NATIONAL FIBER SECURITY DEPARTMENT (800) 624-9675 | NATIONAL FIBER SECURITY DEPARTMENT (800) 624-9675 | |
| MIAMI-DADE WATER & SEWER MDWS | SEWER, WATER | LAZARO GUERRA (786) 268-5273 | | RADIO COMMUNICATION CENTER (305) 274-9272 | |
| TOWN OF MIAMI LAKES ML1426 | IRRIGATION, STREET LIGHTS | LUIS SANCHEZ (305) 364-6100 | LUIS SANCHEZ (305) 364-6100 | LUIS SANCHEZ (305) 364-6100 | |

| | | | |
|--------------------------------|--------------|--|---|
| NMB WATER/JACOBS NMBPU | SEWER, WATER | KARIM ROSSY (305) 948-2980 x7962 | JOHN POLLARD (305) 218-1484 |
| CROWN CASTLE NG NN1882 | FIBER | FIBERDIG TEAM (888) 632-0931 x2 | CROWN CASTLE FIBER NOC (855) 933-4237 x1 |
| A T & T/ DISTRIBUTION SBF23 | TELEPHONE | DINO FARRUGGIO (561) 997-0240 | USIC DISPATCH OFFICE (CLS) (800) 778-9140 |
| SUBURBAN PROPANE SP1898 | PROPANE GAS | DMITRY PRESSMAN (305) 635-4427 x102 | USIC DISPATCH OFFICE (CLS) (800) 778-9140 |

